



Experiment 2

Student Name: Raj Verma

Branch: CSE

Semester: 5th

Subject Name: ADBMS

UID: 23BCS12244

Section/Group: KRG 3-A

Date of Performance: 24/07/2025

Subject Code: 23CSP-333

1. Aim: To demonstrate the use of self-joins and conditional joins in SQL for managing hierarchical employee relationships and performing conditional lookups using LEFT JOIN and IFNULL across two related tables.

- a. Employee-Manager Hierarchy Using Self-Join
- b. Conditional Join Between Financial Tables

2. Objective:

- To design and populate relational tables with hierarchical and temporal data.
- To perform a **self-join** on an employee table to retrieve manager-employee relationships.
- To implement a **conditional LEFT JOIN** between two tables to handle non-matching records.
- To apply the **IFNULL** function to handle missing values in joined queries.
- To practice using joins for **querying structured business-related datasets**.

3. DBMS script and output:

Solution-(a)

```
CREATE DATABASE company;
```

```
USE company;
```

```
CREATE TABLE employee (
```

```
    empid INT PRIMARY KEY,
```

```
    ename VARCHAR(50),
```

```
    department VARCHAR(50),
```

```
    managerid INT
```

```
);
```

```
INSERT INTO employee (empid, ename, department, managerid) VALUES
```

```
(1, 'Alice', 'HR', NULL),
```

```
(2, 'Bob', 'Finance', 1),
```



(3, 'Charlie', 'IT', 1),
(4, 'David', 'Finance', 2),
(5, 'Eve', 'IT', 3),
(6, 'Frank', 'HR', 1);

SELECT

e.ename AS EmployeeName,
e.department AS EmployeeDepartment,
m.ename AS ManagerName,
m.department AS ManagerDepartment

FROM

employee e

LEFT JOIN

employee m ON e.managerid = m.empid;

EMPLOYEE NAME	EMPLOYEE DEPARTMENT	MANAGER NAME	MANAGER DEPARTMENT
Frank	HR	Alice	HR
Charlie	IT	Alice	HR
Bob	Finance	Alice	HR
David	Finance	Bob	Finance
Eve	IT	Charlie	IT
Alice	HR	-	-

Solution-(b)

create database *company2*;

use *company2*;

CREATE TABLE *Year_tbl* (

ID INT,

YEAR INT,

NPV INT

);



CREATE TABLE *Queries* (

ID INT,

YEAR INT

);

INSERT INTO Year_tbl (ID, YEAR, NPV)

VALUES

(1, 2018, 100),

(7, 2020, 30),

(13, 2019, 40),

(1, 2019, 113),

(2, 2008, 121),

(3, 2009, 12),

(11, 2020, 99),

(7, 2019, 0);

INSERT INTO *Queries* (ID, YEAR)

VALUES

(1, 2019),

(2, 2008),

(3, 2009),

(7, 2018),

(7, 2019),

(7, 2020),

(13, 2019);

SELECT

q.ID,

q.YEAR,

IFNULL(y.NPV, 0) AS NPV

FROM

Queries q

LEFT JOIN

Year_tbl y ON q.ID = y.ID AND q.YEAR = y.YEAR;

ID	YEAR	NPV
3	2009	12
7	2019	0
7	2020	30
13	2019	40
1	2019	113
2	2008	121
7	2018	0

4. Learning Outcomes:

- Understand how to model and query **hierarchical relationships** using self-joins.
- Learn to perform **LEFT JOINS** to include unmatched records from one table.
- Apply **composite join conditions** on multiple columns (e.g., ID and YEAR).
- Use **IFNULL** to handle NULL values in result sets for reporting purposes.
- Develop SQL skills for solving **real-world data retrieval scenarios** in organizations.