FastSpeech 2 for English and Telugu

IIIT Hyderabad Voice AI assignment, Submitted by Yuvraj Verma

Two models were trained independently on about five hours of audio per language. All ten test utterances were generated, with thirty duration, pitch and energy plots. This report adds automatic assessment of every sample and comparison with held-out recordings.

Assessment method:

I do not know Telugu, so I used automatic transcription, predicted-quality scores and acoustic measurements to assess the Telugu outputs. Assessment of both languages is automatic. No native-speaker listening or human MOS study was performed.

Whisper large-v3 and MMS-1b-all independently transcribed the audio without the reference sentences as prompts. Word and character errors were measured against the expanded spoken text. UTMOSv2 predicted quality using three crop repeats. Ten held-out recordings per language provide descriptive controls. These controls are not matched to the test sentences by speaker or length.

Model and implementation:

- Adapted ming024/FastSpeech2: text encoder, variance adaptor, length regulator, mel decoder and postnet. Encoder/decoder use four blocks each, hidden size 192 and two attention heads. Each language has separate weights, speaker embeddings and statistics.
- Both models use romanized characters; Telugu uses uroman. Pitch is predicted as mean log F0 per token. Fixed energy-control routing, device allocation and long-output truncation. A frozen SpeechBrain HiFi-GAN generates 22.05 kHz waveforms.

Data preparation:

Data	English	Telugu
Source	Svarah	IndicTTS Telugu
Training	5.0014 h / 3,220 clips	5.0001 h / 1,922 clips
Validation	1.0020 h / 655 clips	1.0009 h / 382 clips
Voice conditioning	115 profile groups	2 voice labels

Removed invalid/silent clips and duplicate audio; retained 0.7-20 s recordings with at most 450 tokens. Grouped normalized prompts before seeded splitting, with no audio or prompt overlap. Added 15% candidate audio for alignment failures. Svarah profile groups are proxies, not verified speaker IDs.

Features and training:


NFC normalization expands numbers, dates and times while retaining the supplied internal spacing. MMS alignment supplies token durations. Features use FFT/window 1,024, hop 256 and 80 mel filters over 0-8,000 Hz. WORLD estimates F0; unvoiced gaps are interpolated. Energy is the log STFT-magnitude norm. Statistics use training data only.

AdamW; peak learning rate 0.0005; 1,000-step warmup; batch sizes 6/4; gradient clipping 1.0; CUDA mixed precision. Validation runs every 1,000 steps, with a 40,000-step limit. Early stopping starts after 15,000 steps, with patience 12 and minimum improvement 0.002. Loss adds mel/postnet L1 to duration, pitch and energy MSE.

Training and automatic assessment results:

Model	Run ended	Selected checkpoint	Validation loss
English	19,000	7,000	2.7096
Telugu	26,000	14,000	2.0241

Training loss kept falling while validation loss flattened, suggesting overfitting. Both runs stopped early. Telugu's minimum at step 23,000 was 2.0231, but the improvement over the saved step-14,000 checkpoint was below 0.002. Validation uses reference variance features; test synthesis uses predictions.



Training and validation losses. Separate component curves are retained in Results/English and Results/Telugu. The two languages' normalized losses cannot be ranked directly.

Language and audio	N	Whisper CER %	MMS CER %	Raw UTMOS mean
English Generated	5	33.7	49.7	0.73
English Held-out	10	3.8	8.4	2.77
Telugu Generated	5	15.9	8.9	1.81
Telugu Held-out	10	12.3	3.5	3.14

Both recognizers show a larger synthetic-versus-control CER gap for English than Telugu. Quality predictions are below control means for both languages. CER counts normalized Unicode characters with spaces removed; WER and raw transcripts are also saved. Equivalent number readings and Telugu spelling/segmentation can affect scores. The two recognizers and real-speech controls expose this uncertainty. UTMOS values are raw predictions, not human ratings; the regressor can fall outside the nominal 1-5 listener scale.

Results for each test sentence:

ID	Time s	CER W %	CER M %	UTMOS	Predicted F0 Hz	Energy range
E1	6.34	36.7	57.1	0.84	114-173	1.7-96.1
E2a	5.19	0.0	35.0	0.80	97-182	2.1-109.7
E2b	4.27	39.1	46.9	0.64	84-165	1.0-88.0
E3	2.96	35.7	47.6	0.66	117-173	1.3-90.5
E4	6.78	46.2	53.8	0.69	105-171	1.6-97.9
T1	6.05	24.2	14.5	1.72	100-294	0.1-108.9
T2a	3.33	3.6	0.0	1.99	113-247	0.3-78.2
T2b	3.54	20.6	11.8	1.57	89-252	0.3-78.0
T3	3.23	6.9	0.0	2.05	106-270	0.1-86.1
T4	9.83	15.2	9.5	1.74	100-258	0.1-91.4

W = Whisper; M = MMS. Energy uses relative STFT units. Continuous predicted F0 is not a voicing decision. All waveforms are unclipped. Native-script transcripts, error counts and per-sample measurements are linked from the repository's results indexes.

Duration, pitch and energy observations

E1 The target word takes 1393 ms; its mean F0 is 144.9 Hz and energy 48.7. Whisper did not recover the target word exactly.

E2a Conduct takes 360 ms. Con/duct mean F0 is 135.7/125.2 Hz; energy is 49.1/29.4. Whisper recovered the sentence text exactly.

E2b Conduct takes 372 ms. Con/duct mean F0 is 122.4/119.2 Hz; energy is 51.7/28.3. Whisper retained conduct but changed surrounding words.

E3 The boundary at the supplied internal split lasts 35 ms. Fragment mean F0 is 133/146 Hz and energy 64.6/83.8. Whisper did not recover rhythm.

E4 The a/m tokens each receive 23 ms. Andaroo has mean F0 138.5 Hz and energy 66.8. Both zero-duration tokens are boundaries. Whisper did not retain the supplied date or andaroo.

T1 The target word takes 1289 ms; its mean F0 is 249.1 Hz and energy 53.8.

T2a Pattu takes 279 ms, with mean F0 201.9 Hz and energy 19.4. Whisper retained pattu.


T2b Pattu takes 267 ms, with mean F0 200.2 Hz and energy 16.3. Whisper retained pattu.

T3 The boundary at the supplied internal split lasts 81 ms. Fragment mean F0 is 174/210 Hz and energy 38.8/53.8.

T4 The forty/five boundary is 348 ms. Mean word F0 falls 200 to 121 Hz and energy 54.2 to 13.5. The zero-duration token is a boundary.

Word and con/duct regions follow the model's grapheme durations; they are not independently validated phonetic boundaries. The supplied E3/T3 spacing was preserved. No zero-duration item is a lexical character. Measured waveform F0, energy and low-energy intervals are plotted separately for every sample.

Target word comparisons:



E2a/E2b are conduct; T2a/T2b are pattu. These are within-model descriptions, not cross-language quality scores.

- Conduct has similar total duration in the two contexts. Both contexts assign higher predicted energy to the first grapheme region; a clear noun/verb stress reversal is not demonstrated. Whole-word means and ASR text recovery cannot establish syllable stress.
- Pattu has similar duration and mean F0 in both contexts. The two meanings need not change segmental pronunciation. Phrase-level correctness remains uncertain without a Telugu speaker's judgment.
- Whisper recovered E2a's normalized transcript exactly, while UTMOS predicted 0.80. Text recovery and predicted naturalness assess different properties. Rare-word, spacing and date/time cases show transcript mismatches; neither recognizer is treated as a pronunciation authority.

Limitations and improvements

The assessment is automatic. Telugu ASR errors on real recordings limit the strength of pronunciation claims. UTMOS is not calibrated for these Telugu voices, and predictions below 1 are extrapolations rather than valid listener ratings. The ten controls per language are descriptive, not a matched perceptual study. Native pronunciation, stress and naturalness remain unverified.

Priorities are better phonetic text processing, more reliable voice conditioning and review of low-confidence alignments. Romanization can merge sounds; alignment errors affect duration targets. Resynthesizing reference mels through the fixed vocoder would help separate vocoder artifacts from acoustic-model errors.