

```
#CREACIÓN DE LA BASE DE DATOS BAÑERAS
CREATE DATABASE if not exists Bañeras;
```

```
#Selección de la base de datos
USE Bañeras;
```

```
# Creacion de las tablas
#Articulos
CREATE TABLE if not exists articulos(
cod_articulo int PRIMARY KEY,
descripcion VARCHAR(30),
stock INT,
stock_min INT,
Pcoste FLOAT,
PVP FLOAT)ENGINE=INNODB;
```

```
#Creación de una tabla respaldo con triggers
CREATE TABLE respaldo_articulos LIKE articulos;
INSERT INTO respaldo_articulos SELECT * FROM articulos;
SELECT * FROM respaldo_articulos;
DROP TABLE respaldo_articulos;
```

```
DELIMITER $$
CREATE TRIGGER copia_articulosAI AFTER INSERT ON articulos FOR EACH ROW
BEGIN INSERT INTO
respaldo_articulos(cod_articulo,descripcion,stock_min,Pcoste,PVP)
VALUES(NEW.cod_articulo,NEW.descripcion,NEW.stock_min,NEW.Pcoste,NEW.PVP)
;
END $$
DELIMITER ;
```

```
INSERT INTO articulos VALUES
(009,'arena2',1,36,100,300);
```

```
select * from respaldo_articulos;
select * from articulos;
```

```
DELIMITER $$
CREATE TRIGGER copia_articulosAU AFTER UPDATE ON articulos FOR EACH ROW
BEGIN
UPDATE respaldo_articulos SET descripcion=NEW.descripcion,
stock_min=NEW.stock_min, Pcoste=NEW.Pcoste, PVP=NEW.PVP
WHERE cod_articulo=NEW.cod_articulo;
END $$
DELIMITER ;
DELIMITER $$
```

```
UPDATE articulos SET descripcion='arena' WHERE cod_articulo=009;

CREATE TRIGGER copia_articulosAD AFTER DELETE ON articulos FOR EACH ROW
BEGIN
DELETE FROM respaldo_articulos WHERE  cod_articulo=OLD.cod_articulo;
END $$
DELIMITER ;

#CREATE TABLE respaldo_articulos SELECT * FROM articulos;
#CREACION DE LA TABLA AUDITORIA
```

```
#CLIENTES
CREATE TABLE if not exists clientes(
cod_cli INT PRIMARY KEY,
nombre VARCHAR(50),
direccion VARCHAR(30),
tlfno VARCHAR(12),
provincia VARCHAR(20))ENGINE=INNODB;
```

```
#FACTURA
CREATE TABLE if not exists factura(
num_fact INT PRIMARY KEY,
cod_cli INT,
fecha DATE,
descuento INT,
FOREIGN KEY(cod_cli) references clientes(cod_cli)
ON DELETE CASCADE ON UPDATE CASCADE)ENGINE=INNODB;
```

```
#LINEAS FACTURAS
CREATE TABLE if not exists lineas_factura(
num_fact INT,
num_linea INT,
cod_articulo INT,
cantidad INT,
PRIMARY KEY(num_fact, num_linea),
FOREIGN KEY(num_fact) references factura(num_fact)
ON DELETE CASCADE ON UPDATE CASCADE)ENGINE=INNODB;
```

```
#INSERSION DE LOS DATOS
#ARTICULOS
INSERT INTO articulos VALUES
(001,'Bañera de hidromasaje',10,2,1000,3000),
(002,'cemento',60,30,23,50),
(003,'ladrillo',100,30,45,85),
(004,'chimenea',32,5,657,1300),
(005,'teja',255,45,67,90),
(006,'Gres o azulejo',56,5,75,146),
```

```
(007,'lavabo',40,7,123,234);
```

#CLIENTES

```
INSERT INTO clientes VALUES
```

```
(001,'Pepito Pérez','C/Fortaleza -3','980637237','Zamora'),  
(002,'Fulanito de tal','C/Sinnombre -10','9876543','Valladolid'),  
(003,'Enriquito Fdez.','C/Manganees -12','980657893','Zamora');
```

#FACTURAS

```
INSERT INTO factura VALUES
```

```
(001,001,'2025-01-26',10),  
(002,002,'2025-01-15',3),  
(003,003,'2025-01-18',0),  
(005,001,'2025-01-01',0),  
(006,002,'2025-01-20',5),  
(007,001,'2024-12-30',0);
```

#LINEAS FACTURAS

```
INSERT INTO lineas_factura VALUES
```

```
(003,1,001,5),  
(001,1,001,4),  
(001,2,003,4),  
(001,3,004,10),  
(002,1,001,23),  
(002,2,002,2),  
(002,3,003,14),  
(002,4,004,56),  
(002,5,005,34),  
(002,6,006,22),  
(002,7,007,89),  
(005,1,001,1567),  
(005,2,006,23),  
(006,1,001,23),  
(006,2,007,2),  
(006,3,005,15),  
(007,1,001,23),  
(007,2,004,2),  
(007,3,002,24),  
(007,4,005,15);
```