

## Weer\_mobiele\_app

### Main.ts

```
import { bootstrapApplication } from '@angular/platform-browser';
import { provideAnimationsAsync } from '@angular/platform-browser/animations/async';
import { RouteReuseStrategy, provideRouter, withHashLocation } from '@angular/router';
import { provideHttpClient } from '@angular/common/http';
import { provideStore } from '@ngrx/store';
import { provideEffects } from '@ngrx/effects';
import { IonicRouteStrategy, provideIonicAngular } from '@ionic/angular/standalone';

import { AppComponent } from './app/app.component';
import { routes } from './app/app.routes';
import { locationReducer } from './app/location-reducer';
import { LocationEffects } from './app/location.effects';

bootstrapApplication(AppComponent, {
  providers: [
    provideRouter(routes, withHashLocation()),

    provideHttpClient(),
    provideAnimationsAsync(),

    { provide: RouteReuseStrategy, useClass: IonicRouteStrategy },
    provideIonicAngular({}),

    provideStore({ location: locationReducer }),
    provideEffects(LocationEffects)
  ]
}).catch(err => console.error(err));
```

Index.html

```
<!doctype html>
<html lang="nl">
<head>
  <meta charset="utf-8" />
  <title>Weerapp</title>
  <base href="." />
  <meta name="color-scheme" content="light dark" />
  <meta name="viewport" content="viewport-fit=cover, width=device-width,
initial-scale=1.0" />
  <meta name="format-detection" content="telephone=no" />
  <meta name="msapplication-tap-highlight" content="no" />
</head>
<body>
  <app-root></app-root>
</body>
</html>
```

## Global.scss

```
@use '@angular/material' as mat;

:root {
  color-scheme: light;
  --theme-primary: #556b2f;
  --theme-secondary: #fafad2;
  --theme-text-dark: #2c3e50;
  --mat-sys-surface: var(--theme-secondary);
  --mat-sys-primary: var(--theme-primary);
}

html, body {
  height: 100%;
  margin: 0;
  font-family: 'Verdana', Roboto, sans-serif;
  color: var(--theme-text-dark);
}

ion-app {
  height: 100vh;
}

ion-content {
  --background: var(--theme-secondary);
}

.table-responsive {
  width: 100%;
  overflow-x: auto;
  scroll-behavior: smooth;
  overscroll-behavior-x: contain;
}

.weather-table {
  width: 100%;
  border-collapse: collapse;
  margin: 15px 0;
  background: #ffffff;
  border-radius: 8px;
  overflow: hidden;
  box-shadow: 0 2px 5px rgba(0,0,0,0.05);

  tr {
    border-bottom: 1px solid #f0f0f0;
    &:last-child { border-bottom: none; }
  }
}
```

```
th {
  background-color: var(--theme-primary);
  color: var(--theme-secondary);
  text-align: left;
  padding: 14px;
  font-weight: 700;
}

td {
  padding: 12px 14px;
  color: var(--theme-text-dark);
}
}

.badge {
  padding: 5px 10px;
  border-radius: 4px;
  display: inline-block;
  font-weight: bold;
  color: #ffffff;

  &-success { background-color: #2ecc71; }
  &-warning { background-color: #f39c12; color: #2c3e50; }
  &-danger { background-color: #e74c3c; }
}
```

## Location.reducer.ts

```
import { createAction, createReducer, on, props, createFeatureSelector,
createSelector } from '@ngrx/store';

export interface CurrentWeather {
  temperature: number;
  windspeed: number;
  winddirection: number;
}

export interface DailyWeather {
  time: string[];
  temperature_2m_max: number[];
  temperature_2m_min: number[];
  sunrise: string[];
  sunset: string[];
  uv_index_max: number[];
}

export interface LocationState {
  city: string;
  lat: number;
  lon: number;
  current: CurrentWeather | null;
  daily: DailyWeather | null;
  loading: boolean;
}

export const loadLocation = createAction('[Location] Load Location',
props<{ cityName: string }>());
export const setLocation = createAction('[Location] Set Location',
props<{ city: string; lat: number; lon: number; current: CurrentWeather;
daily: DailyWeather }>());
export const loadLocationFailed = createAction('[Location] Load Location
Failed');

const initialState: LocationState = {
  city: '',
  lat: 0,
  lon: 0,
  current: null,
  daily: null,
  loading: false
};

export const locationReducer = createReducer(
```

```
    initialState,
    on(loadLocation, (state) => ({ ...state, loading: true })),
    on(setLocation, (state, { city, lat, lon, current, daily }) => ({ ...state,
city, lat, lon, current, daily, loading: false })),
    on(loadLocationFailed, (state) => ({ ...state, loading: false }))
  );

export const selectLocationFeature =
createFeatureSelector<LocationState>('location');
export const selectCity = createSelector(selectLocationFeature, (state) =>
state?.city || '');
export const selectCurrentWeather = createSelector(selectLocationFeature,
(state) => state?.current);
export const selectDailyWeather = createSelector(selectLocationFeature,
(state) => state?.daily);
export const selectWeatherLoading = createSelector(selectLocationFeature,
(state) => state?.loading);
```

## Location.effects.ts

```
import { Injectable, inject } from '@angular/core';
import { Actions, createEffect, ofType } from '@ngrx/effects';
import { WeatherService } from '../weather.service';
import { loadLocation, setLocation, loadLocationFailed } from '../location-reducer';
import { map, switchMap, catchError, of } from 'rxjs';
import { ToastController } from '@ionic/angular/standalone';

@Injectable()
export class LocationEffects {
  private actions$ = inject(Actions);
  private weatherService = inject(WeatherService);
  private toastController = inject(ToastController);

  loadLocation$ = createEffect(() =>
    this.actions$.pipe(
      ofType(loadLocation),
      switchMap(action =>
        this.weatherService.getCompleteWeather(action.cityName).pipe(
          map(weatherData => setLocation({
            city: weatherData.name,
            lat: weatherData.lat,
            lon: weatherData.lon,
            current: weatherData.current,
            daily: weatherData.daily
          })),
          catchError(error => {
            console.error('Fout tijdens ophalen weerdata:', error);

            this.showErrorToast(action.cityName);

            return of(loadLocationFailed());
          })
        )
      )
    );

  private async showErrorToast(cityName: string) {
    const toast = await this.toastController.create({
      message: `Locatie "${cityName}" kon niet worden gevonden.`,
      duration: 3000,
      position: 'bottom',
      color: 'danger'
    });
    await toast.present();
  }
}
```

## Weather.service.ts

```
import { Injectable } from '@angular/core';
import { HttpClient } from '@angular/common/http';
import { Observable, switchMap, map, throwError } from 'rxjs';

@Injectable({
  providedIn: 'root'
})
export class WeatherService {
  constructor(private http: HttpClient) {}

  public getCompleteWeather(loc: string): Observable<any> {

    const geoUrl = `https://geocoding-api.open-
meteo.com/v1/search?name=${encodeURIComponent(loc)}&count=1&language=nl&format
=json`;

    return this.http.get<any>(geoUrl).pipe(
      switchMap((geoRes: any) => {
        if (!geoRes || !geoRes.results || geoRes.results.length === 0) {
          return throwError(() => new Error(`Locatie "${loc}" niet
gevonden.`));
        }

        const city = geoRes.results[0];

        const weatherUrl = `https://api.open-
meteo.com/v1/forecast?latitude=${city.latitude}&longitude=${city.longitude}&cu
rrent=temperature_2m,wind_speed_10m,wind_direction_10m&daily=temperature_2m_ma
x,temperature_2m_min,sunrise,sunset,uv_index_max&timezone=auto`;

        return this.http.get<any>(weatherUrl).pipe(
          map((weatherRes: any) => {
            return {
              name: city.name,
              lat: city.latitude,
              lon: city.longitude,
              current: {
                temperature: weatherRes.current?.temperature_2m,
                windspeed: weatherRes.current?.wind_speed_10m,
                winddirection: weatherRes.current?.wind_direction_10m
              },
              daily: {
                time: weatherRes.daily?.time || [],
                temperature_2m_max: weatherRes.daily?.temperature_2m_max ||
[],
                temperature_2m_min: weatherRes.daily?.temperature_2m_min ||
[],
                sunrise: weatherRes.daily?.sunrise || [],
```



```
        sunset: weatherRes.daily?.sunset || [],  
        uv_index_max: weatherRes.daily?.uv_index_max || []  
      }  
    }  
  }  
);  
}  
}
```

Child.service.ts

```
import { Injectable, signal, computed } from '@angular/core';

@Injectable({
  providedIn: 'root'
})
export class ChildService {
  private invoerLijstSignal = signal<string[]>([]);

  public invoerLijst = this.invoerLijstSignal.asReadonly();

  public laatsteInvoer = computed(() => {
    const lijst = this.invoerLijstSignal();
    return lijst.length > 0 ? lijst[lijst.length - 1] : '';
  });

  public onChildInvoerCreated(nieuweInvoer: string): void {
    const trimmed = nieuweInvoer?.trim();
    if (!trimmed) return;
    this.invoerLijstSignal.update(huidigeLijst => [...huidigeLijst, trimmed]);
  }

  public onChildInvoerDeleted(indexTeVerwijderen: number): void {
    this.invoerLijstSignal.update(huidigeLijst =>
      huidigeLijst.filter((_, index) => index !== indexTeVerwijderen)
    );
  }
}
```

## App.routes.ts

```
import { Routes } from '@angular/router';
import { ParentComponent } from '../parent/parent.component';

export const routes: Routes = [
  {
    path: '',
    component: ParentComponent,
    children: [

      { path: '', redirectTo: 'child1', pathMatch: 'full' },

      {
        path: 'child1',
        loadChildren: () => import('../child1/child1.component').then(m =>
m.Child1Component)
      },
      {
        path: 'child2',
        loadChildren: () => import('../child2/child2.component').then(m =>
m.Child2Component)
      },
      {
        path: 'child3',
        loadChildren: () => import('../child3/child3.component').then(m =>
m.Child3Component)
      }
    ]
  },
  { path: '**', redirectTo: '' }
];
```

## App.component.ts

```
import { Component } from '@angular/core';
import { CommonModule } from '@angular/common';
import { RouterOutlet } from '@angular/router';
import { IonApp, IonContent } from '@ionic/angular/standalone';
import { TopBarComponent } from '../topbar/topbar.component';
import { FooterComponent } from '../footer/footer.component';

@Component({
  selector: 'app-root',
  templateUrl: './app.component.html',
  styleUrls: ['./app.component.scss'],
  standalone: true,
  imports: [
    CommonModule,
    IonApp,
    IonContent,
    RouterOutlet,
    TopBarComponent,
    FooterComponent
  ]
})
export class AppComponent {}
```

App.component.html

```
<ion-app>
  <div class="app-container">

    <div class="topbar-section">
      <app-topbar></app-topbar>
    </div>

    <ion-content class="main-content-section">

      <router-outlet></router-outlet>
    </ion-content>

    <div class="footer-section">
      <app-footer></app-footer>
    </div>

  </div>
</ion-app>
```

## App.component.scss

```
.app-container {
  display: flex;
  flex-direction: column;
  height: 100dvh;
  width: 100%;
  background-color: lightgoldenrodyellow;
  box-sizing: border-box;
  overflow: hidden;
}

.topbar-section {
  z-index: 10;
  position: relative;
  background-color: darkolivegreen;
  padding: 10px;
  width: 100%;
  box-sizing: border-box;
  flex-shrink: 0;
}

.navigation-section {
  z-index: 9;
  position: relative;
  background-color: darkolivegreen;
  padding: 10px;
  border-top: 1px solid rgba(255, 255, 255, 0.1);
  width: 100%;
  box-sizing: border-box;
  flex-shrink: 0;

  ul {
    display: flex;
    list-style: none;
    margin: 0;
    padding: 0;
    gap: 20px;

    li {
      a {
        color: lightgoldenrodyellow;
        text-decoration: none;
        font-weight: bold;
        padding-bottom: 4px;
        transition: color 0.2s ease;
        cursor: pointer;

        &:hover {
          color: white;
        }
      }
    }
  }
}
```

```

    }
  }
}
}

.main-content-section {
  z-index: 1;
  position: relative;
  flex: 1;
  padding: 20px;
  box-sizing: border-box;
  width: 100%;
  overflow-y: auto;
  -webkit-overflow-scrolling: touch;
}

.active-link {
  border-bottom: 2px solid lightgoldenrodyellow;
  color: white !important;
}

.footer-section {
  z-index: 10;
  display: block;
  width: 100%;
  flex-shrink: 0;
}

@media (max-width: 600px) {
  .navigation-section ul {
    justify-content: space-around;
    gap: 10px;

    li a {
      font-size: 0.9rem;
    }
  }
}

```

## Topbar.component.ts

```
import { Component } from '@angular/core';
import { Store } from '@ngrx/store';
import { NgForm, FormsModule } from '@angular/forms';
import { Observable } from 'rxjs';
import { CommonModule, AsyncPipe } from '@angular/common';
import { loadLocation, selectCity } from '../location-reducer';

import { MatFormFieldModule } from '@angular/material/form-field';
import { MatInputModule } from '@angular/material/input';
import { MatButtonModule } from '@angular/material/button';

@Component({
  selector: 'app-topbar',
  templateUrl: './topbar.component.html',
  styleUrls: ['./topbar.component.scss'],
  standalone: true,
  imports: [
    CommonModule,
    AsyncPipe,
    FormsModule,
    MatFormFieldModule,
    MatInputModule,
    MatButtonModule
  ]
})
export class TopBarComponent {
  public loc: string = '';
  public cityName$: Observable<string>;

  constructor(private store: Store) {

    this.cityName$ = this.store.select(selectCity);
  }

  public search(searchForm: NgForm): void {
    if (searchForm.invalid || !this.loc.trim()) return;

    this.store.dispatch(loadLocation({ cityName: this.loc.trim() }));

    this.loc = '';
    searchForm.resetForm();
  }
}
```



## Topbar.component.html

```
<header class="top-bar-wrapper">
  <div class="logo">
    <h2>
      <span class="app-icon"><img alt="Weather icon" data-bbox="405 155 425 170"/></span> WeerApp
      <span *ngIf="cityName$ | async as city" class="current-location">{{ city }}</span>
    </h2>
  </div>

  <form #searchForm="ngForm" (ngSubmit)="searchForm.valid &&
search(searchForm)" novalidate>
    <div class="form-layout">

      <mat-form-field appearance="outline" class="search-field">
        <mat-label>Zoek een locatie</mat-label>
        <input
          matInput
          id="locationInput"
          name="location"
          [(ngModel)]="loc"
          required
          autocomplete="off"
          placeholder="bijv. Amsterdam, Parijs"
          title="Invoerveld voor het zoeken naar een stad of locatie" />
      </mat-form-field>

      <button
        mat-flat-button
        type="submit"
        class="search-button"
        [disabled]="searchForm.invalid">
        Zoeken
      </button>

    </div>
  </form>
</header>
```

## Topbar.component.scss

```
.top-bar-wrapper {
  display: flex;
  align-items: center;
  justify-content: space-between;
  width: 100%;
  box-sizing: border-box;
  padding: 10px 20px;
  background-color: #556b2f;
  box-shadow: 0 2px 5px rgba(0, 0, 0, 0.1);

  .logo h2 {
    color: #fefefa;
    margin: 0;
    font-family: sans-serif;
    font-size: 1.3rem;
    display: flex;
    align-items: center;
    gap: 8px;

    .current-location {
      font-weight: normal;
      color: #fafad2;
    }
  }
}

form {
  margin: 0;

  .form-layout {
    display: flex;
    align-items: center;
    gap: 10px;

    ::ng-deep .mat-mdc-form-field-subscript-wrapper {
      display: none;
    }

    .search-field {
      width: 240px;

      ::ng-deep {
        .mdc-text-field--outlined:not(.mdc-text-field--disabled) .mdc-
notched-outline__leading,
        .mdc-text-field--outlined:not(.mdc-text-field--disabled) .mdc-
notched-outline__notch,
        .mdc-text-field--outlined:not(.mdc-text-field--disabled) .mdc-
notched-outline__trailing {
          border-color: rgba(255, 255, 255, 0.5);
        }
      }
    }
  }
}
```

```

    }
    .mdc-text-field--outlined:not(.mdc-text-field--disabled).mdc-text-
field--focused .mdc-notched-outline__leading,
    .mdc-text-field--outlined:not(.mdc-text-field--disabled).mdc-text-
field--focused .mdc-notched-outline__notch,
    .mdc-text-field--outlined:not(.mdc-text-field--disabled).mdc-text-
field--focused .mdc-notched-outline__trailing {
        border-color: #ffffff !important;
    }
    .mat-mdc-form-field-label {
        color: rgba(255, 255, 255, 0.8) !important;
    }
    .mdc-text-field--focused .mat-mdc-form-field-label {
        color: #ffffff !important;
    }
    input.mat-mdc-input-element {
        color: #ffffff;
    }
}

.search-button {
    height: 48px !important;
    background-color: #2c3e50 !important;
    color: white !important;
    font-weight: bold;
    border-radius: 4px;

    &.disabled {
        background-color: rgba(0, 0, 0, 0.12) !important;
        color: rgba(0, 0, 0, 0.26) !important;
    }
}

}

}

}

}

@media (max-width: 600px) {
    .top-bar-wrapper {
        flex-direction: column;
        gap: 12px;
        padding: 15px;
        text-align: center;

        .search-field {
            width: 100% !important;
        }
    }
}

```

## Parent.component.ts

```
import { Component, OnInit, inject, ViewChild, ElementRef } from
 '@angular/core';
import { Store } from '@ngrx/store';
import { Router, NavigationEnd, RouterModule, RouterOutlet } from
 '@angular/router';
import { CommonModule } from '@angular/common';
import { toSignal } from '@angular/core/rxjs-interop';
import { filter } from 'rxjs/operators';
import { selectCity } from '../location-reducer';
import { MatCardModule } from '@angular/material/card';
import { IonSegment, IonSegmentButton, IonLabel } from
 '@ionic/angular/standalone';

@Component({
  selector: 'app-parent',
  templateUrl: './parent.component.html',
  styleUrls: ['./parent.component.scss'],
  standalone: true,
  imports: [
    CommonModule,
    MatCardModule,
    RouterModule,
    RouterOutlet,
    IonSegment,
    IonSegmentButton,
    IonLabel
  ]
})
export class ParentComponent implements OnInit {
  private store = inject(Store);
  private router = inject(Router);

  @ViewChild('scrollTarget', { static: false }) scrollTarget!: ElementRef;

  cityName = toSignal(this.store.select(selectCity));
  activeTab: string = 'child1';

  ngOnInit(): void {
    this.updateActiveTab(this.router.url);

    this.router.events.pipe(
      filter((event): event is NavigationEnd => event instanceof
NavigationEnd)
    ).subscribe((event: NavigationEnd) => {
      this.updateActiveTab(event.url);

      setTimeout(() => {
        if (this.scrollTarget) {

```

```
        this.scrollTarget.nativeElement.scrollIntoView({
            behavior: 'smooth',
            block: 'start'
        });
    }
}, 50);
});
}

private updateActiveTab(url: string): void {
    if (!url) return;
    if (url.includes('child3')) {
        this.activeTab = 'child3';
    } else if (url.includes('child2')) {
        this.activeTab = 'child2';
    } else {
        this.activeTab = 'child1';
    }
}
}
```

## Parent.component.html

```
<!-- GEWIJZIGD: #scrollTarget referentie toegevoegd -->
<div #scrollTarget class="main-container">

  <div class="main-container">

    <!-- Welkom scherm (wanneer er nog GEEN locatie is gezocht) -->
    <div *ngIf="!cityName()" class="welcome-section">
      <mat-card>
        <mat-card-content class="welcome-content">
          <h1>🌤 Welkom bij de WeerApp</h1>
          <p>Voer hierboven in de balk een locatie in om de weersinformatie te
starten.</p>
        </mat-card-content>
      </mat-card>
    </div>

    <!-- Dashboard Container (Verschijnt in de body zodra de stad gekozen is) -
->
    <div *ngIf="cityName()">
      <header class="location-header">
        <h1>Weer Dashboard voor {{ cityName() }}</h1>
      </header>

      <!-- GEWIJZIGD: De '/' is verwijderd voor relatieve sub-routing binnen de
parent -->
      <ion-segment [value]="activeTab">
        <ion-segment-button value="child1" routerLink="child1">
          <ion-label>Huidig</ion-label>
        </ion-segment-button>
        <ion-segment-button value="child2" routerLink="child2">
          <ion-label>Toekomst</ion-label>
        </ion-segment-button>
        <ion-segment-button value="child3" routerLink="child3">
          <ion-label>UV-Score</ion-label>
        </ion-segment-button>
      </ion-segment>

      <!-- Subpagina router-outlet waar Child1, Child2 of Child3 in landen -->
      <main class="sub-page-outlet">
        <router-outlet></router-outlet>
      </main>

      <!-- Extra info card onderaan -->
      <mat-card class="signals-card">
        <mat-card-content class="signals-content">
          <h2>Live updates voor <strong>{{ cityName() }}</strong></h2>
          <p class="placeholder-text">Gegevens worden direct verwerkt via NgRx
Signals</p>
```

```
<hr />
<div class="badge-container">
  <button class="custom-badge-btn badge-success">Verversen</button>
  <button class="custom-badge-btn badge-warning">Favoriet ★</button>
</div>
</mat-card-content>
</mat-card>
</div>
</div>
```

## Parent.component.scss

```
/* --- HOOFD DASHBOARD CONTAINER --- */
.main-container {
  max-width: 900px;
  margin: 0 auto;
  padding: 15px;
  width: 100%;
  box-sizing: border-box;
  display: block;
  overflow: visible;
}

/* --- WELKOMSCHEM (WANNEER GEEN LOCATIE GEKOZEN IS) --- */
.welcome-section {
  text-align: center;
  padding: 20px 0;

  .welcome-content {
    display: block !important;
    padding: 40px 20px !important;

    h1 {
      color: #2c3e50;
      font-weight: bold;
    }
    p {
      color: #7f8c8d;
    }
  }
}

/* --- DASHBOARD HEADER MET DE STADSNAAM --- */
.location-header {
  text-align: center;
  margin-bottom: 25px;

  h1 {
    font-size: 2.2rem;
    font-weight: 800;
    color: #2c3e50;
    margin: 0;
  }
}

/* --- IONIC SEGMENT (MENUBALK IN DE BODY) --- */
ion-segment {
  margin-bottom: 20px;
  background: #ffffff !important;
  border-radius: 12px !important;
}
```



```

    box-shadow: 0 4px 12px rgba(0, 0, 0, 0.05) !important;
    padding: 4px;
    border: 1px solid #f0f3f4;
}

ion-segment-button {
  --color: #555555;
  --color-checked: darkolivegreen;
  --color-activated: darkolivegreen;
  --indicator-color: rgba(85, 107, 47, 0.15);
  font-weight: 600;

  &.segment-button-checked ion-label {
    color: darkolivegreen !important;
  }
}

/* --- SUBPAGINA ROUTER-OUTLET WRAPPER --- */
.sub-page-outlet {
  display: block;
  margin-top: 10px;
  height: auto;
  overflow: visible;
}

/* --- LIVE SIGNALS UPDATE CARD ONDERAAN --- */
.signals-card {
  margin-top: 20px;

  .signals-content {
    text-align: center;
    display: block !important;
    padding: 20px !important;

    h2 {
      margin: 0;
      font-size: 1.3rem;

      strong {
        color: darkolivegreen;
      }
    }

    .placeholder-text {
      color: #7f8c8d;
      font-style: italic;
    }

    hr {
      margin: 20px 0;
      border: 0;
    }
  }
}

```

```
border-top: 1px solid #e2e8f0;
}

/* BADGES (VERVERSEN & FAVORIET) */
.badge-container {
  display: flex;
  gap: 10px;
  justify-content: center;
  flex-wrap: wrap;

  .custom-badge-btn {
    border: none;
    cursor: pointer;
    padding: 8px 16px;
    font-size: 0.85rem;
    font-weight: bold;
    border-radius: 20px;
    transition: transform 0.2s ease;

    &:hover {
      transform: scale(1.05);
    }
  }
}
}
```

## Child1.component.ts

```
import { Component, OnInit, inject } from '@angular/core';
import { Store } from '@ngrx/store';
import { Observable, combineLatest } from 'rxjs';
import { map } from 'rxjs/operators';
import { selectCity, selectCurrentWeather, selectDailyWeather } from
'../location-reducer';

import { CommonModule, AsyncPipe, DecimalPipe, DatePipe } from
'@angular/common';
import { MatCardModule } from '@angular/material/card';

@Component({
  selector: 'app-child1',
  templateUrl: './child1.component.html',
  styleUrls: ['./child1.component.scss'],
  standalone: true,
  imports: [
    CommonModule,
    AsyncPipe,
    DecimalPipe,
    DatePipe,
    MatCardModule
  ]
})
export class Child1Component implements OnInit {
  private store = inject(Store);

  public weatherData$: Observable<any> | undefined;
  public loc$: Observable<string> = this.store.select(selectCity);

  constructor() {}

  ngOnInit(): void {
    this.weatherData$ = combineLatest([
      this.loc$,
      this.store.select(selectCurrentWeather),
      this.store.select(selectDailyWeather)
    ]).pipe(
      map(([name, current, daily]) => {
        if (!name || !current || !daily) return null;
        return { name, current, daily };
      })
    );
  }

  public parseDate(dateStr: string): Date {
    return dateStr ? new Date(dateStr) : new Date();
  }
}
```

## Child1.component.html

```
<div class="child-container">

  <div *ngIf="weatherData$ | async as data; else loadingOnError"
class="forecast-wrapper">
    <mat-card>
      <mat-card-header>
        <mat-card-title>Actuele weersituatie voor {{ data.name }}</mat-card-
title>
      </mat-card-header>
      <mat-card-content class="table-card-content">
        <table class="weather-table">
          <tbody>
            <tr><td><strong>Huidige
temperatuur</strong></td><td>{{ data.current?.temperature | number:'1.0-
0' }}°C</td></tr>
            <tr><td><strong>Windsnelheid</strong></td><td>{{ data.current?.win
dspeed }} km/h</td></tr>
            <tr><td><strong>Windrichting</strong></td><td>{{ data.current?.win
ddirection }}°</td></tr>
            <tr><td><strong>Maximum
(Vandaag)</strong></td><td>{{ data.daily?.temperature_2m_max[0] | number:'1.0-
0' }}°C</td></tr>
            <tr><td><strong>Minimum
(Vandaag)</strong></td><td>{{ data.daily?.temperature_2m_min[0] | number:'1.0-
0' }}°C</td></tr>
            <tr><td><strong>Zonsopgang</strong></td><td>{{ parseDate(data.dail
y?.sunrise[0]) | date:'HH:mm' }} uur</td></tr>
            <tr><td><strong>Zonsondergang</strong></td><td>{{ parseDate(data.d
aily?.sunset[0]) | date:'HH:mm' }} uur</td></tr>
          </tbody>
        </table>
      </mat-card-content>
    </mat-card>
  </div>

  <ng-template #loadingOnError>
    <mat-card class="loading-card" *ngIf="loc$ | async as city">
      <mat-card-content class="text-center-loading">
        Weergegevens ophalen voor <strong>{{ city }}</strong>...
      </mat-card-content>
    </mat-card>
  </ng-template>
</div>
```

Child1.component.scss

```
.child-container {  
  display: block;  
  width: 100%;  
}  
  
mat-card-content {  
  padding: 20px !important;  
}  
  
.table-card-content {  
  display: block !important;  
  padding: 15px 20px !important;  
}  
  
.text-center-loading {  
  display: block !important;  
  text-align: center;  
  color: #7f8c8d;  
}
```

## Child2.component.ts

```
import { Component, OnInit, inject } from '@angular/core';
import { Store } from '@ngrx/store';
import { Observable, combineLatest } from 'rxjs';
import { map } from 'rxjs/operators';
import { selectCity, selectDailyWeather } from '../location-reducer';

import { CommonModule, AsyncPipe, DecimalPipe, DatePipe } from
 '@angular/common';
import { MatCardModule } from '@angular/material/card';

@Component({
  selector: 'app-child2',
  templateUrl: './child2.component.html',
  styleUrls: ['./child2.component.scss'],
  standalone: true,
  imports: [
    CommonModule,
    AsyncPipe,
    DecimalPipe,
    DatePipe,
    MatCardModule
  ]
})
export class Child2Component implements OnInit {
  private store = inject(Store);

  public forecastData$: Observable<{ cityName: string; list: any[] } | null> |
  undefined;
  public loc$: Observable<string> = this.store.select(selectCity);

  constructor() {}

  ngOnInit(): void {
    this.forecastData$ = combineLatest([
      this.loc$,
      this.store.select(selectDailyWeather)
    ]).pipe(
      map(([city, daily]) => {
        if (!city || !daily || !daily.time) return null;

        const list = daily.time.map((timeStr: string, index: number) => ({
          date: new Date(timeStr),
          temp_max: daily.temperature_2m_max?.[index],
          temp_min: daily.temperature_2m_min?.[index],
          sunrise: daily.sunrise?.[index] ? new Date(daily.sunrise[index]) :
null,
          sunset: daily.sunset?.[index] ? new Date(daily.sunset[index]) :
null,

```

```
        uv: daily.uv_index_max?.[index] ?? null
    }));

    return { cityName: city, list };
  })
};
}}
```

## Child2.component.html

```
<div class="child-container">

  <div *ngIf="forecastData$ | async as data; else loading" class="forecast-
wrapper">
    <mat-card *ngIf="data.list && data.list.length > 0">
      <mat-card-header>
        <mat-card-title>7-daagse voorspelling voor {{ data.cityName }}</mat-
card-title>
      </mat-card-header>
      <mat-card-content class="table-card-content">

        <table class="weather-table intermediate-forecast-table">
          <thead>
            <tr class="table-header-row">
              <th class="text-left">Datum</th>
              <th>Min / Max temp</th>
              <th>Zon (Op / Onder)</th>
              <th class="text-right">UV</th>
            </tr>
          </thead>
          <tbody>
            <tr *ngFor="let day of data.list">
              <td class="text-left"><strong>{{ day.date | date:'EEEE d
MMMM' }}</strong></td>
              <td>{{ day.temp_min | number:'1.0-0' }}°C / {{ day.temp_max |
number:'1.0-0' }}°C</td>
              <td>
                <span *ngIf="day.sunrise">
                  🌅 {{ day.sunrise | date:'HH:mm' }} | 🌇 {{ day.sunset |
date:'HH:mm' }}
                </span>
              </td>
              <td class="text-right">
                <span [ngClass]="{
                  'badge-success': day.uv <= 2,
                  'badge-warning': day.uv > 2 && day.uv <= 5,
                  'badge-danger': day.uv > 5
                }">
                  {{ day.uv ?? '-' }}
                </span>
              </td>
            </tr>
          </tbody>
        </table>

      </mat-card-content>
    </mat-card>
  </div>
```



```
<ng-template #loading>
  <mat-card *ngIf="loc$ | async as city">
    <mat-card-content class="text-center-loading">
      Weergegevens ophalen voor <strong>{{ city }}</strong>...
    </mat-card-content>
  </mat-card>
</ng-template>

</div>
```

## Child2.component.scss

```
.child-container {
  display: block;
  width: 100%;
}

.table-card-content {
  display: block !important;
  padding: 15px 20px !important;
}

.text-center-loading {
  display: block !important;
  text-align: center;
  color: #7f8c8d;
  width: 100%;
}

.weather-table {
  width: 100%;
  border-collapse: collapse;
  margin-top: 5px;

  tr {
    border-bottom: 1px solid #f0f0f0;
    &:last-child { border-bottom: none; }
  }

  td {
    padding: 12px 4px;
    color: #2c3e50;
    font-size: 1rem;

    &:last-child {
      text-align: right;
    }
  }
}

.intermediate-forecast-table th {
  font-size: 0.9rem;
  text-transform: uppercase;
  letter-spacing: 0.5px;
}
```

### Child3.component.ts

```
import { Component, OnInit, inject } from '@angular/core';
import { Store } from '@ngrx/store';
import { Observable, combineLatest } from 'rxjs';
import { map } from 'rxjs/operators';
import { selectCity, selectDailyWeather } from '../location-reducer';

import { CommonModule, AsyncPipe, DecimalPipe, DatePipe } from
 '@angular/common';
import { MatCardModule } from '@angular/material/card';

@Component({
  selector: 'app-child3',
  templateUrl: './child3.component.html',
  styleUrls: ['./child3.component.scss'],
  standalone: true,
  imports: [
    CommonModule,
    AsyncPipe,
    DecimalPipe,
    DatePipe,
    MatCardModule
  ]
})
export class Child3Component implements OnInit {
  private store = inject(Store);

  public uvData$: Observable<{ cityName: string; list: any[] } | null> |
undefined;
  public loc$: Observable<string> = this.store.select(selectCity);

  constructor() {}

  ngOnInit(): void {
    this.uvData$ = combineLatest([
      this.loc$,
      this.store.select(selectDailyWeather)
    ]).pipe(
      map(([city, daily]) => {
        if (!city || !daily || !daily.time || !daily.uv_index_max) return
null;

        const list = daily.time.map((timeStr: string, index: number) => ({
          date: new Date(timeStr),
          value: daily.uv_index_max[index]
        }));

        return { cityName: city, list };
      })
    );
  }
}
```

```
    );  
  }  
  
  public getBadgeClass(value: number): string {  
    if (value <= 2) return 'badge-success';  
    if (value <= 5) return 'badge-warning';  
    return 'badge-danger';  
  }  
}
```

Child3.component.html

```
<div class="child-container">

  <div *ngIf="uvData$ | async as data; else loading" class="uv-dashboard-
wrapper">
    <div *ngIf="data.list && data.list.length > 0">
      <h2 class="grid-title">7-Daagse UV-Index voor {{ data.cityName }}</h2>

      <div class="uv-grid">
        <mat-card *ngFor="let item of data.list" class="uv-day-card">
          <mat-card-header>
            <mat-card-title class="card-date">{{ item.date | date:'EEEE d
MMMM' }}</mat-card-title>
          </mat-card-header>

          <mat-card-content class="card-score-content">
            <div class="uv-score-display">
              <h1 class="score-number">{{ item.value | number:'1.0-1' }}</h1>
            </div>
            <span [ngClass]="getBadgeClass(item.value)" class="uv-local-
badge">
              {{ item.value >= 3 ? 'Hoge UV - Smeer zonnebrand!' : 'Veilige
UV-waarde' }}
            </span>
          </mat-card-content>
        </mat-card>
      </div>

    </div>
  </div>

  <ng-template #loading>
    <mat-card *ngIf="loc$ | async as city">
      <mat-card-content class="text-center-loading">
        UV-gegevens ophalen voor <strong>{{ city }}</strong>...
      </mat-card-content>
    </mat-card>
  </ng-template>

</div>
```

### Child3.component.scss

```
.child-container {
  display: block;
  width: 100%;
}

.grid-title {
  font-size: 1.4rem;
  font-weight: 700;
  color: #2c3e50;
  margin: 0 0 20px 0;
}

.uv-grid {
  display: grid;
  grid-template-columns: repeat(auto-fit, minmax(240px, 1fr));
  gap: 16px;
  margin-bottom: 25px;
}

.uv-day-card {
  background: #ffffff !important;
  border-radius: 12px !important;
  border: 1px solid #e2e8f0;
  box-shadow: 0 4px 6px rgba(0, 0, 0, 0.02) !important;

  .card-date {
    font-size: 1rem;
    font-weight: 600;
    color: #7f8c8d;
    text-transform: capitalize;
  }
}

.card-score-content {
  display: flex !important;
  flex-direction: column;
  align-items: center;
  justify-content: center;
  text-align: center;
  padding: 15px 20px 20px 20px !important;

  .score-number {
    font-size: 3rem;
    font-weight: 800;
    color: #2c3e50;
    margin: 0 0 12px 0;
  }
}
```

```
.uv-local-badge {
  display: inline-block;
  padding: 6px 12px;
  font-size: 0.8rem;
  font-weight: 700;
  border-radius: 20px;
  color: #ffffff;
  width: 100%;
  box-sizing: border-box;
}

.badge-success { background-color: #2ecc71 !important; }
.badge-warning { background-color: #f39c12 !important; }
.badge-danger { background-color: #e74c3c !important; }

.text-center-loading {
  display: block !important;
  text-align: center;
  color: #7f8c8d;
  width: 100%;
}
```

### Footer.component.ts

```
import { Component } from '@angular/core';

@Component({
  selector: 'app-footer',
  templateUrl: './footer.component.html',
  styleUrls: ['./footer.component.scss'],
  standalone: true
})
export class FooterComponent {
  huidigeJaar: number = new Date().getFullYear();
}
```

### Footer.component.html

```
<div class="footer-container">
  <p class="footer-text">Overonedevries {{ huidigeJaar }} WeerApp – Alle
rechten voorbehouden.</p>
</div>
```

### Footer.component.scss

```
.footer-container {
  background-color: darkolivegreen;
  border-top: 3px solid #556b2f; // Sluit aan op je olijfgroene thema
  padding: 15px 20px;
  text-align: center;
  width: 100%;
  box-sizing: border-box;
}

.footer-text {
  margin: 0;
  color: #ecf0f1;
  font-size: 0.9rem;
  font-weight: 500;
}
```



Tsconfig.json

```
{
  "compileOnSave": false,
  "compilerOptions": {
    "outDir": "./dist/out-tsc",
    "forceConsistentCasingInFileNames": true,
    "strict": true,
    "noImplicitOverride": true,
    "noPropertyAccessFromIndexSignature": false,
    "noImplicitReturns": true,
    "noFallthroughCasesInSwitch": true,
    "sourceMap": true,
    "declaration": false,
    "experimentalDecorators": true,
    "moduleResolution": "bundler",
    "importHelpers": true,
    "target": "ES2022",
    "module": "ES2022",
    "lib": [
      "ES2022",
      "dom"
    ],
    "skipLibCheck": true,
    "useDefineForClassFields": false
  },
  "angularCompilerOptions": {
    "enableI18nLegacyMessageIdFormat": false,
    "strictInjectionParameters": true,
    "strictInputAccessModifiers": true,
    "strictTemplates": true
  }
}
```

Tsconfig.app.json

```
{
  "extends": "../tsconfig.json",
  "compilerOptions": {
    "outDir": "../out-tsc/app",
    "types": []
  },
  "files": [
    "src/main.ts"
  ],
  "include": [
    "src/**/*.d.ts",
    "src/**/*.ts"
  ],
  "exclude": [
    "src/test.ts",
    "src/environments/environment.ts",
    "src/environments/environment.prod.ts",
    "src/app/parent/parent.component.ts"
  ]
}
```

## Package.json

```
{
  "name": "weer_mobiele_app",
  "version": "0.0.1",
  "author": "Ionic Framework",
  "homepage": "https://ionicframework.com/",
  "scripts": {
    "ng": "ng",
    "start": "ng serve",
    "build": "ng build",
    "watch": "ng build --watch --configuration development",
    "test": "ng test",
    "lint": "ng lint"
  },
  "private": true,
  "dependencies": {
    "@angular/animations": "^20.0.0",
    "@angular/cdk": "^20.2.14",
    "@angular/common": "^20.0.0",
    "@angular/compiler": "^20.0.0",
    "@angular/core": "^20.0.0",
    "@angular/forms": "^20.0.0",
    "@angular/material": "^20.2.14",
    "@angular/platform-browser": "^20.0.0",
    "@angular/platform-browser-dynamic": "^20.0.0",
    "@angular/router": "^20.0.0",
    "@capacitor/app": "8.1.0",
    "@capacitor/core": "8.4.0",
    "@capacitor/haptics": "8.0.2",
    "@capacitor/keyboard": "8.0.3",
    "@capacitor/status-bar": "8.0.2",
    "@ionic/angular": "^8.0.0",
    "@ngrx/effects": "^20.1.0",
    "@ngrx/store": "^20.1.0",
    "ionicons": "^7.0.0",
    "rxjs": "~7.8.0",
    "tslib": "^2.3.0",
    "zone.js": "~0.15.0"
  },
  "devDependencies": {
    "@angular-devkit/build-angular": "^20.0.0",
    "@angular-eslint/builder": "^20.0.0",
    "@angular-eslint/eslint-plugin": "^20.0.0",
    "@angular-eslint/eslint-plugin-template": "^20.0.0",
    "@angular-eslint/schematics": "^20.0.0",
    "@angular-eslint/template-parser": "^20.0.0",
    "@angular/cli": "^20.0.0",
    "@angular/compiler-cli": "^20.0.0",
    "@angular/language-service": "^20.0.0",
  }
}
```

```
"@capacitor/cli": "8.4.0",
"@ionic/angular-toolkit": "^12.0.0",
"@types/jasmine": "~5.1.0",
"@typescript-eslint/eslint-plugin": "^8.18.0",
"@typescript-eslint/parser": "^8.18.0",
"eslint": "^9.16.0",
"eslint-plugin-import": "^2.29.1",
"eslint-plugin-jsdoc": "^48.2.1",
"eslint-plugin-prefer-arrow": "1.2.2",
"jasmine-core": "~5.1.0",
"jasmine-spec-reporter": "~5.0.0",
"karma": "~6.4.0",
"karma-chrome-launcher": "~3.2.0",
"karma-coverage": "~2.2.0",
"karma-jasmine": "~5.1.0",
"karma-jasmine-html-reporter": "~2.1.0",
"typescript": "~5.9.0"
},
"description": "An Ionic project"
}
```

