

WIC API Examples

General Information

Examples

Read Data

[Get Inventory Item by Name](#)

[Get Inventory Item with additional Data](#)

[Read all Log Entries](#)

[Read all task with Filter](#)

[Get Inventory with entity Filter](#)

Write Data

[Create an item in inventory](#)

[Update an item in inventory](#)

General Information [🔗](#)

On this page are more examples for the use of the WHINT Integration Cockpit API and how it is possible to get more specific data from the API.

Examples [🔗](#)

Read Data [🔗](#)

Get Inventory Item by Name [🔗](#)

Read all items from inventory, where the name contains the word “Connect”

Request:

```
1 {
2   "query": {
3     "entity": "inventory",
4     "fields": ["name", "sender_name", "receiver_name", "description", "type"],
5     "where": [{
6       "option": 1,
7       "conditions": [
8         {
9           "field": {
10            "name": "name",
11            "like": "Connect"
12          }
13        }
14      ]
15    }],
16    "limit": 300,
17    "offset": 0
18  }
19 }
```

Response:

```
1 [
2   {
```

```

3      "id": "aq8j_F61YSA",
4      "type": 21,
5      "name": "Just Connect >> easysoft. Competence 16.06.02 ",
6      "sender_name": "Just Connect"
7  },
8  {
9      "id": "Mx0knF2Rans",
10     "type": 19,
11     "name": "CALM XML Mapping_Test_Connection"
12 },
13 {
14     "id": "U9_1KhSIAS0",
15     "type": 21,
16     "name": "WHINT IFC Cloud Connector | D-9HfdPPNg"
17 },
18 ...
19 ]

```

Get Inventory Item with additional Data [🔗](#)

Read all inventory items with properties and metadata as additional data.

Request:

```

1  {
2    "query": {
3      "entity": "inventory",
4      "fields": ["name", "sender_name", "receiver_name", "description", "type"],
5      "with": [
6        {
7          "entity": "metadata",
8          "fields": ["name", "value"]
9        },
10       {
11         "entity": "properties",
12         "fields": ["type_id", "value"]
13       }
14     ]
15   }
16 }

```

Response:

```

1  [
2    {
3      "id": "a0iNYYruYkw",
4      "type": 19,
5      "name": "Demo_flow_5",
6      "metadata": [
7        {
8          "id": "E0yJC50l0uc",
9          "name": "Created",
10         "value": "2024-09-18 (S0015449940)",
11         "inventory_id": "a0iNYYruYkw"
12       },
13       {
14         "id": "aMeTTy2adWc",
15         "name": "Changed",

```

```

16         "value": "2024-09-18 (S0015449940)",
17         "inventory_id": "a0iNYYruYkw"
18     },
19     {
20         "id": "QWZ5XBGP3Ac",
21         "name": "Package",
22         "value": "DEMO End To End iflow",
23         "inventory_id": "a0iNYYruYkw"
24     },
25     ...
26 ],
27 "properties": [
28     {
29         "id": "0lxmKkrmAus",
30         "value": "Demo_flow_5",
31         "type_id": "2cmCEqbv7Hf4WETpH2qyCnacaX0",
32         "inventory_id": "a0iNYYruYkw"
33     }
34 ]
35 },
36 ...
37 ]

```

Read all Log Entries [🔗](#)

Request:

```

1 {
2   "query": {
3     "entity": "logEntry"
4   }
5 }

```

Response:

```

1 [
2   {
3     "id": "Q1lGVZQ149Y",
4     "create_time": "2024-11-09T12:00:00Z",
5     "change_time": "2024-11-09T12:00:00Z",
6     "level": 1,
7     "message": "starting task"
8   },
9   {
10    "id": "KWZHripd_hI",
11    "create_time": "2024-11-09T12:00:01Z",
12    "change_time": "2024-11-09T12:00:01Z",
13    "level": 1,
14    "message": "task finished"
15  },
16  {
17    "id": "dW0R0n5emic",
18    "create_time": "2024-11-09T12:00:01Z",
19    "change_time": "2024-11-09T12:00:01Z",
20    "level": 1,
21    "message": "rescheduling next run"
22  },

```

```
23 ...
24 ]
```

Read all task with Filter [🔗](#)

Read all tasks, with the related failed runs

Request:

```
1 {
2   "query": {
3     "entity": "task",
4     "fields": [],
5     "with": [
6       {
7         "entity": "runs",
8         "where" : [{
9           "option" : 1,
10          "conditions" : [
11            {
12              "field" : {
13                "name" : "successful",
14                "eq" : "false"
15              }
16            }
17          ]
18        }]
19      }
20    ]
21  }
22 }
```

Response:

```
1 [
2   {
3     "id": "yusZtg",
4     "create_time": "2024-03-05T12:59:55Z",
5     "change_time": "2024-05-31T14:41:01Z",
6     "start_date": "2024-01-01T00:00:00Z",
7     "data_source_id": "p8g5Qw"
8   },
9   {
10    "id": "sVmtMA",
11    "create_time": "2024-03-05T15:57:38Z",
12    "change_time": "2024-05-31T14:41:01Z",
13    "type": 1,
14    "start_date": "2024-01-01T00:00:00Z",
15    "data_source_id": "p8g5Qw",
16    "runs": [
17      {
18        "id": "QWBxY10fstk",
19        "create_time": "2024-07-16T12:40:50Z",
20        "change_time": "2024-07-16T12:40:50Z",
21        "start_time": "2024-07-16T12:40:47Z",
22        "end_time": "2024-07-16T12:40:49Z",
23        "duration": 2267955853,
24        "task_id": "sVmtMA"
```

```

25     },
26     {
27         "id": "MsE0bpwveu8",
28         "create_time": "2024-07-25T09:01:08Z",
29         "change_time": "2024-07-25T09:01:08Z",
30         "start_time": "2024-07-25T09:01:04Z",
31         "end_time": "2024-07-25T09:01:07Z",
32         "duration": 3175619586,
33         "task_id": "sVmtMA"
34     },
35     ...
36 ]
37 },
38 {
39     "id": "JaPVFTyUyww",
40     "create_time": "2024-06-04T09:55:11Z",
41     "change_time": "2024-06-06T08:52:50Z",
42     "start_date": "2024-06-04T09:55:07Z",
43     "data_source_id": "YvWd8qFAeZk"
44 },
45 ...
46 ]

```

In this response, only the tasks which has failed runs will have a child object “runs: [..]”.

Get Inventory with entity Filter [🔗](#)

This is a more advanced and complex request with the following parameter:

Read all inventory items

- where:
 - Sender or Receiver has a specific datasource (by name)
 - type is not type “21” (EAM) or “13” (PLANNED)
- with
 - sender / receiver Datasource name
 - metadata
 - properties
 - objects
 - tags

Request

```

1  {
2    "query": {
3      "entity": "inventory",
4      "fields": ["name", "sender_name", "receiver_name", "description", "type"],
5      "where": [{
6        "conditions": [
7          {
8            "entity": {
9              "name": "sender",
10             "predicates": [{
11               "conditions": [{
12                 "field": {
13                   "name": "data_source_id",
14                   "like": "djtSuXNusGA"
15                 }

```

```

16         }]
17     }]
18 }
19 },
20 {
21     "entity": {
22         "name": "receiver",
23         "predicates": [{
24             "conditions": [{
25                 "field": {
26                     "name": "data_source_id",
27                     "like": "djtSuXNusGA"
28                 }
29             }]
30         }]
31     }
32 },
33 {
34     "not": true,
35     "field": {
36         "name": "type",
37         "eq": "21"
38     }
39 },
40 {
41     "not": true,
42     "field": {
43         "name": "type",
44         "eq": "21"
45     }
46 }
47 ]
48 }],
49 "with": [
50     {
51         "entity": "dataSource",
52         "fields": ["name"]
53     },
54     {
55         "entity": "sender",
56         "with": [
57             {
58                 "entity" : "dataSource",
59                 "fields": ["name"]
60             }
61         ]
62     },
63     {
64         "entity": "receiver",
65         "with" : [
66             {
67                 "entity" : "dataSource",
68                 "fields": ["name"]
69             }
70         ]
71     },
72     {
73         "entity": "metadata",

```

```

74         "fields": ["name", "value"]
75     },
76     {
77         "entity": "properties",
78         "fields": ["type_id", "value"]
79     },
80     {
81         "entity": "objects",
82         "fields": ["id", "name", "description"]
83     },
84     {
85         "entity": "tags"
86     }
87 ]
88 }
89 }

```

Response:

```

1  [
2      {
3          "id": "FXtX7taqAnM",
4          "type": 19,
5          "name": "WHINT IMS",
6          "description": "for Bee360 API.",
7          "sender_id": "ej3dkdcynfY",
8          "sender_name": "Enterprise Alert",
9          "receiver_id": "J0pnb9qjH0g",
10         "receiver_name": "SAP NetWeaver",
11         "data_source_id": "EjA9oQ",
12         "data_source": {
13             "id": "EjA9oQ",
14             "name": "CPI CF FreeTier"
15         },
16         "sender": {
17             "id": "ej3dkdcynfY",
18             "create_time": "2024-10-29T08:28:22Z",
19             "change_time": "2024-10-29T08:28:22Z",
20             "name": "Enterprise Alert",
21             "description": "The software is used for the prevention of incidents in our company systems, which
are e.g. IT monitoring systems (e.g. Microsoft Operations Manager), production control systems, process
control systems, building management, etc, to ensure automated alarms and notifications via various
communication channels to previously defined or dynamically determined locations and persons and to enable
mobile incident response. Alarming processes are mainly triggered by external events (e.g. IT failures,
disturbances in the production process, etc.",
22             "data_source_id": "djtSuXNusGA",
23             "data_source": {
24                 "id": "djtSuXNusGA",
25                 "name": "BEE360"
26             }
27         },
28         "receiver": {
29             "id": "J0pnb9qjH0g",
30             "create_time": "2024-10-29T08:28:22Z",
31             "change_time": "2024-10-29T08:28:22Z",
32             "name": "SAP NetWeaver",

```

```

33     "description": "Netweaver is the runtime environment for the SAP applications, and all of the
mySAP Business Suite runs on SAP WebAS: supplier relationship management (SRM), customer relationship
management (CRM), supply chain management (SCM), product lifecycle management (PLM), enterprise resource
planning (ERP), transportation management system (TMS) .",
34     "data_source_id": "djtSuXNusGA",
35     "data_source": {
36         "id": "djtSuXNusGA",
37         "name": "BEE360"
38     }
39 },
40 "metadata": [
41     {
42         "id": "dAQu09-1tNU",
43         "name": "Adapter",
44         "value": "HTTP Mail ProcessDirect XI",
45         "inventory_id": "FXtX7taqAnM"
46     },
47     {
48         "id": "CFsPWVP0jtg",
49         "name": "Adapters",
50         "value": "HTTP, Mail, ProcessDirect, XI",
51         "inventory_id": "FXtX7taqAnM"
52     },
53     ...
54 ],
55 "properties": [
56     {
57         "id": "VGpweSU3Q5k",
58         "value": "2027",
59         "type_id": "aXJD8pABA-c",
60         "inventory_id": "FXtX7taqAnM"
61     },
62     ...
63 ],
64 "tags": [
65     {
66         "id": "CHSjIsY0udQ",
67         "create_time": "2024-06-13T07:18:36Z",
68         "change_time": "2024-10-16T07:37:37Z",
69         "value": "DE",
70         "tag_id": "KUz6tinWcc8"
71     },
72     ...
73 ]
74 }
75 ]

```

Write Data [🔗](#)

Create an item in inventory [🔗](#)

Request:

```

1  {
2    "upsert": {
3      "inventory": [
4        {

```



```
5     "name": "SAP EM Router",
6     "description": "",
7     "type": 16
8   }
9 ]
10 }
11 }
```

Response:

```
1 [
2   "eoF-BJHppnA"
3 ]
```

Update an item in inventory [🔗](#)

Update the description of the item.

Request:

```
1 {
2   "upsert": {
3     "inventory": [
4       {
5         "id": "eoF-BJHppnA",
6         "name": "SAP EM Router",
7         "description": "Routes XML documents between SAP Event Mesh and other EM"
8       }
9     ]
10  }
11 }
```

Response:

```
1 [
2   "eoF-BJHppnA"
3 ]
```