



QUOTATION			
SELLER ZHENGZHOU CY SCIENTIFIC INSTRUMENT CO.,LTD Tel: 86-0371-55199322 Fax: 86-0371-86036875 Email: shirley@cysi.wang		REF NO.: CYG200521 DATE: 2020-5-21	
BUYER			
Goods name	Specification	Price (FOB Zhengzhou)	Pictures
Induction heater	25KW	2286USD	
Shipping cost by courier(door-to-door delivery)		457USD	
Total		2743USD	
1.Delivery time: one week after receiving the payment			
2.Payment: T/T in advance			
3.Warranty: one year with whole life technical support			
4. PLY Wooden Box with FOAM			
5.Price valid: 25 days			

****Picture is only for reference, our company reserve the right to upgrade the product without prior notice****

25KW (30-80kHz) Induction Heating System with Timer Control



CY-SP-25BD induction heater features the latest inverting technology so as to make itself light and convenient. Its 25KW Induction Heater is designed for the material research lab to quickly melt and perform heat treating to metallic materials.

Induction Heater	Working Voltage: 220V AC, 50/ 60Hz, Three Phases (380VAC, 3phase available upon request) Working Current: 10~86 Amps (100A breaker required) Max. Input Power: 25 KW Output Frequency: 30 - 80 kHz Duty Cycle: 100% Induction Coil: 150mm(OD) x 140mm(ID) x 65mm(H) Air Cooling: Rear Fan Protection: Automatic water pressure, over temperature, and overpower protection Refractory Assembling: Complete refractory assembling made of alumina, including bottom crucible support, crucible holder, and cover
Timer Control	Automatic timer control or Manual control selectable Manual Control: by Foot Pedal Automatic Heating Time: 1-99 Seconds Automatic Dwell Time: 1-99 Seconds Automatic Cooling Time: 1-99 Seconds



Temp. Controller & Thermocouple (optional)	Precision digital temperature controller with Automatic PID tuning 30 segments programmable for controlling heating and cooling rate as well as dwell time. Overheating & thermocouple failure protection. +/- 3°C temperature accuracy. +/- 3°C temperature accuracy. Thermocouple: C type (1/4"x10"L) Continuous Working Temp. Range: 1000°C~1900°C Max. Working Temperature: 2000°C (for less than an hour) Max. Heating Rate: 4°C/second (1000°C-1200°C) 3°C/second (1200°C~1500°C) 1°C~2°C/second (1500°C~2000°C)
Water Cooling	Flowrate: >10 L/Min Pressure: ≥0.2 MPa (29 Psi) Tap water is acceptable, but using Recirculating Water Chiller is highly recommended. Protection: Overpressure and over temperature switch Water Chiller (optional) Temperature range: 5 - 30°C Water Flow Rate: > 58 L/m Note: It is recommended to use a specific coolant to get the best performance.
Warranty	One year limited warranty with lifetime support Consumable parts such as processing tube, thermocouple, refractory liners, o-rings, and heating coil are not covered by the warranty

Have any need and question, please feel free to contact us via shirley@cysi.wang