

~~Utah NASA Space Grant Consortium Fellowship~~ ~~Proposal~~ Multi-Material 3D-Printed Tensegrity Energy Absorbers for Planetary Landing and CubeSat Payload Protection

~~Working Title~~ ~~— To Be Finalized~~ Utah NASA Space Grant Consortium Fellowship
Proposal, 2026–2027

Marcus Madsen, Undergraduate Researcher, Mechanical Engineering
Faculty Advisor: Sterling G. Baird, Department of Mechanical Engineering
Brigham Young University May 7, 2026

1 Introduction and Motivation

~~[TODO: Open with the problem statement and motivate why this research matters to NASA and~~

I am applying for a Utah NASA Space Grant Consortium fellowship to support a year of focused undergraduate research on multi-material 3D-printed tensegrity-inspired structures for spacecraft and payload energy absorption. Every NASA mission that lands on a planet, returns a sample to Earth, or deploys a CubeSat from a launch vehicle has to dissipate a large pulse of kinetic energy in a very short time. Mars 2020 landed on aluminum-honeycomb crush pads; the OSIRIS-REx sample-return capsule used a crushable composite heat shield; CubeSats and instruments routinely sit on foam or elastomer isolators to survive launch loads [National Aeronautics and Space Administration, 2022]. These incumbent energy-absorbers work, but they are heavy, single-use, and tuned to a narrow load profile.

Tensegrity-inspired structures—networks of rigid struts suspended in a continuous web of tension elements—offer a promising alternative. NASA Ames’ *Super Ball Bot* project has demonstrated that tensegrity geometries can survive impacts that would destroy a comparable rigid lander and can be tuned for landing, mobility, and packaging in a single structure [Sabelhaus et al., 2015, Vespignani et al., 2018]. What has been missing is a fast, low-cost way to design and *experimentally* validate tensegrity-inspired geometries against NASA-relevant impact scenarios. Recent work shows that tensegrity-inspired unit cells can be directly 3D-printed on consumer-grade FDM hardware and retain a load-limiting plateau under drop-weight impact [Pajunen et al., 2019]. Multi-material rigid-soft FDM (rigid struts + flexible tension skins) yields tunable energy absorption without delamination [Ye et al., 2023, Khatri and Ebrahimi, 2023], and our group has access to a dual-nozzle **Bambu Lab H2D** printer that makes this multi-material workflow practical at undergraduate-friendly throughput.

I propose to use that capability to run a focused, year-long print-test-optimize campaign aimed squarely at two NASA-relevant load cases: (1) low-velocity *lander-class* crush attenuation and (2) launch-/deployment-class *shock isolation* for small-payload (CubeSat scale) hardware. This work directly supports the Utah NASA Space Grant Consortium’s mission of preparing students for the NASA workforce and aligns with NASA Space Technology Mission Directorate (STMD) priorities in advanced manufacturing, lightweight structures, and entry/descent/landing (EDL) systems [National Aeronautics and Space Administration, 2022]. ~~[NOTE: Refine this NASA-priority paragraph]~~

2 Background and Relation to NASA ~~/Space~~ Priorities

~~[TODO: Summarize the relevant scientific and engineering background, cite prior work, and explicitly~~

Tensegrity in space systems. Tensegrity structures [Skelton and de Oliveira, 2009, Sultan, 2009] have a long history in NASA-funded research. SunSpiral, Agogino, and collaborators at NASA Ames proposed tensegrity-based planetary probes that combine landing and surface mobility in a single deployable structure [Sabelhaus et al., 2015, Vespignani et al., 2018]. Pajunen et al. [Pajunen et al., 2019] showed that 3D-printable *tensegrity-inspired* unit cells exhibit a long plateau in their force–displacement response under drop-weight impact—exactly the behavior desired in a crush core, where peak transmitted force must stay below a hardware/biological tolerance. Compared to honeycomb or foam, tensegrity geometries can be *tuned* (struts, cables, topology) without changing manufacturing process, opening the door to mission-specific designs.

~~A representative early citation to verify the bibliography pipeline: [?Skelton and de Oliveira, 2009]~~

Multi-material 3D printing as an enabling technology. In-space manufacturing is an active NASA priority: the ISS has hosted FDM printers since 2014, and on-demand fabrication is expected to be central to long-duration missions [Prater et al., 2019]. Demonstrating that tensegrity energy-absorbers can be reliably produced on a single FDM platform with two materials (PLA struts + TPU tension elements) contributes to that broader trajectory while staying achievable within a single fellowship year. The **Bambu Lab H2D**’s dual-nozzle architecture and Automatic Material System let me switch between rigid PLA and flexible TPU within a single print, dramatically reducing iteration time on each new geometry. I expect to print on the order of **50–100 specimens** over the year.

Bayesian optimization of impact-absorbers. The design space (strut diameter and length, TPU skin thickness, tiling and topology) is too large to sweep exhaustively, and physical specimens are expensive in time, not just filament. Bayesian optimization (BO) [Shahriari et al., 2016, Frazier, 2018] fits the problem: each printed specimen updates a Gaussian process surrogate that recommends the next geometry to print and test. BO has been applied to architected and metamaterial design [Mo et al., 2023] and to closed-loop materials discovery in domains ranging from concrete [Ament et al., 2023] to organic emitters [Strieth-Kalthoff et al., 2024]; here I apply it directly to a NASA-relevant impact-attenuation problem.

3 Research Objectives

~~[TODO: State 2–3 concrete, measurable objectives for the fellowship year.]~~

I have three concrete, measurable objectives for the fellowship year:

1. ~~Objective 1.~~**Build a parameterized tensegrity-inspired unit-cell family** that prints reliably on the Bambu Lab H2D in PLA + TPU, with verified geometric fidelity (CT or caliper-and-mass) on at least 5 baseline geometries.
2. ~~Objective 2.~~**Quantify NASA-relevant impact response** for ≥ 30 distinct geometries via quasi-static compression and drop-weight tests, extracting peak transmitted force, specific energy absorption (SEA), and crush-plateau efficiency. Compare against a 3D-printed honeycomb baseline of equal areal density.
3. ~~Objective 3.~~**Close the loop with Bayesian optimization** to find geometries that minimize peak transmitted force at a target SEA for two NASA-motivated load cases: a low-velocity “lander” drop ($\sim 3\text{--}6\text{ m/s}$, $20\text{--}50\text{ J}$) and a high-frequency “CubeSat” shock pulse [NASA Goddard Space Flight C

4 Proposed Approach and Methods

~~[TODO: Describe the methodology: experimental setup, computational tools, data collection plan,~~

Design. I will parameterize a family of tensegrity-inspired unit cells in Fusion 360—strut diameter and length, TPU skin thickness, connectivity topology, and tiling pattern—following the wrapping-based core/skin strategy of Ye et al. [Ye et al., 2023] so that PLA struts remain mechanically interlocked with continuous TPU tension members and do not delaminate under cyclic loading [Khatri and Egan, 2024]

~

Task Plan

~~[TODO: Replace placeholder tasks with the actual milestones.]~~ **Fabrication.** All specimens will be printed on the Bambu Lab H2D in our lab, using its dual-nozzle, multi-material capability to produce PLA + TPU parts in a single build. I will keep a **print log** (slicer settings, AMS routing, post-print mass and geometric checks) so that downstream test data can be traced back to a specific build configuration. Early in the year I will validate PLA-TPU interface robustness on a reduced set of test coupons before committing to full unit-cell prints.

Testing. Two complementary protocols, both NASA-relevant:

- *Quasi-static compression* on a benchtop universal testing machine to extract force-displacement curves, plateau stress, and densification strain (analogous to the characterization done for honeycomb crush cores in EDL design).
- *Drop-weight impact* from instrumented fixed-mass drops to measure peak transmitted force and SEA at lander-relevant velocities, following the protocol of Pajunen et al. [Pajunen et al., 2019]. A piezoelectric accelerometer or load cell at the base captures the transmitted pulse.

A 3D-printed aluminum-equivalent honeycomb baseline of equal areal density will be tested under the same conditions to anchor performance claims to a NASA incumbent.

Bayesian optimization loop. I will implement a BO loop in Python using BoTorch / Ax [Balandat et al., 2020] that operates directly on experimental measurements. Each round of physical tests updates a Gaussian process surrogate; the acquisition function (expected hypervolume improvement for the multi-objective peak-force / SEA trade-off) recommends the next batch of ~ 3 – 5 designs to print and test. This closed loop is the experimental analogue of the multifidelity BO framework of Mo et al. [Mo et al., 2023], but here grounded entirely in physical data so that conclusions are not limited by simulation fidelity—an important property for NASA-relevant impact problems where rate-dependent TPU damping is hard to model accurately.

Quarterly Task Plan

5 Expected Outcomes and Broader Impact

~~[TODO: Describe deliverables (data sets, code, conference paper, manuscript, poster at the annual~~

By the end of the fellowship year I expect to deliver: (i) a publicly released data set of ~ 50 – 100 PLA/TPU tensegrity-inspired specimens with quasi-static and drop-weight impact characterization, (ii) an open-source Python implementation of the experimental BO loop, and (iii) a poster or talk at the annual UNSGC conference (a deliverable required of all Space Grant fellows) and a draft journal manuscript targeting *Smart Materials and Structures* or the *ASME Journal of Mechanical Design*.

The broader impact is twofold. Scientifically, this is an early empirical demonstration that an undergraduate, with a single multi-material FDM printer and a Bayesian optimization loop, can

Task	Q1 (Fa)	Q2 (Wi)	Q3 (Sp)
Literature review and NASA load-case scoping	•		
Experimental /computational setup Bambu H2D PLA/TPU print process validation	•	•	
Data collection and analysis Unit-cell parameterization and CAD	•	•	
Quasi-static compression campaigns		•	•
UNSGC Drop-weight impact testing			•
BO-guided design iteration			•
UNSGC annual conference presentation			•
Manuscript / final report Final report and manuscript preparation			•

Table 1: Quarterly task plan for the 2026–2027 fellowship year(~~placeholder~~). [Q1 = Fall 2026, Q2 = Winter 2027, Q3 = Spring 2027, Q4 = Summer 2027.](#)

[systematically discover impact attenuators that out-perform a NASA-incumbent geometry on a relevant load case. Educationally, this fellowship would give me hands-on training in exactly the skills NASA’s strategic plan calls out for the future workforce \[National Aeronautics and Space Administration, 2021\]: multi-material additive manufacturing, mechanical testing, and data-driven design. I plan to use the experience as a springboard into graduate study in aerospace structures or in-space manufacturing.](#)

6 Qualifications and Mentoring Plan

~~[TODO: Briefly describe Marcus’s preparation (coursework, GPA, prior research or projects) and~~

[My background. \[TODO: Marcus to fill in: current year \(e.g., sophomore/junior\), GPA, relevant course](#)

[Mentoring structure. I will work under Prof. Sterling G. Baird in the Department of Mechanical Engineering, with weekly one-on-one meetings \(30 min\) for technical guidance and professional development, and weekly lab group meetings \(1 hr\) covering progress updates, literature, and skill workshops. Prof. Baird’s master’s student will provide day-to-day co-mentoring on the Bambu H2D, mechanical testing equipment, and the Python BO codebase. I will keep a public lab notebook \(GitHub\) and present progress monthly to the lab. The PI will provide the required 50% non-federal cost share from laboratory startup funds.](#)

References

- Sebastian Ament, Andrew Witte, Nishant Garg, and Julius Kusuma. Sustainable concrete via Bayesian optimization. *arXiv preprint arXiv:2310.18288*, 2023. URL <https://arxiv.org/abs/2310.18288>. NeurIPS 2023 Workshop on Adaptive Experimental Design and Active Learning in the Real World.
- Maximilian Balandat, Brian Karrer, Daniel R. Jiang, Samuel Daulton, Benjamin Letham, Andrew Gordon Wilson, and Eytan Bakshy. BoTorch: A framework for efficient Monte-Carlo Bayesian optimization. In *Advances in Neural Information Processing Systems 33 (NeurIPS 2020)*, 2020. URL <https://arxiv.org/abs/1910.06403>.
- Peter I. Frazier. A tutorial on Bayesian optimization. *arXiv preprint arXiv:1807.02811*, 2018. URL <https://arxiv.org/abs/1807.02811>.
- Nava Raj Khatri and Paul F. Egan. Energy absorption of 3D printed ABS and TPU multimaterial

- honeycomb structures. *3D Printing and Additive Manufacturing*, 11:e840–e850, 2024. doi: 10.1089/3dp.2022.0196.
- Changyu Mo, Paris Perdikaris, and Jordan R. Raney. Accelerated design of architected materials with multifidelity Bayesian optimization. *Journal of Engineering Mechanics*, 149(6):04023028, 2023. doi: 10.1061/JENMDT.EMENG-7033.
- NASA Goddard Space Flight Center. General environmental verification standard (GEVS) for GSFC flight programs and projects. GSFC-STD-7000B, 2019. URL <https://standards.nasa.gov/standard/GSFC/GSFC-STD-7000>.
- National Aeronautics and Space Administration. NASA 2022 strategic plan. NP-2022-02-3066-HQ, 2022. URL <https://www.nasa.gov/wp-content/uploads/2023/09/fy-22-strategic-plan-1.pdf>.
- Kirsti Pajunen, Paul Johanns, Raj Kumar Pal, Julian J. Rimoli, and Chiara Daraio. Design and impact response of 3D-printable tensegrity-inspired structures. *Materials & Design*, 182:107966, 2019. doi: 10.1016/j.matdes.2019.107966.
- Tracie Prater, Niki Werkheiser, Frank Ledbetter, Doga Timucin, Kevin Wheeler, and Michael Snyder. Summary report on phase I and phase II results from the 3D printing in zero-g technology demonstration mission. *The International Journal of Advanced Manufacturing Technology*, 101: 391–417, 2019. doi: 10.1007/s00170-018-2827-7.
- Andrew P. Sabelhaus, Jonathan Bruce, Ken Caluwaerts, Pavlo Manovi, Roya Fallah Firoozi, Sarah Dobi, Alice M. Agogino, and Vytas SunSpiral. System design and locomotion of SUPERball, an untethered tensegrity robot. In *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2867–2873, 2015. doi: 10.1109/ICRA.2015.7139590.
- Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P. Adams, and Nando de Freitas. Taking the human out of the loop: A review of Bayesian optimization. *Proceedings of the IEEE*, 104(1): 148–175, 2016. doi: 10.1109/JPROC.2015.2494218.
- Robert E. Skelton and Mauricio C. de Oliveira. *Tensegrity Systems*. Springer, New York, 2009. doi: 10.1007/978-0-387-74242-7.
- Felix Strieth-Kalthoff, Han Hao, Vandana Rathore, Joshua Derasp, Théophile Gaudin, Nicholas H. Angello, Martin Seifrid, Ekaterina Trushina, Mason Guy, Junliang Liu, et al. Delocalized, asynchronous, closed-loop discovery of organic laser emitters. *Science*, 384(6697):eadk9227, 2024. doi: 10.1126/science.adk9227.
- Cornel Sultan. Tensegrity: 60 years of art, science, and engineering. *Advances in Applied Mechanics*, 43:69–145, 2009. doi: 10.1016/S0065-2156(09)43002-3.
- Massimo Vespignani, Jeffrey M. Friesen, Vytas SunSpiral, and Jonathan Bruce. Design of SUPERball v2, a compliant tensegrity robot for absorbing large impacts. pages 2865–2871, 2018. doi: 10.1109/IROS.2018.8594374.
- Alexandra Witze. NASA’s OSIRIS-REx delivers asteroid sample to Earth. *Nature*, 622:220–221, 2023. doi: 10.1038/d41586-023-02993-9.
- Haitao Ye, Qingjiang Liu, Jianxiang Cheng, Honggeng Li, Bingcong Jian, Rong Wang, Zechu Sun, Yang Lu, and Qi Ge. Multimaterial 3D printed self-locking thick-panel origami metamaterials. *Nature Communications*, 14:1607, 2023. doi: 10.1038/s41467-023-37343-w.