

# D208\_task1\_hindes

March 26, 2024

---

## 1 Performance Assessment: D208 Predictive Modeling Task 1 - Multiple Linear Regression.

### 1.1 Michael Hindes

Department of Information Technology, Western Governors University D208: Predictive Modeling  
Professor Dr. Straw March 21, 2024

## 2 Part I: Research Question

### 2.1 Describe the purpose of this data analysis by doing the following::

#### 2.1.1 A1. Research Question:

**A1. Research Question: “What factors contribute to the length of a patient’s initial hospital stay?”**

This question aims to identify key variables within the dataset that influence `Initial_days`; The number of days the patient stayed in the hospital during the initial visit to the hospital.

#### 2.1.2 A2. Define the goals of the data analysis.

The project sets out to explore the relationship between a response and predictor variables by exploring raw medical data and developing a multiple linear regression model. The research question focuses on identifying any potential factors that affect the length of a patient’s initial hospital stay by exploring factors such as demographic details, medical history, financial factors, and services received. Python and associated libraries are used for analysis, and that supported by visual aids for clarity. Data cleaning and wrangling is emphasized to ensure accuracy and reliability. The Python code for analysis, data cleaning, and preparation will be shared. The culmination of this project involves creating, evaluating and reducing a multiple linear regression model, discussing its significance both statistically and practically, highlighting limitations, and suggesting actionable steps for stakeholders and future analysts based on the findings. Length of hospital stay is a critical metric in healthcare, as it can impact resource allocation, patient satisfaction, and overall hospital efficiency. By identifying the factors that contribute to a patient’s hospital stay, healthcare providers can optimize their services, improve patient outcomes, and enhance the overall quality of care.

---

## 3 Part II: Method Justification

### 3.1 B. Describe multiple linear regression methods by doing the following:

#### 3.1.1 B1. Summarize four assumptions of a multiple linear regression model:

In the research on the assumption of multiple linear regression, five key assumptions were found in some places and four in others, in different combinations. They all appear critical to the validity of a model. As such I will list five assumptions below. (Statology 2023)

- **Linearity** asserts that there is a straight-line relationship between each predictor (independent variable) and the response (dependent variable). In other words, a straight line can best show the average change in a dependent variable for one unit of change in the independent variable, holding all other independent variables constant. This can be assessed through visualizations.
- **Little to no Multicollinearity** In an ideal scenario, the explanatory variables in the dataset should not significantly influence each other. Each observation's response should be primarily determined by its own predictor values and should be minimally affected by the values of other independent variables.
- **Independence of Observations** Assumes the observations in the dataset be independent of each other, meaning that the value of one observation should not be influenced by the value of another. Violations may occur in temporal or clustered data. If violated, it can lead to biased standard errors and incorrect inferences. Independence can be assessed using residual plots or statistical tests like the Durbin-Watson test.
- **Homoscedasticity** refers to the requirement that the error terms (differences between observed and predicted values) maintain a constance variance across all points. This constant variance ensures that the model's accuracy does not depend on the value of the predictors. Homoscedasticity is often checked with a residuals plots to look for patterns where there should be none, and can be caused by a variety of factors.
- **Normality of Errors** states that the residuals (errors) in the model are normally distributed around a mean of zero. This can be checked with a histogram or Q-Q plot of the residuals. If the residuals are not normally distributed, the model may not be accurate.

#### 3.1.2 B2. Describe two benefits of using Python for data analysis:

- **Rich Libraries:** While R was specifically designed with statistics and data analysis in mind, Python was chosen for its suite of libraries that facilitate every phase of the data analysis process. Libraries such as Pandas for data manipulation, NumPy for numerical computations, and Matplotlib along with Seaborn for visualizations. Statsmodels and Scikit-learn offers a platforms for applying regression and machine learning algorithms, streamlining the development of predictive models. These libraries help with a range of data analysis tasks. (Western Governors University)
- **Versatility** Python's syntax is known for its intuitiveness and readability, and wide ranging application, making it a favorite for many, from data science to web development. This versatility extends beyond data analysis to other applications such as web development, automation, and deep learning. For instance, an analyst can easily switch from analyzing data to deploying a machine-learning model as a web application within the same programming

environment. This flexibility is a significant advantage for working across multiple domains. (Western Governors University)

### **3.1.3 B3. Explain why multiple linear regression is an appropriate technique for analyzing the research question summarized in part I:**

Multiple linear regression (MLR) is an appropriate statistical technique for addressing the research question at hand. Unlike simple linear regression, MLR can handle multiple explanatory or predictor (independent) variables, which is necessary for this case. MLR uses these variables to predict the outcome of a response or target (dependent) variable, which in this case is `Initial_days`, representing the length of a patient's initial stay in the hospital. This analytical method is good at identifying and quantifying the strength and nature of the relationships between `Initial_days` and various predictors. By accounting for multiple factors simultaneously, MLR provides more nuanced insights into their combined effects on the length of a hospital stay. This is essential for creating a predictive model that can effectively inform decision-making processes and help understand the key factors influencing patient outcomes. MLR's ability to handle multiple variables makes it an appropriate tool for analyzing datasets like `medical_clean.csv` and uncovering meaningful patterns that can guide healthcare strategies and interventions.

## **4 Part III: Data Preparation**

### **4.1 C. Summarize the data preparation process for multiple linear regression analysis by doing the following:**

#### **4.1.1 C1. Describe your data cleaning goals and the steps used to clean the data to achieve the goals that align with your research question including your annotated code.**

The cleaning process starts by reading the data into a pandas DataFrame and performing an initial examination to gain a preliminary understanding of its structure and content. This involves checking data types, identifying duplicate rows, and detecting missing values. Outliers are important to detect and be aware of, particularly when creating predictive regression models. In the context of medical data, outliers can often be the very things that are of interest, such as patients with very high cholesterol levels or very low blood pressure. These values are not necessarily errors but rather important indicators of health conditions. Therefore, outliers will be noted but not necessarily treated unless they are obvious data entry errors or if they hinder the model.

Unique values will be examined to understand the variety of information within the dataset, dropping unnecessary columns that are not relevant to the research question or predictive model, and converting categorical variables into numerical formats. Some demographic and identifier data, which represents static information about patients and cannot be altered by the hospital, will be excluded from the analysis. Missing data will be identified and addressed, ensuring its proper mitigation, and any duplicate records will be eliminated. Renaming of certain variables for a more descriptive understanding. Rounding data to a reasonable number of decimal places can improve readability and reduce computational complexity. Data visualizations such as scatter plots, histograms, and box plots will be used to understand the relationships between variables and identify patterns in the data distribution.

4.1.2 The following requirements from Part C of the performance assessment will be demonstrated in the multiple cells below.

- C2. Describe the dependent variable and all independent variables using summary statistics that are required to answer the research question.
- C3. Generate univariate and bivariate visualizations of the distributions of the dependent and independent variables.
- C4. Describe your data transformation goals that align with your research question

*(The Python code used in the project was heavily informed and sometimes directly pulled from the documentation listed in the **Software** section of the References section concluding this project )*

```
[ ]: # Import packages and libraries
%pip install scikit-learn
%pip install Jinja2
%matplotlib inline
%pip install statsmodels
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import scipy.stats as stats
import seaborn as sns
from pandas import DataFrame
import statsmodels.api as sm
from statsmodels.stats.outliers_influence import variance_inflation_factor
from statsmodels.tools.tools import add_constant
```

```
Requirement already satisfied: scikit-learn in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages
(1.4.1.post1)
Requirement already satisfied: numpy<2.0,>=1.19.5 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
scikit-learn) (1.26.4)
Requirement already satisfied: scipy>=1.6.0 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
scikit-learn) (1.12.0)
Requirement already satisfied: joblib>=1.2.0 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
scikit-learn) (1.3.2)
Requirement already satisfied: threadpoolctl>=2.0.0 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
scikit-learn) (3.3.0)
Note: you may need to restart the kernel to use updated packages.
```

[notice] A new release of pip is available: 23.3.2 -> 24.0

[notice] To update, run: python.exe -m pip install --upgrade pip

```
[notice] A new release of pip is available: 23.3.2 -> 24.0
[notice] To update, run: python.exe -m pip install --upgrade pip

Requirement already satisfied: Jinja2 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (3.1.2)
Requirement already satisfied: MarkupSafe>=2.0 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
Jinja2) (2.1.3)
Note: you may need to restart the kernel to use updated packages.
```

```
[notice] A new release of pip is available: 23.3.2 -> 24.0
[notice] To update, run: python.exe -m pip install --upgrade pip

Requirement already satisfied: statsmodels in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages
(0.14.1)
Requirement already satisfied: numpy<2,>=1.18 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
statsmodels) (1.26.4)
Requirement already satisfied: scipy!=1.9.2,>=1.4 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
statsmodels) (1.12.0)
Requirement already satisfied: pandas!=2.1.0,>=1.0 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
statsmodels) (2.2.1)
Requirement already satisfied: patsy>=0.5.4 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
statsmodels) (0.5.6)
Requirement already satisfied: packaging>=21.3 in
c:\users\hinde\appdata\roaming\python\python312\site-packages (from statsmodels)
(23.2)
Requirement already satisfied: python-dateutil>=2.8.2 in
c:\users\hinde\appdata\roaming\python\python312\site-packages (from
pandas!=2.1.0,>=1.0->statsmodels) (2.8.2)
Requirement already satisfied: pytz>=2020.1 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
pandas!=2.1.0,>=1.0->statsmodels) (2024.1)
Requirement already satisfied: tzdata>=2022.7 in
c:\users\hinde\appdata\local\programs\python\python312\lib\site-packages (from
pandas!=2.1.0,>=1.0->statsmodels) (2024.1)
Requirement already satisfied: six in
c:\users\hinde\appdata\roaming\python\python312\site-packages (from
patsy>=0.5.4->statsmodels) (1.16.0)
Note: you may need to restart the kernel to use updated packages.
```

```
[ ]: # original data variable description and data types with examples.
      from IPython.display import Image
```

```
Image(filename='variable_description_208.png')
```

```
[ ]:
```

Variable name	Data type	Variable Type	Description	Example
CaseOrder	int64	Numerical - Discrete	A variable to maintain the original sequence of the raw data file.	1
Customer_id	object	Categorical - Nominal	Distinct ID for each patient.	C412403
Interaction	object	Categorical - Nominal	Unique identifiers associated with patient interactions, operations, and hospitalizations.	8cd49b13-f45a-4b47-a2bd-173ffa932c2f
UID	object	Categorical - Nominal	Distinct identifiers linked to patient transactions, operations, and hospitalizations.	3a83ddb66e2ae73798bdf1d705dc0932
City	object	Categorical - Nominal	The city where the patient resides.	Mobile
State	object	Categorical - Nominal	The state where the patient resides.	AL
County	object	Categorical - Nominal	The county where the patient resides.	Morgan
Zip	int64	Categorical - Nominal	The zip code of the patient's residence.	35621
Lat	float64	Numerical - Continuous	Latitudinal coordinates of the patient's home.	34.3496
Lng	float64	Numerical - Continuous	Longitudinal coordinates of the patient's home.	-86.72508
Population	int64	Numerical - Discrete	Number of people within a one-mile radius of the patient, as per census data.	2951
Area	object	Categorical - Nominal	Classification of area (suburban, urban, rural) according to unofficial census data.	Suburban
Timezone	object	Categorical - Nominal	Time zone of the patient's residence based on their registration information.	America/Chicago
Job	object	Categorical - Nominal	Occupation of the patient (or the primary insurance holder).	Psychologist, sport and exercise
Children	float64	Numerical - Discrete	Count of children in the patient's home.	1
Age	float64	Numerical - Discrete	Patient's age.	53
Employment	object	Categorical - Nominal	Patient's current employment status.	Full Time
Income	float64	Numerical - Continuous	Yearly income of the patient (or the primary insurance holder).	86575.93
Marital	object	Categorical - Nominal	Patient's marital status (or the primary insurance holder).	Divorced
Gender	object	Categorical - Nominal	Patient's self-identified gender as male, female, or nonbinary.	Male
ReAdmis	object	Categorical - Binary	Indication of whether the patient was readmitted within a month of discharge (Yes, No).	No
VitD_levels	float64	Numerical - Continuous	Measurement of the patient's vitamin D levels in ng/mL.	17.80233049
Doc_visits	int64	Numerical - Discrete	Count of primary physician's visits to the patient during the first hospital stay.	6
Full_meals_eaten	int64	Numerical - Discrete	Count of complete meals consumed by the patient during hospitalization (partial meals are counted as 0).	0
VitD_supp	int64	Numerical - Discrete	Frequency of supplemental vitamin D administration to the patient.	0
Soft_drink	object	Categorical - Binary	Indication of whether the patient regularly consumes three or more sodas per day (Yes, No).	Yes
Initial_admin	object	Categorical - Nominal	The method of initial hospital admission for the patient (emergency admission, elective admission, observation).	Emergency Admission
HighBlood	object	Categorical - Binary	Indication of whether the patient has hypertension (Yes, No).	Yes
Stroke	object	Categorical - Binary	Indication of whether patient has experienced a stroke in past (Yes, No).	No
Complication_risk	object	Categorical - Ordinal	Patient's risk level for complications as determined by a primary patient assessment (high, medium, low).	Medium
Overweight	float64	Categorical - Binary	Specifies if patient is deemed overweight based on age, gender, and height (Yes, No).	0
Arthritis	object	Categorical - Binary	Specifies if patient has arthritis (Yes, No).	Yes
Diabetes	object	Categorical - Binary	Specifies if patient has diabetes (Yes, No).	Yes
Hyperlipidemia	object	Categorical - Binary	Specifies if patient has hyperlipidemia (Yes, No).	No
BackPain	object	Categorical - Binary	Specifies if patient suffers from chronic back pain (Yes, No).	Yes
Anxiety	float64	Categorical - Binary	Specifies if patient has an anxiety disorder (Yes, No).	1
Allergic_rhinitis	object	Categorical - Binary	Specifies if patient has allergic rhinitis (Yes, No).	Yes
Reflux_esophagitis	object	Categorical - Binary	Specifies if patient has reflux esophagitis (Yes, No).	No
Asthma	object	Categorical - Binary	Specifies if patient has asthma (Yes, No).	Yes
Services	object	Categorical - Nominal	Main service provided to the patient during hospitalization (blood work, intravenous, CT scan, MRI).	Blood Work
Initial_days	float64	Numerical - Continuous	Duration of the patient's initial hospital stay in days.	10.58576971
TotalCharge	float64	Numerical - Continuous	Daily charge to the patient. Figure represents the usual charges billed to patients, excluding specialized treatments.	3191.048774
Additional_charges	float64	Numerical - Continuous	Average charge to the patient for additional procedures, treatments, medications, anesthesiology, etc.	17939.40342
Item1	int64	Categorical - Ordinal	Prompt admission.	3
Item2	int64	Categorical - Ordinal	Timely care.	3
Item3	int64	Categorical - Ordinal	Regular visits.	2
Item4	int64	Categorical - Ordinal	Dependability.	2
Item5	int64	Categorical - Ordinal	Choices.	4
Item6	int64	Categorical - Ordinal	Treatment hours.	3
Item7	int64	Categorical - Ordinal	Polite staff.	3
Item8	int64	Categorical - Ordinal	Doctor's demonstration of active listening.	4

```
[ ]: # import the data and read it into a dataframe, setting the first column
      ↪ `CaseOrder` as the index for consistency.

df_medical = pd.read_csv('D208_templates/medical_clean.csv', index_col=0)

# Display the first five rows of the data
df_medical.head()
```

```
[ ]: Customer_id      Interaction \
CaseOrder
1      C412403      8cd49b13-f45a-4b47-a2bd-173ffa932c2f
2      Z919181      d2450b70-0337-4406-bdbb-bc1037f1734c
3      F995323      a2057123-abf5-4a2c-abad-8ffe33512562
4      A879973      1dec528d-eb34-4079-adce-0d7a40e82205
5      C544523      5885f56b-d6da-43a3-8760-83583af94266
```

	UID	City	State	County \
CaseOrder				
1	3a83ddb66e2ae73798bdf1d705dc0932	Eva	AL	Morgan
2	176354c5eef714957d486009feabf195	Marianna	FL	Jackson
3	e19a0fa00aeda885b8a436757e889bc9	Sioux Falls	SD	Minnehaha
4	cd17d7b6d152cb6f23957346d11c3f07	New Richland	MN	Waseca
5	d2f0425877b10ed6bb381f3e2579424a	West Point	VA	King William

	Zip	Lat	Lng	Population	...	TotalCharge \
CaseOrder					...	
1	35621	34.34960	-86.72508	2951	...	3726.702860
2	32446	30.84513	-85.22907	11303	...	4193.190458
3	57110	43.54321	-96.63772	17125	...	2434.234222
4	56072	43.89744	-93.51479	2162	...	2127.830423
5	23181	37.59894	-76.88958	5287	...	2113.073274

	Additional_charges	Item1	Item2	Item3	Item4	Item5	Item6	Item7 \
CaseOrder								
1	17939.403420	3	3	2	2	4	3	3
2	17612.998120	3	4	3	4	4	4	3
3	17505.192460	2	4	4	4	3	4	3
4	12993.437350	3	5	5	3	4	5	5
5	3716.525786	2	1	3	3	5	3	4

	Item8
CaseOrder	
1	4
2	3
3	3
4	5
5	3

[5 rows x 49 columns]

```
[ ]: # View the last 5 rows of the dataframe
df_medical.tail()
```

```
[ ]: Customer_id Interaction \
CaseOrder
9996      B863060 a25b594d-0328-486f-a9b9-0567eb0f9723
9997      P712040 70711574-f7b1-4a17-b15f-48c54564b70f
9998      R778890 1d79569d-8e0f-4180-a207-d67ee4527d26
9999      E344109 f5a68e69-2a60-409b-a92f-ac0847b27db0
10000     I569847 bc482c02-f8c9-4423-99de-3db5e62a18d5
```

UID	City	State	County \
-----	------	-------	----------

CaseOrder						
9996	39184dc28cc038871912ccc4500049e5	Norlina	NC	Warren		
9997	3cd124ccd43147404292e883bf9ec55c	Milmay	NJ	Atlantic		
9998	41b770ae97a5b9e7f69c906a8119d7	Southside	TN	Montgomery		
9999	2bb491ef5b1beb1fed758cc6885c167a	Quinn	SD	Pennington		
10000	95663a202338000abdf7e09311c2a8a1	Coraopolis	PA	Allegheny		

	Zip	Lat	Lng	Population	...	TotalCharge	\
CaseOrder					...		
9996	27563	36.42886	-78.23716	4762	...	6850.942	
9997	8340	39.43609	-74.87302	1251	...	7741.690	
9998	37171	36.36655	-87.29988	532	...	8276.481	
9999	57775	44.10354	-102.01590	271	...	7644.483	
10000	15108	40.49998	-80.19959	41524	...	7887.553	

	Additional_charges	Item1	Item2	Item3	Item4	Item5	Item6	Item7	\
CaseOrder									
9996	8927.642	3	2	2	3	4	3	4	
9997	28507.150	3	3	4	2	5	3	4	
9998	15281.210	3	3	3	4	4	2	3	
9999	7781.678	5	5	3	4	4	3	4	
10000	11643.190	4	3	3	2	3	6	4	

	Item8
CaseOrder	
9996	2
9997	4
9998	2
9999	3
10000	3

[5 rows x 49 columns]

```
[ ]: # Check the DataFrame information
df_medical.info(verbose=True)
```

```
<class 'pandas.core.frame.DataFrame'>
Index: 10000 entries, 1 to 10000
Data columns (total 49 columns):
#   Column                Non-Null Count  Dtype
---  -
0   Customer_id           10000 non-null   object
1   Interaction            10000 non-null   object
2   UID                   10000 non-null   object
3   City                  10000 non-null   object
4   State                 10000 non-null   object
5   County               10000 non-null   object
6   Zip                   10000 non-null   int64
```



7	Lat	10000	non-null	float64
8	Lng	10000	non-null	float64
9	Population	10000	non-null	int64
10	Area	10000	non-null	object
11	TimeZone	10000	non-null	object
12	Job	10000	non-null	object
13	Children	10000	non-null	int64
14	Age	10000	non-null	int64
15	Income	10000	non-null	float64
16	Marital	10000	non-null	object
17	Gender	10000	non-null	object
18	ReAdmis	10000	non-null	object
19	VitD_levels	10000	non-null	float64
20	Doc_visits	10000	non-null	int64
21	Full_meals_eaten	10000	non-null	int64
22	vitD_supp	10000	non-null	int64
23	Soft_drink	10000	non-null	object
24	Initial_admin	10000	non-null	object
25	HighBlood	10000	non-null	object
26	Stroke	10000	non-null	object
27	Complication_risk	10000	non-null	object
28	Overweight	10000	non-null	object
29	Arthritis	10000	non-null	object
30	Diabetes	10000	non-null	object
31	Hyperlipidemia	10000	non-null	object
32	BackPain	10000	non-null	object
33	Anxiety	10000	non-null	object
34	Allergic_rhinitis	10000	non-null	object
35	Reflux_esophagitis	10000	non-null	object
36	Asthma	10000	non-null	object
37	Services	10000	non-null	object
38	Initial_days	10000	non-null	float64
39	TotalCharge	10000	non-null	float64
40	Additional_charges	10000	non-null	float64
41	Item1	10000	non-null	int64
42	Item2	10000	non-null	int64
43	Item3	10000	non-null	int64
44	Item4	10000	non-null	int64
45	Item5	10000	non-null	int64
46	Item6	10000	non-null	int64
47	Item7	10000	non-null	int64
48	Item8	10000	non-null	int64

dtypes: float64(7), int64(15), object(27)

memory usage: 3.8+ MB

```
[ ]: # Check for duplicate rows.
      print(df_medical.duplicated().value_counts())
```

```
print('Total Duplicated Rows: ', df_medical.duplicated().sum())
```

```
False      10000  
Name: count, dtype: int64  
Total Duplicated Rows: 0
```

```
[ ]: # Check for null values  
df_medical.isnull().sum()
```

```
[ ]: Customer_id      0  
Interaction          0  
UID                 0  
City                0  
State               0  
County              0  
Zip                 0  
Lat                 0  
Lng                 0  
Population          0  
Area                0  
TimeZone            0  
Job                 0  
Children            0  
Age                 0  
Income              0  
Marital             0  
Gender              0  
ReAdmis             0  
VitD_levels         0  
Doc_visits          0  
Full_meals_eaten    0  
vitD_supp           0  
Soft_drink          0  
Initial_admin       0  
HighBlood           0  
Stroke              0  
Complication_risk   0  
Overweight          0  
Arthritis           0  
Diabetes            0  
Hyperlipidemia      0  
BackPain            0  
Anxiety             0  
Allergic_rhinitis   0  
Reflux_esophagitis  0  
Asthma              0  
Services            0  
Initial_days        0
```

```
TotalCharge      0
Additional_charges 0
Item1             0
Item2             0
Item3             0
Item4             0
Item5             0
Item6             0
Item7             0
Item8             0
dtype: int64
```

```
[ ]: # rename columns Item 1 to Item 8 to the appropriate column names. The 'S_'
      ↪modifier is used to indicate the column is a survey item.
```

```
new_col_names={
    'Item1':'S_T_Admission',
    'Item2':'S_T_Treatment',
    'Item3':'S_T_Visits',
    'Item4':'S_Reliability', 'Item5':'S_Options',
    'Item6':'S_Hours_Treatment',
    'Item7':'S_Staff',
    'Item8':'S_Active_Listening'}
df_medical.rename(columns=new_col_names, inplace=True)
df_medical.columns
```

```
[ ]: Index(['Customer_id', 'Interaction', 'UID', 'City', 'State', 'County', 'Zip',
            'Lat', 'Lng', 'Population', 'Area', 'TimeZone', 'Job', 'Children',
            'Age', 'Income', 'Marital', 'Gender', 'ReAdmis', 'VitD_levels',
            'Doc_visits', 'Full_meals_eaten', 'vitD_supp', 'Soft_drink',
            'Initial_admin', 'HighBlood', 'Stroke', 'Complication_risk',
            'Overweight', 'Arthritis', 'Diabetes', 'Hyperlipidemia', 'BackPain',
            'Anxiety', 'Allergic_rhinitis', 'Reflux_esophagitis', 'Asthma',
            'Services', 'Initial_days', 'TotalCharge', 'Additional_charges',
            'S_T_Admission', 'S_T_Treatment', 'S_T_Visits', 'S_Reliability',
            'S_Options', 'S_Hours_Treatment', 'S_Staff', 'S_Active_Listening'],
            dtype='object')
```

```
[ ]: # combine the data types and unique values count into a DataFrame easy
      ↪reference and comparison
data_types = df_medical.dtypes
unique_values = df_medical.nunique()
comparison_df = pd.DataFrame({'Data Type': data_types, 'Unique Values':
      ↪unique_values})
comparison_df.sort_values(by='Unique Values', ascending=False)
```

```
[ ]:
Customer_id      Data Type  Unique Values
Customer_id      object        10000
```

UID	object	10000
Interaction	object	10000
Initial_days	float64	9997
TotalCharge	float64	9997
Income	float64	9993
VitD_levels	float64	9976
Additional_charges	float64	9418
Lng	float64	8725
Zip	int64	8612
Lat	float64	8588
City	object	6072
Population	int64	5951
County	object	1607
Job	object	639
Age	int64	72
State	object	52
TimeZone	object	26
Children	int64	11
Doc_visits	int64	9
Full_meals_eaten	int64	8
S_T_Visits	int64	8
S_T_Admission	int64	8
S_Options	int64	7
S_Reliability	int64	7
S_T_Treatment	int64	7
S_Staff	int64	7
S_Hours_Treatment	int64	7
S_Active_Listening	int64	7
vitD_supp	int64	6
Marital	object	5
Services	object	4
Complication_risk	object	3
Area	object	3
Gender	object	3
Initial_admin	object	3
Asthma	object	2
Reflux_esophagitis	object	2
Overweight	object	2
Diabetes	object	2
Stroke	object	2
HighBlood	object	2
Soft_drink	object	2
Allergic_rhinitis	object	2
ReAdmis	object	2
Anxiety	object	2
BackPain	object	2
Hyperlipidemia	object	2

## 5 Cardinality and Data Type Summary of Variables

### 5.1 Numerical Variables

- Income: 9993 unique values (float64)
- VitD\_levels: 9976 unique values (float64)
- Initial\_days: 9997 unique values (float64)
- TotalCharge: 9997 unique values (float64)
- Additional\_charges: 9418 unique values (float64)
- Population: 5951 unique values (int64)
- Children: 11 unique values (int64)
- Age: 72 unique values (int64)
- Doc\_visits: 9 unique values (int64)
- Full\_meals\_eaten: 8 unique values (int64)
- vitD\_supp: 6 unique values (int64)
- Lat: 8588 unique values (float64)
- Lng: 8725 unique values (float64)

### 5.2 Ordinal Variables (Categorical)

- S\_T\_Admission: 8 unique values (int64)
- S\_T\_Treatment: 7 unique values (int64)
- S\_T\_Visits: 8 unique values (int64)
- S\_Reliability: 7 unique values (int64)
- S\_Options: 7 unique values (int64)
- S\_Hours\_Treatment: 7 unique values (int64)
- S\_Staff: 7 unique values (int64)
- S\_Active\_Listening: 7 unique values (int64)

### 5.3 Nominal Variables (Categorical)

- Customer\_id: 10000 unique values (object)
- Interaction: 10000 unique values (object)
- UID: 10000 unique values (object)
- City: 6072 unique values (object)
- State: 52 unique values (object)
- County: 1607 unique values (object)
- Zip: 8612 unique values (int64)
- Area: 3 unique values (object)
- TimeZone: 26 unique values (object)
- Job: 639 unique values (object)
- Marital: 5 unique values (object)
- Gender: 3 unique values (object)
- ReAdmis: 2 unique values (object)
- Soft\_drink: 2 unique values (object)
- Initial\_admin: 3 unique values (object)

- HighBlood: 2 unique values (object)
- Stroke: 2 unique values (object)
- Complication\_risk: 3 unique values (object)
- Overweight: 2 unique values (object)
- Arthritis: 2 unique values (object)
- Diabetes: 2 unique values (object)
- Hyperlipidemia: 2 unique values (object)
- BackPain: 2 unique values (object)
- Anxiety: 2 unique values (object)
- Allergic\_rhinitis: 2 unique values (object)
- Reflux\_esophagitis: 2 unique values (object)
- Asthma: 2 unique values (object)
- Services: 4 unique values (object)

Given the nature of the data, there are several variables that will be excluded from the analysis. Here is a brief summary of the variables that will be excluded and the rationale for their exclusion:

### 5.3.1 Current Strategy Overview:

1. **Broad Inclusion:** *Cast a wide net* (Middleton, 2024) Start with a wide array of variables to capture potential influences on `Initial_days`, informed by domain knowledge and based on the recommendation of the instructors of this course.
2. **Build Initial Model:** Use this dataset to identify significant variables.
3. **Analyze & Refine:** Eliminate non-contributing or highly correlated variables based on initial model insights.
4. **Develop Reduced Model:** Focus on key variables for a streamlined, effective model.

### 5.3.2 Variables Eliminated:

*Note: I am a former health care professional who has worked in several hospitals, and unfortunately have had extensive hospital stays as a patient as well. While I am not an expert on this particular data, I do have some domain knowledge, and this domain knowledge helps inform some of my decision making here.*

- **TotalCharge & Additional Charges:** Possible high correlation and generally a result of `Initial_days` not a cause of. Patients and staff often unaware of these charges until after the fact.
- **Latitude & Longitude:** Limited interpretive value and adds to model complexity.
- **Identifiers (Customer\_id, Interaction, UID):** High uniqueness; ethical concerns.
- **Geographic (City, State, County, Zip, Population):** Overly detailed, increasing model complexity, not short/medium term actionable.
- **TimeZone:** Relevance to hospital stay length is questionable, increases complexity.
- **Full\_meals\_eaten:** Restrictive and targeted diets and meals are so common and depends on patient and services that without context this variable is not useful.
- **Job:** Subjective and variable in interpretation. Better suited for targeted occupational study.
- **Services:** All very common in diagnostic phase and itself dependent on too many unknown factors, and not likely to be significant predictors. Could add confusion.
- **Soft\_drink:** Poorly defined as soft drink can mean anything from uncaffeinated carbonated water to a caffeinated sugary soda.

```
[ ]: # create reduced dataframe with only the columns for the analysis
cols_to_drop = ['TotalCharge', 'Services', 'Soft_drink', 'Additional_charges', '
↳ 'Lat', 'Full_meals_eaten', 'Lng', 'Customer_id', 'Interaction', 'UID', '
↳ 'City', 'State', 'County', 'Zip', 'TimeZone', 'Job', 'Population']

df_reduced = df_medical.drop(cols_to_drop, axis=1)

# display the dataframe in full
pd.set_option('display.max_columns', None)
df_reduced.head().transpose()
```

```
[ ]: CaseOrder          1          2 \
Area          Suburban          Urban
Children          1          3
Age          53          51
Income          86575.93          46805.99
Marital          Divorced          Married
Gender          Male          Female
ReAdmis          No          No
VitD_levels          19.141466          18.940352
Doc_visits          6          4
vitD_supp          0          1
Initial_admin          Emergency Admission  Emergency Admission
HighBlood          Yes          Yes
Stroke          No          No
Complication_risk          Medium          High
Overweight          No          Yes
Arthritis          Yes          No
Diabetes          Yes          No
Hyperlipidemia          No          No
BackPain          Yes          No
Anxiety          Yes          No
Allergic_rhinitis          Yes          No
Reflux_esophagitis          No          Yes
Asthma          Yes          No
Initial_days          10.58577          15.129562
S_T_Admission          3          3
S_T_Treatment          3          4
S_T_Visits          2          3
S_Reliability          2          4
S_Options          4          4
S_Hours_Treatment          3          4
S_Staff          3          3
S_Active_Listening          4          3

CaseOrder          3          4          5
Area          Suburban          Suburban          Rural
```

Children	3	0	1
Age	53	78	22
Income	14370.14	39741.49	1209.56
Marital	Widowed	Married	Widowed
Gender	Female	Male	Female
ReAdmis	No	No	No
VitD_levels	18.057507	16.576858	17.439069
Doc_visits	4	4	5
vitD_supp	0	0	2
Initial_admin	Elective Admission	Elective Admission	Elective Admission
HighBlood	Yes	No	No
Stroke	No	Yes	No
Complication_risk	Medium	Medium	Low
Overweight	Yes	No	No
Arthritis	No	Yes	No
Diabetes	Yes	No	No
Hyperlipidemia	No	No	Yes
BackPain	No	No	No
Anxiety	No	No	No
Allergic_rhinitis	No	No	Yes
Reflux_esophagitis	No	Yes	No
Asthma	No	Yes	No
Initial_days	4.772177	1.714879	1.254807
S_T_Admission	2	3	2
S_T_Treatment	4	5	1
S_T_Visits	4	5	3
S_Reliability	4	3	3
S_Options	3	4	5
S_Hours_Treatment	4	5	3
S_Staff	3	5	4
S_Active_Listening	3	5	3

```
[ ]: # Summary Stats For numeric variables
selected_columns = df_reduced[['Age', 'Income', 'Children', 'VitD_levels', '
↳ 'Doc_visits', 'vitD_supp', 'Initial_days']].copy()
selected_columns.describe()
```

```
[ ]:
count    Age      Income      Children  VitD_levels  Doc_visits  \
count    10000.000000  10000.000000  10000.000000  10000.000000  10000.000000
mean      53.511700   40490.495160    2.097200    17.964262    5.012200
std       20.638538   28521.153293    2.163659     2.017231    1.045734
min       18.000000    154.080000    0.000000     9.806483    1.000000
25%       36.000000   19598.775000    0.000000    16.626439    4.000000
50%       53.000000   33768.420000    1.000000    17.951122    5.000000
75%       71.000000   54296.402500    3.000000    19.347963    6.000000
max       89.000000  207249.100000   10.000000    26.394449    9.000000
```



	vitD_supp	Initial_days
count	10000.000000	10000.000000
mean	0.398900	34.455299
std	0.628505	26.309341
min	0.000000	1.001981
25%	0.000000	7.896215
50%	0.000000	35.836244
75%	1.000000	61.161020
max	5.000000	71.981490

### 5.3.3 Initial Takeaways:

- **Age:** Averages 53 years, ranging from 18 to 89, with a diverse age profile.
- **Income:** Averages \$40,490, with wide variation (154 to 207249), indicating economic diversity.
- **Children:** Averages 2 children with a similar median, with a range of 0 to 10.
- **VitD\_levels:** Averages 17.96, mostly within a narrow range (9.81 to 26.39), suggesting more consistent levels across patients.
- **Doc\_visits:** Averages 5 visits, indicating a similar frequency of medical consultations.
- **vitD\_supp:** Averages less than 0.5 supplements, with low intake common among patients.
- **Categorical** nominal and ordinal variables are not included here and will include a separate summary of proportions along with univariate and bivariate visualizations.
- **Initial\_days:** Our dependent (target) variable will be fully summarized and visualized below

## 6 Rounding Justification.

- Rounding 'Initial\_days' from 8 decimal places to 2 reduces the number of unique values, which can simplify analyses and visualizations by reducing the granularity of the data. Precision beyond 2 decimal places for representing days does not add meaningful information for the analysis. In many practical scenarios, especially related to days, a precision of 2 decimal places is sufficient to capture relevant variations without unnecessarily complicating the dataset. In healthcare data, for instance, it's unlikely that fractions of a day to eight decimal places would impact decisions or care outcomes.
- Similarly, rounding Income to whole numbers, and 'VitD\_levels' to 2 decimal places seems appropriate in this context.

```
[ ]: # round 'Initial_days' and 'VitD_levels' to 2 decimal places
df_reduced = df_reduced.round({'VitD_levels': 2})
df_reduced = df_reduced.round({'Initial_days': 2})

# round 'Income' to 0 decimal places by converting to integer
df_reduced = df_reduced.astype({'Income': 'int64'})
```

```
# display the dataframe with the rounded values
df_reduced[['Initial_days', 'VitD_levels', 'Income']].head()
```

```
[ ]:      Initial_days  VitD_levels  Income
CaseOrder
1           10.59         19.14    86575
2           15.13         18.94    46805
3            4.77         18.06    14370
4            1.71         16.58    39741
5            1.25         17.44     1209
```

```
[ ]: # Export to csv and to save results so far and to reduce memory consumption.
df_reduced.to_csv('df_reduced.csv', index='CaseOrder')
```

---

```
[ ]: # Load the data
df = pd.read_csv('df_reduced.csv', index_col=0)
```

---

## 7 C3. Visualizations

Below are Univariate and Bivariate Visualizations for explanatory variables showing their relationship with the dependent variable `Initial_days`. Seaborn and Matplotlib will be used to create visualizations and the choice of graph will depend on the nature of the variable being visualized. (Python Graph Gallery. n.d), (Eyre, 2024)


## 8 Univariate Visualizations

```
[ ]: # Boxplot for 'Initial_days'
plt.figure(figsize=(6, 4))
sns.boxplot(x=df['Initial_days'])
plt.title('Boxplot for Initial_days')
plt.show()


# Histogram for 'Initial_days'
plt.figure(figsize=(5, 4))
sns.histplot(data=df, x='Initial_days', kde=True, bins=50)
plt.title('Histogram for Initial_days')
plt.show()

df['Initial_days'].describe()
```

Boxplot for Initial\_days



Histogram for Initial\_days



```
[ ]: count    10000.000000
     mean      34.455284
     std       26.309382
     min       1.000000
     25%       7.900000
     50%      35.840000
     75%      61.162500
     max      71.980000
Name: Initial_days, dtype: float64
```

- **Boxplot Observations:** The median appears to be above the mid-30s, suggesting that roughly half of the patients have shorter initial stays and the other half have longer. There are no visible outliers, indicating no extreme values or anomalies that fall outside the typical range. The interquartile range shows that the middle 50% of the data spans a rather large range, suggesting a concentration of data within this segment.
- **Histogram Observations:** The distribution is bimodal, with two peaks: one just under a few days and another around 70 days. This suggests there are two groups of patients with different typical hospital stay lengths. The histogram indicates that shorter initial stays are more common than longer stays, with a significant drop-off in frequency as the number of days increases towards the middle values. The spread between the two modes shows that there is variability in the data, not concentrated around a single central value. Understanding the reasons behind this bimodal distribution may require further investigation into the factors affecting hospital stay lengths. This distribution is important to keep in mind when interpreting the results of the regression analysis, as it may influence the model's predictive accuracy and the significance of the predictors.

**Summary:** Statistical measures for `Initial_days` across all patients in the dataset, including:

- **Count:** 10,000 observations. This represents the number of patients included in the analysis.
- **Mean:** Approximately 34 days. On average, patients spend a little over a month in the hospital.
- **Standard Deviation:** About 26 days. This indicates a wide variation in the length of hospital stays among patients; while some patients have short stays, others have significantly longer stays.
- **Minimum:** Just over 1 day. This shows that some patients are discharged almost immediately after admission.
- **25% (First Quartile):** About 8 days or less. A quarter of the patients have hospital stays just over a week.
- **Median (50%):** Approximately 36 days. This is very close to the mean. However, the slight difference between the mean and median indicates a slight skew in the data.
- **75% (Third Quartile):** About 61 days or less. Most patients are discharged within two months.
- **Maximum:** Nearly 72 days. Indicates that some patients have extended hospital stays.

```
[ ]: # subplots for the histplots
fig, axes = plt.subplots(1, 3, figsize=(10, 3))

# distribution/count of children
```

```

sns.histplot(data=df, x='Children', ax=axes[0], kde=True)
axes[0].set_title('Distribution/Count of Children')


# distribution of ages
sns.histplot(data=df, x='Age', ax=axes[1], kde=True)
axes[1].set_title('Distribution of Ages')

# distribution of income
sns.histplot(data=df, x='Income', ax=axes[2], kde=True)
axes[2].set_title('Distribution of Income')

plt.tight_layout()
plt.show()

# summary statistics for the variables
df[['Children', 'Age', 'Income']].describe().transpose()

```



```

[ ]:
      count      mean      std      min      25%      50%  \
Children  10000.0    2.0972    2.163659    0.0      0.00      1.0
Age       10000.0   53.5117   20.638538   18.0     36.00     53.0
Income    10000.0  40490.0021  28521.152883  154.0    19598.25  33768.0

      75%      max
Children    3.00    10.0
Age         71.00    89.0
Income     54295.75  207249.0

```

```

[ ]: # subplots for the boxplots
fig, axes = plt.subplots(1, 3, figsize=(10, 3))

# boxplot of children
sns.boxplot(data=df, x='Children', ax=axes[0])
axes[0].set_title('Boxplot of Children')

# boxplot of ages

```


```

sns.boxplot(data=df, x='Age', ax=axes[1])
axes[1].set_title('Boxplot of Ages')

# boxplot of income
sns.boxplot(data=df, x='Income', ax=axes[2])
axes[2].set_title('Boxplot of Income')

plt.tight_layout()
plt.show()

```



- The outliers here will be noted as they may impact the regression model, particularly with OLS regression. For now, we will note them and include as is in the initial model.

```

[ ]: # subplots for the histplots
fig, axes = plt.subplots(1, 3, figsize=(10, 3))

# distribution/count of VitD_levels
sns.histplot(data=df, x='VitD_levels', ax=axes[0], kde=True)
axes[0].set_title('Distribution of VitD_levels')


# distribution/count of Doc_visits with bigger bins
sns.histplot(data=df, x='Doc_visits', ax=axes[1], kde=True)
axes[1].set_title('Distribution/Count of Doc_visits')

# distribution/count of vitD_supp with bigger bins
sns.histplot(data=df, x='vitD_supp', ax=axes[2], kde=True)
axes[2].set_title('Distribution/count of vitD_supp')

plt.tight_layout()
plt.show()

# descriptive statistics for the variables
df[['VitD_levels', 'Doc_visits', 'vitD_supp']].describe().transpose()

```



```
[ ]:
```

	count	mean	std	min	25%	50%	75%	max
VitD_levels	10000.0	17.964272	2.017259	9.81	16.6275	17.95	19.35	26.39
Doc_visits	10000.0	5.012200	1.045734	1.00	4.0000	5.00	6.00	9.00
vitD_supp	10000.0	0.398900	0.628505	0.00	0.0000	0.00	1.00	5.00

- The Vitamin D levels appear normally distributed around a middle value, suggesting that most patients have Vitamin D levels within a standard range, with fewer individuals having very high or very low levels. Doc\_visits show a pattern with most patients having 4-6 visits, and the frequency drops for higher numbers of visits. For Vitamin D supplements, most patients are not given supplements, which aligns with the distribution of Vitamin D levels.

```
[ ]: # Create a 2 by 2 subplot grid
fig, axes = plt.subplots(2, 2, figsize=(10, 6))

# Area
sns.countplot(data=df, x='Area', ax=axes[0, 0])
axes[0, 0].set_title('Count of Area')

# Marital
sns.countplot(data=df, x='Marital', ax=axes[0, 1])
axes[0, 1].set_title('Count of Marital Status')



# Gender
sns.countplot(data=df, x='Gender', ax=axes[1, 0])
axes[1, 0].set_title('Count of Gender')

# ReAdmis
sns.countplot(data=df, x='ReAdmis', ax=axes[1, 1])
axes[1, 1].set_title('Numer of ReAdmissions')

plt.tight_layout()
plt.show()

# create a countplot for initial_admin
```

```
plt.figure(figsize=(5, 4))
sns.countplot(data=df, x='Initial_admin')
plt.title('Count of Initial_admin')
plt.show()
```





## 9 Proportion Summary

Area - Rural: 33.69% - Urban: 33.03% - Suburban: 33.28%

Gender - Female: 50.18% - Male: 47.68% - Nonbinary: 2.14%

Marital - Widowed: 20.45% - Married: 20.23% - Separated: 19.87% - Never Married: 19.84% - Divorced: 19.61%

ReAdmis - No: 63.31% - Yes: 36.69%

Initial\_admin - Emergency: 51.60% - Elective: 25.04% - Observation: 24.36%

```
[ ]: # Survey items
# 2 by 4 subplot grid
fig, axes = plt.subplots(2, 4, figsize=(12, 6))

# S_T_Admission
sns.countplot(data=df, x='S_T_Admission', ax=axes[0, 0])
axes[0, 0].set_title('Count of S_T_Admission')

# S_T_Treatment
sns.countplot(data=df, x='S_T_Treatment', ax=axes[0, 1])
axes[0, 1].set_title('Count of S_T_Treatment')

# S_T_Visits
sns.countplot(data=df, x='S_T_Visits', ax=axes[0, 2])
axes[0, 2].set_title('Count of S_T_Visits')

# S_Reliability
sns.countplot(data=df, x='S_Reliability', ax=axes[0, 3])
axes[0, 3].set_title('Count of S_Reliability')

# S_Options
sns.countplot(data=df, x='S_Options', ax=axes[1, 0])
axes[1, 0].set_title('Count of S_Options')

# S_Hours_Treatment
sns.countplot(data=df, x='S_Hours_Treatment', ax=axes[1, 1])
axes[1, 1].set_title('Count of S_Hours_Treatment')

# S_Staff
sns.countplot(data=df, x='S_Staff', ax=axes[1, 2])
axes[1, 2].set_title('Count of S_Staff')

# S_Active_Listening
```


```

sns.countplot(data=df, x='S_Active_Listening', ax=axes[1, 3])
axes[1, 3].set_title('Count of S_Active_Listening')

plt.tight_layout()
plt.show()

# value counts for the survey items
df[['S_T_Admission', 'S_T_Treatment', 'S_T_Visits', 'S_Reliability', 'S_Options', 'S_Hours_Treatment', 'S_Staff', 'S_Active_Listening']].apply(pd.Series.value_counts)

```



```

[ ]:  S_T_Admission  S_T_Treatment  S_T_Visits  S_Reliability  S_Options  \
1          213          213.0          211          207.0          211.0
2         1315         1360.0         1356         1346.0         1380.0
3         3404         3439.0         3379         3422.0         3423.0
4         3455         3351.0         3464         3394.0         3446.0
5         1377         1421.0         1358         1388.0         1308.0
6          225          204.0          220          231.0          219.0
7           10           12.0           11           12.0           13.0
8            1           NaN            1           NaN           NaN

      S_Hours_Treatment  S_Staff  S_Active_Listening
1          213.0        215.0          209.0
2         1319.0        1345.0         1391.0
3         3371.0        3456.0         3401.0
4         3464.0        3487.0         3337.0
5         1403.0        1274.0         1429.0
6          220.0        212.0          221.0

```

7	10.0	11.0	12.0
8	NaN	NaN	NaN

- Survey responses across various rating scales appear to be fairly evenly distributed among the different survey items. This uniformity could indicate a degree of correlation among the responses to these items. To explore potential patterns, we will utilize pie charts to visualize the distribution of responses and a correlation matrix to quantitatively assess the relationships between the items.

```
[ ]: textprops = {"fontsize":10}

# 2 by 4 subplot grid
fig, axes = plt.subplots(4, 2, figsize=(6, 10))

# S_T_Admission
df['S_T_Admission'].value_counts().plot.pie(ax=axes[0, 0], autopct='%1.1f%%',
    ↳textprops=textprops)
axes[0, 0].set_title('S_T_Admission')

# S_T_Treatment
df['S_T_Treatment'].value_counts().plot.pie(ax=axes[0, 1], autopct='%1.1f%%',
    ↳textprops=textprops)
axes[0, 1].set_title('S_T_Treatment')

# S_T_Visits
df['S_T_Visits'].value_counts().plot.pie(ax=axes[1, 0], autopct='%1.1f%%',
    ↳textprops=textprops)
axes[1, 0].set_title('S_T_Visits')

# S_Reliability
df['S_Reliability'].value_counts().plot.pie(ax=axes[1, 1], autopct='%1.1f%%',
    ↳textprops=textprops)
axes[1, 1].set_title('S_Reliability')

# S_Options
df['S_Options'].value_counts().plot.pie(ax=axes[2, 0], autopct='%1.1f%%',
    ↳textprops=textprops)
axes[2, 0].set_title('S_Options')

# S_Hours_Treatment
df['S_Hours_Treatment'].value_counts().plot.pie(ax=axes[2, 1], autopct='%1.
    ↳1f%%', textprops=textprops)
axes[2, 1].set_title('S_Hours_Treatment')

# S_Staff
df['S_Staff'].value_counts().plot.pie(ax=axes[3, 0], autopct='%1.1f%%',
    ↳textprops=textprops)
```

```


axes[3, 0].set_title('S_Staff')

# S_Active_Listening
df['S_Active_Listening'].value_counts().plot.pie(ax=axes[3, 1],
        ↪textprops=textprops)
axes[3, 1].set_title('S_Active_Listening')
plt.tight_layout()
plt.show()


# display descriptive statistics for the survey items
df[['S_T_Admission', 'S_T_Treatment', 'S_T_Visits', 'S_Reliability',
        ↪'S_Options', 'S_Hours_Treatment', 'S_Staff', 'S_Active_Listening']].
        ↪describe().transpose()

```


S\_T\_Admission




S\_T\_Treatment




S\_T\_Visits




S\_Reliability




S\_Options




S\_Hours\_Treatment



S\_Staff



S\_Active\_Listening



```
[ ]:
```


	count	mean	std	min	25%	50%	75%	max
S_T_Admission	10000.0	3.5188	1.031966	1.0	3.0	4.0	4.0	8.0
S_T_Treatment	10000.0	3.5067	1.034825	1.0	3.0	3.0	4.0	7.0
S_T_Visits	10000.0	3.5111	1.032755	1.0	3.0	4.0	4.0	8.0
S_Reliability	10000.0	3.5151	1.036282	1.0	3.0	4.0	4.0	7.0
S_Options	10000.0	3.4969	1.030192	1.0	3.0	3.0	4.0	7.0
S_Hours_Treatment	10000.0	3.5225	1.032376	1.0	3.0	4.0	4.0	7.0
S_Staff	10000.0	3.4940	1.021405	1.0	3.0	3.0	4.0	7.0
S_Active_Listening	10000.0	3.5097	1.042312	1.0	3.0	3.0	4.0	7.0

- The pie charts and summary show similar pattern across with some survey responses having almost identical proportions. This could indicate a lack of variability in the responses, which may impact the predictive power of these variables in the regression model.

```
[ ]: # Create a correlation matrix
# the columns correlation matrix
cols = ['S_T_Admission', 'S_T_Treatment', 'S_T_Visits', 'S_Reliability',
        'S_Options', 'S_Hours_Treatment', 'S_Staff', 'S_Active_Listening']

corr_matrix = df[cols].corr()

# Create a heatmap of the correlation matrix
plt.figure(figsize=(8, 6))
sns.heatmap(corr_matrix, annot=True, cmap='coolwarm', center=0, vmin=-1, vmax=1)
plt.title('Correlation Matrix')
plt.tight_layout()
plt.show()
```



- The correlation matrix shows that there may indeed be correlation amongst the different survey items. This could introduce multicollinearity into the regression model.
- These pairs of items have correlation coefficients very close to zero, suggesting that there is little to no linear relationship between them. When selecting variables for a regression model, these items might be preferred as they are less likely to introduce multicollinearity issues. We will note this during the initial model building phase. And check the VIF scores to confirm.
- S\_T\_Admission and S\_Reliability: -0.0046
- S\_T\_Visits and S\_Reliability: -0.0063
- S\_T\_Admission and S\_Options: -0.0037
- S\_T\_Treatment and S\_Options: -0.01
- S\_T\_Visits and S\_Options: -0.01

## 10 Bivariate Visualizations

```
[ ]: # Bivariate Graphs with Initial_days
plt.figure(figsize=(10, 6))

# vitD_levels vs. Initial_days
plt.subplot(2, 2, 1)
sns.regplot(data=df, x='VitD_levels', y='Initial_days',
            scatter_kws={'edgecolor': 'black'}, line_kws={'color': 'orange'})
plt.title('VitD_levels vs. Initial_days')

# Children vs. Initial_days
plt.subplot(2, 2, 2)
sns.regplot(data=df, x='Children', y='Initial_days', scatter_kws={'edgecolor':
            'black'}, line_kws={'color': 'orange'})
plt.title('Children vs. Initial_days')


# Age vs. Initial_days
plt.subplot(2, 2, 3)
sns.regplot(data=df, x='Age', y='Initial_days', scatter_kws={'edgecolor':
            'black'}, line_kws={'color': 'orange'})
plt.title('Age vs. Initial_days')

# income vs. Initial_days
plt.subplot(2, 2, 4)
sns.regplot(data=df, x='Income', y='Initial_days', scatter_kws={'edgecolor':
            'black'}, line_kws={'color': 'orange'})
plt.title('Income vs. Initial_days')

plt.tight_layout()
plt.show()

plt.figure(figsize=(5, 3))
sns.regplot(data=df, x='Doc_visits', y='Initial_days', scatter_kws={'edgecolor':
            'black'}, line_kws={'color': 'orange'})
plt.title('Initial_days vs. Doc_visits')
plt.show()
```





- **Vitamin D** levels and initial days don't seem to have a clear pattern, with no obvious relationship. When it comes to **children** there is no distinct trend, suggesting the number of children doesn't linearly affect the length of hospital stay. **Age** shows a spread of data across the age range without a strong trend. For **income**, there's more variability at higher income levels, but there is no clear pattern suggesting a strong relationship. Overall, these plots suggest that individually, these variables do not have a simple linear relationship with the number of

initial days spent in the hospital. However, together they might. Income might benefit from a transformation to better understand the relationship. Doc\_visits suggest that there is no strong, straightforward relationship between the number of doctor visits and the average initial days, as increased doctor visits do not correlate with either a significant increase or decrease in the initial days. The bimodal distribution of Initial\_days may be why one sees distributions grouped above and below the lines.

```
[ ]: # Bivariate Graphs with Initial_days
plt.figure(figsize=(8, 8))

# Marital
plt.subplot(2, 2, 1)
sns.boxplot(data=df, x='Marital', y='Initial_days', color='lightgreen')
sns.pointplot(data=df, x='Marital', y='Initial_days', color='red', estimator=np.
    ↳mean, errorbar=None)
plt.title('Initial_days vs Marital statuses')

# Gender
plt.subplot(2, 2, 2)
sns.boxplot(data=df, x='Gender', y='Initial_days', color='lightgreen')
sns.pointplot(data=df, x='Gender', y='Initial_days', color='red', estimator=np.
    ↳mean, errorbar=None)
plt.title('Initial_days vs Gender categories')


# Initial_days for Readmission status
plt.subplot(2, 2, 3)
sns.boxplot(data=df, x='ReAdmis', y='Initial_days', color='lightgreen')
sns.pointplot(data=df, x='ReAdmis', y='Initial_days', color='red', estimator=np.
    ↳mean, errorbar=None)
plt.title('Initial_days for Readmission status')


# Initial_days vs Area categories
plt.subplot(2, 2, 4)
sns.boxplot(data=df, x='Area', y='Initial_days', color='lightgreen')
sns.pointplot(data=df, x='Area', y='Initial_days', color='red', estimator=np.
    ↳mean, errorbar=None)
plt.title('Initial_days vs Area')

plt.tight_layout()
plt.show()

# boxplot with Initial_admin and Initial_days
plt.figure(figsize=(5, 4))
sns.boxplot(data=df, x='Initial_admin', y='Initial_days', color='lightgreen')
sns.pointplot(data=df, x='Initial_admin', y='Initial_days', color='red',
    ↳estimator=np.mean, errorbar=None)
plt.title('Boxplot for Initial_admin and Initial_days')
```

```
plt.show()
```





- The **Marital** statuses plot shows that separated and single patients tend to have the highest number of days in the hospital, and that divorced and married tended to spend fewer days. The significance of this is unknown. The **Gender** categories show slightly higher median **Initial\_days** for males and non binary patients and a notably lower median for females compared to males. The **Readmission** plot is very interesting. It shows a significantly higher median and and grouping of **Initial\_days** for readmitted patients compared to non-readmitted patients, with several outliers showing long stays among readmitted patients. Curiously, this appears to also show two distinct groups. This is noted. Lastly, the **Area** plot demonstrates a slightly lower median for urban areas, suggesting hospital time is less for urban patients compared to rural and suburban patients. Interestingly, **Initial\_admin** shows a higher median for elective admissions compared to emergency admissions.
- *The red lines in the boxplots show the mean values for each group. This is more about practice with visualizations than anything and to quickly compare the mean to the median. If the mean is far away from the median, could suggests that the distribution of **Initial\_days** within the category is skewed, possibly indicating the presence of outliers or a non-normal distribution. However, the skewness alone does not directly tell one that it is a poor candidate for the model. Additionally, the order of the arrangement of categories on the x-axis of can influence the interpretation and direction of the mean line trend. If the categories are arranged in a certain order, the mean line might appear to trend up, down, or remain flat. So it's important to not draw those kinds of conclusions from the mean line alone.*

```
[ ]: # 4 by 2 subplot grid
fig, axes = plt.subplots(4, 2, figsize=(8, 16))
```

```

# S_T_Admission
sns.boxplot(data=df, x='S_T_Admission', y='Initial_days', ax=axes[0, 0],
            color='lightblue')
sns.pointplot(data=df, x='S_T_Admission', y='Initial_days', ax=axes[0, 0],
            color='brown', estimator=np.mean, errorbar=None)
axes[0, 0].set_title('S_T_Admission vs. Initial_days')

# S_T_Treatment
sns.boxplot(data=df, x='S_T_Treatment', y='Initial_days', ax=axes[0, 1],
            color='lightblue')
sns.pointplot(data=df, x='S_T_Treatment', y='Initial_days', ax=axes[0, 1],
            color='brown', estimator=np.mean, errorbar=None)
axes[0, 1].set_title('S_T_Treatment vs. Initial_days')

# S_T_Visits
sns.boxplot(data=df, x='S_T_Visits', y='Initial_days', ax=axes[1, 0],
            color='lightblue')
sns.pointplot(data=df, x='S_T_Visits', y='Initial_days', ax=axes[1, 0],
            color='brown', estimator=np.mean, errorbar=None)
axes[1, 0].set_title('S_T_Visits vs. Initial_days')

# S_Reliability
sns.boxplot(data=df, x='S_Reliability', y='Initial_days', ax=axes[1, 1],
            color='lightblue')
sns.pointplot(data=df, x='S_Reliability', y='Initial_days', ax=axes[1, 1],
            color='brown', estimator=np.mean, errorbar=None)
axes[1, 1].set_title('S_Reliability vs. Initial_days')

# S_Options
sns.boxplot(data=df, x='S_Options', y='Initial_days', ax=axes[2, 0],
            color='lightblue')
sns.pointplot(data=df, x='S_Options', y='Initial_days', ax=axes[2, 0],
            color='brown', estimator=np.mean, errorbar=None)
axes[2, 0].set_title('S_Options vs. Initial_days')

# S_Hours_Treatment
sns.boxplot(data=df, x='S_Hours_Treatment', y='Initial_days', ax=axes[2, 1],
            color='lightblue')
sns.pointplot(data=df, x='S_Hours_Treatment', y='Initial_days', ax=axes[2, 1],
            color='brown', estimator=np.mean, errorbar=None)
axes[2, 1].set_title('S_Hours_Treatment vs. Initial_days')

# S_Staff
sns.boxplot(data=df, x='S_Staff', y='Initial_days', ax=axes[3, 0],
            color='lightblue')

```









```

sns.pointplot(data=df, x='S_Staff', y='Initial_days', ax=axes[3, 0],
    color='brown', estimator=np.mean, errorbar=None)
axes[3, 0].set_title('S_Staff vs. Initial_days')

# S_Active_Listening
sns.boxplot(data=df, x='S_Active_Listening', y='Initial_days', ax=axes[3, 1],
    color='lightblue')
sns.pointplot(data=df, x='S_Active_Listening', y='Initial_days', ax=axes[3, 1],
    color='brown', estimator=np.mean, errorbar=None)
axes[3, 1].set_title('S_Active_Listening vs. Initial_days')

plt.tight_layout()
plt.show()

```



- Seeing these survey results in a bivariate plot with Initial\_days is interesting in the variation in the median Initial\_days across the different survey responses. Admittedly, I am a little unsure about how to interpret this. The initial thinking is that there is some interesting insights to glean from this. Perhaps this suggests that the survey responses may have some predictive power in determining the length of a patient's hospital stay.
- It is interesting to see the relationship between the highest survey responses and the length of hospital stay though, where it the highest rating in most categories is correlated with the highest and lowest hospital stay lengths. This may be insightful to hospitals in terms of patient care and satisfaction.

---

```
[ ]: df = pd.read_csv('df_reduced.csv', index_col=0)
```

## 11 C4 Data Transformation

### 11.1 Reexpression of categorical variables

- Since the dataset contains several nominal categorical variables, it is essential to re-express these variables in a numerical format to include them in the regression model. This process is known as one-hot encoding, and it involves re-expressing categorical variables as binary variables, a format the regression model can use, by creating dummy variables for each category within a categorical variable. The Pandas library provides a method for performing this transformation using the `pd.get_dummies()` function. This function creates a new binary column for each category in a categorical variable,; 1 indicating the presence of that category and 0 indicating the absence. The original categorical variable is then dropped from the dataset to avoid multicollinearity issues in the regression model.
- Ordinal and binary variables (*Yes/No*->1/0) will be re-expressed as well using python's `replace` method.
- (`replace` is apparently being depreciated: “*FutureWarning: Downcasting behavior in replace is deprecated and will be removed in a future version. To retain the old behavior, explicitly call result.infer\_objects(copy=False). To opt-in to the future behavior, set pd.set\_option('future.no\_silent\_downcasting', True)*”)  
`df[binary_vars] = df[binary_vars].replace({'Yes': 1, 'No': 0})`

```
[ ]: # select and show values counts for binary variables to compare before and
      ↪after reexpression
binary_vars = [col for col in df.columns if df[col].isin(['Yes', 'No']).all()]
for col in binary_vars:
    print(df[col].value_counts())
```

```
ReAdmis
No      6331
Yes     3669
Name: count, dtype: int64
```



```

HighBlood
No      5910
Yes     4090
Name: count, dtype: int64
Stroke
No      8007
Yes     1993
Name: count, dtype: int64
Overweight
Yes     7094
No      2906
Name: count, dtype: int64
Arthritis
No      6426
Yes     3574
Name: count, dtype: int64
Diabetes
No      7262
Yes     2738
Name: count, dtype: int64
Hyperlipidemia
No      6628
Yes     3372
Name: count, dtype: int64
BackPain
No      5886
Yes     4114
Name: count, dtype: int64
Anxiety
No      6785
Yes     3215
Name: count, dtype: int64
Allergic_rhinitis
No      6059
Yes     3941
Name: count, dtype: int64
Reflux_esophagitis
No      5865
Yes     4135
Name: count, dtype: int64
Asthma
No      7107
Yes     2893
Name: count, dtype: int64

```

```

[ ]: # re-expression of binary variables
df[binary_vars] = df[binary_vars].replace({'Yes': 1, 'No': 0})

```

```
# check the unique values for the binary variables
for col in binary_vars:
    print(df[col].value_counts())
```

```
ReAdmis
0    6331
1    3669
Name: count, dtype: int64
HighBlood
0    5910
1    4090
Name: count, dtype: int64
Stroke
0    8007
1    1993
Name: count, dtype: int64
Overweight
1    7094
0    2906
Name: count, dtype: int64
Arthritis
0    6426
1    3574
Name: count, dtype: int64
Diabetes
0    7262
1    2738
Name: count, dtype: int64
Hyperlipidemia
0    6628
1    3372
Name: count, dtype: int64
BackPain
0    5886
1    4114
Name: count, dtype: int64
Anxiety
0    6785
1    3215
Name: count, dtype: int64
Allergic_rhinitis
0    6059
1    3941
Name: count, dtype: int64
Reflux_esophagitis
0    5865
1    4135
```

```
Name: count, dtype: int64
```

```
Asthma
```

```
0    7107
```

```
1     2893
```

```
Name: count, dtype: int64
```

```
C:\Users\hinde\AppData\Local\Temp\ipykernel_1160\2645779669.py:2: FutureWarning:
Downcasting behavior in `replace` is deprecated and will be removed in a future
version. To retain the old behavior, explicitly call
`result.infer_objects(copy=False)`. To opt-in to the future behavior, set
`pd.set_option('future.no_silent_downcasting', True)`
df[binary_vars] = df[binary_vars].replace({'Yes': 1, 'No': 0})
```

- The data dictionary states: “The (Survey) variables represent responses to an eight question survey asking customers to rate the importance of various factors/surfaces on a scale of 1 to 8 (1 most important, 8 least important)” Generally 1 is low and 8 is high in terms of importance and having 1 as most important and 8 as least important is not intuitive, and has caused this analyst confusion. Therefore, we will reverse the scale of survey variables so that 1 is the lowest and 8 is the highest in terms of importance. This will make the interpretation more intuitive in the regression analysis.

```
[ ]: # Collect values and compare before and after
survey_vars = ['S_T_Admission', 'S_T_Treatment', 'S_T_Visits', 'S_Reliability',
               'S_Options', 'S_Hours_Treatment', 'S_Staff', 'S_Active_Listening']
df[survey_vars].head()
```

```
[ ]:
      S_T_Admission  S_T_Treatment  S_T_Visits  S_Reliability  S_Options  \
CaseOrder
1                3                3            2                2            4
2                3                4            3                4            4
3                2                4            4                4            3
4                3                5            5                3            4
5                2                1            3                3            5

      S_Hours_Treatment  S_Staff  S_Active_Listening
CaseOrder
1                    3         3                    4
2                    4         3                    3
3                    4         3                    3
4                    5         5                    5
5                    3         4                    3
```

```
[ ]: # reverse the scale of survey variables so that 1 is the lowest and 8 is the
      highest in terms of importance. and after the change.
df[survey_vars] = df[survey_vars].replace({1: 8, 2: 7, 3: 6, 4: 5, 5: 4, 6: 3,
      7: 2, 8: 1})
df[survey_vars].head()
```

```
[ ]:      S_T_Admission  S_T_Treatment  S_T_Visits  S_Reliability  S_Options  \
CaseOrder
1           6           6           7           7           5
2           6           5           6           5           5
3           7           5           5           5           6
4           6           4           4           6           5
5           7           8           6           6           4
```

```
      S_Hours_Treatment  S_Staff  S_Active_Listening
CaseOrder
1           6           6           5
2           5           6           6
3           5           6           6
4           4           4           4
5           6           5           6
```

```
[ ]: # reexpress `complication_risk` from categorical variable to numerical variable
      ↳where 1 is the lowest and 3 is the highest in terms of risk.
# Check values before and after
print(df['Complication_risk'].value_counts())
df['Complication_risk'] = df['Complication_risk'].replace({'Low': 1, 'Medium': 2,
      ↳'High': 3}).astype(int)
df['Complication_risk'].value_counts()
```

```
Complication_risk
Medium    4517
High      3358
Low       2125
Name: count, dtype: int64
```

```
C:\Users\hinde\AppData\Local\Temp\ipykernel_1160\1705884698.py:4: FutureWarning:
Downcasting behavior in `replace` is deprecated and will be removed in a future
version. To retain the old behavior, explicitly call
`result.infer_objects(copy=False)`. To opt-in to the future behavior, set
`pd.set_option('future.no_silent_downcasting', True)`
df['Complication_risk'] = df['Complication_risk'].replace({'Low': 1, 'Medium':
2, 'High': 3}).astype(int)
```

```
[ ]: Complication_risk
2     4517
3     3358
1     2125
Name: count, dtype: int64
```

```
[ ]: #to csv to save progress so far.
df.to_csv('df_for_one_hot.csv', index='CaseOrder')
```

```
[ ]: #read the csv
df = pd.read_csv('df_for_one_hot.csv', index_col=0)
df.head().transpose()
```

```
[ ]: CaseOrder          1          2 \
Area          Suburban          Urban
Children          1          3
Age             53          51
Income          86575          46805
Marital          Divorced          Married
Gender           Male          Female
ReAdmis          0          0
VitD_levels      19.14          18.94
Doc_visits        6          4
vitD_supp         0          1
Initial_admin      Emergency Admission  Emergency Admission
HighBlood          1          1
Stroke             0          0
Complication_risk  2          3
Overweight         0          1
Arthritis          1          0
Diabetes           1          0
Hyperlipidemia     0          0
BackPain           1          0
Anxiety            1          0
Allergic_rhinitis  1          0
Reflux_esophagitis 0          1
Asthma             1          0
Initial_days       10.59          15.13
S_T_Admission      6          6
S_T_Treatment      6          5
S_T_Visits         7          6
S_Reliability      7          5
S_Options          5          5
S_Hours_Treatment  6          5
S_Staff            6          6
S_Active_Listening 5          6

CaseOrder          3          4          5
Area          Suburban          Suburban          Rural
Children          3          0          1
Age             53          78          22
Income          14370          39741          1209
Marital          Widowed          Married          Widowed
Gender           Female          Male          Female
ReAdmis          0          0          0
VitD_levels      18.06          16.58          17.44
```

Doc_visits	4	4	5
vitD_supp	0	0	2
Initial_admin	Elective Admission	Elective Admission	Elective Admission
HighBlood	1	0	0
Stroke	0	1	0
Complication_risk	2	2	1
Overweight	1	0	0
Arthritis	0	1	0
Diabetes	1	0	0
Hyperlipidemia	0	0	1
BackPain	0	0	0
Anxiety	0	0	0
Allergic_rhinitis	0	0	1
Reflux_esophagitis	0	1	0
Asthma	0	1	0
Initial_days	4.77	1.71	1.25
S_T_Admission	7	6	7
S_T_Treatment	5	4	8
S_T_Visits	5	4	6
S_Reliability	5	6	6
S_Options	6	5	4
S_Hours_Treatment	5	4	6
S_Staff	6	4	5
S_Active_Listening	6	4	6

- To handle nominal variables (categorical variables with no inherent order) in a regression model, one-hot encoding is often used. This transforms each unique category of a variable into a separate binary variable. Each new binary variable represents the presence (1) or absence (0) of the category for a data point. (Middleton, 2022)
- To avoid introducing multicollinearity, it's common practice to drop one of the binary variables from each encoded category. Which will be done with the optional argument `drop_first=True` in the `pd.get_dummies` method.

```
[ ]: # Using get_dummies to convert nominal variables to 1 and 0 for one-hot
      ↪ encoding and drop the first column to avoid multicollinearity.
nominal_vars = ['Area', 'Marital', 'Gender', 'Initial_admin']
df_encoded = pd.get_dummies(df, columns=nominal_vars, dtype=int,
      ↪ drop_first=True)
```

```
[ ]: # Show the head of the encoded DataFrame
pd.set_option('display.max_columns', None)
df_encoded
```

```
[ ]:      Children  Age  Income  ReAdmis  VitD_levels  Doc_visits  vitD_supp  \
CaseOrder
1           1    53   86575         0        19.14         6         0
2           3    51   46805         0        18.94         4         1
```

3	3	53	14370	0	18.06	4	0
4	0	78	39741	0	16.58	4	0
5	1	22	1209	0	17.44	5	2
...	...	...	...	...	...	...	...
9996	2	25	45967	0	16.98	4	1
9997	4	87	14983	1	18.18	5	0
9998	3	45	65917	1	17.13	4	0
9999	3	43	29702	1	19.91	5	1
10000	8	70	62682	1	18.39	5	1

	HighBlood	Stroke	Complication_risk	Overweight	Arthritis	\
CaseOrder						
1	1	0	2	0	1	
2	1	0	3	1	0	
3	1	0	2	1	0	
4	0	1	2	0	1	
5	0	0	1	0	0	
...	...	...	...	...	...	
9996	1	0	2	0	0	
9997	1	0	2	1	1	
9998	1	0	3	1	0	
9999	0	0	2	1	0	
10000	0	0	1	1	1	

	Diabetes	Hyperlipidemia	BackPain	Anxiety	Allergic_rhinitis	\
CaseOrder						
1	1	0	1	1	1	
2	0	0	0	0	0	
3	1	0	0	0	0	
4	0	0	0	0	0	
5	0	1	0	0	1	
...	...	...	...	...	...	
9996	0	0	0	1	0	
9997	1	0	0	0	0	
9998	0	0	0	1	1	
9999	0	0	1	0	0	
10000	0	1	0	0	1	

	Reflux_esophagitis	Asthma	Initial_days	S_T_Admission	\
CaseOrder					
1	0	1	10.59	6	
2	1	0	15.13	6	
3	0	0	4.77	7	
4	1	1	1.71	6	
5	0	0	1.25	7	
...	...	...	...	...	
9996	1	0	51.56	6	

9997	0	1	68.67	6
9998	0	0	70.15	6
9999	0	0	63.36	4
10000	0	0	70.85	5

	S_T_Treatment	S_T_Visits	S_Reliability	S_Options	\
CaseOrder					
1	6	7	7	5	
2	5	6	5	5	
3	5	5	5	6	
4	4	4	6	5	
5	8	6	6	4	
...	...	...	...	...	
9996	7	7	6	5	
9997	6	5	7	4	
9998	6	6	5	5	
9999	4	6	5	5	
10000	6	6	7	6	

	S_Hours_Treatment	S_Staff	S_Active_Listening	Area_Suburban	\
CaseOrder					
1	6	6	5	1	
2	5	6	6	0	
3	5	6	6	1	
4	4	4	4	1	
5	6	5	6	0	
...	...	...	...	...	
9996	6	5	7	0	
9997	6	5	5	0	
9998	7	6	7	0	
9999	6	5	6	0	
10000	3	5	6	0	

	Area_Urban	Marital_Married	Marital_Never Married	\
CaseOrder				
1	0	0	0	
2	1	1	0	
3	0	0	0	
4	0	1	0	
5	0	0	0	
...	...	...	...	
9996	1	0	0	
9997	1	0	0	
9998	0	0	0	
9999	0	0	0	
10000	1	0	0	



CaseOrder	Marital_Separated	Marital_Widowed	Gender_Male	Gender_Nonbinary	\
1	0	0	1	0	
2	0	0	0	0	
3	0	1	0	0	
4	0	0	1	0	
5	0	1	0	0	
...	...	...	...	...	
9996	0	1	1	0	
9997	0	1	1	0	
9998	1	0	0	0	
9999	0	0	1	0	
10000	1	0	0	0	

CaseOrder	Initial_admin_Emergency Admission	\
1	1	
2	1	
3	0	
4	0	
5	0	
...	...	
9996	1	
9997	0	
9998	0	
9999	1	
10000	0	

CaseOrder	Initial_admin_Observation Admission
1	0
2	0
3	0
4	0
5	0
...	...
9996	0
9997	0
9998	0
9999	0
10000	1

[10000 rows x 38 columns]

- Noting the shape to be sure extra columns drop: 38 columns

```
[ ]: #FINAL CLEAN TRANSFORMED CSV
df_encoded.to_csv('medical_transformed.csv', index='CaseOrder')
```

- Import Transformed Data for Initial model

```
[ ]: df = pd.read_csv('medical_transformed.csv', index_col=0)
df.head()
```

```
[ ]:
      Children  Age  Income  ReAdmis  VitD_levels  Doc_visits  vitD_supp  \
CaseOrder
1             1   53   86575         0        19.14           6           0
2             3   51   46805         0        18.94           4           1
3             3   53   14370         0        18.06           4           0
4             0   78   39741         0        16.58           4           0
5             1   22    1209         0        17.44           5           2
```

```

      HighBlood  Stroke  Complication_risk  Overweight  Arthritis  \
CaseOrder
1             1       0                  2           0           1
2             1       0                  3           1           0
3             1       0                  2           1           0
4             0       1                  2           0           1
5             0       0                  1           0           0
```

```

      Diabetes  Hyperlipidemia  BackPain  Anxiety  Allergic_rhinitis  \
CaseOrder
1             1                0         1         1                1
2             0                0         0         0                0
3             1                0         0         0                0
4             0                0         0         0                0
5             0                1         0         0                1
```

```

      Reflux_esophagitis  Asthma  Initial_days  S_T_Admission  \
CaseOrder
1                    0         1        10.59           6
2                    1         0        15.13           6
3                    0         0         4.77           7
4                    1         1         1.71           6
5                    0         0         1.25           7
```

```

      S_T_Treatment  S_T_Visits  S_Reliability  S_Options  \
CaseOrder
1                 6           7              7           5
2                 5           6              5           5
3                 5           5              5           6
4                 4           4              6           5
```

	5	8	6	6	4
	S_Hours_Treatment	S_Staff	S_Active_Listening	Area_Suburban	\
CaseOrder					
1	6	6	5	1	
2	5	6	6	0	
3	5	6	6	1	
4	4	4	4	1	
5	6	5	6	0	

	Area_Urban	Marital_Married	Marital_Never Married	\
CaseOrder				
1	0	0	0	
2	1	1	0	
3	0	0	0	
4	0	1	0	
5	0	0	0	

	Marital_Separated	Marital_Widowed	Gender_Male	Gender_Nonbinary	\
CaseOrder					
1	0	0	1	0	
2	0	0	0	0	
3	0	1	0	0	
4	0	0	1	0	
5	0	1	0	0	


  

	Initial_admin_Emergency Admission	\
CaseOrder		
1	1	
2	1	
3	0	
4	0	
5	0	

	Initial_admin_Observation Admission
CaseOrder	
1	0
2	0
3	0
4	0
5	0

```
[ ]: # create a histogram of the initial_days column
plt.figure(figsize=(4, 3))
plt.hist(df['Initial_days'], bins=50)
plt.xlabel('Initial_days')
plt.show()
```



## 12 Part IV: Model Comparison and Analysis

12.1 D. Compare an initial and a reduced linear regression model by doing the following:

12.1.1 D1. Construct an initial multiple linear regression model from all independent variables that were identified in part C2:

*The processes and code below were informed by several source mentioned in the refrence section. (Sewell, 2024), (UnfoldDataScience YouTube, 2023), (Stack Overflow, 2020), (GeeksforGeeks, 2023), (Indhumathy Chelliah, 2021)*

```
[ ]: # multiple regression model using df and ols and 'Initial_days' as the
      ↳ dependent variable and all other variables in the dataset as independent
      ↳ variables
X = df.drop('Initial_days', axis=1)
Y = df['Initial_days']
X = sm.add_constant(X)
model = sm.OLS(Y, X).fit()
predictions = model.predict(X)
model_summary = model.summary()
model_summary
```

[ ]:

<b>Dep. Variable:</b>	Initial_days	<b>R-squared:</b>	0.726
<b>Model:</b>	OLS	<b>Adj. R-squared:</b>	0.725
<b>Method:</b>	Least Squares	<b>F-statistic:</b>	714.1
<b>Date:</b>	Tue, 26 Mar 2024	<b>Prob (F-statistic):</b>	0.00
<b>Time:</b>	01:24:44	<b>Log-Likelihood:</b>	-40411.
<b>No. Observations:</b>	10000	<b>AIC:</b>	8.090e+04
<b>Df Residuals:</b>	9962	<b>BIC:</b>	8.117e+04
<b>Df Model:</b>	37		
<b>Covariance Type:</b>	nonrobust		

	coef	std err	t	P>  t	[0.025	0.975]
const	19.4602	2.467	7.889	0.000	14.625	24.295
Children	0.0401	0.064	0.628	0.530	-0.085	0.165
Age	0.0035	0.007	0.521	0.603	-0.010	0.017
Income	-3.442e-06	4.84e-06	-0.710	0.477	-1.29e-05	6.06e-06
ReAdmis	46.4505	0.287	162.028	0.000	45.889	47.012
VitD_levels	-0.0775	0.069	-1.130	0.259	-0.212	0.057
Doc_visits	-0.1714	0.132	-1.297	0.195	-0.430	0.088
vitD_supp	0.2924	0.220	1.331	0.183	-0.138	0.723
HighBlood	-0.4475	0.281	-1.592	0.111	-0.998	0.103
Stroke	-0.2008	0.346	-0.581	0.561	-0.878	0.477
Complication_risk	-0.3944	0.189	-2.084	0.037	-0.765	-0.023
Overweight	-0.2090	0.304	-0.687	0.492	-0.805	0.387
Arthritis	0.6649	0.288	2.305	0.021	0.100	1.230
Diabetes	0.0132	0.310	0.042	0.966	-0.595	0.621
Hyperlipidemia	-0.3959	0.292	-1.354	0.176	-0.969	0.177
BackPain	0.3505	0.281	1.247	0.213	-0.201	0.902
Anxiety	0.5303	0.296	1.793	0.073	-0.049	1.110
Allergic_rhinitis	0.4092	0.283	1.447	0.148	-0.145	0.963
Reflux_esophagitis	0.4223	0.281	1.505	0.132	-0.128	0.972
Asthma	0.0406	0.305	0.133	0.894	-0.557	0.638
S_T_Admission	0.4003	0.199	2.013	0.044	0.010	0.790
S_T_Treatment	0.1342	0.183	0.732	0.464	-0.225	0.494
S_T_Visits	-0.1296	0.169	-0.765	0.444	-0.462	0.202
S_Reliability	0.3911	0.151	2.592	0.010	0.095	0.687
S_Options	0.0093	0.159	0.058	0.953	-0.302	0.321
S_Hours_Treatment	-0.2056	0.164	-1.254	0.210	-0.527	0.116
S_Staff	-0.2466	0.154	-1.596	0.110	-0.549	0.056
S_Active_Listening	-0.1981	0.145	-1.362	0.173	-0.483	0.087
Area_Suburban	0.1602	0.338	0.475	0.635	-0.501	0.822
Area_Urban	0.3731	0.339	1.102	0.271	-0.291	1.037
Marital_Married	-0.0263	0.438	-0.060	0.952	-0.885	0.832
Marital_Never Married	0.4302	0.440	0.977	0.328	-0.433	1.293
Marital_Separated	0.7953	0.440	1.809	0.070	-0.066	1.657
Marital_Widowed	0.2762	0.437	0.632	0.527	-0.580	1.132
Gender_Male	-0.0963	0.279	-0.344	0.731	-0.644	0.452
Gender_Nonbinary	-0.2836	0.964	-0.294	0.769	-2.174	1.606
Initial_admin_Emergency Admission	-1.6011	0.338	-4.741	0.000	-2.263	-0.939
Initial_admin_Observation Admission	-0.2463	0.393	-0.626	0.531	-1.018	0.525

<b>Omnibus:</b>	1948.374	<b>Durbin-Watson:</b>	1.272
<b>Prob(Omnibus):</b>	0.000	<b>Jarque-Bera (JB):</b>	3298.126
<b>Skew:</b>	1.318	<b>Prob(JB):</b>	0.00
<b>Kurtosis:</b>	3.983	<b>Cond. No.</b>	8.88e+05

Notes:

- [1] Standard Errors assume that the covariance matrix of the errors is correctly specified.  
[2] The condition number is large, 8.88e+05. This might indicate that there are strong multicollinearity or other numerical problems.

## 13 Initial Regression Model based on all predictors

- $(\hat{y}) = 19.4602 + 0.0401(\text{Children}) + 0.0035(\text{Age}) - 3.442\text{e-}06(\text{Income}) + 46.4505(\text{ReAdmis}) - 0.0775(\text{VitD\_levels}) - 0.1714(\text{Doc\_visits}) + 0.2924(\text{vitD\_supp}) - 0.4475(\text{HighBlood}) - 0.2008(\text{Stroke}) - 0.3944(\text{Complication\_risk}) - 0.2090(\text{Overweight}) + 0.6649(\text{Arthritis}) + 0.0132(\text{Diabetes}) - 0.3959(\text{Hyperlipidemia}) + 0.3505(\text{BackPain}) + 0.5303(\text{Anxiety}) + 0.4092(\text{Allergic\_rhinitis}) + 0.4223(\text{Reflux\_esophagitis}) + 0.0406(\text{Asthma}) + 0.4003(\text{S\_T\_Admission}) + 0.1342(\text{S\_T\_Treatment}) - 0.1296(\text{S\_T\_Visits}) + 0.3911(\text{S\_Reliability}) + 0.0093(\text{S\_Options}) - 0.2056(\text{S\_Hours\_Treatment}) - 0.2466(\text{S\_Staff}) - 0.1981(\text{S\_Active\_Listening}) + 0.1602(\text{Area\_Suburban}) + 0.3731(\text{Area\_Urban}) - 0.0263(\text{Marital\_Married}) + 0.4302(\text{Marital\_Never Married}) + 0.7953(\text{Marital\_Separated}) + 0.2762(\text{Marital\_Widowed}) - 0.0963(\text{Gender\_Male}) - 0.2836(\text{Gender\_Nonbinary}) - 1.6011(\text{Initial\_admin\_Emergency Admission}) - 0.2463(\text{Initial\_admin\_Observation Admission})$

**13.0.1 D2. Justify a statistically based feature selection procedure or a model evaluation metric to reduce the initial model in a way that aligns with the research question:**

- A backwards selection method will be used to reduce the initial model. To justify the feature selection, model summary statistics will be analyzed, certain assumptions will be checked, and visualizations will be created and analyzed.

**13.0.2 Note: The following requirements from Part E of the performance assessment will be demonstrated in the multiple cells below, but not necessarily in the exact order of the PA.**

•

**13.0.3 E. Analyze the data set using your reduced linear regression model by doing the following:**

- \*E1. Explain your data analysis process by comparing the initial multiple linear regression model and reduced linear regression model, including the following element:\*\* • a model evaluation metric\*
- \*E2. Provide the output and all calculations of the analysis you performed, including the following elements for your reduced linear regression model:\*\* • a residual plot • the model's

residual standard error\*


```
[ ]: fig, axes = plt.subplots(1, 3, figsize=(15, 5))

# actual vs predicted initial days
sns.regplot(x=predictions, y=Y, fit_reg=True, line_kws={'color': 'orange'},
            ax=axes[0])
axes[0].set_xlabel('Predicted Initial Days')
axes[0].set_ylabel('Actual Initial Days')
axes[0].set_title('Actual vs Predicted Initial Days')

# histogram of actual values
axes[1].hist(Y, bins=100)
axes[1].set_xlabel('Initial Days')
axes[1].set_ylabel('Frequency')
axes[1].set_title('Histogram of Actual Initial Days')

# histogram of predicted values
axes[2].hist(predictions, bins=100)
axes[2].set_xlabel('Predicted Initial Days')
axes[2].set_ylabel('Frequency')
axes[2].set_title('Histogram of Predicted Initial Days')

plt.tight_layout()
plt.show()
```



- The plot of Actual vs Predicted days seems to miss much of the data in the middle, predicting at lower and higher values. The actual Initial Days histogram again shows it's bimodal distribution, suggesting two distinct groups or patterns within the data. The predicted Initial Days histogram clearly shows a large range of missing values in the middle, and is heavily concentrated at the low and high ends of the range.

```
[ ]: # calculate RSE
mse = model.scale
```

```
# Calculate RSE
rse = np.sqrt(mse)
print("Residual Standard Error (RSE):", rse)
```

Residual Standard Error (RSE): 13.792044580624435

Rse calculation: (Stack Overflow 2023)

### 13.1 Initial Model Fit:

- The R-squared is 0.726, suggesting that approximately 72.6% of the variability in `Initial_days` may be explained by the model, which in combination with the almost identical Adj. R-squared of 0.725 indicating a good fit with initial model.
- The F-statistic is 714.14 with a Prob (F-statistic) of 0.00, *suggesting* that the model is statistically significant overall.
- The AIC 8.090e+04 and BIC 8.117e+04 are very similar, suggesting suggests that both are close in their evaluation of model complexity. These will be re-examined in the reduced model to see if they are lowered.
- Residual Standard Error calculation (RSE): 13.79 `Initial_days` ranges from 1 to 72 days. An RSE of 13.79 days represents over 19% ( $13.792 / 72 * 100$ ) of the total range. This suggests that, on average, the model's predictions for length of stay can deviate from the actual values by up to 13.792 days. This seems significant in this context and indicates room for improvement.

Variables. Some predictor variables have high t-values and low p-values ( $P > |t|$ ), sometimes indicating that they are statistically significant. Of note is the `ReAdmis` feature, it has a very low p-value and a highly significant coefficient (46.4505), suggesting a strong association with `Initial_days`. However, variables such as `Children`, `Age`, `Income`, and others have high p-values, indicating that they might not be significant predictors of `Initial_days` in the presence of other variables. The const coefficient (y-intercept) is 19.5835, which represents the expected value of `Initial_days` when all other predictors are at zero. It is also important to note the values of the coefficients for the predictors. Larger values can suggest a more important role for the predictor in the model. For example, the coefficient for `ReAdmis` is 46.4505, which means that for every unit increase in `ReAdmis`, the expected value of `Initial_days` increases by 46.4505 units, holding all other predictors constant. This is a large coefficient compared to others, indicating a strong relationship between `ReAdmis` and `Initial_days`.

- Overall, even though there are some summary statistics points to a reliable model, we should be skeptical with the warning about potential multicollinearity, and the plot of the actual vs predicted values not accounting for much of the data. There are several things we should check.

Issues: The note on multicollinearity “[2] The condition number is large, 8.89e+05. This might indicate that there are strong multicollinearity or other numerical problems.” indicates that there might be high correlation between some predictors. This needs to be investigated. Checking the residuals and Variance inflation factor (VIF) analysis can help to identify and highly correlated predictors.

```
[ ]: residuals = model.resid
# Plot the residuals
```



```

fig, axes = plt.subplots(1, 3, figsize=(10, 3))

# reesiduals Dist
sns.histplot(residuals, bins=30, ax=axes[0])
axes[0].set_xlabel('Residuals')
axes[0].set_ylabel('Frequency')
axes[0].set_title('Residuals Distribution')

# mean and median lines to the histogram
mean_residuals = residuals.mean()
median_residuals = residuals.median()
axes[0].axvline(x=mean_residuals, color='green', linestyle='--', label='Mean')
axes[0].axvline(x=median_residuals, color='blue', linestyle='--',
    ↪label='Median')
axes[0].legend()


# QQ plot of residuals
sm.qqplot(residuals, line='s', ax=axes[1])
axes[1].set_xlabel("Theoretical Quantiles")
axes[1].set_ylabel("Sample Quantiles")
axes[1].set_title("QQ plot of residuals")

plt.axhline(y=0, color='red', linestyle='--')
sns.scatterplot(x=predictions, y=residuals, ax=axes[2])
axes[2].set_xlabel("Predicted values")
axes[2].set_ylabel("Residuals")
axes[2].set_title("Residuals vs. predicted values")

# mean and median lines
mean_residuals = residuals.mean()
median_residuals = residuals.median()
axes[2].axhline(y=mean_residuals, color='green', linestyle='--', label='Mean')
axes[2].axhline(y=median_residuals, color='blue', linestyle='--',
    ↪label='Median')
axes[2].legend()

plt.tight_layout()
plt.show()

```



- Ideally, one would like to see a normal distribution centered around zero for the residual distribution, but this **histogram** indicates a slightly bimodal distribution that is skewed to the right, with a tail that grows slightly positive values. However, the mean is in fact around 0, which presents an interesting challenge.
- The **Q-Q plot** shows that the residuals are not normally distributed, as the points do not fall along the straight line. This plot required research to interpret as I was not familiar with it. From S. Kross as seankross.com: “The points in Q-Q plot then cross below the blue line indicating that the actual quantiles that are close to zero are farther from zero than they should be theoretically. At the center of the theoretical distribution there are no data in the actual dataset, and therefore there is no point in the Q-Q plot at (0, 0). The upper half of the Q-Q plot is a reflection across X and Y of the bottom half.” (Kross, 2016) The author also suggests this is the result of a residual distribution that is similar to the one I have. Additionally, the center of the theoretical distribution indeed did not have any data points as mentioned above.
- According to The residuals (errors) should be scattered randomly above and below the zero line across the entire range of predicted value and There should be no discernible pattern in the scatter plot of residuals. This is not the case in my scatter plot of residuals. Indicating that the model is not a good fit for the data.
- VIF analysis will be used to identify highly correlated predictors.

```
[ ]: # perform VIF analysis to check for multicollinearity
X = add_constant(X)
vif = pd.DataFrame()
vif["variables"] = X.columns
vif["VIF"] = [variance_inflation_factor(X, i) for i in range(X.shape[1])]
vif.sort_values(by='VIF', ascending=False)
```

```
[ ]:
```

	variables	VIF
0	const	319.858939
20	S_T_Admission	2.213926
21	S_T_Treatment	1.894971
33	Marital_Widowed	1.631655
30	Marital_Married	1.628373
31	Marital_Never Married	1.619690

32	Marital_Separated	1.617689
22	S_T_Visits	1.608013
25	S_Hours_Treatment	1.506889
37	Initial_admin_Observation Admission	1.499497
36	Initial_admin_Emergency Admission	1.498651
24	S_Options	1.410290
29	Area_Urban	1.333409
28	Area_Suburban	1.329986
26	S_Staff	1.308483
23	S_Reliability	1.284892
27	S_Active_Listening	1.208676
34	Gender_Male	1.024240
35	Gender_Nonbinary	1.023449
15	BackPain	1.005983
5	VitD_levels	1.005793
14	Hyperlipidemia	1.005034
13	Diabetes	1.004894
18	Reflux_esophagitis	1.004395
12	Arthritis	1.004353
1	Children	1.004208
19	Asthma	1.003903
8	HighBlood	1.003838
2	Age	1.003822
3	Income	1.003645
4	ReAdmis	1.003605
10	Complication_risk	1.003576
6	Doc_visits	1.003550
17	Allergic_rhinitis	1.003475
11	Overweight	1.003189
7	vitD_supp	1.003085
16	Anxiety	1.003029
9	Stroke	1.002031

From the VIF analysis, most variables have VIF values well below 5, indicating no significant multicollinearity among them, which is surprising given the message from the model summary: “[2] The condition number is large,  $8.89e+05$ . This might indicate that there are strong multicollinearity or other numerical problems.” The highest VIF values observed for **S\_T\_Admission**, **S\_T\_Treatment**, and **marital** status categories, but even these do not exceed the threshold of 5, suggesting moderate correlation at most. (Stack Exchange, 2012)

Given the generally low VIF values, the summary statistics mentioned above the suggest a good model fit, the residuals and Q-Q plots, and the actual and predicted values, something less obvious must be wrong with the initial model. It is also important to keep in mind the bimodal distribution of the actual **Initial\_days** values, which may be contributing to the model’s poor performance due to the violation of the assumption of normality.

One option is to try to transform the **Initial\_days** variable to make it more normally distributed. This could involve taking the log of the variable, or splitting the data into two groups based on the bimodal distribution and creating separate models for each group.(Bradley, 2023) However, this


would likely be complex at this point in the process and may not be necessary if a reduced model can be created that performs better than the initial model. Therefore, before that is attempted, I will employ what *domain knowledge* I have regarding the variable and use a *correlation matrix* to help identify pairwise relationships between the independent variable. In this context, perhaps a better model can be created by removing some of the predictors that are not significantly associated with `Initial_days` and may be contributing to the model's poor performance.

```
[ ]: # assign independent variables
corr_matrix = df.drop('Initial_days', axis=1).corr()

plt.figure(figsize=(20, 12))

# correlation matrix with values and adjusted font size
sns.heatmap(corr_matrix, annot=True, cmap='coolwarm', center=0,
            annot_kws={"size": 8}, vmin=-1, vmax=1)

plt.title('Correlation Matrix of Independent Variables')
plt.show()
```



- The correlation matrix shows that most of the variables that contain any correlation with each other are the survey items, marital status, area, and initial admission. These would be interesting to explore further but in the context of this analyst, are not as useful as the

other predictors which are largely health and biological factors and importantly, readmission status. The survey items are likely to be highly correlated with each other, and subjective feedback worthy of their own separate analyses, but here may be getting in the way of the model. Marital status, in my personal experience, has never been a factor health care providers consider except when contacting family members. I feel that these are good candidates for removal from the model.

```
[ ]: df = df.drop(['S_T_Admission', 'S_T_Treatment', 'Marital_Widowed',
↳ 'Marital_Married', 'Marital_Never Married', 'Marital_Separated',
↳ 'S_T_Visits', 'S_Hours_Treatment', 'S_Reliability', 'S_Staff', 'S_Options',
↳ 'Area_Urban', 'Initial_admin_Observation Admission', 'S_Active_Listening',
↳ 'Area_Suburban', 'Initial_admin_Emergency Admission'], axis=1)
df.head().transpose()
```

```
[ ]: CaseOrder      1      2      3      4      5
Children          1.00    3.00    3.00    0.00    1.00
Age               53.00   51.00   53.00   78.00   22.00
Income           86575.00 46805.00 14370.00 39741.00 1209.00
ReAdmis          0.00    0.00    0.00    0.00    0.00
VitD_levels      19.14   18.94   18.06   16.58   17.44
Doc_visits        6.00    4.00    4.00    4.00    5.00
vitD_supp         0.00    1.00    0.00    0.00    2.00
HighBlood         1.00    1.00    1.00    0.00    0.00
Stroke            0.00    0.00    0.00    1.00    0.00
Complication_risk 2.00    3.00    2.00    2.00    1.00
Overweight        0.00    1.00    1.00    0.00    0.00
Arthritis         1.00    0.00    0.00    1.00    0.00
Diabetes          1.00    0.00    1.00    0.00    0.00
Hyperlipidemia    0.00    0.00    0.00    0.00    1.00
BackPain          1.00    0.00    0.00    0.00    0.00
Anxiety           1.00    0.00    0.00    0.00    0.00
Allergic_rhinitis 1.00    0.00    0.00    0.00    1.00
Reflux_esophagitis 0.00    1.00    0.00    1.00    0.00
Asthma            1.00    0.00    0.00    1.00    0.00
Initial_days      10.59   15.13    4.77    1.71    1.25
Gender_Male       1.00    0.00    0.00    1.00    0.00
Gender_Nonbinary  0.00    0.00    0.00    0.00    0.00
```

```
[ ]: df.to_csv('medical_transformed_drop1.csv', index='CaseOrder')
```

```
[ ]: # read in the new csv file
df = pd.read_csv('medical_transformed_drop1.csv', index_col=0)
```

```
[ ]: X = df.drop(['Initial_days'], axis=1)
Y = df['Initial_days']
X = sm.add_constant(X)
model_2 = sm.OLS(Y, X).fit()
predictions = model_2.predict(X)
```

```
residuals_2 = model_2.resid
model_summary_2 = model_2.summary()
model_summary_2
```

[ ]:

<b>Dep. Variable:</b>	Initial_days	<b>R-squared:</b>	0.725
<b>Model:</b>	OLS	<b>Adj. R-squared:</b>	0.724
<b>Method:</b>	Least Squares	<b>F-statistic:</b>	1251.
<b>Date:</b>	Tue, 26 Mar 2024	<b>Prob (F-statistic):</b>	0.00
<b>Time:</b>	01:24:56	<b>Log-Likelihood:</b>	-40437.
<b>No. Observations:</b>	10000	<b>AIC:</b>	8.092e+04
<b>Df Residuals:</b>	9978	<b>BIC:</b>	8.108e+04
<b>Df Model:</b>	21		
<b>Covariance Type:</b>	nonrobust		

	coef	std err	t	P>  t	[0.025	0.975]
const	20.1671	1.574	12.816	0.000	17.082	23.252
Children	0.0302	0.064	0.473	0.636	-0.095	0.156
Age	0.0034	0.007	0.511	0.610	-0.010	0.017
Income	-2.567e-06	4.85e-06	-0.529	0.597	-1.21e-05	6.94e-06
ReAdmis	46.4258	0.287	161.793	0.000	45.863	46.988
VitD_levels	-0.0904	0.069	-1.319	0.187	-0.225	0.044
Doc_visits	-0.1729	0.132	-1.307	0.191	-0.432	0.086
vitD_supp	0.2930	0.220	1.332	0.183	-0.138	0.724
HighBlood	-0.4396	0.281	-1.563	0.118	-0.991	0.112
Stroke	-0.1677	0.346	-0.485	0.628	-0.846	0.511
Complication_risk	-0.3983	0.189	-2.103	0.035	-0.770	-0.027
Overweight	-0.1958	0.305	-0.643	0.520	-0.793	0.401
Arthritis	0.6633	0.289	2.298	0.022	0.098	1.229
Diabetes	0.0037	0.310	0.012	0.990	-0.604	0.612
Hyperlipidemia	-0.4339	0.293	-1.483	0.138	-1.007	0.140
BackPain	0.3146	0.281	1.119	0.263	-0.237	0.866
Anxiety	0.5385	0.296	1.819	0.069	-0.042	1.119
Allergic_rhinitis	0.3978	0.283	1.406	0.160	-0.157	0.952
Reflux_esophagitis	0.3974	0.281	1.415	0.157	-0.153	0.948
Asthma	0.0539	0.305	0.177	0.860	-0.544	0.652
Gender_Male	-0.0881	0.280	-0.315	0.753	-0.636	0.460
Gender_Nonbinary	-0.2433	0.965	-0.252	0.801	-2.135	1.649

<b>Omnibus:</b>	1977.930	<b>Durbin-Watson:</b>	1.270
<b>Prob(Omnibus):</b>	0.000	<b>Jarque-Bera (JB):</b>	3374.405
<b>Skew:</b>	1.331	<b>Prob(JB):</b>	0.00
<b>Kurtosis:</b>	4.007	<b>Cond. No.</b>	5.66e+05

Notes:

[1] Standard Errors assume that the covariance matrix of the errors is correctly specified.

[2] The condition number is large, 5.66e+05. This might indicate that there are strong multicollinearity or other numerical problems.

```
[ ]: # calculate RSE
mse = model_2.scale
# Calculate RSE
rse = np.sqrt(mse)
print("Residual Standard Error (RSE):", rse)
```

Residual Standard Error (RSE): 13.816250934091325

- The R-squared went from 0.726 to 0.725
- Adj. R-squared went from 0.725 to 0.724
- The F-statistic went from 714.14 with a Prob (F-statistic) of 0.0 to 1314 with a Prob (F-statistic) of 0.0. The f-statistic increase suggests that the model is a better fit than the previous model.
- The AIC and BIC went from 8.090e+04 and 8.117e+04 to AIC 8.092e+04 and BIC 8.107e+04 are very similar to the previous model.
- Residual Standard Error calculation (RSE): 13.79 to 13.8, almost unchanged
- The condition number went from 8.88e+05 to 5.64e+05 which is a significant improvement, suggesting that the multicollinearity is less of an issue in this model. But still the condition number is high, so multicollinearity may still be a problem.

```
[ ]: # Calculate the residuals_2
residuals_2_2 = model_2.resid

# Plot the residuals_2
fig, axes = plt.subplots(1, 3, figsize=(10, 3))

# iduals_2 Distribution
sns.histplot(residuals_2, bins=30, ax=axes[0])
axes[0].set_xlabel('Residuals_2residuals_2')
axes[0].set_ylabel('Frequency')
axes[0].set_title('Residuals_2residuals_2 Distribution')

#mean and median lines
mean_residuals_2 = residuals_2.mean()
median_residuals_2 = residuals_2.median()
axes[0].axvline(x=mean_residuals_2, color='green', linestyle='--', label='Mean')
axes[0].axvline(x=median_residuals_2, color='blue', linestyle='--',
               ↵label='Median')
axes[0].legend()

# QQ plot
sm.qqplot(residuals_2, line='s', ax=axes[1])
axes[1].set_xlabel("Theoretical Quantiles")
axes[1].set_ylabel("Sample Quantiles")
axes[1].set_title("QQ plot of residuals_2")

plt.axhline(y=0, color='red', linestyle='--')
sns.scatterplot(x=predictions, y=residuals_2, ax=axes[2])
```


```

axes[2].set_xlabel("Predicted values")
axes[2].set_ylabel("Residuals_2")
axes[2].set_title("Residuals_2 vs. predicted values")

# Add mean and median lines
mean_residuals_2 = residuals_2.mean()
median_residuals_2 = residuals_2.median()
axes[2].axhline(y=mean_residuals_2, color='green', linestyle='--', label='Mean')
axes[2].axhline(y=median_residuals_2, color='blue', linestyle='--',
                label='Median')
axes[2].legend()

plt.tight_layout()
plt.show()

```



- Not much has changed in our residual plots. Although our model is slightly improved according to the F-statistic, the R-squared and the condition number, the residual plots are still showing some patterns that suggest that the model is not capturing all the information in the data.
- Let's check VIF values for each of the predictors again to see if we gain any new insights.

```

[ ]: # perform VIF analysis to check for multicollinearity
X = add_constant(X)
vif = pd.DataFrame()
vif["variables"] = X.columns
vif["VIF"] = [variance_inflation_factor(X, i) for i in range(X.shape[1])]
vif.sort_values(by='VIF', ascending=False)

```

```

[ ]:

```

	variables	VIF
0	const	129.727015
20	Gender_Male	1.022089
21	Gender_Nonbinary	1.021966
15	BackPain	1.003004
13	Diabetes	1.002739
2	Age	1.002475



14	Hyperlipidemia	1.002397
19	Asthma	1.002384
11	Overweight	1.002341
18	Reflux_esophagitis	1.002326
12	Arthritis	1.002284
1	Children	1.002179
6	Doc_visits	1.002152
5	VitD_levels	1.002145
8	HighBlood	1.002063
4	ReAdmis	1.001930
7	vitD_supp	1.001864
3	Income	1.001701
10	Complication_risk	1.001472
16	Anxiety	1.001259
9	Stroke	1.001181
17	Allergic_rhinitis	1.001157

- The VIF values for the predictors are all essentially 1.
- Given this information, re-examining the p-values of the predictors and their coefficients, we can eliminate the predictors with the highest p-values and lower coefficients to see if that improves the model. Here we have to be careful, because predictors with high p-values may still be important for the model. Examining the p-values and the coefficients together,
- After reviewing p-values and coefficients, I am choosing to remove based on coefficient as it is associated with higher p-values.
- Eliminate those variables with coefficients less than an absolute value of 0.4.

```
[ ]: # statistically significant variables
significant_vars = model_2.params[model_2.params.abs() > 0.4].index.tolist()

# Remove 'const' from the list
if 'const' in significant_vars:
    significant_vars.remove('const')

print('Significant variables:', significant_vars)
```

Significant variables: ['ReAdmis', 'HighBlood', 'Arthritis', 'Hyperlipidemia', 'Anxiety']

```
[ ]: # Create a reduced model with only significant variables above
X_reduced = X[significant_vars]

# Fit the OLS model with reduced variables
model_reduced = sm.OLS(Y, sm.add_constant(X_reduced)).fit()

# Print the summary of the reduced model
model_reduced.summary()
```

```
[ ]:
```

<b>Dep. Variable:</b>	Initial_days	<b>R-squared:</b>	0.724
<b>Model:</b>	OLS	<b>Adj. R-squared:</b>	0.724
<b>Method:</b>	Least Squares	<b>F-statistic:</b>	5252.
<b>Date:</b>	Tue, 26 Mar 2024	<b>Prob (F-statistic):</b>	0.00
<b>Time:</b>	01:24:59	<b>Log-Likelihood:</b>	-40445.
<b>No. Observations:</b>	10000	<b>AIC:</b>	8.090e+04
<b>Df Residuals:</b>	9994	<b>BIC:</b>	8.095e+04
<b>Df Model:</b>	5		
<b>Covariance Type:</b>	nonrobust		

	coef	std err	t	P> t	[0.025	0.975]
<b>const</b>	17.3266	0.269	64.387	0.000	16.799	17.854
<b>ReAdmis</b>	46.4413	0.287	161.990	0.000	45.879	47.003
<b>HighBlood</b>	-0.4551	0.281	-1.619	0.105	-1.006	0.096
<b>Arthritis</b>	0.6742	0.288	2.338	0.019	0.109	1.239
<b>Hyperlipidemia</b>	-0.4176	0.292	-1.429	0.153	-0.991	0.155
<b>Anxiety</b>	0.5454	0.296	1.843	0.065	-0.035	1.125

<b>Omnibus:</b>	1986.555	<b>Durbin-Watson:</b>	1.269
<b>Prob(Omnibus):</b>	0.000	<b>Jarque-Bera (JB):</b>	3396.713
<b>Skew:</b>	1.335	<b>Prob(JB):</b>	0.00
<b>Kurtosis:</b>	4.013	<b>Cond. No.</b>	3.63

Notes:

[1] Standard Errors assume that the covariance matrix of the errors is correctly specified.

```
[ ]: # calculate RSE
mse = model_reduced.scale
# Calculate RSE
rse = np.sqrt(mse)
print("Residual Standard Error (RSE):", rse)
```

Residual Standard Error (RSE): 13.816762081780023

```
[ ]: # new residual check and assign
residuals_reduced = model_reduced.resid
residuals_reduced
```

```
[ ]: CaseOrder
1      -7.501182
2      -1.741505
3     -12.101505
4     -16.290821
5     -15.659016
...
9996    34.143050
9997     4.683002
9998     6.291788
9999    -0.407851
```

```
10000      6.825491
Length: 10000, dtype: float64
```

```
[ ]: # Plot the residuals_reduced
fig, axes = plt.subplots(1, 3, figsize=(10, 3))

# residuals_reduced Distribution
sns.histplot(residuals_reduced, bins=30, ax=axes[0])
axes[0].set_xlabel('residuals_reduced')
axes[0].set_ylabel('Frequency')
axes[0].set_title('residuals_reduced Distribution')


# mean and median lines the histogram
mean_residuals_reduced = residuals_reduced.mean()
median_residuals_reduced = residuals_reduced.median()
axes[0].axvline(x=mean_residuals_reduced, color='green', linestyle='--',
               ↪label='Mean')
axes[0].axvline(x=median_residuals_reduced, color='blue', linestyle='--',
               ↪label='Median')
axes[0].legend()

# QQ plot of residuals_reduced
sm.qqplot(residuals_reduced, line='s', ax=axes[1])
axes[1].set_xlabel("Theoretical Quantiles")
axes[1].set_ylabel("Sample Quantiles")
axes[1].set_title("QQ plot of residuals_reduced")

plt.axhline(y=0, color='red', linestyle='--')
sns.scatterplot(x=predictions, y=residuals_reduced, ax=axes[2])
axes[2].set_xlabel("Predicted values")
axes[2].set_ylabel("residuals_reduced")
axes[2].set_title("residuals_reduced vs. predicted values")

# Add mean and median
mean_residuals_reduced = residuals_reduced.mean()
median_residuals_reduced = residuals_reduced.median()
axes[2].axhline(y=mean_residuals_reduced, color='green', linestyle='--',
               ↪label='Mean')
axes[2].axhline(y=median_residuals_reduced, color='blue', linestyle='--',
               ↪label='Median')
axes[2].legend()

plt.tight_layout()
plt.show()
```



## Part V: Data Summary and Implications

F. Summarize your findings and assumptions by doing the following:

1. Discuss the results of your data analysis, including the following elements:
  - a regression equation for the reduced model
  - an interpretation of the coefficients of the reduced model
  - the statistical and practical significance of the reduced model
  - the limitations of the data analysis
2. Recommend a course of action based on your results.

### 13.1.1 Reduced model:

$$(\hat{y}) = 17.3266 + 46.4413(\text{ReAdmis}) - 0.4551(\text{HighBlood}) + 0.6742(\text{Arthritis}) - 0.4176(\text{Hyperlipidemia}) + 0.5454(\text{Anxiety})$$

**MODEL Statistical Significance SUMMARY:** - The **R-squared** went from 0.726 to 0.725 to 0.724 - **Adj. R-squared** went from 0.725 to 0.724 to 0.724 as well. - The **F-statistic** went from 714.14 to 1314 to 5252 all with a Prob (F-statistic) of 0.0. The f-statistic increase suggests that the model is a much better fit than the previous model. - The **AIC** and **BIC** went from 8.090e+04 and 8.117e+04 to AIC 8.092e+04 and BIC 8.107e+04 to AIC 8.090e+04 and BIC 8.095e+04, very close to each other. - **Residual Standard Error** calculation (RSE): 13.79 to remain at 13.8 no matter the model change. - The *condition number* went from 8.88e+05 to 5.64e+05 to 3.63 suggesting that the multicollinearity is less of an issue in this model. Likely helped by the remove of features. - a **Durbin-Watson** statistic of 1.269 suggests that there is some positive autocorrelation in the model's residuals. This could potentially be a problem because the assumption of independence of errors may be violated.

$$(\hat{y}) = 17.3266 + 46.4413(\text{ReAdmis}) - 0.4551(\text{HighBlood}) + 0.6742(\text{Arthritis}) - 0.4176(\text{Hyperlipidemia}) + 0.5454(\text{Anxiety})$$

**Interpretation of the coefficients:** (*Note, this is a very basic interpretation of what this formula tells us, this does not mean what the model is telling us is actually accurate or useful.*)

$(\hat{y})$  represents the predicted value of the dependent variable, which in this case is the *initial* number of days spent in the hospital.

- The intercept (17.3266) is the value of  $(\hat{y})$  when all independent variables are zero. In other

words, if a patient has not been `ReAdmitted`, has no `HighBlood` pressure, no `Arthritis`, no `Hyperlipidemia`, and no `Anxiety`, the predicted number of `Initial_days` in the hospital would be approximately 17 days

- The coefficients for each explanatory variable indicate the change in the predicted value of ( $\hat{y}$ ) for a *one-unit* increase in that variable, when all other variables remain constant.

**Relationships between the independent variables and the predicted number of `Initial_days` in the hospital are such:**

- – A readmitted patient (`ReAdmis`) is associated with a longer hospital stay.
- – High blood pressure (`HighBlood`) is associated with a shorter hospital stay.
- – Arthritis (`Arthritis`) is associated with a longer hospital stay.
- – Hyperlipidemia (`Hyperlipidemia`) is associated with a shorter hospital stay.
- – Anxiety (`Anxiety`) is associated with a longer hospital stay.

The magnitudes of the coefficients also indicate the relative strength of each variable's association with the predicted outcome. The coefficient for `ReAdmis` (46.4413) is the largest, suggesting that a history of readmission has the strongest impact on the length of hospital stay among the variables included in the model. However, there is a major problem that the high coefficient and low P-value for `ReAdmis` admittedly mislead me on.

We have a model that's designed to predict how many days a patient might initially spend in the hospital, and it uses various health conditions as input factors. However, it has a significant limitation in its design and the way I used one of these factors, namely the patient's readmission status. In a real-world context, according to the data dictionary, the patient's **readmission** can only occur after they have had an Initial stay, making readmission a *future event compared to their initial stay*. In this model, `ReAdmission` status is currently being treated as a factor that can predict the initial hospital stay. But logically, this isn't possible because one can't use information from the future to predict the past. This is a fundamental issue with how the prediction model was constructed and a reminder that models aren't just about variables and coefficients, but having a fundamental understanding of the data and its context in the real world.

Given the results and limitations of the model, my recommended course of action would include a few key steps. At this point, I wouldn't recommend using this model in its current state. If this were a real-world scenario, I would consider myself to be in the exploratory phase of the project. Taking the information we've gathered, I suggest re-evaluating both the explanatory and target variables.

One issue that stands out is the bimodal distribution of the target variable, initial days. During this project, I learned that bimodal distributions can represent two distinct populations within the data set. To address this, I recommend possibly splitting the data and performing appropriate transformations to try and make the distributions of each population more normal.

Moving forward, it's crucial to better understand all the variables. Consulting with domain experts and getting additional data analytics expertise, particularly when it comes to selecting and transforming potential explanatory variables, would be highly beneficial.

I want to highlight something interesting I noticed while creating the visualizations, although I'm not entirely sure what it means yet. If we look at the box plot comparing the `Initial_days` with the `rReAdmis` variable, it forms a pattern that stood out in the visualizations from part C. Interestingly, the scatterplot of the model's predicted values against the actual values has a strikingly similar pattern to the boxplots I mentioned. I believe there's something worth exploring here.


The next project involves logistical regression, and I'm curious to investigate whether it would be useful to explore these variables in the opposite context. Perhaps the initial days in the hospital can help predict readmission status. This is the direction I plan to pursue in my next course of investigation.

```
[ ]: fig, axes = plt.subplots(1, 2, figsize=(6, 3))

# Actual vs Predicted Initial Days
sns.regplot(x=predictions, y=Y, fit_reg=True, line_kws={'color':'orange'},
            ax=axes[0])
axes[0].set_xlabel('Predicted Initial Days')
axes[0].set_ylabel('Actual Initial Days')
axes[0].set_title('Actual vs Predicted Initial Days')

# Boxplot for ReAdmis and Initial_days
sns.boxplot(data=df, x='ReAdmis', y='Initial_days', color='lightgreen',
            ax=axes[1])
sns.pointplot(data=df, x='ReAdmis', y='Initial_days', color='red', estimator=np.
            mean, errorbar=None, ax=axes[1])
axes[1].set_title('Boxplot for ReAdmis and Initial_days')

plt.tight_layout()
plt.show()
```



## 14 Conclusion

This project was a remarkable learning experience, the instructors indicated that the project would force tough decisions, highlighting the absence of standout models and the essential nature of hard choices. As I reached the project's conclusion, I recognized possible mistakes and oversights along

the way. Despite the urge to correct these errors, I opted to keep them, valuing the learning process over the creation of a flawless model as well as the reality of deadlines. This project provides a blueprint of my thinking; a reminder of overlooked aspects crucial for future analysis projects.

### 14.0.1 References

- Datacamp. (2023, December 12). D207 - Exploratory Data Analysis. Retrieved from <https://app.datacamp.com/learn/custom-tracks/custom-d207-exploratory-data-analysis>
- Middleton, K. (2022, November). Getting started with D208 Part I [Webinar]. Western Governors University. Retrieved March 2024, from <https://wgu.hosted.panopto.com/Panopto/Pages/Viewer.aspx?id=15e09c73-c5aa-439d-852f-af47001b8970>
- Eyre, I. (2024, March). Python Seaborn: A Guide to Using Seaborn for Data Visualization. Real Python. Retrieved March 2024, from <https://realpython.com/python-seaborn/>
- Statology. (n.d.). *The Five Assumptions of Multiple Linear Regression*. Statology. Retrieved March 10, 2024, from [www.statology.org/multiple-linear-regression-assumptions/](http://www.statology.org/multiple-linear-regression-assumptions/)
- GeeksforGeeks. (n.d.). Interpreting the results of linear regression using OLS summary. Retrieved March 24, 2024, from <https://www.geeksforgeeks.org/interpreting-the-results-of-linear-regression-using-ols-summary/>
- Indhumathy Chelliah. (2021, August 3). Everything to know about residuals in linear regression. Retrieved March 24, 2024, from <https://indhumathychelliah.com/2021/08/03/everything-to-know-about-residuals-in-linear-regression/>
- Kross, S. (2016, February 29). A Q-Q Plot Dissection Kit. Retrieved March 24, 2024, from <https://seankross.com/2016/02/29/A-Q-Q-Plot-Dissection-Kit.html>
- Bradley, C. (2023). How do you transform a skewed bimodal data set into a normal distribution? Retrieved March 24, 2024, from <https://www.kaggle.com/code/chrisbradley/tab-playground-predicting-bimodal-distribution>
- Manl, F. (n.d.). Intermediate Regression with statsmodels in Python. Retrieved March 24, 2024, from <https://github.com/FraManl/DataCamp/blob/main/Intermediate%20Regression%20with%20statsmodels>
- Python Graph Gallery. (n.d.). Retrieved March 24, 2024, from <https://python-graph-gallery.com/>
- ResearchGate. (n.d.). Normal probability plots. Retrieved March 24, 2024, from [https://www.researchgate.net/figure/Normal-pro-bability-plots-a-ideal-b-heavy-tailed-distribution-c-light-tailed\\_fig1\\_262663278](https://www.researchgate.net/figure/Normal-pro-bability-plots-a-ideal-b-heavy-tailed-distribution-c-light-tailed_fig1_262663278)
- Statology. (n.d.). Multiple Linear Regression Assumptions. Retrieved March 24, 2024, from <https://www.statology.org/multiple-linear-regression-assumptions/>
- Stack Exchange. (n.d.). Multicollinearity: When individual regressions are significant but VIFs are low. Retrieved March 24, 2024, from <https://stats.stackexchange.com/questions/24464/multicollinearity-when-individual-regressions-are-significant-but-vifs-are-low>

- Stack Overflow. (2020, August 10). Residual standard error of a regression in Python. Retrieved March 24, 2024, from <https://stackoverflow.com/questions/63333999/residual-standard-error-of-a-regression-in-python>
- Western Governors University. (n.d.). R or Python? Retrieved March 24, 2024, from <https://www.wgu.edu/online-it-degrees/programming-languages/r-or-python.html>
- @UnfoldDataScience YouTube. (n.d.). Checking MLR Assumptions. Retrieved March 24, 2024, from [https://www.youtube.com/watch?v=\\_\\_XAurJJQ7jw](https://www.youtube.com/watch?v=__XAurJJQ7jw)
- Sewell, W. (2024). [PowerPoint slides on model tuning]. Western Governors University. Retrieved March 24, 2024, from [https://westerngovernorsuniversity-my.sharepoint.com/:p:/g/personal/william\\_sewell\\_wgu\\_edu/ERPQ0YpiQktOl-7YyAVnfLMBR5qeBh2cSv6lVaJqe\\_aHKg?e=FjPhPz](https://westerngovernorsuniversity-my.sharepoint.com/:p:/g/personal/william_sewell_wgu_edu/ERPQ0YpiQktOl-7YyAVnfLMBR5qeBh2cSv6lVaJqe_aHKg?e=FjPhPz)

## Software References

The following software packages were used in this project:

- **pandas** pandas is a Python library providing data structures and data analysis tools.
- **numpy** NumPy is a Python library for scientific computing.
- **matplotlib** Matplotlib is a Python library for creating static, animated, and interactive visualizations.
- **seaborn** Seaborn is a Python library for statistical data visualization built on top of matplotlib.
- **statsmodels** Statsmodels is a Python library for statistical modeling and econometrics.
- **Scikit-learn** Scikit-learn is a free machine learning library for Python.
- Python Software Foundation. (2023). Python Language Reference, version 3.9.6. Retrieved from <https://www.python.org>
- Scikit-Learn: Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., ... & Duchesnay, E. (2011). Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12, 2825-2830. Retrieved from <https://scikit-learn.org>
- Jinja2: Ronacher, A. (2023). Jinja2: The modern and designer-friendly templating engine for Python. Retrieved from <https://jinja.palletsprojects.com/>
- Matplotlib: Hunter, J. D. (2007). Matplotlib: A 2D graphics environment. *Computing in Science & Engineering*, 9(3), 90-95. Retrieved from <https://matplotlib.org>
- Statsmodels: Seabold, S., & Perktold, J. (2010). Statsmodels: Econometric and statistical modeling with python. In *Proceedings of the 9th Python in Science Conference* (Vol. 57, p. 61). Retrieved from <https://www.statsmodels.org>
- Pandas: McKinney, W. (2010). Data Structures for Statistical Computing in Python. In *Proceedings of the 9th Python in Science Conference* (pp. 51-56). Retrieved from <https://pandas.pydata.org>
- NumPy: Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D., ... & Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357-362. Retrieved from <https://numpy.org>



- Seaborn: Waskom, M. (2021). Seaborn: statistical data visualization. *Journal of Open Source Software*, 6(60), 3021. Retrieved from <https://seaborn.pydata.org>