Day 5 of 15 · Self-Check

# Day 5 Self-Check Quiz — Aggregates, JOINs and Export to Excel

Name: _____ Date: _____ Score: _____ / 15

**Instructions:** Write the letter of the best answer, or the query asked. You have 20 minutes. Passing score: 12/15 (80%).

**Part I — Multiple Choice**

1. ___ Which function gives the **total** of a column?

   A. COUNT B. SUM C. AVG D. MAX

2. ___ `SELECT COUNT(customer_id) FROM sales;` counts:

   A. All 500 rows B. Only rows where customer_id is not NULL C. Only NULL rows D. Different customers

3. ___ In `SELECT SUM(total_amount) AS revenue FROM sales;`, the word `revenue` is:

   A. A table B. A column alias C. A function D. A filter

4. ___ In `FROM sales AS s`, `s` is:

   A. A table alias B. A column C. A syntax error D. A new table

5. ___ The usual join condition is:

   A. PK = PK of the same table B. foreign key = primary key C. column = NULL D. COUNT = SUM

6. ___ An **INNER JOIN** returns:

   A. All rows of both tables B. Only rows that match in both tables C. Only unmatched rows D. Only the left table

7. ___ `FROM products AS p LEFT JOIN sales AS s ON p.product_id = s.product_id` keeps:

   A. Only sold products B. All products, sold or not C. All sales only D. Nothing

8. ___ To find products that were **never sold**, add:

   A. `WHERE s.sale_id IS NULL` B. `WHERE p.product_id IS NULL` C. `WHERE s.sale_id = 0` D. `LIMIT 0`

9. ___ The error "*ambiguous column name: product_id*" means:

   A. The column does not exist B. Two joined tables both have that column; add the table alias C. The database is locked D. A missing semicolon

10. ___ The safest way to bring a CSV into Excel is:

    A. Double-click the file B. Copy-paste from Notepad C. Data → From Text/CSV D. Rename it to .xlsx

11. ___ After importing, Excel's SUM of total_amount is ₱49,319 and SQL's is ₱49,319. This check is called:

    A. Normalization  B. Reconciliation  C. Aggregation  D. Joining

12. ___ In pair programming, the **navigator**:

    A. Types all the code  B. Reads, checks and thinks ahead  C. Only watches silently  D. Works on another PC

**Part II — Read the result**

13. `branches` has 5 rows; Antipolo has no sales. `sales` has 500 rows. How many rows does `FROM branches AS b LEFT JOIN sales AS s ON b.branch_id = s.branch_id` return? _____

**Part III — Write the query**

14. Total quantity of items sold at the **Pasig (BR03)** branch, with the alias `pasig_qty`:

---

---

15. Show each sale's `sale_id`, `branch_name` and `total_amount` for sales paid with **Maya** (join sales and branches):

---

---

---