

Memcheck Tool

A Memory Error Detector for C and C++ programs

<https://valgrind.org/docs/manual/mc-manual.html>

Carmen Torres Lopez
Elisa Gonzalez Boix
Maarten Vandercammen

Could we check our programs for memory leaks?



<http://valgrind.org>

- Instrumentation framework for building dynamic analysis tools.
- Includes a **memory error detector (Memcheck)** to automatically detect memory management errors.
- Other tools:
 - a cache and branch-prediction profiler
 - a call-graph generating cache
 - branch-prediction profiler
 - two different heap profilers
 - two thread error detectors

What does Memcheck Detect for C programs?

<https://valgrind.org/docs/manual/mc-manual.html>

1. **Accessing memory you shouldn't**, e.g. accessing an address in the heap memory beyond the size that was requested, accessing memory after it has been freed, etc.
2. **Using undefined values**
3. **Incorrect freeing of heap memory**, such as double-freeing heap blocks.
4. **Overlapping `src` and `dst` pointers in `memcpy` and related functions.**
5. **Passing a fishy (presumably negative) value to the `size` parameter of a memory allocation function.**
6. **Memory leaks.**

Memcheck by Example 1

```
#include <stdlib.h>

void f(void)
{
    int* x = malloc(10 * sizeof(int));
    x[10] = 0;          // problem 1: heap block overrun
                        // problem 2: memory leak -- x not freed
}

int main(void)
{
    f();
    return 0;
}
```



Tip: Fix errors in the order they are reported, as later errors can be caused by earlier ones.

Error message for problem 1: Heap block overrun

```
==19182== Invalid write of size 4
==19182==    at 0x804838F: f (example.c:6)
==19182==    by 0x80483AB: main (example.c:11)
```

Kind of error

} Stack trace

Process ID

<https://valgrind.org/docs/manual/quick-start.html>

Memcheck by Example 2

```
#include <stdlib.h>

void f(void)
{
    int* x = malloc(10 * sizeof(int));
    x[10] = 0;          // problem 1: heap block overrun
}                      // problem 2: memory leak -- x not freed

int main(void)
{
    f();
    return 0;
}
```

Error message for problem 2: Memory leaks

```
==19182== 40 bytes in 1 blocks are definitely lost in loss record 1 of 1
==19182==    at 0x1B8FF5CD: malloc (vg_replace_malloc.c:130)
==19182==    by 0x8048385: f (a.c:5)
==19182==    by 0x80483AB: main (a.c:11)
```

Definitely lost: the program is leaking memory.

The stack trace tells you where the leaked memory was allocated.

Valgrind @ Eclipse in Linux

Linux Tools Project Valgrind plugin: <http://www.eclipse.org/linuxtools/projectPages/valgrind/>

Step 0. Install Valgrind in your computer. Write in the terminal:


```
sudo apt-get install valgrind
```

Step 1. Install plugin Linux Tools Project Valgrind: http://wiki.eclipse.org/Linux_Tools_Project/PluginInstallHelp

Step 2. Create new project with your C program and run Valgrind (see next slides)

Step 1: Install Linux Tools plugin in Eclipse


Select the three Linux Tools options shown below




Step 2: Run Memcheck in Eclipse

Right click on the project and select **Profiling Tools** -> **Profile with Valgrind**

Demo program in Files/HOC/
Code/Chapter3b/mallocEx2



Results of Memcheck in Eclipse



Valgrind @ CLion in Linux

Valgrind Memcheck in CLion: <https://www.jetbrains.com/help/clion/memory-profiling-with-valgrind.html#start>

Note: This option only works for Linux, Windows and older (pre Sierra) versions of MacOS

Alternative for Valgrind in MacOS

Run Address Sanitizer

1.1 For detecting dangling pointer dereferences:

```
$ clang -fsanitize=address -g program.c  
$ ./a.out
```

Step 1: you need to compile and link your program using clang with `-fsanitize`

Step 2: run the executable

If you get the following error

```
clang: error: unsupported option '-fsanitize=leak' for target 'x86_64-apple-darwin20.6.0'
```

- Install LLVM on Homebrew (<https://stackoverflow.com/questions/53456304/mac-os-leaks-sanitizer>)

```
brew install llvm@8
```

- Overwrite default Clang

```
echo 'export PATH="/usr/local/opt/llvm@8/bin:$PATH"' >> ~/.bash_profile
```


Address Sanitizer by Example 1

```
#include <stdlib.h>

void f(void)
{
    int* x = malloc(10 * sizeof(int));
    x[10] = 0;           // problem 1: heap block overrun
                        // problem 2: memory leak -- x not freed
}

int main(void)
{
    f();
    return 0;
}
```

To get nicer stack traces in error messages add
`-fno-omit-frame-pointer`

Error message for problem 1: Heap block overflow

```
demo-valgrind -- -bash -- 111x53
carmens-MacBook-Pro-9:demo-valgrind carmentorres$ clang -fsanitize=address -g main.c
carmens-MacBook-Pro-9:demo-valgrind carmentorres$ ./a.out
=====
==10535==ERROR: AddressSanitizer: heap-buffer-overflow on address 0x6040000002b8 at pc 0x000101491f16 bp 0x7ffe
ee771710 sp 0x7ffeee771708
WRITE of size 4 at 0x6040000002b8 thread T0
#0 0x101491f15 in f main.c:6
#1 0x101491f43 in main main.c:11
#2 0x7fff20529f3c in start (libdyld.dylib:x86_64+0x15f3c)

0x6040000002b8 is located 0 bytes to the right of 40-byte region [0x604000000290,0x6040000002b8)
allocated by thread T0 here:
#0 0x1014f6a77 in wrap_malloc (libclang_rt.asan_osx_dynamic.dylib:x86_64+0x56a77)
#1 0x101491ec1 in f main.c:5
#2 0x101491f43 in main main.c:11
#3 0x7fff20529f3c in start (libdyld.dylib:x86_64+0x15f3c)

SUMMARY: AddressSanitizer: heap-buffer-overflow main.c:6 in f
Shadow bytes around the buggy address:
 0x1c0800000000: fa fa 00 00 00 00 00 00 fa fa 00 00 00 00 00 00
 0x1c08000000010: fa fa 00 00 00 00 00 00 fa fa 00 00 00 00 00 00
 0x1c08000000020: fa fa 00 00 00 00 00 05 fa fa 00 00 00 00 00 00
 0x1c08000000030: fa fa 00 00 00 00 00 05 fa fa 00 00 00 00 00 00
 0x1c08000000040: fa fa 00 00 00 00 00 07 fa fa 00 00 00 00 00 00
=>0x1c08000000050: fa fa 00 00 00 00 00[fa]fa fa fa fa fa fa fa fa
 0x1c08000000060: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
 0x1c08000000070: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
 0x1c08000000080: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
 0x1c08000000090: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
 0x1c080000000a0: fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa fa
Shadow byte legend (one shadow byte represents 8 application bytes):
Addressable: 00
Partially addressable: 01 02 03 04 05 06 07
Heap left redzone: fa
Freed heap region: fd
Stack left redzone: f1
Stack mid redzone: f2
Stack right redzone: f3
Stack after return: f5
Stack use after scope: f8
Global redzone: f9
Global init order: f6
Poisoned by user: f7
Container overflow: fc
Array cookie: ac
Intra object redzone: bb
ASan internal: fe
Left alloca redzone: ca
Right alloca redzone: cb
Shadow gap: cc
==10535==ABORTING
Abort trap: 6
carmens-MacBook-Pro-9:demo-valgrind carmentorres$
```


Address Sanitizer by Example 2

```
#include <stdlib.h>

void f(void)
{
    int* x = malloc(10 * sizeof(int));
    x[10] = 0;           // problem 1: heap block overrun
                          // problem 2: memory leak -- x not freed
}

int main(void)
{
    f();
    return 0;
}
```

Leak Sanitizer shows memory leaks
under the label “Direct leak”


Run Address Sanitizer

For detecting memory leaks (Leak Sanitizer):

```
$ clang -fsanitize=leak -g program.c
$ ./a.out
```

<https://clang.llvm.org/docs/LeakSanitizer.html>

Error message for problem 2: Memory leaks



```
demo-valgrind -- -bash -- 116x16
[carmens-MacBook-Pro-9:demo-valgrind carmentorres$ clang -fsanitize=leak -g main.c
[carmens-MacBook-Pro-9:demo-valgrind carmentorres$ ./a.out

=====
==11204==ERROR: LeakSanitizer: detected memory leaks

Direct leak of 40 byte(s) in 1 object(s) allocated from:
    #0 0x10c44f01a in wrap_malloc (libclang_rt.lsan_osx_dynamic.dylib:x86_64h+0x801a)
    #1 0x10c439f51 in f demo-valgrind.c:5
    #2 0x10c439f83 in main demo-valgrind.c:11
    #3 0x7fff20529f3c in start (libdyld.dylib:x86_64+0x15f3c)

SUMMARY: LeakSanitizer: 40 byte(s) leaked in 1 allocation(s).
[carmens-MacBook-Pro-9:demo-valgrind carmentorres$
```