

Bar bending schedule

Sattva Court



Project Sattva Court (SC-001)
 Client Sattva Holdings
 Site Bashundhara R/A, Dhaka

Drawings Issued Structural drawings, revision 2, pinned 22 Sep 2026
 24 Sep 2026
 Cut from Stock bars of 12,000 mm; each length rounded once, up to the next 25 mm

Bar mark	Role	Dia (mm)	Shape	Dimensions (mm)	Cutting length (mm)	Rounded (mm)	IS 2502 length (mm)	In each	Total	Mass (kg)
C1 • Column • FDN										3 members
C1-d	Main	16		11 A 1,830, B 192	1,990	2,000	1,990	8	24	75.414
Lap		16		800 × 1 per bar						30.318
C1-t	Tie	10		51 A 320, B 320, C 320, D 320, E 100, F 100	1,380	1,400	1,360	16	48	40.803
C2 • Column • FDN										8 members
C2-d	Main	20		11 A 1,830, B 240	2,015	2,025	2,030	10	80	397.520
Lap		20		1,000 × 1 per bar						197.280
C2-t	Tie	10		51 A 220, B 520, C 220, D 520, E 100, F 100	1,580	1,600	1,560	20	160	155.728
C3 • Column • FDN										6 members
C3-d	Main	20		11 A 1,830, B 240	2,015	2,025	2,030	8	48	238.512
Lap		20		1,000 × 1 per bar						118.368
C3-t	Tie	10		51 A 220, B 420, C 220, D 420, E 100, F 100	1,380	1,400	1,360	18	108	91.806
C4 • Column • FDN										7 members
C4-d	Main	25		11 A 1,830, B 300	2,061.25	2,075	2,080	12	84	667.303
Lap		25		1,250 × 1 per bar						404.670

Bar mark	Role	Dia (mm)	Shape	Dimensions (mm)	Cutting length (mm)	Rounded (mm)	IS 2502 length (mm)	In each	Total	Mass (kg)
C4 • Column • FDN										7 members
C4-ct	Tie	10	 CT	A 520, B 100, C 100	680	700	660	40	280	117.285
C4-t	Tie	10	 51	A 370, B 520, C 370, D 520, E 100, F 100	1,880	1,900	1,860	20	140	162.134
C6 • Column • FDN										1 member
C6-d	Main	20	 11	A 1,830, B 240	2,015	2,025	2,030	8	8	39.752
Lap		20		1,000 × 1 per bar						19.728
C6-t	Tie	10	 51	A 220, B 420, C 220, D 420, E 100, F 100	1,380	1,400	1,360	18	18	15.301
C7 • Column • FDN										1 member
C7-d	Main	20	 11	A 1,830, B 240	2,015	2,025	2,030	8	8	39.752
Lap		20		1,000 × 1 per bar						19.728
C7-sp	Spiral	10	 SP	A 8,166.78	8,166.78	8,175	8,166.78	1	1	5.031
SW1 • Shear wall • FDN										2 members
SW1-v	Main	12	 00	A 609.6	609.6	625	609.6	34	68	36.810
Lap		12		600 × 1 per bar						36.230
SW1-h	Horizontal	10	 11	A 2,523.4, B 120	2,623.4	2,625	2,623.4	8	16	25.856
SW1 • Shear wall • FDN										1 member
SW1-v	Main	12	 00	A 609.6	609.6	625	609.6	34	34	18.405
Lap		12		600 × 1 per bar						18.115
SW1-h	Horizontal	10	 11	A 2,453.2, B 120	2,553.2	2,575	2,553.2	8	8	12.582

Bar mark	Role	Dia (mm)	Shape	Dimensions (mm)	Cutting length (mm)	Rounded (mm)	IS 2502 length (mm)	In each	Total	Mass (kg)
C1 • Column • GF										3 members
C1-v	Main	16		A 3,352.8	3,352.8	3,375	3,352.8	8	24	127.059
Lap		16		800 × 1 per bar						30.318
C1-t	Tie	10		A 320, B 320, C 320, D 320, E 100, F 100	1,380	1,400	1,360	28	84	71.406
C2 • Column • GF										8 members
C2-v	Main	20		A 3,352.8	3,352.8	3,375	3,352.8	10	80	661.440
Lap		20		1,000 × 1 per bar						197.280
C2-t	Tie	10		A 220, B 520, C 220, D 520, E 100, F 100	1,580	1,600	1,560	31	248	241.376
C3 • Column • GF										6 members
C3-v	Main	20		A 3,352.8	3,352.8	3,375	3,352.8	8	48	396.864
Lap		20		1,000 × 1 per bar						118.368
C3-t	Tie	10		A 220, B 420, C 220, D 420, E 100, F 100	1,380	1,400	1,360	30	180	153.012
C4 • Column • GF										7 members
C4-v	Main	25		A 3,352.8	3,352.8	3,375	3,352.8	12	84	1,085.420
Lap		25		1,250 × 1 per bar						404.670
C4-ct	Tie	10		A 520, B 100, C 100	680	700	660	62	434	181.797
C4-t	Tie	10		A 370, B 520, C 370, D 520, E 100, F 100	1,880	1,900	1,860	31	217	251.300
C6 • Column • GF										1 member
C6-v	Main	20		A 3,352.8	3,352.8	3,375	3,352.8	8	8	66.144
Lap		20		1,000 × 1 per bar						19.728
C6-t	Tie	10		A 220, B 420, C 220, D 420, E 100, F 100	1,380	1,400	1,360	30	30	25.502

Bar mark	Role	Dia (mm)	Shape	Dimensions (mm)	Cutting length (mm)	Rounded (mm)	IS 2502 length (mm)	In each	Total	Mass (kg)
C7 • Column • GF										1 member
C7-v	Main	20		A 3,352.8	3,352.8	3,375	3,352.8	8	8	66.144
Lap		20		1,000 × 1 per bar						19.728
C7-sp	Spiral	10		A 39,667.216	39,667.216	39,675	39,667.216	1	1	24.435
Lap		10		500 × 3 per bar						0.924
SW1 • Shear wall • GF										2 members
SW1-v	Main	12		A 3,352.8	3,352.8	3,375	3,352.8	34	68	202.456
Lap		12		600 × 1 per bar						36.230
SW1-h	Horizontal	10		A 2,523.4, B 120	2,623.4	2,625	2,623.4	44	88	142.210
SW1 • Shear wall • GF										1 member
SW1-v	Main	12		A 3,352.8	3,352.8	3,375	3,352.8	34	34	101.228
Lap		12		600 × 1 per bar						18.115
SW1-h	Horizontal	10		A 2,453.2, B 120	2,553.2	2,575	2,553.2	44	44	69.202
C1 • Column • 1F										3 members
C1-v	Main	16		A 3,048	3,048	3,050	3,048	8	24	115.506
Lap		16		800 × 1 per bar						30.318
C1-t	Tie	10		A 320, B 320, C 320, D 320, E 100, F 100	1,380	1,400	1,360	27	81	68.856
C2 • Column • 1F										8 members
C2-v	Main	20		A 3,048	3,048	3,050	3,048	10	80	601.312
Lap		20		1,000 × 1 per bar						197.280
C2-t	Tie	10		A 220, B 520, C 220, D 520, E 100, F 100	1,580	1,600	1,560	29	232	225.800

Bar mark	Role	Dia (mm)	Shape	Dimensions (mm)	Cutting length (mm)	Rounded (mm)	IS 2502 length (mm)	In each	Total	Mass (kg)
C3 • Column • 1F										6 members
C3-v	Main	20		A 3,048	3,048	3,050	3,048	8	48	360.786
Lap		20		1,000 × 1 per bar						118.368
C3-t	Tie	10		A 220, B 420, C 220, D 420, E 100, F 100	1,380	1,400	1,360	28	168	142.812
C4 • Column • 1F										7 members
C4-v	Main	25		A 3,048	3,048	3,050	3,048	12	84	986.748
Lap		25		1,250 × 1 per bar						404.670
C4-ct	Tie	10		A 520, B 100, C 100	680	700	660	58	406	170.065
C4-t	Tie	10		A 370, B 520, C 370, D 520, E 100, F 100	1,880	1,900	1,860	29	203	235.088
C5 • Column • 1F										1 member
C5-v	Main	20		A 3,048	3,048	3,050	3,048	8	8	60.131
Lap		20		1,000 × 1 per bar						19.728
C5-t	Tie	10		A 220, B 370, C 220, D 370, E 100, F 100	1,280	1,300	1,260	27	27	21.289
C6 • Column • 1F										1 member
C6-v	Main	20		A 3,048	3,048	3,050	3,048	8	8	60.131
Lap		20		1,000 × 1 per bar						19.728
C6-t	Tie	10		A 220, B 420, C 220, D 420, E 100, F 100	1,380	1,400	1,360	28	28	23.802
SW1 • Shear wall • 1F										2 members
SW1-v	Main	12		A 3,048	3,048	3,050	3,048	34	68	184.050
Lap		12		600 × 1 per bar						36.230
SW1-h	Horizontal	10		A 2,523.4, B 120	2,623.4	2,625	2,623.4	40	80	129.282

Bar mark	Role	Dia (mm)	Shape	Dimensions (mm)	Cutting length (mm)	Rounded (mm)	IS 2502 length (mm)	In each	Total	Mass (kg)
SW1 · Shear wall · 1F										1 member
SW1-v	Main	12		A 3,048	3,048	3,050	3,048	34	34	92.025
Lap		12		600 × 1 per bar						18.115
SW1-h	Horizontal	10		A 2,453.2, B 120	2,553.2	2,575	2,553.2	40	40	62.911

Cutting stock by diameter

Dia (mm)	Mass (kg)	Stock bars	Pieces	Offcut (m)
10	2,867.595	401	3,373	92.625
12	798.009	68	306	96.900
16	408.927	19	72	25.800
20	4,053.800	116	432	175.200
25	3,953.481	68	252	102.000
Total mass	12,081.812			

Stock bars, pieces and offcut describe what a site cuts from a stock bar. They are informational and are never billed.

Prepared by

Name _____

Signature _____

Date _____

Checked by

Name _____

Signature _____

Date _____

Completed by hand. This schedule is a draft: it names no surveyor and certifies no quantity.