

Points to recall

- ▶ Heuristic function must be _____ for A* Graph Search Algorithm to give optimal solution.

Points to recall

- ▶ Heuristic function must be _____ for A* Graph Search Algorithm to give optimal solution.
- ▶ The heuristic function that _____ will lead to a fewer number of nodes being expanded.

Relaxed 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:

Relaxed 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.

Relaxed 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to an adjacent position, which may result in more than one tile being present at the same position.

Relaxed 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to an adjacent position, which may result in more than one tile being present at the same position.
- ▶ Each action can move one tile one position closer to its goal position.

Relaxed 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to an adjacent position, which may result in more than one tile being present at the same position.
- ▶ Each action can move one tile one position closer to its goal position.
- ▶ What will be the cost of the shortest path in this relaxed state space?

Relaxed 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to an adjacent position, which may result in more than one tile being present at the same position.
- ▶ Each action can move one tile one position closer to its goal position.
- ▶ What will be the cost of the shortest path in this relaxed state space? Manhattan distance (h_2)

h_2 is consistent in the relaxed state space for 8-puzzle

To prove : $h_2(n) \leq c(n, a, n') + h_2(n')$

Proof:

Approach to generating a heuristic function

1. Relax a problem in such a manner that the shortest path cost in the relaxed problem becomes easy to compute.

Approach to generating a heuristic function

1. Relax a problem in such a manner that the shortest path cost in the relaxed problem becomes easy to compute.
2. The shortest path costs in any relaxed problem will be consistent.

Approach to generating a heuristic function

1. Relax a problem in such a manner that the shortest path cost in the relaxed problem becomes easy to compute.
2. The shortest path costs in any relaxed problem will be consistent.
3. Therefore, these shortest path costs can form a consistent heuristic for the original problem.

Another way to relax the 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:

Another way to relax the 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.

Another way to relax the 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to any position, which may result in more than one tile being present at the same position.

Another way to relax the 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to any position, which may result in more than one tile being present at the same position.
- ▶ Each action can move one tile to its correct position.

Another way to relax the 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to any position, which may result in more than one tile being present at the same position.
- ▶ Each action can move one tile to its correct position.
- ▶ What will be the cost of the shortest path in this relaxed state space?

Another way to relax the 8-puzzle problem

- ▶ To the original state space for the 8-puzzle problem we add the following:
 - ▶ We allow additional states where more than one tile can be present at a position and more than one blank space can be present in the puzzle.
 - ▶ We allow additional actions where any tile can be moved to any position, which may result in more than one tile being present at the same position.
- ▶ Each action can move one tile to its correct position.
- ▶ What will be the cost of the shortest path in this relaxed state space? Number of misplaced tiles (h_1)

h_1 is consistent in the relaxed state space for 8-puzzle

To prove : $h_1(n) \leq c(n, a, n') + h_1(n')$

Proof:

Chapter 7: Logical Agents

Chapter 7: Logical Agents

- ▶ Knowledge base


Chapter 7: Logical Agents

- ▶ Knowledge base
- ▶ Propositional logic


Chapter 7: Logical Agents

- ▶ Knowledge base
- ▶ Propositional logic
- ▶ Inference

Logical Agents



Logical Agents



Percept in each time step: [Stench, Breeze, Glitter, Bump, Scream]

First Two Steps

1,4	2,4	3,4	4,4
1,3	2,3	3,3	4,3
1,2	2,2	3,2	4,2
<div> <div>OK</div> <div>A</div> <div>OK</div> </div>	2,1	3,1	4,1

A = Agent
B = Breeze
G = Glitter, Gold
OK = Safe square
P = Pit
S = Stench
V = Visited
W = Wumpus

1,4	2,4	3,4	4,4
1,3	2,3	3,3	4,3
1,2	2,2 <div><div></div><div>P?</div></div>	3,2	4,2
1,1 <div><div>V</div><div>OK</div></div>	2,1 <div><div>A</div><div>B</div><div>OK</div></div>	3,1 <div><div>P?</div></div>	4,1

Figure 7.3 The first step taken by the agent in the wumpus world. (a) The initial situation, after percept $[None, None, None, None, None]$. (b) After one move, with percept $[None, Breeze, None, None, None]$.

$$\begin{array}{ccc} [2,1] & \xrightarrow{\alpha} & [3,1] \\ \uparrow & & \uparrow \\ & 2,1 & \end{array}$$

$(1,2) \rightarrow$
 $\begin{matrix} 1 & 2 \\ \rightarrow & \rightarrow \end{matrix}$
 $\begin{matrix} \boxed{A} \\ S \\ OK \end{matrix}$

1,4	2,4 P?	3,4	4,4
1,3 W!	2,3 A S G B	3,3 P?	4,3
1,2 S V OK	2,2 V OK	3,2	4,2
1,1 V OK	2,1 B V OK	3,1 P!	4,1

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ▶ ↺ 🔍 ↻




Wupus-world inference example

1,4	2,4	3,4	4,4
1,3	2,3	3,3	4,3
1,2 OK	2,2 P?	3,2	4,2
1,1 V OK	2,1 <div style="border: 1px solid black; display: inline-block; padding: 2px;">A</div> B OK	3,1 P?	4,1



- ▶ KB contains agent's percepts (in the first 2 steps) and rules of the Wumpus world

Wupus-world inference example

1,4	2,4	3,4	4,4
1,3 	2,3	3,3	4,3
1,2  OK	2,2  P?	3,2	4,2
1,1 V OK	2,1 <div><div>A</div><div>B</div></div> OK	3,1 P?	4,1

- ▶ KB contains agent's percepts (in the first 2 steps) and rules of the Wumpus world
- ▶ Agent wants to know whether pit is present in [1,2], [2,2] and [1,3].

Wupus-world inference example

1,4	2,4	3,4	4,4
1,3	2,3	3,3	4,3
1,2 OK	2,2 P?	3,2	4,2
1,1 V OK	2,1 <div style="border: 1px solid black; display: inline-block; padding: 2px;">A</div> B OK	3,1 P?	4,1

- ▶ KB contains agent's percepts (in the first 2 steps) and rules of the Wumpus world
- ▶ Agent wants to know whether pit is present in [1,2],[2,2] and [1,3].
- ▶ $\alpha_1 \equiv$ "No pit in [1,2]"
- ▶ $\alpha_2 \equiv$ "No pit in [2,2]"

Wupus-world inference example


1,4	2,4	3,4	4,4
1,3	2,3	3,3	4,3
1,2 OK	2,2 P?	3,2	4,2
1,1 V OK	2,1 A B OK	3,1 P?	4,1

- ▶ KB contains agent's percepts (in the first 2 steps) and rules of the Wumpus world
- ▶ Agent wants to know whether pit is present in [1,2],[2,2] and [1,3].
- ▶ $\alpha_1 \equiv$ "No pit in [1,2]"
- ▶ $\alpha_2 \equiv$ "No pit in [2,2]"
- ▶ $KB \models \alpha_1?$




Wupus-world inference example

1,4	2,4	3,4	4,4
1,3	2,3	3,3	4,3
1,2 OK	2,2 P?	3,2	4,2
1,1 V OK	2,1 A B OK	3,1 P?	4,1


- ▶ KB contains agent's percepts (in the first 2 steps) and rules of the Wumpus world
- ▶ Agent wants to know whether pit is present in [1,2], [2,2] and ~~[1,3]~~. [3,1]
- ▶ $\alpha_1 \equiv$ "No pit in [1,2]" 
- ▶ $\alpha_2 \equiv$ "No pit in [2,2]"
- ▶ $KB \models \alpha_1?$
- ▶ $KB \models \alpha_2?$

$KB \models \alpha_1?$

$\alpha_1 \equiv$ no pit [1,2]



$KB \models \alpha_2$?



Knowledge Base and Models