## Project objective:


- I trained the resnet 18 network to classify the full MNIST dataset.
- 1 epoch of training produced the following accuracy using testing as the validation set epoch train\_loss valid\_loss accuracy time

```
0 0.115339 1.785593 0.983200 02:01
```

- I used the code from Chapter 2 of the fast.ai textbook to help me set up the training. It was fairly simple to set up. The following is my code to open MNIST and load the data and train the resnet18 model.


As indicated above, the results were surprisingly accurate with the resnet 18 model. The accuracy is on par with the 784, 300, 10 model used in the MNIST lab, but runs substantially faster.

Here is the confusion matrix:



## Here are the top losses:

## Prediction/Actual/Loss/Probability



Here are the most commonly confused labels, they seem to be plausible – according to the top losses, a two sometimes does look like a 7:

[('2', '7', 8), ('9', '7', 8), ('3', '5', 7), ('7', '2', 7), ('9', '8', 7), ('2', '0', 6), ('3', '8', 6), ('9', '4', 6), ('0', '5', 5), ('6', '8', 5), ('7', '9', 5), ('9', '5', 5), ('0', '6', 4), ('2', '1', 4), ('3', '2', 4), ('4', '6', 4), ('4', '9', 4), ('6', '1', 4), ('7', '1', 4), ('8', '2', 4), ('1', '2', 3), ('2', '8', 3), ('5', '6', 3), ('8', '6', 3), ('8', '9', 3), ('0', '2', 2), ('0', '7', 2), ('1', '8', 2), ('2', '3', 2), ('2', '4', 2), ('2', '5', 2), ('5', '3', 2), ('5', '8', 2), ('6', '4', 2), ('7', '3', 2), ('7', '8', 2), ('9', '0', 2), ('9', '1', 2), ('9', '3', 2), ('0', '8', 1), ('1', '3', 1), ('1', '4', 1), ('1', '7', 1), ('2', '6', 1), ('3', '9', 1), ('4', '1', 1), ('4', '2', 1), ('4', '7', 1), ('4', '8', 1), ('6', '0', 1), ('6', '2', 1), ('6', '5', 1), ('7', '4', 1), ('8', '3', 1), ('8', '4', 1), ('8', '5', 1), ('9', '2', 1)]