

Concolic Testing: An Application of Solvers

Vijay Ganesh Affiliation: University of Waterloo


A Foundation for Software Engineering Logic Abstractions of Computation




A Foundation for Software Engineering Logic Abstractions of Computation




Software Engineering & SAT/SMT Solvers An Indispensable Tactic for Any Strategy



Software Engineering & SAT/SMT Solvers An Indispensable Tactic for Any Strategy




Software Engineering using Solvers Engineering, Usability, Novelty



Program is correct? or Generate Counterexamples (test cases)

SAT/SMT Solver Research Story A 1000x Improvement: Democratization of Logic



The SAT/SMT Problem



- Rich logics (Modular arithmetic, Arrays, Strings,...)
- NP-complete, PSPACE-complete,...
- Practical, scalable, usable, automatic
- Enable novel software reliability approaches

Symbolic execution for testing first proposed by Lori Clarke (1975) ACM SIGSOFT Outstanding Researcher Award 2012

Symbolic execution for testing first proposed by Lori Clarke (1975) ACM SIGSOFT Outstanding Researcher Award 2012

Follow up work by J.C. King (1976)

- Symbolic execution for testing first proposed by Lori Clarke (1975) ACM SIGSOFT Outstanding Researcher Award 2012
- Follow up work by J.C. King (1976)
- Rediscovered/modified in the context of powerful solvers, analysis and appropriate concretizations by two independent groups


- Symbolic execution for testing first proposed by Lori Clarke (1975) ACM SIGSOFT Outstanding Researcher Award 2012
- Follow up work by J.C. King (1976)
- Rediscovered/modified in the context of powerful solvers, analysis and appropriate concretizations by two independent groups
 - Patrice Godefroid and Koushik Sen (2005)

- Symbolic execution for testing first proposed by Lori Clarke (1975) ACM SIGSOFT Outstanding Researcher Award 2012
- Follow up work by J.C. King (1976)
- Rediscovered/modified in the context of powerful solvers, analysis and appropriate concretizations by two independent groups
 - Patrice Godefroid and Koushik Sen (2005)
 - Marian Dawson Engler et al. (2005)

- Symbolic execution for testing first proposed by Lori Clarke (1975) ACM SIGSOFT Outstanding Researcher Award 2012
- Follow up work by J.C. King (1976)
- Rediscovered/modified in the context of powerful solvers, analysis and appropriate concretizations by two independent groups
 - Patrice Godefroid and Koushik Sen (2005)
 - Marian Dawson Engler et al. (2005)
- Many follow up works by George Candea, Dawn Song, David Molnar, researchers in the audience,...

- Symbolic execution for testing first proposed by Lori Clarke (1975) ACM SIGSOFT Outstanding Researcher Award 2012
- Follow up work by J.C. King (1976)
- Rediscovered/modified in the context of powerful solvers, analysis and appropriate concretizations by two independent groups
 - Patrice Godefroid and Koushik Sen (2005)
 - Marian Dawson Engler et al. (2005)
- Many follow up works by George Candea, Dawn Song, David Molnar, researchers in the audience,...
- Beyond testing: Fault localization, repair, security,...

<u>Dynamic Symbolic Testing</u> Symbolic/Concrete Execution + Solvers




Program is correct? or Generate Counterexamples (test cases)

Concolic Testing: Example

```
int double (int v) {
   return 2*v;
void testme (int x, int y) {
   z = double(y);
   if (z == x) {
         if (x > y+10) {
             ERROR;
```


Concolic Testing: Example

```
int double (int v) {
   return 2*v;
void testme (int x, int y) {
   z = double(y);
   if (z == x) {
         if (x > y+10) {
             ERROR;
```



```
Symbolic
                                                 Concrete
                                                 Execution
                                                                    Execution
int double (int v) {
                                                            symbolic
                                        concrete
                                                                              path
   return 2*v;
                                                               state
                                                                           condition
                                          state
                                         x = 22, y = 7
                                                           x = x_0, y = y_0
void testme (int x, int y) {
   z = double(y);
   if (z == x) {
        if (x > y+10) {
             ERROR;
```

```
Symbolic
                                                  Concrete
                                                  Execution
                                                                     Execution
int double (int v) {
                                                             symbolic
                                         concrete
                                                                               path
   return 2*v;
                                                                             condition
                                           state
                                                                state
void testme (int x, int y) {
                                        x = 22, y = 7,
                                                            x = x_0, y = y_0,
   z = double(y);
   if (z == x) {
                                               z = 14
                                                                 z = 2*y_0
         if (x > y+10) {
             ERROR;
```



```
Concrete
                                                                       Symbolic
                                                   Execution
                                                                       Execution
int double (int v) {
                                          concrete
                                                               symbolic
                                                                                 path
   return 2*v;
                                                                               condition
                                            state
                                                                 state
                                       Solve: 2^*y_0 == x_0
void testme (int x, int y) {
                                       Solution: x_0 = 2, y_0 = 1
   z = double(y);
                                                                               2*y_0!=x_0
   if (z == x) {
         if (x > y+10) {
             ERROR;
                                     x = 22, y = 7, z
                                                            x = x_0, y = y_0, z
                                                                     = 2*y_0
```

```
Symbolic
                                                   Concrete
                                                   Execution
                                                                      Execution
int double (int v) {
                                                               symbolic
                                          concrete
                                                                                 path
   return 2*v;
                                                                               condition
                                                                 state
                                            state
}
void testme (int x, int y) {
   z = double(y);
                                                                             2*y_0 == x_0
   if (z == x) {
                                           x = 2, y = 1,
                                                             x = x_0, y = y_0,
         if (x > y+10) {
                                                  z = 2
                                                                  z = 2*y_0
             ERROR;
```

```
Concrete
                                                                      Symbolic
                                                   Execution
                                                                      Execution
int double (int v) {
                                          concrete
                                                              symbolic
                                                                                path
   return 2*v;
                                                                               condition
                                            state
                                                                 state
}
void testme (int x, int y) {
   z = double(y);
                                                                             2*y_0 == x_0
   if (z == x) {
         if (x > y+10) {
                                                                             x_0 > y_0 + 10
             ERROR;
                                    x = 2, y = 1, z
                                                           x = x_0, y = y_0, z
                                                                    = 2*y_0
```

```
Concrete
                                                                          Symbolic
                                                     Execution
                                                                         Execution
int double (int v) {
                                            concrete
                                                                  symbolic
                                                                                    path
   return 2*v;
                                                                                  condition
                                              state
                                                                    state
}
                                     Solve: (2^*y_0 == x_0) AND (x_0 > y_0 +
                                     10)
void testme (int x, int y) {
                                     Solution: x_0 = 30, y_0 = 15
   z = double(y);
                                                                                 2*y_0 == x_0
   if (z == x) {
         if (x > y+10) {
                                                                                  x_0 \cdot y_0 + 10
              ERROR;
                                            x = 2, y = 1,
                                                                x = x_0, y = y_0,
                                                   z = 2
                                                                     z = 2*y_0
```

```
Symbolic
                                                  Concrete
                                                 Execution
                                                                    Execution
int double (int v) {
                                                             symbolic
                                        concrete
                                                                              path
   return 2*v;
                                                                            condition
                                          state
                                                               state
                                       x = 30, y = 15
                                                            x = x_0, y = y_0
void testme (int x, int y) {
   z = double(y);
   if (z == x) {
        if (x > y+10) {
             ERROR;
```

```
Symbolic
                                                    Concrete
                                                    Execution
                                                                       Execution
int double (int v) {
                                                                symbolic
                                                                                  path
   return 2*v;
                                                                                condition
                                                                  state
                                            Program Error
void testme (int x, int y) {
   z = double(y);
   if (z == x) {
                                                                               2*y_0 == x_0
         if (x > y+10) {
                                                                               x_0 > y_0 + 10
             ERROR;
                                          x = 30, y = 15
                                                                x = x_0, y = y_0
```

Explicit Path (not State) Model Checking

- Traverse all execution paths one by one to detect errors
 - assertion violations
 - program crash
 - uncaught exceptions
- combine with valgrind to discover memory errors

