

ECE750T-28:
Computer-aided Reasoning for Software Engineering

Lecture 11: Theory of Equality with Uninterpreted Functions

Vijay Ganesh
(Original notes from Isil Dillig)

Review

- Previous lecture: talked about signature and axioms of $T_{=}$

$$\Sigma_{=} : \{=, a, b, c, \dots, f, g, h, \dots, p, q, r, \dots\}$$

Review

- Previous lecture: talked about signature and axioms of $T_{=}$

$$\Sigma_{=} : \{=, a, b, c, \dots, f, g, h, \dots, p, q, r, \dots\}$$

- Axioms:

1. $\forall x. x = x$ (reflexivity)

2. $\forall x, y. x = y \rightarrow y = x$ (symmetry)

3. $\forall x, y, z. x = y \wedge y = z \rightarrow x = z$ (transitivity)

4. $\forall x_1, \dots, x_n, y_1, \dots, y_n. \bigwedge_i x_i = y_i \rightarrow f(x_1, \dots, x_n) = f(y_1, \dots, y_n)$ (congruence)

5. for each positive integer n and n -ary predicate symbol p ,

$$\forall x_1, \dots, x_n, y_1, \dots, y_n. \bigwedge_i x_i = y_i \rightarrow (p(x_1, \dots, x_n) \leftrightarrow p(y_1, \dots, y_n))$$
 (equivalence)

Overview

- **Today:** look at decision procedures for deciding satisfiability in the quantifier-free fragment of $T_{=}$

Overview

- ▶ **Today:** look at decision procedures for deciding satisfiability in the quantifier-free fragment of $T_{=}$
- ▶ However, our decision procedure has two "restrictions":

Overview

- ▶ **Today:** look at decision procedures for deciding satisfiability in the quantifier-free fragment of $T_{=}$
- ▶ However, our decision procedure has two "restrictions":
 - ▶ formulas consist of conjunctions of literals

Overview

- ▶ **Today:** look at decision procedures for deciding satisfiability in the quantifier-free fragment of $T_{=}$
- ▶ However, our decision procedure has two "restrictions":
 - ▶ formulas consist of conjunctions of literals
 - ▶ we'll allow functions, but no predicates

Overview

- ▶ **Today:** look at decision procedures for deciding satisfiability in the quantifier-free fragment of $T_{=}$
- ▶ However, our decision procedure has two "restrictions":
 - ▶ formulas consist of conjunctions of literals
 - ▶ we'll allow functions, but no predicates
- ▶ However, these "restrictions" are not real restrictions

Overview

- ▶ **Today:** look at decision procedures for deciding satisfiability in the quantifier-free fragment of $T_{=}$
- ▶ However, our decision procedure has two "restrictions":
 - ▶ formulas consist of conjunctions of literals
 - ▶ we'll allow functions, but no predicates
- ▶ However, these "restrictions" are not real restrictions
- ▶ For formulas with disjunctions, can convert to DNF and check each clause separately (will consider efficient methods later)

Overview

- ▶ **Today:** look at decision procedures for deciding satisfiability in the quantifier-free fragment of $T_{=}$
- ▶ However, our decision procedure has two "restrictions":
 - ▶ formulas consist of conjunctions of literals
 - ▶ we'll allow functions, but no predicates
- ▶ However, these "restrictions" are not real restrictions
- ▶ For formulas with disjunctions, can convert to DNF and check each clause separately (will consider efficient methods later)
- ▶ Furthermore, any formula containing predicates can be converted to **equisatisfiable** formula containing only functions!

Eliminating Predicates

- ▶ Simple transformation yields equisatisfiable formula with only functions

Eliminating Predicates

- ▶ Simple transformation yields equisatisfiable formula with only functions
- ▶ **The trick:** For each relation constant p :
 1. introduce a fresh function constant f_p

Eliminating Predicates

- ▶ Simple transformation yields equisatisfiable formula with only functions
- ▶ **The trick:** For each relation constant p :
 1. introduce a fresh function constant f_p
 2. rewrite $p(x_1, \dots, x_n)$ as $f_p(x_1, \dots, x_n) = t$where t is a fresh object constant

Eliminating Predicates

- ▶ Simple transformation yields equisatisfiable formula with only functions
- ▶ **The trick:** For each relation constant p :
 1. introduce a fresh function constant f_p
 2. rewrite $p(x_1, \dots, x_n)$ as $f_p(x_1, \dots, x_n) = t$where t is a fresh object constant
- ▶ **Example:** How do we transform $x = y \rightarrow (p(x) \leftrightarrow p(y))$ to equisatisfiable formula?

Eliminating Predicates

- ▶ Simple transformation yields equisatisfiable formula with only functions
- ▶ **The trick:** For each relation constant p :
 1. introduce a fresh function constant f_p
 2. rewrite $p(x_1, \dots, x_n)$ as $f_p(x_1, \dots, x_n) = t$where t is a fresh object constant
- ▶ **Example:** How do we transform $x = y \rightarrow (p(x) \leftrightarrow p(y))$ to equisatisfiable formula? $x = y \rightarrow (f_p(x) = t \leftrightarrow f_p(y) = t)$

$T_{=}$ without Predicates

- ▶ Signature without predicates:

$$\Sigma_{=} : \{=, a, b, c, \dots, f, g, h, \dots\}$$

$T_=$ without Predicates

- ▶ Signature without predicates:

$$\Sigma_= : \{=, a, b, c, \dots, f, g, h, \dots\}$$

- ▶ Axioms:

1. $\forall x. x = x$ (reflexivity)

2. $\forall x, y. x = y \rightarrow y = x$ (symmetry)

3. $\forall x, y, z. x = y \wedge y = z \rightarrow x = z$ (transitivity)

4. $\forall x_1, \dots, x_n, y_1, \dots, y_n. \bigwedge_i x_i = y_i \rightarrow f(x_1, \dots, x_n) = f(y_1, \dots, y_n)$ (congruence)

Examples

- ▶ Let's consider some examples

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid?

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid? **unsat**

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid? **unsat**
- ▶ What about $x \neq y \wedge f(x) = f(y)$?

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid? **unsat**
- ▶ What about $x \neq y \wedge f(x) = f(y)$? **sat**

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid? **unsat**
- ▶ What about $x \neq y \wedge f(x) = f(y)$? **sat**
- ▶ What about $x = g(y, z) \rightarrow f(x) = f(g(y, z))$?

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid? **unsat**
- ▶ What about $x \neq y \wedge f(x) = f(y)$? **sat**
- ▶ What about $x = g(y, z) \rightarrow f(x) = f(g(y, z))$? **valid**

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid? **unsat**
- ▶ What about $x \neq y \wedge f(x) = f(y)$? **sat**
- ▶ What about $x = g(y, z) \rightarrow f(x) = f(g(y, z))$? **valid**
- ▶ What about $f(a) = a \wedge f(f(a)) \neq a$?

Examples

- ▶ Let's consider some examples
- ▶ Is the formula $x = y \wedge f(x) \neq f(y)$ sat, unsat, valid? **unsat**
- ▶ What about $x \neq y \wedge f(x) = f(y)$? **sat**
- ▶ What about $x = g(y, z) \rightarrow f(x) = f(g(y, z))$? **valid**
- ▶ What about $f(a) = a \wedge f(f(a)) \neq a$? **unsat**

Example, cont.

- What about $f(f(f(a))) = a \wedge f(f(f(f(f(a))))) = a \wedge f(a) \neq a$?

Example, cont.

- ▶ What about $f(f(f(a))) = a \wedge f(f(f(f(f(a)))) = a \wedge f(a) \neq a$? **unsat**
- ▶ **Reasoning:** Substitute a for $f(f(f(a)))$ in second equality, this yields:
 $f(f(a)) = a$

Example, cont.

- ▶ What about $f(f(f(a))) = a \wedge f(f(f(f(f(a)))) = a \wedge f(a) \neq a$? **unsat**
- ▶ **Reasoning:** Substitute a for $f(f(f(a)))$ in second equality, this yields:
 $f(f(a)) = a$
- ▶ Since $f(f(a)) = a$, by congruence $f(f(f(a))) = f(a)$

Example, cont.

- ▶ What about $f(f(f(a))) = a \wedge f(f(f(f(f(a)))) = a \wedge f(a) \neq a$? **unsat**
- ▶ **Reasoning:** Substitute a for $f(f(f(a)))$ in second equality, this yields:
 $f(f(a)) = a$
- ▶ Since $f(f(a)) = a$, by congruence $f(f(f(a))) = f(a)$
- ▶ By first equality, we have $f(a) = a \Rightarrow$ contradiction!

Equivalence Relations

- ▶ Decision procedure for theory of equality known as **congruence closure** algorithm

Equivalence Relations

- ▶ Decision procedure for theory of equality known as **congruence closure** algorithm
- ▶ But need to understand what congruence closure is first \Rightarrow new terminology and concepts

Equivalence Relations

- ▶ Decision procedure for theory of equality known as **congruence closure** algorithm
- ▶ But need to understand what congruence closure is first \Rightarrow new terminology and concepts
- ▶ A binary relation R over a set S is an **equivalence relation** if

Equivalence Relations

- ▶ Decision procedure for theory of equality known as **congruence closure** algorithm
- ▶ But need to understand what congruence closure is first \Rightarrow new terminology and concepts
- ▶ A binary relation R over a set S is an **equivalence relation** if
 1. reflexive: $\forall s \in S. sRs$

Equivalence Relations

- ▶ Decision procedure for theory of equality known as **congruence closure** algorithm
- ▶ But need to understand what congruence closure is first \Rightarrow new terminology and concepts
- ▶ A binary relation R over a set S is an **equivalence relation** if
 1. reflexive: $\forall s \in S. sRs$
 2. symmetric: $\forall s_1, s_2 \in S. s_1Rs_2 \rightarrow s_2Rs_1$;

Equivalence Relations

- ▶ Decision procedure for theory of equality known as **congruence closure** algorithm
- ▶ But need to understand what congruence closure is first \Rightarrow new terminology and concepts
- ▶ A binary relation R over a set S is an **equivalence relation** if
 1. reflexive: $\forall s \in S. sRs$
 2. symmetric: $\forall s_1, s_2 \in S. s_1Rs_2 \rightarrow s_2Rs_1$;
 3. transitive: $\forall s_1, s_2, s_3 \in S. s_1Rs_2 \wedge s_2Rs_3 \rightarrow s_1Rs_3$.

Equivalence and Congruence Relations

- ▶ Equality predicate $=$ is equivalence relation over real numbers

Equivalence and Congruence Relations

- ▶ Equality predicate $=$ is equivalence relation over real numbers
- ▶ The relation "has same birthday as" is an equivalence relation over set of people

Equivalence and Congruence Relations

- ▶ Equality predicate $=$ is equivalence relation over real numbers
- ▶ The relation "has same birthday as" is an equivalence relation over set of people
- ▶ The relation \equiv_2 is equivalence relation over \mathbb{Z}

Equivalence and Congruence Relations

- ▶ Equality predicate $=$ is equivalence relation over real numbers
- ▶ The relation "has same birthday as" is an equivalence relation over set of people
- ▶ The relation \equiv_2 is equivalence relation over \mathbb{Z}
- ▶ A relation R is **congruence relation** over set S if it is an equivalence relation and for every n 'ary function f :

$$\forall \vec{s}, \vec{t}. \bigwedge_{i=1}^n s_i R t_i \rightarrow f(\vec{s}) R f(\vec{t}) .$$

Equivalence and Congruence Classes

- ▶ For a given equivalence relation over S , every member of S belongs to an **equivalence class**

Equivalence and Congruence Classes

- ▶ For a given equivalence relation over S , every member of S belongs to an **equivalence class**
- ▶ The equivalence class of $s \in S$ under R is the set:

$$[s]_R \stackrel{\text{def}}{=} \{s' \in S : sRs'\} .$$

Equivalence and Congruence Classes

- ▶ For a given equivalence relation over S , every member of S belongs to an **equivalence class**
- ▶ The equivalence class of $s \in S$ under R is the set:

$$[s]_R \stackrel{\text{def}}{=} \{s' \in S : sRs'\} .$$

- ▶ If R is a congruence relation, then this set is called **congruence class**

Equivalence and Congruence Classes

- ▶ For a given equivalence relation over S , every member of S belongs to an **equivalence class**
- ▶ The equivalence class of $s \in S$ under R is the set:

$$[s]_R \stackrel{\text{def}}{=} \{s' \in S : sRs'\} .$$

- ▶ If R is a congruence relation, then this set is called **congruence class**
- ▶ **Example:** What is the equivalence class of 1 under \equiv_2 ?

Equivalence and Congruence Classes

- ▶ For a given equivalence relation over S , every member of S belongs to an **equivalence class**
- ▶ The equivalence class of $s \in S$ under R is the set:

$$[s]_R \stackrel{\text{def}}{=} \{s' \in S : sRs'\} .$$

- ▶ If R is a congruence relation, then this set is called **congruence class**
- ▶ **Example:** What is the equivalence class of 1 under \equiv_2 ? **odd numbers**

Equivalence and Congruence Classes

- ▶ For a given equivalence relation over S , every member of S belongs to an **equivalence class**
- ▶ The equivalence class of $s \in S$ under R is the set:

$$[s]_R \stackrel{\text{def}}{=} \{s' \in S : sRs'\} .$$

- ▶ If R is a congruence relation, then this set is called **congruence class**
- ▶ **Example:** What is the equivalence class of 1 under \equiv_2 ? **odd numbers**
- ▶ What is the equivalence class of 6 under \equiv_3 ?

Equivalence and Congruence Classes

- ▶ For a given equivalence relation over S , every member of S belongs to an **equivalence class**
- ▶ The equivalence class of $s \in S$ under R is the set:

$$[s]_R \stackrel{\text{def}}{=} \{s' \in S : sRs'\} .$$

- ▶ If R is a congruence relation, then this set is called **congruence class**
- ▶ **Example:** What is the equivalence class of 1 under \equiv_2 ? **odd numbers**
- ▶ What is the equivalence class of 6 under \equiv_3 ? **multiples of 3**

Relation Refinements

- ▶ A binary relation R_1 is a **refinement** of another binary relation R_2 , written $R_1 \prec R_2$, if

$$\forall s_1, s_2 \in S. s_1 R_1 s_2 \rightarrow s_1 R_2 s_2 .$$

Relation Refinements

- ▶ A binary relation R_1 is a **refinement** of another binary relation R_2 , written $R_1 \prec R_2$, if

$$\forall s_1, s_2 \in S. s_1 R_1 s_2 \rightarrow s_1 R_2 s_2 .$$

- ▶ **Example 1:** Consider set $S = \{a, b\}$, and relations $R_1 = \{\langle a, b \rangle\}$ and $R_2 = \{\langle a, b \rangle, \langle b, b \rangle\}$

Relation Refinements

- ▶ A binary relation R_1 is a **refinement** of another binary relation R_2 , written $R_1 \prec R_2$, if

$$\forall s_1, s_2 \in S. s_1 R_1 s_2 \rightarrow s_1 R_2 s_2 .$$

- ▶ **Example 1:** Consider set $S = \{a, b\}$, and relations $R_1 = \{\langle a, b \rangle\}$ and $R_2 = \{\langle a, b \rangle, \langle b, b \rangle\}$
- ▶ Do either of these hold? $R_1 \prec R_2$ or $R_2 \prec R_1$?

Relation Refinements

- ▶ A binary relation R_1 is a **refinement** of another binary relation R_2 , written $R_1 \prec R_2$, if

$$\forall s_1, s_2 \in S. s_1 R_1 s_2 \rightarrow s_1 R_2 s_2 .$$

- ▶ **Example 1:** Consider set $S = \{a, b\}$, and relations $R_1 = \{\langle a, b \rangle\}$ and $R_2 = \{\langle a, b \rangle, \langle b, b \rangle\}$
- ▶ Do either of these hold? $R_1 \prec R_2$ or $R_2 \prec R_1$? **$R_1 \prec R_2$**

Relation Refinements

- ▶ A binary relation R_1 is a **refinement** of another binary relation R_2 , written $R_1 \prec R_2$, if

$$\forall s_1, s_2 \in S. s_1 R_1 s_2 \rightarrow s_1 R_2 s_2 .$$

- ▶ **Example 1:** Consider set $S = \{a, b\}$, and relations $R_1 = \{\langle a, b \rangle\}$ and $R_2 = \{\langle a, b \rangle, \langle b, b \rangle\}$
- ▶ Do either of these hold? $R_1 \prec R_2$ or $R_2 \prec R_1$? **$R_1 \prec R_2$**
- ▶ **Example 2:** Consider set \mathbb{Z} and the relations:
 $R_1 : \{x R_1 y : x \bmod 2 = y \bmod 2\}$ $R_2 : \{x R_2 y : x \bmod 4 = y \bmod 4\}$

Relation Refinements

- ▶ A binary relation R_1 is a **refinement** of another binary relation R_2 , written $R_1 \prec R_2$, if

$$\forall s_1, s_2 \in S. s_1 R_1 s_2 \rightarrow s_1 R_2 s_2 .$$

- ▶ **Example 1:** Consider set $S = \{a, b\}$, and relations $R_1 = \{\langle a, b \rangle\}$ and $R_2 = \{\langle a, b \rangle, \langle b, b \rangle\}$

- ▶ Do either of these hold? $R_1 \prec R_2$ or $R_2 \prec R_1$? **$R_1 \prec R_2$**

- ▶ **Example 2:** Consider set \mathbb{Z} and the relations:

$$R_1 : \{x R_1 y : x \bmod 2 = y \bmod 2\} \quad R_2 : \{x R_2 y : x \bmod 4 = y \bmod 4\}$$

- ▶ What is the refinement relationship between R_1 and R_2 ?

Relation Refinements

- ▶ A binary relation R_1 is a **refinement** of another binary relation R_2 , written $R_1 \prec R_2$, if

$$\forall s_1, s_2 \in S. s_1 R_1 s_2 \rightarrow s_1 R_2 s_2 .$$

- ▶ **Example 1:** Consider set $S = \{a, b\}$, and relations $R_1 = \{\langle a, b \rangle\}$ and $R_2 = \{\langle a, b \rangle, \langle b, b \rangle\}$

- ▶ Do either of these hold? $R_1 \prec R_2$ or $R_2 \prec R_1$? **$R_1 \prec R_2$**

- ▶ **Example 2:** Consider set \mathbb{Z} and the relations:

$$R_1 : \{x R_1 y : x \bmod 2 = y \bmod 2\} \quad R_2 : \{x R_2 y : x \bmod 4 = y \bmod 4\}$$

- ▶ What is the refinement relationship between R_1 and R_2 ? **$R_2 \prec R_1$**

Equivalence Closure

- ▶ The **equivalence closure** R^E of a binary relation R over S is the equivalence relation such that:

Equivalence Closure

- ▶ The **equivalence closure** R^E of a binary relation R over S is the equivalence relation such that:

1. R refines R^E , i.e. $R \prec R^E$;

Equivalence Closure

- ▶ The **equivalence closure** R^E of a binary relation R over S is the equivalence relation such that:
 1. R refines R^E , i.e. $R \prec R^E$;
 2. for all other equivalence relations R' s.t. $R \prec R'$, either $R' = R^E$ or $R^E \prec R'$

Equivalence Closure

- ▶ The **equivalence closure** R^E of a binary relation R over S is the equivalence relation such that:
 1. R refines R^E , i.e. $R \prec R^E$;
 2. for all other equivalence relations R' s.t. $R \prec R'$, either $R' = R^E$ or $R^E \prec R'$
- ▶ Thus, R^E is the smallest equivalence relation that includes R .

Equivalence Closure Example

- Consider set $S = \{a, b, c, d\}$ and binary relation

$$R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$$

Equivalence Closure Example

- ▶ Consider set $S = \{a, b, c, d\}$ and binary relation

$$R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$$

- ▶ Is R an equivalence relation?

Equivalence Closure Example

- ▶ Consider set $S = \{a, b, c, d\}$ and binary relation

$$R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$$

- ▶ Is R an equivalence relation? **No**

Equivalence Closure Example

- ▶ Consider set $S = \{a, b, c, d\}$ and binary relation

$$R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$$

- ▶ Is R an equivalence relation? **No**
- ▶ We want to compute the equivalence closure R^E , i.e., smallest equivalence relation including R

Equivalence Closure Example

- ▶ Consider set $S = \{a, b, c, d\}$ and binary relation

$$R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$$

- ▶ Is R an equivalence relation? **No**
- ▶ We want to compute the equivalence closure R^E , i.e., smallest equivalence relation including R
- ▶ Thus, R^E needs to include all tuples in R and must obey reflexivity, symmetry, and transitivity.

Equivalence Closure Example, cont

► $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ?

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity?

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity? $\langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity? $\langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle$
- ▶ What elements in R^E due to symmetry?

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity? $\langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle$
- ▶ What elements in R^E due to symmetry? $\langle b, a \rangle, \langle c, b \rangle$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity? $\langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle$
- ▶ What elements in R^E due to symmetry? $\langle b, a \rangle, \langle c, b \rangle$
- ▶ What elements in R^E due to transitivity?

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity? $\langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle$
- ▶ What elements in R^E due to symmetry? $\langle b, a \rangle, \langle c, b \rangle$
- ▶ What elements in R^E due to transitivity? $\langle a, c \rangle, \langle c, a \rangle$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity? $\langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle$
- ▶ What elements in R^E due to symmetry? $\langle b, a \rangle, \langle c, b \rangle$
- ▶ What elements in R^E due to transitivity? $\langle a, c \rangle, \langle c, a \rangle$
- ▶ What is R^E ?

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ Since R^E must include R , which elements are in R^E ? $\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle$
- ▶ Since R^E equivalence relation, it must obey reflexivity. What other elements in R^E due to reflexivity? $\langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle$
- ▶ What elements in R^E due to symmetry? $\langle b, a \rangle, \langle c, b \rangle$
- ▶ What elements in R^E due to transitivity? $\langle a, c \rangle, \langle c, a \rangle$
- ▶ What is R^E ?

$$R^E = \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle a, a \rangle, \langle b, b \rangle, \langle c, c \rangle, \langle b, a \rangle, \langle c, b \rangle, \langle a, c \rangle, \langle c, a \rangle\}$$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ $R^E = \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle b, a \rangle, \langle c, b \rangle, \langle a, c \rangle, \langle c, a \rangle\}$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ $R^E = \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle b, a \rangle, \langle c, b \rangle, \langle a, c \rangle, \langle c, a \rangle\}$
- ▶ Consider relation $R' = R^E \cup \{\langle c, d \rangle, \langle d, c \rangle, \langle b, d \rangle, \langle d, b \rangle, \langle a, d \rangle, \langle d, a \rangle\}$

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ $R^E = \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle b, a \rangle, \langle c, b \rangle, \langle a, c \rangle, \langle c, a \rangle\}$
- ▶ Consider relation $R' = R^E \cup \{\langle c, d \rangle, \langle d, c \rangle, \langle b, d \rangle, \langle d, b \rangle, \langle a, d \rangle, \langle d, a \rangle\}$
- ▶ R' is also an equivalence relation and covers R

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ $R^E = \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle b, a \rangle, \langle c, b \rangle, \langle a, c \rangle, \langle c, a \rangle\}$
- ▶ Consider relation $R' = R^E \cup \{\langle c, d \rangle, \langle d, c \rangle, \langle b, d \rangle, \langle d, b \rangle, \langle a, d \rangle, \langle d, a \rangle\}$
- ▶ R' is also an equivalence relation and covers R
- ▶ Is R' also an equivalence closure of R ?

Equivalence Closure Example, cont

- ▶ $R : \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle\}$
- ▶ $R^E = \{\langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle a, b \rangle, \langle b, c \rangle, \langle d, d \rangle, \langle b, a \rangle, \langle c, b \rangle, \langle a, c \rangle, \langle c, a \rangle\}$
- ▶ Consider relation $R' = R^E \cup \{\langle c, d \rangle, \langle d, c \rangle, \langle b, d \rangle, \langle d, b \rangle, \langle a, d \rangle, \langle d, a \rangle\}$
- ▶ R' is also an equivalence relation and covers R
- ▶ Is R' also an equivalence closure of R ? **No!**

Congruence Closure

- ▶ Given a set S and binary relation R , we also define **congruence closure** of R

Congruence Closure

- ▶ Given a set S and binary relation R , we also define **congruence closure** of R
- ▶ Congruence closure is similar to equivalence closure, but it is the smallest **congruence relation** that covers R

Congruence Closure

- ▶ Given a set S and binary relation R , we also define **congruence closure** of R
- ▶ Congruence closure is similar to equivalence closure, but it is the smallest **congruence relation** that covers R
- ▶ Formally, the **congruence closure** R^C of a binary relation R over S is the congruence relation such that:
 1. R refines R^C , i.e. $R \prec R^C$;
 2. for all other congruence relations R' s.t. $R \prec R'$, either $R' = R^C$ or $R^C \prec R'$

Congruence Closure Algorithm

- ▶ The decision procedure for $T_=$ computes **congruence closure** of equality over the **subterm set** of formula

Congruence Closure Algorithm

- ▶ The decision procedure for $T_=$ computes congruence closure of equality over the subterm set of formula
- ▶ Subterm set S_F of F is the set of all subterms of F

Congruence Closure Algorithm

- ▶ The decision procedure for $T_=$ computes **congruence closure** of equality over the **subterm set** of formula
- ▶ **Subterm set** S_F of F is the set of all subterms of F
- ▶ **Example:** Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$

Congruence Closure Algorithm

- ▶ The decision procedure for $T_=$ computes **congruence closure** of equality over the **subterm set** of formula
- ▶ **Subterm set** S_F of F is the set of all subterms of F
- ▶ **Example:** Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ What is S_F ?

Congruence Closure Algorithm

- ▶ The decision procedure for $T_=$ computes **congruence closure** of equality over the **subterm set** of formula
- ▶ **Subterm set** S_F of F is the set of all subterms of F
- ▶ **Example:** Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ What is S_F ? $\{a, b, f(a, b), f(f(a, b), b)\}$

Satisfiability using Congruence Relations

- ▶ We can now define satisfiability of a $\Sigma_{=}$ formula in terms of congruence closure over subterm set

Satisfiability using Congruence Relations

- ▶ We can now define satisfiability of a $\Sigma_{=}$ formula in terms of congruence closure over subterm set
- ▶ Consider $\Sigma_{=}$ formula F :

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

Satisfiability using Congruence Relations

- ▶ We can now define satisfiability of a $\Sigma_{=}$ formula in terms of congruence closure over subterm set
- ▶ Consider $\Sigma_{=}$ formula F :

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

- ▶ **Theorem:** F is satisfiable iff there exists a congruence relation \sim over the subterm set S_F of F such that:

Satisfiability using Congruence Relations

- ▶ We can now define satisfiability of a $\Sigma_{=}$ formula in terms of congruence closure over subterm set
- ▶ Consider $\Sigma_{=}$ formula F :

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

- ▶ **Theorem:** F is satisfiable iff there exists a congruence relation \sim over the subterm set S_F of F such that:
 1. For each i in $[1, m]$, $s_i \sim t_i$

Satisfiability using Congruence Relations

- ▶ We can now define satisfiability of a $\Sigma_{=}$ formula in terms of congruence closure over subterm set
- ▶ Consider $\Sigma_{=}$ formula F :

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

- ▶ **Theorem:** F is satisfiable iff there exists a congruence relation \sim over the subterm set S_F of F such that:
 1. For each i in $[1, m]$, $s_i \sim t_i$
 2. For each i in $[m + 1, n]$, $s_i \not\sim t_i$

Congruence Closure Algorithm: Basic Idea

Congruence closure algorithm decide satisfiability of

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

Congruence Closure Algorithm: Basic Idea

Congruence closure algorithm decide satisfiability of

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Construct the **congruence closure** \sim of

$$\{s_1 = t_1, \dots, s_m = t_m\}$$

over the subterm set S_F .

Congruence Closure Algorithm: Basic Idea

Congruence closure algorithm decide satisfiability of

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Construct the **congruence closure** \sim of

$$\{s_1 = t_1, \dots, s_m = t_m\}$$

over the subterm set S_F .

2. If $s_i \sim t_i$ for any i in $[m + 1, n]$, F is unsatisfiable

Congruence Closure Algorithm: Basic Idea

Congruence closure algorithm decide satisfiability of

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Construct the **congruence closure** \sim of

$$\{s_1 = t_1, \dots, s_m = t_m\}$$

over the subterm set S_F .

2. If $s_i \sim t_i$ for any i in $[m+1, n]$, F is unsatisfiable
3. Otherwise, F is satisfiable

Example

- Consider the formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$

Example

- ▶ Consider the formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ We'll represent \sim as a set of congruence classes, i.e., if t_1 and t_2 are in the same set, this means $t_1 \sim t_2$, otherwise $t_1 \not\sim t_2$

Example

- ▶ Consider the formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ We'll represent \sim as a set of congruence classes, i.e., if t_1 and t_2 are in the same set, this means $t_1 \sim t_2$, otherwise $t_1 \not\sim t_2$
- ▶ First, construct subterm set S_F and place each subterm in a separate set:

Example

- ▶ Consider the formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ We'll represent \sim as a set of congruence classes, i.e., if t_1 and t_2 are in the same set, this means $t_1 \sim t_2$, otherwise $t_1 \not\sim t_2$
- ▶ First, construct subterm set S_F and place each subterm in a separate set:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

Example

- ▶ Consider the formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ We'll represent \sim as a set of congruence classes, i.e., if t_1 and t_2 are in the same set, this means $t_1 \sim t_2$, otherwise $t_1 \not\sim t_2$

- ▶ First, construct subterm set S_F and place each subterm in a separate set:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

- ▶ Because of equality $f(a, b) = a$, merge congruence classes of $f(a, b)$ and a :

Example

- ▶ Consider the formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ We'll represent \sim as a set of congruence classes, i.e., if t_1 and t_2 are in the same set, this means $t_1 \sim t_2$, otherwise $t_1 \not\sim t_2$

- ▶ First, construct subterm set S_F and place each subterm in a separate set:

$$\{\{a\}, \{b\}, \{f(a, b)\}, \{f(f(a, b), b)\}\}$$

- ▶ Because of equality $f(a, b) = a$, merge congruence classes of $f(a, b)$ and a :

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

Example, cont

- ▶ Formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Current congruence classes:

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

Example, cont

- ▶ Formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

- ▶ Using $a \sim f(a, b)$ and $b \sim b$, what does function congruence imply?

Example, cont

- ▶ Formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

- ▶ Using $a \sim f(a, b)$ and $b \sim b$, what does function congruence imply?
 $f(f(a, b), b) = f(a, b)$

Example, cont

- ▶ Formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

- ▶ Using $a \sim f(a, b)$ and $b \sim b$, what does function congruence imply?
 $f(f(a, b), b) = f(a, b)$

- ▶ Thus, merge congruence classes of $f(a, b)$ and $f(f(a, b), b)$:

$$\{\{a, f(a, b), f(f(a, b), b)\}, \{b\}\}$$

Example, cont

- ▶ Formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f(a, b)\}, \{b\}, \{f(f(a, b), b)\}\}$$

- ▶ Using $a \sim f(a, b)$ and $b \sim b$, what does function congruence imply?
 $f(f(a, b), b) = f(a, b)$

- ▶ Thus, merge congruence classes of $f(a, b)$ and $f(f(a, b), b)$:

$$\{\{a, f(a, b), f(f(a, b), b)\}, \{b\}\}$$

- ▶ This represents the congruence closure over S_F .

Example, cont

- ▶ Formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Congruence closure: $\{\{a, f(a, b), f(f(a, b), b)\}, \{b\}\}$
- ▶ Is F satisfiable?

Example, cont

- ▶ Formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Congruence closure: $\{\{a, f(a, b), f(f(a, b), b)\}, \{b\}\}$
- ▶ Is F satisfiable? **No**
- ▶ Since a and $f(f(a, b), b)$ are in same congruence class, we have $a \sim f(f(a, b), b)$
- ▶ This contradicts $f(f(a, b), b) \neq a$!

Another Example

- Consider formula:

$$F : f(f(f(a))) = a \wedge f(f(f(f(f(a))))) = a \wedge f(a) \neq a$$

Another Example

- ▶ Consider formula:

$$F : f(f(f(a))) = a \wedge f(f(f(f(f(a))))) = a \wedge f(a) \neq a$$

- ▶ What is the subterm set S_F ?

Another Example

- Consider formula:

$$F : f(f(f(a))) = a \wedge f(f(f(f(f(a)))) = a \wedge f(a) \neq a$$

- What is the subterm set S_F ?

$$\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}$$

Another Example

- Consider formula:

$$F : f(f(f(a))) = a \wedge f(f(f(f(f(a)))) = a \wedge f(a) \neq a$$

- What is the subterm set S_F ?

$$\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}$$

- Initially, place each subterm in its own congruence class:

$$\{\{a\}, \{f(a)\}, \{f^2(a)\}, \{f^3(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

Another Example

- ▶ Consider formula:

$$F : f(f(f(a))) = a \wedge f(f(f(f(f(a)))) = a \wedge f(a) \neq a$$

- ▶ What is the subterm set S_F ?

$$\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}$$

- ▶ Initially, place each subterm in its own congruence class:

$$\{\{a\}, \{f(a)\}, \{f^2(a)\}, \{f^3(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

- ▶ Because of equality $f^3(a) = a$, $f^3(a)$ and a are placed in same congruence class:

Another Example

- Consider formula:

$$F : f(f(f(a))) = a \wedge f(f(f(f(f(a)))) = a \wedge f(a) \neq a$$

- What is the subterm set S_F ?

$$\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}$$

- Initially, place each subterm in its own congruence class:

$$\{\{a\}, \{f(a)\}, \{f^2(a)\}, \{f^3(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

- Because of equality $f^3(a) = a$, $f^3(a)$ and a are placed in same congruence class:

$$\{\{a, f^3(a)\}, \{f(a)\}, \{f^2(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$
- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a)\}, \{f^2(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a)\}, \{f^2(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

- ▶ From $a = f^3(a)$, what can we infer using function congruence?

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a)\}, \{f^2(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

- ▶ From $a = f^3(a)$, what can we infer using function congruence?
 $f(a) = f^4(a)$ and $f^2(a) = f^5(a)$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a)\}, \{f^2(a)\}, \{f^4(a)\}, \{f^5(a)\}\}$$

- ▶ From $a = f^3(a)$, what can we infer using function congruence?

$$f(a) = f^4(a) \text{ and } f^2(a) = f^5(a)$$

- ▶ Resulting congruence classes:

$$\{\{a, f^3(a)\}, \{f(a), f^4(a)\}, \{f^2(a), f^5(a)\}\}$$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$
- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a), f^4(a)\}, \{f^2(a), f^5(a)\}\}$$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a), f^4(a)\}, \{f^2(a), f^5(a)\}\}$$

- ▶ Now, process equality $f^5(a) = a$; which classes do we merge?

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a), f^4(a)\}, \{f^2(a), f^5(a)\}\}$$

- ▶ Now, process equality $f^5(a) = a$; which classes do we merge?

$$\{\{a, f^3(a), f^2(a), f^5(a)\}, \{f(a), f^4(a)\}\}$$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a), f^4(a)\}, \{f^2(a), f^5(a)\}\}$$

- ▶ Now, process equality $f^5(a) = a$; which classes do we merge?

$$\{\{a, f^3(a), f^2(a), f^5(a)\}, \{f(a), f^4(a)\}\}$$

- ▶ From $a = f^2(a)$, what can we infer via function congruence?

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a), f^4(a)\}, \{f^2(a), f^5(a)\}\}$$

- ▶ Now, process equality $f^5(a) = a$; which classes do we merge?

$$\{\{a, f^3(a), f^2(a), f^5(a)\}, \{f(a), f^4(a)\}\}$$

- ▶ From $a = f^2(a)$, what can we infer via function congruence? $f(a) = f^3(a)$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f^3(a)\}, \{f(a), f^4(a)\}, \{f^2(a), f^5(a)\}\}$$

- ▶ Now, process equality $f^5(a) = a$; which classes do we merge?

$$\{\{a, f^3(a), f^2(a), f^5(a)\}, \{f(a), f^4(a)\}\}$$

- ▶ From $a = f^2(a)$, what can we infer via function congruence? $f(a) = f^3(a)$

- ▶ Thus, merge the two congruence classes:

$$\{\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}\}$$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$
- ▶ Current congruence classes:

$$\{\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}\}$$

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$
- ▶ Current congruence classes:

$$\{\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}\}$$

- ▶ Is the formula satisfiable?

Another Example, cont

- ▶ Formula $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Current congruence classes:

$$\{\{a, f(a), f^2(a), f^3(a), f^4(a), f^5(a)\}\}$$

- ▶ Is the formula satisfiable? **No**
- ▶ Since $f(a)$ and a are in same congruence class, this contradicts $f(a) \neq a$

One More Example

- Consider formula $F : f(x) = f(y) \wedge x \neq y$

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set?

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$
- ▶ Each subterm starts in its own congruence class:
 $\{\{x\}, \{y\}, \{f(x)\}, \{f(y)\}\}$

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$
- ▶ Each subterm starts in its own congruence class:
 $\{\{x\}, \{y\}, \{f(x)\}, \{f(y)\}\}$
- ▶ Process equality $f(x) = f(y) \Rightarrow$

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$
- ▶ Each subterm starts in its own congruence class:
 $\{\{x\}, \{y\}, \{f(x)\}, \{f(y)\}\}$
- ▶ Process equality $f(x) = f(y) \Rightarrow \{\{x\}, \{y\}, \{f(x), f(y)\}\}$

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$
- ▶ Each subterm starts in its own congruence class:
 $\{\{x\}, \{y\}, \{f(x)\}, \{f(y)\}\}$
- ▶ Process equality $f(x) = f(y) \Rightarrow \{\{x\}, \{y\}, \{f(x), f(y)\}\}$
- ▶ What new equalities can we infer from congruence?

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$
- ▶ Each subterm starts in its own congruence class:
 $\{\{x\}, \{y\}, \{f(x)\}, \{f(y)\}\}$
- ▶ Process equality $f(x) = f(y) \Rightarrow \{\{x\}, \{y\}, \{f(x), f(y)\}\}$
- ▶ What new equalities can we infer from congruence? **None!**

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$
- ▶ Each subterm starts in its own congruence class:
 $\{\{x\}, \{y\}, \{f(x)\}, \{f(y)\}\}$
- ▶ Process equality $f(x) = f(y) \Rightarrow \{\{x\}, \{y\}, \{f(x), f(y)\}\}$
- ▶ What new equalities can we infer from congruence? **None!**
- ▶ Is the formula satisfiable?

One More Example

- ▶ Consider formula $F : f(x) = f(y) \wedge x \neq y$
- ▶ What is the subterm set? $\{x, y, f(x), f(y)\}$
- ▶ Each subterm starts in its own congruence class:
 $\{\{x\}, \{y\}, \{f(x)\}, \{f(y)\}\}$
- ▶ Process equality $f(x) = f(y) \Rightarrow \{\{x\}, \{y\}, \{f(x), f(y)\}\}$
- ▶ What new equalities can we infer from congruence? **None!**
- ▶ Is the formula satisfiable? **Yes**

How to Compute Congruence Closure

- So far, we described how to decide satisfiability using congruence closure

How to Compute Congruence Closure

- ▶ So far, we described how to decide satisfiability using congruence closure
- ▶ But we haven't discussed an algorithm for efficiently computing congruence closure

How to Compute Congruence Closure


- ▶ So far, we described how to decide satisfiability using congruence closure
- ▶ But we haven't discussed an algorithm for efficiently computing congruence closure
- ▶ There is a very efficient algorithm called **Union-Find** for computing congruence classes

How to Compute Congruence Closure

- ▶ So far, we described how to decide satisfiability using congruence closure
- ▶ But we haven't discussed an algorithm for efficiently computing congruence closure
- ▶ There is a very efficient algorithm called **Union-Find** for computing congruence classes
- ▶ **Next:** Talk about Union-Find algorithm for computing congruence closures


Representing Subterms

- To compute congruence closure efficiently, we'll represent the subterm set of the formula as a DAG



Representing Subterms


- To compute congruence closure efficiently, we'll represent the subterm set of the formula as a DAG



- Each node corresponds to a subterm and has unique id

Representing Subterms


- ▶ To compute congruence closure efficiently, we'll represent the subterm set of the formula as a DAG



- ▶ Each node corresponds to a subterm and has unique id
- ▶ Edges point from function symbol to arguments

Representing Subterms


- ▶ To compute congruence closure efficiently, we'll represent the subterm set of the formula as a DAG



- ▶ Each node corresponds to a subterm and has unique id
- ▶ Edges point from function symbol to arguments
- ▶ **Question:** What subterm does node labeled 1 represent?

Representing Subterms

- ▶ To compute congruence closure efficiently, we'll represent the subterm set of the formula as a DAG



- ▶ Each node corresponds to a subterm and has unique id
- ▶ Edges point from function symbol to arguments
- ▶ **Question:** What subterm does node labeled 1 represent? $f(f(a,b), b)$

Representative of Congruence Class

- ▶ To compute congruence closure, we need to merge congruence classes

Representative of Congruence Class


- ▶ To compute congruence closure, we need to merge congruence classes
- ▶ To do this efficiently, each congruence class has a **representative**: When merging two classes, only need to update the representative

Representative of Congruence Class

- ▶ To compute congruence closure, we need to merge congruence classes
- ▶ To do this efficiently, each congruence class has a **representative**: When merging two classes, only need to update the representative
 - ▶ Thus, for a given subterm, we need to be able to find the representative of its class

Representative of Congruence Class


- ▶ To compute congruence closure, we need to merge congruence classes
- ▶ To do this efficiently, each congruence class has a **representative**: When merging two classes, only need to update the representative



- ▶ Thus, for a given subterm, we need to be able to find the representative of its class
- ▶ Each subterm contains a pointer that eventually leads to the representative of its congruence class

Representative of Congruence Class

- ▶ To compute congruence closure, we need to merge congruence classes
- ▶ To do this efficiently, each congruence class has a **representative**: When merging two classes, only need to update the representative



- ▶ Thus, for a given subterm, we need to be able to find the representative of its class
- ▶ Each subterm contains a pointer that eventually leads to the representative of its congruence class
- ▶ In this example, $a, f(a, b), f(f(a, b), b)$ are in same congruence class; a is the representative

Parents of a Subterm

- ▶ In addition to efficiently finding representative, also need to efficiently find **parents** of terms

Parents of a Subterm

- ▶ In addition to efficiently finding representative, also need to efficiently find **parents** of terms
- ▶ Why? Because if $x_1 = y_1, \dots, x_k = y_k$, function congruence implies $f(\vec{x}) = f(\vec{y})$

Parents of a Subterm

- ▶ In addition to efficiently finding representative, also need to efficiently find **parents** of terms
- ▶ Why? Because if $x_1 = y_1, \dots, x_k = y_k$, function congruence implies $f(\vec{x}) = f(\vec{y})$
- ▶ Thus, when each x_i, y_i pair is in same congruence class, need to merge congruence classes of their parents $f(\vec{x})$ and $f(\vec{y})$

Parents of a Subterm

- ▶ In addition to efficiently finding representative, also need to efficiently find **parents** of terms
- ▶ Why? Because if $x_1 = y_1, \dots, x_k = y_k$, function congruence implies $f(\vec{x}) = f(\vec{y})$
- ▶ Thus, when each x_i, y_i pair is in same congruence class, need to merge congruence classes of their parents $f(\vec{x})$ and $f(\vec{y})$
- ▶ Thus, keep pointer from **representative** of congruence class to **parents of all subterms** in the congruence class

Summary of Data Structure

- ▶ Represent subterms as a DAG

Summary of Data Structure

- ▶ Represent subterms as a DAG
- ▶ Each node in the DAG corresponds to a subterm

Summary of Data Structure

- ▶ Represent subterms as a DAG
- ▶ Each node in the DAG corresponds to a subterm
- ▶ Each node stores its unique id, name of function or variable, and list of argument subterms

Summary of Data Structure

- ▶ Represent subterms as a DAG
- ▶ Each node in the DAG corresponds to a subterm
- ▶ Each node stores its unique id, name of function or variable, and list of argument subterms
- ▶ Each node n has a **find** pointer field that leads to its representative

Summary of Data Structure

- ▶ Represent subterms as a DAG
- ▶ Each node in the DAG corresponds to a subterm
- ▶ Each node stores its unique id, name of function or variable, and list of argument subterms
- ▶ Each node n has a **find** pointer field that leads to its representative
- ▶ The **find** field of a representative points to itself

Summary of Data Structure

- ▶ Represent subterms as a DAG
- ▶ Each node in the DAG corresponds to a subterm
- ▶ Each node stores its unique id, name of function or variable, and list of argument subterms
- ▶ Each node n has a **find** pointer field that leads to its representative
- ▶ The **find** field of a representative points to itself
- ▶ Each representative stores the set of **parents** for all subterms in that class

Summary of Data Structure

- ▶ Represent subterms as a DAG
- ▶ Each node in the DAG corresponds to a subterm
- ▶ Each node stores its unique id, name of function or variable, and list of argument subterms
- ▶ Each node n has a **find** pointer field that leads to its representative
- ▶ The **find** field of a representative points to itself
- ▶ Each representative stores the set of **parents** for all subterms in that class
- ▶ If a term is not a representative, then its **parents** field is empty

Finding Representative of Congruence Class

- ▶ Given a term t , we need to find representative for that term

Finding Representative of Congruence Class

- ▶ Given a term t , we need to find representative for that term
- ▶ If t 's **find** field points to itself, then t is the representative of its congruence class

Finding Representative of Congruence Class

- ▶ Given a term t , we need to find representative for that term
- ▶ If t 's **find** field points to itself, then t is the representative of its congruence class
- ▶ Otherwise, we follow the chain of **find** references until we find a node t' that points to itself

Finding Representative of Congruence Class

- ▶ Given a term t , we need to find representative for that term
- ▶ If t 's **find** field points to itself, then t is the representative of its congruence class
- ▶ Otherwise, we follow the chain of **find** references until we find a node t' that points to itself
- ▶ In this case, t' is t 's representative

Merging Congruence Classes

- ▶ Using this data structure, how do we merge congruence classes of two terms t_1 and t_2 ?

Merging Congruence Classes

- ▶ Using this data structure, how do we merge congruence classes of two terms t_1 and t_2 ?
- ▶ First find representatives of t_1 and t_2 as described earlier

Merging Congruence Classes

- ▶ Using this data structure, how do we merge congruence classes of two terms t_1 and t_2 ?
- ▶ First find representatives of t_1 and t_2 as described earlier
- ▶ Want to make $Rep(t_2)$ new representative for merged class

Merging Congruence Classes

- ▶ Using this data structure, how do we merge congruence classes of two terms t_1 and t_2 ?
- ▶ First find representatives of t_1 and t_2 as described earlier
- ▶ Want to make $Rep(t_2)$ new representative for merged class
- ▶ Thus, change **find** field of $Rep(t_1)$ to point to $Rep(t_2)$

Merging Congruence Classes

- ▶ Using this data structure, how do we merge congruence classes of two terms t_1 and t_2 ?
- ▶ First find representatives of t_1 and t_2 as described earlier
- ▶ Want to make $Rep(t_2)$ new representative for merged class
- ▶ Thus, change **find** field of $Rep(t_1)$ to point to $Rep(t_2)$
- ▶ Update parents: add parent terms stored in $Rep(t_1)$ to those of $Rep(t_2)$, and remove parents stored in $Rep(t_1)$

Processing Equalities

- ▶ How do we process an equality $t_1 = t_2$?

Processing Equalities

- ▶ How do we process an equality $t_1 = t_2$?
- ▶ Need to merge equivalence classes of t_1 and t_2

Processing Equalities

- ▶ How do we process an equality $t_1 = t_2$?
- ▶ Need to merge equivalence classes of t_1 and t_2
- ▶ Might potentially also need to merge t_1 and t_2 's parents due to function congruence

Processing Equalities

- ▶ How do we process an equality $t_1 = t_2$?
- ▶ Need to merge equivalence classes of t_1 and t_2
- ▶ Might potentially also need to merge t_1 and t_2 's parents due to function congruence
- ▶ Given parent p_1 of t_1 and p_2 of t_2 , when do we merge p_1 and p_2 's congruence classes?

Processing Equalities

- ▶ How do we process an equality $t_1 = t_2$?
- ▶ Need to merge equivalence classes of t_1 and t_2
- ▶ Might potentially also need to merge t_1 and t_2 's parents due to function congruence
- ▶ Given parent p_1 of t_1 and p_2 of t_2 , when do we merge p_1 and p_2 's congruence classes?
- ▶ If they have the same function name and all of their arguments are congruent (i.e., have same representative)

Processing Equalities, cont

To process equality $t_1 = t_2$:

1. Find representatives of t_1 and t_2

Processing Equalities, cont

To process equality $t_1 = t_2$:

1. Find representatives of t_1 and t_2
2. Merge equivalence classes

Processing Equalities, cont

To process equality $t_1 = t_2$:

1. Find representatives of t_1 and t_2
2. Merge equivalence classes
3. Retrieve the set of parents P_1, P_2 stored in $Rep(t_1), Rep(t_2)$

Processing Equalities, cont

To process equality $t_1 = t_2$:

1. Find representatives of t_1 and t_2
2. Merge equivalence classes
3. Retrieve the set of parents P_1, P_2 stored in $Rep(t_1), Rep(t_2)$
4. For each $(p_i, p_j) \in P_1 \times P_2$, if p_i and p_j are congruent, **process equality**
 $p_i = p_j$

Processing Equalities, cont

To process equality $t_1 = t_2$:

1. Find representatives of t_1 and t_2
2. Merge equivalence classes
3. Retrieve the set of parents P_1, P_2 stored in $Rep(t_1), Rep(t_2)$
4. For each $(p_i, p_j) \in P_1 \times P_2$, if p_i and p_j are congruent, **process equality**
 $p_i = p_j$

Observe: Processing one equality creates new equalities, which in turn might generate other new equalities!

Question about Algorithm

- ▶ **Recall:** The representative stores parents of **all** terms in the congruence class

Question about Algorithm

- ▶ **Recall:** The representative stores parents of **all** terms in the congruence class
- ▶ Thus, when we process equality $t_1 = t_2$, we might also merge terms that are not t_1 and t_2 's parents

Question about Algorithm

- ▶ **Recall:** The representative stores parents of **all** terms in the congruence class
- ▶ Thus, when we process equality $t_1 = t_2$, we might also merge terms that are not t_1 and t_2 's parents
- ▶ Is this correct/necessary?

Question about Algorithm

- ▶ **Recall:** The representative stores parents of **all** terms in the congruence class
- ▶ Thus, when we process equality $t_1 = t_2$, we might also merge terms that are not t_1 and t_2 's parents
- ▶ Is this correct/necessary? **Yes!**

Question about Algorithm

- ▶ **Recall:** The representative stores parents of **all** terms in the congruence class
- ▶ Thus, when we process equality $t_1 = t_2$, we might also merge terms that are not t_1 and t_2 's parents
- ▶ Is this correct/necessary? **Yes!**
- ▶ If s_1, s_2 are in t_1, t_2 's congruence class, $t_1 = t_2$ implies $s_1 = s_2$

Question about Algorithm

- ▶ **Recall:** The representative stores parents of **all** terms in the congruence class
- ▶ Thus, when we process equality $t_1 = t_2$, we might also merge terms that are not t_1 and t_2 's parents
- ▶ Is this correct/necessary? **Yes!**
- ▶ If s_1, s_2 are in t_1, t_2 's congruence class, $t_1 = t_2$ implies $s_1 = s_2$
- ▶ Thus, also need to process equality between s_1, s_2 's parents

Question about Algorithm

- ▶ **Recall:** The representative stores parents of **all** terms in the congruence class
- ▶ Thus, when we process equality $t_1 = t_2$, we might also merge terms that are not t_1 and t_2 's parents
- ▶ Is this correct/necessary? **Yes!**
- ▶ If s_1, s_2 are in t_1, t_2 's congruence class, $t_1 = t_2$ implies $s_1 = s_2$
- ▶ Thus, also need to process equality between s_1, s_2 's parents
- ▶ That's why representative stores **all parents** for cong. class

Full Algorithm for Deciding Satisfiability

Algorithm to decide satisfiability of $T_{=}$ formula

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

Full Algorithm for Deciding Satisfiability

Algorithm to decide satisfiability of $T_{=}$ formula

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Compute subterms and construct initial DAG (each node's representative is itself)

Full Algorithm for Deciding Satisfiability

Algorithm to decide satisfiability of $T_{=}$ formula

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Compute subterms and construct initial DAG (each node's representative is itself)
2. For each $i \in [1, m]$, process equality $s_i = t_i$ as described

Full Algorithm for Deciding Satisfiability

Algorithm to decide satisfiability of $T_=$ formula

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Compute subterms and construct initial DAG (each node's representative is itself)
2. For each $i \in [1, m]$, process equality $s_i = t_i$ as described
3. For each $i \in [m + 1, n]$, check if $Rep(s_i) = Rep(t_i)$

Full Algorithm for Deciding Satisfiability

Algorithm to decide satisfiability of $T_=$ formula

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Compute subterms and construct initial DAG (each node's representative is itself)
2. For each $i \in [1, m]$, process equality $s_i = t_i$ as described
3. For each $i \in [m + 1, n]$, check if $Rep(s_i) = Rep(t_i)$
4. If there exists some $i \in [m + 1, n]$ for which $Rep(s_i) = Rep(t_i)$, return
UNSAT

Full Algorithm for Deciding Satisfiability

Algorithm to decide satisfiability of $T_=$ formula

$$F : s_1 = t_1 \wedge \dots s_m = t_m \wedge s_{m+1} \neq t_{m+1} \wedge \dots s_n \neq t_n$$

1. Compute subterms and construct initial DAG (each node's representative is itself)
2. For each $i \in [1, m]$, process equality $s_i = t_i$ as described
3. For each $i \in [m + 1, n]$, check if $\text{Rep}(s_i) = \text{Rep}(t_i)$
4. If there exists some $i \in [m + 1, n]$ for which $\text{Rep}(s_i) = \text{Rep}(t_i)$, return **UNSAT**
5. If for all i , $\text{Rep}(s_i) \neq \text{Rep}(t_i)$, return **SAT**

Example


- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$

Example

- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$

Example


- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$



- ▶ Construct initial DAG

Example


- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$



- ▶ Construct initial DAG
- ▶ Process equality $f(a, b) = a$

Example


- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$



- ▶ Construct initial DAG
- ▶ Process equality $f(a, b) = a$

Example


- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$



- ▶ Construct initial DAG
- ▶ Process equality $f(a, b) = a$
- ▶ Are parents $f(a, b)$ and $f(f(a, b), b)$ congruent?

Example


- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$



- ▶ Construct initial DAG
- ▶ Process equality $f(a, b) = a$
- ▶ Are parents $f(a, b)$ and $f(f(a, b), b)$ congruent?
- ▶ Yes, so process equality $f(a, b) = f(f(a, b), b)$

Example


- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$



- ▶ Construct initial DAG
- ▶ Process equality $f(a, b) = a$
- ▶ Are parents $f(a, b)$ and $f(f(a, b), b)$ congruent?
- ▶ Yes, so process equality $f(a, b) = f(f(a, b), b)$

Example

- ▶ Consider formula $F : f(a, b) = a \wedge f(f(a, b), b) \neq a$
- ▶ Subterms: $a, b, f(a, b), f(f(a, b), b)$




- ▶ Construct initial DAG
 - ▶ Process equality $f(a, b) = a$
 - ▶ Are parents $f(a, b)$ and $f(f(a, b), b)$ congruent?
 - ▶ Yes, so process equality $f(a, b) = f(f(a, b), b)$
-
- ▶ Formula unsatisfiable because $f(f(a, b), b)$ and a have same representative!

Example II

- Consider formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

Example II


- ▶ Consider formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$
- ▶ Initial DAG:



Example II

- ▶ Consider formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Initial DAG:




- ▶ Process equality $f^3(a) = a$:


Example II

- ▶ Consider formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Initial DAG:




- ▶ Process equality $f^3(a) = a$:




Example II

- ▶ Consider formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Initial DAG:



- ▶ Process equality $f^3(a) = a$:




- ▶ Are parents congruent?


Example II

- ▶ Consider formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Initial DAG:



- ▶ Process equality $f^3(a) = a$:




- ▶ Are parents congruent? **Yes**


Example II

- ▶ Consider formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$

- ▶ Initial DAG:



- ▶ Process equality $f^3(a) = a$:




- ▶ Are parents congruent? **Yes**

- ▶ Process equality $f^4(a) = f(a)$


Example II, cont

- After merging classes:



Example II, cont


- After merging classes:



- Are $f^4(a)$'s and $f(a)$'s parents congruent?

Example II, cont


- After merging classes:




- Are $f^4(a)$'s and $f(a)$'s parents congruent? **Yes**

Example II, cont

- ▶ After merging classes:




- ▶ Are $f^4(a)$'s and $f(a)$'s parents congruent? **Yes**
- ▶ Process equality $f^5(a) = f^2(a)$




Example II, cont

- Formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$



Example II, cont


- Formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$




- Process equality $f^5(a) = a$:

Example II, cont

- Formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$




- Process equality $f^5(a) = a$:




Example II, cont

- Formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$




- Process equality $f^5(a) = a$:



- Now, parents $f^3(a)$ and $f(a)$ congruent; process equality $f^3(a) = f(a)$


Example II, cont

- Formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$



Example II, cont


- Formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$



- Now, everything in same congruence class; so we are done.

Example II, cont

- ▶ Formula: $F : f^3(a) = a \wedge f^5(a) = a \wedge f(a) \neq a$



- ▶ Now, everything in same congruence class; so we are done.
- ▶ Formula UNSAT because a and $f(a)$ have same representative

Summary

- Congruence closure algorithm is used for determining satisfiability of $T_{=}$ formulas (without disjunction)

Summary

- ▶ Congruence closure algorithm is used for determining satisfiability of $T_{=}$ formulas (without disjunction)
- ▶ Our algorithm for computing congruence closures is called **Union-Find**, also used in other applications

Summary

- ▶ Congruence closure algorithm is used for determining satisfiability of $T_=$ formulas (without disjunction)
- ▶ Our algorithm for computing congruence closures is called **Union-Find**, also used in other applications
- ▶ Deciding conjunctive $T_=$ formulas is inexpensive: our algorithm is $O(e^2)$, but can be solved in $O(e \log(e))$

Summary

- ▶ Congruence closure algorithm is used for determining satisfiability of $T_=$ formulas (without disjunction)
- ▶ Our algorithm for computing congruence closures is called **Union-Find**, also used in other applications
- ▶ Deciding conjunctive $T_=$ formulas is inexpensive: our algorithm is $O(e^2)$, but can be solved in $O(e \log(e))$
- ▶ To decide satisfiability of formulas containing disjunctions, can either convert to DNF or use **DPLL(\mathcal{T})** (more on this later)

Summary

- ▶ Congruence closure algorithm is used for determining satisfiability of $T_=$ formulas (without disjunction)
- ▶ Our algorithm for computing congruence closures is called **Union-Find**, also used in other applications
- ▶ Deciding conjunctive $T_=$ formulas is inexpensive: our algorithm is $O(e^2)$, but can be solved in $O(e \log(e))$
- ▶ To decide satisfiability of formulas containing disjunctions, can either convert to DNF or use **DPLL(\mathcal{T})** (more on this later)
- ▶ **Next lecture:** Decision procedure for qff theory of rationals (Simplex algorithm)

Summary

- ▶ Congruence closure algorithm is used for determining satisfiability of $T_=$ formulas (without disjunction)
- ▶ Our algorithm for computing congruence closures is called **Union-Find**, also used in other applications
- ▶ Deciding conjunctive $T_=$ formulas is inexpensive: our algorithm is $O(e^2)$, but can be solved in $O(e \log(e))$
- ▶ To decide satisfiability of formulas containing disjunctions, can either convert to DNF or use **DPLL(\mathcal{T})** (more on this later)
- ▶ **Next lecture:** Decision procedure for qff theory of rationals (Simplex algorithm)
- ▶ **Reminder:** Homework due next lecture!!