

Solvers for Software Reliability and Security


VIJAY GANESH
MIT
2011

The Software Reliability Problem

- Software is error-prone
- Significant and increasing costs
- Foundational research problem and opportunity


What is at the Core?

Logic Abstractions of Computation



What is at the Core?

Logic Abstractions of Computation



Why Logic for Program Reasoning

Logic Abstractions of Computation


Imperative Code: Operational view

```
File Edit Options Buffers Tools IM-Python Python Help
from quickwiki.lib.base import *
from pylons.database import make_session

class PageController(BaseController):
    def __before__(self):
        model.ctx.current = make_session()

    def index(self, title):
        page = model.Page.get_by(title=title)
        if page:
            c.content = page.get_wiki_content()
            return render_response('/page.myt')
        elif model.wikiwords.match(title):
            return render_response('/new_page.m
abort(404)

    def edit(self, title):
        page = model.Page.get_by(title=title)
```




Logic Formula: Declarative View

$$\begin{aligned} &(\forall x.(P(x) \wedge Q(x)) \leftrightarrow ((\forall x.P(x)) \wedge (\forall x.Q(x))) \\ &(\exists x.(P(x) \wedge Q(x)) \rightarrow ((\exists x.P(x)) \wedge (\exists x.Q(x))) \\ &(\exists x.(P(x) \vee Q(x)) \leftrightarrow ((\exists x.P(x)) \vee (\exists x.Q(x))) \\ &((\forall x.P(x)) \vee (\forall x.Q(x))) \rightarrow (\forall x.(P(x) \vee Q(x))) \\ &(\exists x.\forall y.R(x,y)) \rightarrow (\forall y.\exists x.R(x,y)) \\ &(\neg(\exists x.P(x))) \leftrightarrow (\forall x.(\neg P(x))) \\ &(\neg(\forall x.P(x))) \leftrightarrow (\exists x.(\neg P(x))) \\ &(\neg(\exists x_{pt}.P(x))) \leftrightarrow (\forall x_{pt}.(\neg P(x))) \\ &(\neg(\forall x_{pt}.P(x))) \leftrightarrow (\exists x_{pt}.(\neg P(x))) \\ &(\forall x.(x = t \rightarrow F(x))) \leftrightarrow F(t) \\ &(\exists x.(x = t \wedge F(x))) \leftrightarrow F(t) \end{aligned}$$

- Logic provides **abstractions of computation**
- **Easy to work with abstractions**
- **Compact representation** of desired properties

Reliability through Logical Reasoning Engineering, Usability, Novelty



What is at the Core?


The SAT/SMT Problem



- Rich logics (Modular arithmetic, Arrays, Strings,...)
- NP-complete, PSPACE-complete,...
- Practical, scalable, usable, automatic
- **Enable novel software reliability approaches**


So, What's New?

From Reliability Problem to Solvers




So, What's New?

From Reliability Problem to Solvers




- **1000+X** improvement in 10 years
- **Enabled** completely **new** techniques
- **Super-charged** existing techniques


And, The Research Story is....




And, The Research Story is....



And, The Research Story is....




And, The Research Story is....




My Contributions

STP & HAMPI Solvers




My Contributions

STP & HAMPI Solvers



- Can handle real-world formulas with millions of constraints
- **Enabled** completely **new** techniques (e.g., Concolic testing)
- **Enable** test million-line codes
- **Super-charged** existing techniques (e.g., Hardware bounded MC)
- **Future is bright: Multicore, programming language, runtime systems**

And, The Research Story is ...



Key Contributions

| <u>Name</u> | <u>Key Concept</u> | <u>Impact</u> | <u>Pubs</u> |
|--|---|-------------------------------------|---|
| STP Bit-vector & Array Solver ^{1,2} | Abstraction-refinement for Solving | Concolic Testing | CAV 2007 CCS 2006 TISSEC 2008 |
| HAMPI String Solver ¹ | App-driven Bounding for Solving | Analysis of Web Apps | ISSTA 2009 ³ TOSEM 2011 (Invited/in submission) |
| (Un)Decidability results for Strings | Insights from Practical Applications | First results for strings+length | In submission |

1. 100+ research projects use STP and HAMPI
2. STP won the SMTCOMP 2006 and 2010 competitions for bit-vector solvers
3. ACM Best Paper Award 2009

Rest of the Talk

- **STP** Bit-vector and Array Solver

- Why Bit-vectors and Arrays?
- How does STP scale: Abstraction-refinement
- Impact: Concolic testing
- Experimental Results

- **HAMPI** String Solver

- Why Strings?
- How does HAMPI scale: Bounding
- Impact: String-based program analysis
- Experimental Results

- Future Work

- **Multicore SAT**
- **SAT-based Languages**
- Auto-tuning Solvers
- Advice-based Solvers

STP Bit-vector & Array Solver



- Bit-vector or machine arithmetic
- Arrays for memory
- C/C++/Java expressions
- NP-complete

Programs Reasoning & STP

Why Bit-vectors and Arrays


- STP logic tailored for software reliability applications
- Support **symbolic execution**/program analysis

| C/C++/Java/... | Bit-vectors and Arrays |
|---|---|
| Int Var Char Var | 32 bit variable 8 bit variable |
| Arithmetic operation ($x+y$, $x-y$, $x*y$, x/y ,...) | Arithmetic function ($x+y$, $x-y$, $x*y$, x/y ,...) |
| assignments $x = \text{expr};$ | equality $x = \text{expr};$ |
| if conditional $\text{if}(\text{cond})\ x = \text{expr}^1\ \text{else}\ x = \text{expr}^2$ | if-then-else construct $x = \text{if}(\text{cond})\ \text{expr}^1\ \text{else}\ \text{expr}^2$ |
| inequality | inequality predicate |
| Memory read/write $x = *ptr + i;$ | Array read/write $ptr[]; x = \text{Read}(ptr,i);$ |
| Structure/Class | Serialized bit-vector expressions |
| Function | Symbolic execution |
| Loops | Bounding |

How to Automatically Crash Programs?

Concolic Execution & STP

Problem: Automatically generate **crashing tests** given only the code



How to Automate Testing?

Concolic Execution & STP

Structured input processing code:
PDF Reader, Movie Player,...

```
Buggy_C_Program(int* data_field, int len_field) {  
  
    int * ptr = malloc(len_field*sizeof(int));  
    int i; //uninitialized  
  
    while (i++ < process(len_field)) {  
        //1. Integer overflow causing NULL deref  
        //2. Buffer overflow  
        *(ptr+i) = process_data(*(data_field+i));  
    }  
}
```

- Formula captures computation
- Tester attaches formula to capture spec

How to Automate Testing?

Concolic Execution & STP

Structured input processing code:
PDF Reader, Movie Player,...

```
Buggy_C_Program(int* data_field, int len_field) {  
  
    int * ptr = malloc(len_field*sizeof(int));  
    int i; //uninitialized  
  
    while (i++ < process(len_field)) {  
        //1. Integer overflow causing NULL deref  
        //2. Buffer overflow  
        *(ptr+i) = process_data(*(data_field+i));  
    }  
}
```

Equivalent Logic Formula derived using
symbolic execution

```
data_field, mem_ptr : ARRAY;  
len_field : BITVECTOR(32); //symbolic  
i, j, ptr : BITVECTOR(32); //symbolic  
.  
.  
mem_ptr[ptr+i] = process_data(data_field[i]);  
mem_ptr[ptr+i+1] = process_data(data_field[i+1]);  
.  
.
```

- Formula captures computation
- Tester attaches formula to capture spec

How to Automate Testing?

Concolic Execution & STP

Structured input processing code:
PDF Reader, Movie Player,...

```
Buggy_C_Program(int* data_field, int len_field) {  
  
    int * ptr = malloc(len_field*sizeof(int));  
    int i; //uninitialized  
  
    while (i++ < process(len_field)) {  
        //1. Integer overflow causing NULL deref  
        //2. Buffer overflow  
        *(ptr+i) = process_data(*(data_field+i));  
    }  
}
```



Equivalent Logic Formula derived using
symbolic execution

```
data_field, mem_ptr : ARRAY;  
len_field : BITVECTOR(32); //symbolic  
i, j, ptr : BITVECTOR(32); //symbolic  
.  
.  
mem_ptr[ptr+i] = process_data(data_field[i]);  
mem_ptr[ptr+i+1] = process_data(data_field[i+1]);  
.  
.
```

- Formula captures computation
- Tester attaches formula to capture spec

How to Automate Testing?

Concolic Execution & STP

Structured input processing code:
PDF Reader, Movie Player,...

```
Buggy_C_Program(int* data_field, int len_field) {  
  
    int * ptr = malloc(len_field*sizeof(int));  
    int i; //uninitialized  
  
    while (i++ < process(len_field)) {  
        //1. Integer overflow causing NULL deref  
        //2. Buffer overflow  
        *(ptr+i) = process_data(*(data_field+i));  
    }  
}
```




Equivalent Logic Formula derived using
symbolic execution

```
data_field, mem_ptr : ARRAY;  
len_field : BITVECTOR(32); //symbolic  
i, j, ptr : BITVECTOR(32); //symbolic  
.  
.  
mem_ptr[ptr+i] = process_data(data_field[i]);  
mem_ptr[ptr+i+1] = process_data(data_field[i+1]);  
.  
.  
//INTEGER OVERFLOW QUERY  
0 <= j <= process(len_field);  
ptr + i + j = 0?
```

- Formula captures computation
- Tester attaches formula to capture spec

How STP Works

Bird's Eye View: Translate to SAT




Why Translate to SAT?

- Both theories NP-complete
- Non SAT approaches didn't work
- Translation to SAT leverages solid engineering

How STP Works

Rich Theories cause MEM Blow-up



- Making information explicit
 - Space cost
 - Time cost

Explicit Information causes Blow-up

Array Memory Read Problem

Logic Formula derived using
symbolic execution

```
data_field, mem_ptr : ARRAY;  
len_ptr : BITVECTOR(32); //symbolic  
i, j, ptr : BITVECTOR(32); //symbolic  
.  
.  
mem_ptr[ptr+i] = process_data(data_field[i]);  
mem_ptr[ptr+i+1] = process_data(data_field[i+1]);  
.  
.  
if(ptr+i = ptr+i+1) then mem_ptr[ptr+i] = mem_ptr[ptr+i+1];  
  
//INTEGER OVERFLOW QUERY  
0 <= j <= process(len_ptr);  
ptr + i + j < ptr?
```

- Array Aliasing is implicit
- Need to make information explicit during solving
- Cannot be avoided


How STP Works

Array-read MEM Blow-up Problem

- Problem: $O(n^2)$ axioms added, n is number of read indices
- **Lethal, if n is large**, say, $n = 100,000$; # of axioms is 10 Billion

Formula Growth

Read(Mem, i_0) = $expr_0$
Read(Mem, i_1) = $expr_1$
Read(Mem, i_2) = $expr_2$
.
.
.
Read(Mem, i_n) = $expr_n$




$v_0 = expr_0$
 $v_1 = expr_1$
.
.
.
 $v_n = expr_n$

 $(i_0 = i_1) \Rightarrow (v_0 = v_1)$
 $(i_0 = i_2) \Rightarrow (v_0 = v_2)$
...
 $(i_1 = i_2) \Rightarrow (v_1 = v_2)$
...

How STP Works


The Array-read Solution

- Key Observation
 - Most indices don't alias in practice
 - Exploit locality of memory access in typical programs
 - Need only a fraction of array axioms for equivalence



STP Key Conceptual Contribution

Abstraction-refinement Principle




How STP Works

What to Abstract & How to Refine?

| Abstraction | Refinement |
|---|--|
| <ul style="list-style-type: none">1. Less essential parts2. Causes MEM blow-up | <ul style="list-style-type: none">1. Guided2. Must remember |
| Abstraction manages formula growth hardness | Refinement manages search-space hardness |


How STP Works

Abstraction-refinement for Array-reads




How STP Works

Abstraction-refinement for Array-reads




How STP Works

Abstraction-refinement for Array-reads




How STP Works

Abstraction-refinement for Array-reads




How STP Works

Abstraction-refinement for Array-reads



How STP Works

Abstraction-refinement for Array-reads



STP vs. Other Solvers

| Testcase (Formula Size) | Result | Z3 (sec) | Yices (sec) | STP (sec) |
|-------------------------|--------|-------------|----------------|--------------|
| 6l0dd9c (~15K) | SAT | TimeOut | MemOut | 37 |
| Grep65 (~60K) | UNSAT | 0.3 | TimeOut | 4 |
| Grep84 (~69K) | SAT | 176 | TimeOut | 18 |
| Grep106 (~69K) | SAT | 130 | TimeOut | 227 |
| Blaster4 (~262K) | UNSAT | MemOut | MemOut | 10 |
| Testcase20 (~1.2M) | SAT | MemOut | MemOut | 56 |
| Testcase21 (~1.2M) | SAT | MemOut | MemOut | 43 |

* All experiments on 3.2 GHz, 512 Kb cache


* MemOut: 3.2 GB (Memory used by STP much smaller), TimeOut: 1800 seconds

* Examples obtained from Dawn Song at Berkeley, David Molnar at Berkeley and Dawson Engler at Stanford

* Experiments conducted in 2007

STP vs. Other Leading Solvers

■ STP vs. Boolector & MathSAT on 615 SMTCOMP 2007 - 2010 examples



* All experiments on 2.4 GHz, 1 GB RAM

* Timeout: 500 seconds/example

Impact of STP

- **Enabled** existing SE technologies to **scale**
 - Bounded model checkers, e.g., Chang and Dill
- **Easier to engineer** SE technologies
 - Formal tools (ACL2+STP) for verifying Crypto, Smith & Dill
- **Enabled new** SE technologies
 - Concolic testing (EXE,Klee,...) by Engler et al., Binary Analysis by Song et al.

Impact of STP: Notable Projects

- Enabled Concolic Testing
- 100+ reliability and security projects

| <u>Category</u> | <u>Research Project</u> | <u>Project Leader/Institution</u> |
|--|---|--|
| Formal Methods | ACL2 Theorem Prover + STP Verification-aware Design Checker Java PathFinder Model Checker | Eric Smith & David Dill/ Stanford Jacob Chang & David Dill/ Stanford Mehlitz & Pasareanu/ NASA |
| Program Analysis | BitBlaze & WebBlaze BAP | Dawn Song et al./ Berkeley David Brumley/ CMU |
| Automatic Testing Security | Klee, EXE SmartFuzz Kudzu | Engler & Cadar/ Stanford Molnar & Wagner/ Berkeley Saxena & Song/ Berkeley |
| Hardware Bounded Model-checking (BMC) | Blue-spec BMC BMC | Katelman & Dave/ MIT Haimed/ NVIDIA |

Impact of STP

<http://www.metafuzz.com>

| <u>Program Name</u> | <u>Lines of Code</u> | <u>Number of Bugs Found</u> | <u>Team</u> |
|-----------------------------|----------------------|-----------------------------|---|
| Mplayer | ~900,000 | Hundreds | David Molnar/ Berkeley & Microsoft Research |
| Evince | ~90,000 | Hundreds | David Molnar/ Berkeley & Microsoft Research |
| Unix Utilities | 1000s | Dozens | Dawson Engler et al./ Stanford |
| Crypto Hash Implementations | 1000s | Verified | Eric Smith & David Dill/ Stanford |

Rest of the Talk

- STP Bit-vector and Array Solver

- Why Bit-vectors and Arrays?
- How does STP scale: Abstraction-refinement
- Impact: Concolic testing
- Experimental Results

- **HAMPI** String Solver

- Why Strings?
- How does HAMPI scale: Bounding
- Impact: String-based program analysis
- Experimental Results

- Future Work

- Multicore SAT
- SAT-based Languages

HAMPI String Solver



- $X = \text{concat}(\text{"SELECT.."}, v)$ AND $(X \in \text{SQL_grammar})$
- JavaScript and PHP Expressions
- Web applications, SQL queries
- NP-complete


What is the theory of Strings?

- Capture **String Expressions** in PHP, JavaScript, Perl, C/C++/Java
- Support **symbolic execution**/program analysis

| PHP/JavaScript/C++... | Theory of Strings |
|---|---|
| Var a; \$a = 'name' | Var a : l2; //String variable of bounded-size a = 'name' |
| a." is " | Concat(a, " is "); |
| substr(a, l, 3) | sub-string extraction |
| assignments/strcmp a = string_expr; | equality a = string_expr; |
| Sanity check using regular expression RE Expression in a suitable Language (e.g., SQL) | a in RE a in SQL |

Hampi Use-case

String Operations in PHP, JavaScript,...



Hampi Use-case

SQL Injection Vulnerabilities

Buggy PHP/
JavaScript




Malicious SQL Query

Unauthorized
Database Results

Backend
DataBase

Hampi Use-case

SQL Injection Vulnerabilities



Hampi Use-case

SQL Injection Vulnerabilities

Buggy Script

```
if (input in regexp("[0-9]+"))  
  query := "SELECT m FROM messages WHERE id=' " + input + " '")
```

- **input** passes validation (regular expression check)
- **query** is syntactically-valid SQL
- **query** can potentially contain an attack substring (e.g., `I' OR 'I' = 'I`)

Hampi Use-case

SQL Injection Vulnerabilities

Should be: “^[0-9]+\$”

Buggy Script

```
if (input in regexp("[0-9]+"))  
  query := "SELECT m FROM messages WHERE id=' " + input + " '")
```

- **input** passes validation (regular expression check)
- **query** is syntactically-valid SQL
- **query** can potentially contain an attack substring (e.g., `I' OR 'I' = 'I`)

Hampi Use-case

SQL Injection Vulnerabilities

Input String → `Var v : 12;`

SQL Grammar

`cfg SqlSmall := "SELECT " [a-z]+ " FROM " [a-z]+ " WHERE " Cond;`

`cfg Cond := Val "=" Val | Cond " OR " Cond;`

`cfg Val := [a-z]+ | "'" [a-z0-9]* "'" | [0-9]+;`

SQL Query

`val q := concat("SELECT msg FROM messages WHERE topicid=", v, "");`

`assert v in [0-9]+;`

“q is a valid SQL query”

`assert q in SqlSmall;`

SQLI attack conditions

`assert q contains "OR '1'='1';`

“q contains an attack vector”

Hampi finds an attack input: `v := '1' OR '1'='1'`
`SELECT msg FROM messages WHERE topicid='1' OR '1'='1'`

Hampi Key Contribution: Bounded Logics

Testing, Vulnerability Detection,...

- Finding satisfying assignment is key
- Short assignments are sufficient
- Hence, bounding strings is sufficient
- Bounded logics are easier to decide

Hampi Key Conceptual Contribution

Bounding, expressiveness and efficiency

| L_i | Complexity of $\emptyset = L_1 \cap \dots \cap L_n$ | Current Solvers |
|--------------|--|------------------------------|
| Context-free | Undecidable | n/a |
| Regular | PSPACE-complete | Quantified Boolean Logic |
| Bounded | NP-complete | SAT Efficient in practice |

How Hampi Works

Bird's Eye View: Strings into Bit-vectors

```
var v : 4;
```

```
cfg E := "()" | E E | "(" E " ";
```

```
val q := concat( "(" , v , " " );
```

```
assert q in E;
```

```
assert q contains "()()";
```

Hampi

Normalizer

STP Encoder

STP Decoder

Bit-vector
Constraints

STP

Bit-vector
Solution


String Solution
 $v = \text{)()()}$

Find a 4-char string v:

- (v) is in E
- (v) contains ()()


How Hampi Works

Unroll Bounded CFGs into Regular Exp.



How Hampi Works

Unroll Bounded CFGs into Regular Exp.



How Hampi Works

Converting Regular Exp. into Bit-vectors

Encode regular expressions recursively

- Alphabet $\{ (,) \} \rightarrow 0, 1$
- constant \rightarrow bit-vector constant
- union $+$ \rightarrow disjunction \vee
- concatenation \rightarrow conjunction \wedge
- Kleene star $*$ \rightarrow conjunction \wedge
- Membership, equality \rightarrow equality

$(\vee) \in () [() () + (())] + [() () + (())] () + ([() () + (())])$

\Downarrow \Downarrow \Downarrow
 Formula Φ_1 \vee Formula Φ_2 \vee Formula Φ_3


$B[0]=0 \wedge B[1]=1 \wedge \{ B[2]=0 \wedge B[3]=1 \wedge B[4]=0 \wedge B[5]=1 \vee \dots$

How Hampi Works

Decoder converts Bit-vectors to Strings

```
var v : 4;  
cfg E := “()” | E E | “(“ E “)”;  
val q := concat(“(“, v, “)”);  
assert q in E;  
assert q contains “()”;
```

Hampi




Find a 4-char string v:

- (v) is in E
- (v) contains ()()

HAMPI: Result I


Static SQL Injection Analysis



- 1367 string constraints from Wasserman & Su [PLDI'07]
- Hampi scales to **large grammars**
- Hampi solved 99.7% of constraints in < 1 sec
- All solvable constraints had short solutions


HAMPI: Result 2

Security Testing

- Hampi used to build Ardilla security tester [Kiezun et al., ICSE'09]
- 60 new vulnerabilities on 5 PHP applications (300+ kLOC)
 - 23 SQL injection
 - 37 cross-site scripting (XSS) ← 
- 46% of constraints solved in < 1 second per constraint
- 100% of constraints solved in < 10 seconds per constraint

HAMPI: Result 3

Comparison with Competing Tools



- [HAMPI vs. CFGAnalyzer \(U. Munich\)](#): HAMPI ~7x faster for strings of size 50+
- HAMPI vs. Rex (Microsoft Research): HAMPI ~100x faster for strings of size 100+
- HAMPI vs. DPRLE (U.Virginia): HAMPI ~1000x faster for strings of size 100+

Impact of Hampi: Notable Projects

| <u>Category</u> | <u>Research Project</u> | <u>Project Leader/Institution</u> |
|------------------|--|--|
| Static Analysis | SQL-injection vulnerabilities | Wasserman & Su/ UC, Davis |
| Security Testing | Ardilla for PHP (SQL injections, cross-site scripting) | Kiezun & Ernst/ MIT |
| Concolic Testing | Klee SAGE Kudzu NoTamper | Engler & Cadar/ Stanford Godefroid/ Microsoft Research Saxena & Song/ Berkeley Bisht & Venkatakrishnan/ U Chicago |
| New Solvers | Kaluza | Saxena & Song/ Berkeley |

Rest of the Talk

- STP Bit-vector and Array Solver

- Why Bit-vectors and Arrays?
- How does STP scale: Abstraction-refinement
- Impact: Concolic testing
- Experimental Results

- HAMPI String Solver

- Why Strings?
- How does HAMPI scale: Bounding
- Impact: String-based program analysis
- Experimental Results


- Future Work

- Multicore SAT
- SAT-based Languages

Current Parallel SAT Approaches

Won't Scale with more Nodes


- Portfolio or search-space split approach (ManySAT, pLingeling,...)
- Works ok on clusters
- Confirmed thru' experimentation:
 - 12x speedup on a 128 node cluster
 - Not close to linear speedup



PSAT: Parallel SAT Approach

Partition SAT-Input into k Pieces

- Didn't work on clusters; much better prospects with multicore
- Latency much better on multicore than cluster
- Software engineering instances partition well
- Heuristics to minimize communication overhead



Imperative Language With SAT-based Declarative Primitives

- Motivation:
 - Declarative can be more robust
 - Delegating the “how” to runtime
- Combine imperative and SAT-based declarative language
 - Efficient solvers evaluate and search
 - Solvers leverage multicores
- Examples
 - **Squander** by Milicevic, Rayside and Daniel Jackson (MIT)

Related Work

- **Model Checking:**
 - Abstraction-refinement (Ed Clarke et al.)
 - Bounding (Ed Clarke, Daniel Jackson et al.)
- **Other SMT solvers**
 - Unsat core based approximations (Randy Bryant et al.)
 - Z3, CVC3, Boolector, BAT....
- **DPLL(T)**
 - Tinelli, Nieuwenhuis and Oliviera

Conclusions

- Logic formulas can capture meta-properties of software
 - The right logical abstraction (bit-vector and arrays, strings,...)
- Exploit meta-properties in solving formulas efficiently
 - Locality, modularity,...
- The more SMT solving, the less program analysis
 - Automation, ease-of-use,...

Questions?

| <u>Contributions at a Glance</u> | <u>Future Work</u> |
|---|--|
| <ul style="list-style-type: none">• STP* & HAMPI* (CAV 2007, TISSEC 2008, ISSTA 2009)• Decidability/Undecidability results for strings (under submission)• BuzzFuzz: Directed Whitebox Fuzzing (ICSE 2009)• Concolic testers (JFuzz: NFM 2009)• Solvers for integer linear arithmetic (FMCAD 2002, TACAS 2003)• Retargetable compilers (DATE 1999) | <ul style="list-style-type: none">• Parallel SAT• SAT-based programming languages• Program hardening• Solvers for rich theories (attribute grammars, floating-point)• Auto-tuning SAT solvers• Advice-based SAT solvers• Unsound and incomplete solvers• Solver-based concurrency bug-finding |

* 100+ research projects use STP and HAMPI (NSF funding \$600,000.00)

* STP won the SMTCOMP 2006 and 2010 competitions for bit-vector solvers

* HAMPI paper won ACM Best Paper Award 2009