

# Intro to Bottom-up Parsing

## Lecture 9

# Bottom-Up Parsing

---

- Bottom-up parsing is more general than top-down parsing
  - And just as efficient
  - Builds on ideas in top-down parsing
- Bottom-up is the preferred method
- Concepts today, algorithms next time

# An Introductory Example

---

- Bottom-up parsers don't need left-factored grammars
- Revert to the “natural” grammar for our example:

$$E \rightarrow T + E \mid T$$

$$T \rightarrow \text{int} * T \mid \text{int} \mid (E)$$

- Consider the string:  $\text{int} * \text{int} + \text{int}$

# The Idea

---

Bottom-up parsing *reduces* a string to the start symbol by inverting productions:

int \* int + int

$T \rightarrow \text{int}$

int \* T + int

$T \rightarrow \text{int} * T$

T + int

$T \rightarrow \text{int}$

T + T

$E \rightarrow T$

T + E

$E \rightarrow T + E$

E

# Observation

---

- Read the productions in reverse (from bottom to top)
- This is a rightmost derivation!

int \* int + int

$T \rightarrow \text{int}$

int \* T + int

$T \rightarrow \text{int} * T$

T + int

$T \rightarrow \text{int}$

T + T

$E \rightarrow T$

T + E

$E \rightarrow T + E$

E

# Important Fact #1

---

Important Fact #1 about bottom-up parsing:

*A bottom-up parser traces a rightmost derivation in reverse*

# A Bottom-up Parse

---

int \* int + int


int \* T + int

T + int

T + T

T + E

E



# A Bottom-up Parse in Detail (1)

---

int \* int + int

int \* int + int



# A Bottom-up Parse in Detail (2)

---

int \* int + int

int \* T + int

int \* int + int

T

|


# A Bottom-up Parse in Detail (3)

---

int \* int + int

int \* T + int

T + int



# A Bottom-up Parse in Detail (4)


---

int \* int + int

int \* T + int

T + int

T + T



# A Bottom-up Parse in Detail (5)

---


int \* int + int

int \* T + int

T + int

T + T

T + E



# A Bottom-up Parse in Detail (6)

---

int \* int + int


int \* T + int

T + int

T + T

T + E

E



# A Trivial Bottom-Up Parsing Algorithm

---

Let  $I$  = input string

repeat

    pick a non-empty substring  $\beta$  of  $I$

        where  $X \rightarrow \beta$  is a production

    if no such  $\beta$ , backtrack

    replace one  $\beta$  by  $X$  in  $I$

until  $I = "S"$  (the start symbol) or all possibilities are exhausted

# Questions

---

- Does this algorithm terminate?
- How fast is the algorithm?
- Does the algorithm handle all cases?
- How do we choose the substring to reduce at each step?

# Where Do Reductions Happen?

---

Important Fact #1 has an interesting consequence:

- Let  $\alpha\beta\omega$  be a step of a bottom-up parse
- Assume the next reduction is by  $X \rightarrow \beta$
- Then  $\omega$  is a string of terminals

Why? Because  $\alpha X \omega \rightarrow \alpha\beta\omega$  is a step in a right-most derivation



# Notation

---

- Idea: Split string into two substrings
  - Right substring is as yet unexamined by parsing (a string of terminals)
  - Left substring has terminals and non-terminals
- The dividing point is marked by a |
  - The | is not part of the string
- Initially, all input is unexamined |  $x_1 x_2 \dots x_n$

# Shift-Reduce Parsing

---

Bottom-up parsing uses only two kinds of actions:

*Shift*

*Reduce*

# Shift

---

- *Shift*: Move | one place to the right
  - Shifts a terminal to the left string

$ABC|xyz \Rightarrow ABCx|yz$

# Reduce

---

- Apply an inverse production at the right end of the left string
  - If  $A \rightarrow xy$  is a production, then

$$Cbxy|ijk \Rightarrow CbA|ijk$$

# The Example with Reductions Only

---

int \* int | + int

int \* T | + int

reduce  $T \rightarrow \text{int}$

reduce  $T \rightarrow \text{int} * T$

T + int |

T + T |

T + E |

E |

reduce  $T \rightarrow \text{int}$

reduce  $E \rightarrow T$

reduce  $E \rightarrow T + E$

# The Example with Shift-Reduce Parsing

---

int * int + int	shift
int   * int + int	shift
int *   int + int	shift
int * int   + int	reduce $T \rightarrow \text{int}$
int * T   + int	reduce $T \rightarrow \text{int} * T$
T   + int	shift
T +   int	shift
T + int	reduce $T \rightarrow \text{int}$
T + T	reduce $E \rightarrow T$
T + E	reduce $E \rightarrow T + E$
E	

# A Shift-Reduce Parse in Detail (1)

---

| int \* int + int

int \* int + int  
↑

# A Shift-Reduce Parse in Detail (2)

---

| int \* int + int

int | \* int + int

int \* int + int

↑



# A Shift-Reduce Parse in Detail (3)

---

| int \* int + int

int | \* int + int

int \* | int + int

int \* int + int

↑

# A Shift-Reduce Parse in Detail (4)

---

| int \* int + int

int | \* int + int

int \* | int + int

int \* int | + int

int \* int + int

↑

# A Shift-Reduce Parse in Detail (5)

---


| int \* int + int

int | \* int + int

int \* | int + int

int \* int | + int

int \* T | + int



# A Shift-Reduce Parse in Detail (6)

---

| int \* int + int


int | \* int + int

int \* | int + int

int \* int | + int

int \* T | + int

T | + int



# A Shift-Reduce Parse in Detail (7)

---

| int \* int + int

int | \* int + int


int \* | int + int

int \* int | + int

int \* T | + int

T | + int

T + | int



# A Shift-Reduce Parse in Detail (8)

---

| int \* int + int

int | \* int + int

int \* | int + int


int \* int | + int

int \* T | + int

T | + int

T + | int

T + int |



# A Shift-Reduce Parse in Detail (9)

---

| int \* int + int

int | \* int + int

int \* | int + int

int \* int | + int


int \* T | + int

T | + int

T + | int

T + int |

T + T |



# A Shift-Reduce Parse in Detail (10)

| int \* int + int

int | \* int + int

int \* | int + int

int \* int | + int

int \* T | + int


T | + int

T + | int

T + int |

T + T |

T + E |





# A Shift-Reduce Parse in Detail (11)

| int \* int + int

int | \* int + int

int \* | int + int

int \* int | + int

int \* T | + int

T | + int


T + | int

T + int |

T + T |

T + E |

E |



# The Stack

---

- Left string can be implemented by a stack
  - Top of the stack is the |
- Shift pushes a terminal on the stack
- Reduce pops 0 or more symbols off of the stack (production rhs) and pushes a non-terminal on the stack (production lhs)

# Conflicts

---

- In a given state, more than one action (shift or reduce) may lead to a valid parse
- If it is legal to shift or reduce, there is a *shift-reduce* conflict
- If it is legal to reduce by two different productions, there is a *reduce-reduce* conflict