

React Yaml – windows

Starter pipeline

Start with a minimal pipeline that you can customize to build and deploy your code.

Add steps that build, run tests, deploy, and more:

<https://aka.ms/yaml>

trigger:

- main

pool:

vmImage: windows-latest

steps:

- task: Npm@1

inputs:

command: 'install'

- task: Npm@1

inputs:

command: 'custom'

customCommand: 'run build'

- task: PublishBuildArtifacts@1

inputs:

PathtoPublish: 'build'

ArtifactName: 'drop'

publishLocation: 'Container'

- task: AzureRmWebAppDeployment@5

inputs:

ConnectionType: 'AzureRM'

azureSubscription: 'Permanent Connection'

appType: 'webApp'

WebAppName: 'reactwindowsyaml'

packageForLinux: 'build'

React Yaml – Linux

Startup Command - pm2 serve /home/site/wwwroot --no-daemon --spa

1. pm2

PM2 is a Node.js process manager.

Azure Linux App Service uses it to keep applications running continuously.

Think of it like:

- start app
 - monitor app
 - restart if crashed
-

2. serve

This tells PM2:

👉 “Serve static files like a web server”

Your React build contains only:

- HTML
- CSS
- JS

So PM2 acts like a lightweight web server.

3. /home/site/wwwroot

This is the folder where Azure deploys your application files.

In your case:

index.html
static/
asset-manifest.json

are stored here.

So this part means:

👉 "Serve files from this folder"

4. --no-daemon

Normally PM2 runs in background.

Azure App Service does NOT allow background-only processes.

So:

--no-daemon

means:

👉 "Keep process attached to Azure runtime"

Without this:

❌ App may stop immediately.

5. --spa

SPA = Single Page Application

React applications use client-side routing.

Example:

/home
/about
/profile

These routes do not physically exist as files.

So --spa tells PM2:

👉 “Always return index.html for unknown routes”

Without this:

Refreshing a React route gives:

404 Not Found

Actual Yaml

Starter pipeline

Start with a minimal pipeline that you can customize to build and deploy your code.

Add steps that build, run tests, deploy, and more:

<https://aka.ms/yaml>

trigger:

- main

pool:

vmImage: ubuntu-latest

steps:

- task: Npm@1

inputs:

command: 'install'

- task: Npm@1

inputs:

command: 'custom'

customCommand: 'run build'

- task: ArchiveFiles@2

inputs:

rootFolderOrFile: 'build'

includeRootFolder: false

archiveType: 'zip'

archiveFile: '\$(Build.ArtifactStagingDirectory)/\$(Build.BuildId).zip'

replaceExistingArchive: true

- task: AzureRmWebAppDeployment@5

inputs:

ConnectionType: 'AzureRM'

azureSubscription: 'Permanent Connection'

appType: 'webAppLinux'

WebAppName: 'reactyaml'

packageForLinux: '\$(Build.ArtifactStagingDirectory)/\$(Build.BuildId).zip'

DeploymentTypeLinux: 'oneDeploy'

Roll Back

trigger:

- main

pool:

vmImage: ubuntu-latest

variables:

artifactName: 'react-build'

zipFileName: '\$(Build.BuildId).zip'

stages:

=====

BUILD STAGE

=====

- stage: Build

displayName: Build React Application

jobs:

- job: BuildJob

displayName: Install and Build React App

steps:

Install Node Modules

- task: Npm@1

displayName: Install Dependencies

inputs:

command: 'install'

Build React App

- task: Npm@1

displayName: Build React App

inputs:

command: 'custom'

customCommand: 'run build'

Archive Build Folder

- task: ArchiveFiles@2

displayName: Archive Build Folder

inputs:

rootFolderOrFile: 'build'

includeRootFolder: false

archiveType: 'zip'

archiveFile: '\$(Build.ArtifactStagingDirectory)/\$(zipFileName)'

replaceExistingArchive: true

Publish Artifact

- task: PublishBuildArtifacts@1

displayName: Publish Build Artifact

inputs:

PathtoPublish: '\$(Build.ArtifactStagingDirectory)/\$(zipFileName)'

ArtifactName: '\$(artifactName)'

publishLocation: 'Container'

=====

DEPLOY CURRENT BUILD

=====

- stage: Deploy

displayName: Deploy Latest Build

dependsOn: Build

jobs:

- deployment: DeployToLinuxWebApp

displayName: Deploy to Azure Linux Web App

environment: DEV

strategy:

runOnce:

deploy:

steps:

Download Current Artifact

- task: DownloadBuildArtifacts@1

displayName: Download Current Build Artifact

inputs:

buildType: 'current'

downloadType: 'single'

artifactName: '\$(artifactName)'

downloadPath: '\$(System.ArtifactsDirectory)'

Deploy Current Build

- task: AzureRmWebAppDeployment@5

displayName: Deploy Current Build

inputs:

ConnectionType: 'AzureRM'

azureSubscription: 'Permanent Connection'

appType: 'webAppLinux'

WebAppName: 'reactyaml'

packageForLinux: '\$(System.ArtifactsDirectory)/\$(artifactName)/\$(zipFileName)'

DeploymentTypeLinux: 'oneDeploy'

=====

MANUAL ROLLBACK STAGE

=====

- stage: Rollback

displayName: Rollback Deployment

dependsOn: []

condition: true

jobs:

- job: RollbackJob

displayName: Rollback to Specific Build

steps:

Download Specific Old Build Artifact

- task: DownloadBuildArtifacts@1

displayName: Download Old Build Artifact

inputs:

buildType: 'specific'

project: '\$(System.TeamProject)'

pipeline: '691' # Pipeline ID

buildVersionToDownload: 'specific'

buildId: '2168' # BUILD ID

downloadType: 'single'

artifactName: '\$(artifactName)'

downloadPath: '\$(System.ArtifactsDirectory)'

Deploy Old Build

- task: AzureRmWebAppDeployment@5

displayName: Deploy Old Build

inputs:

ConnectionType: 'AzureRM'

azureSubscription: 'Permanent Connection'

appType: 'webAppLinux'

WebAppName: 'reactyaml'

packageForLinux: '\$(System.ArtifactsDirectory)/\$(artifactName)/2168.zip'

DeploymentTypeLinux: 'oneDeploy'

Condition for Deploy failed

dependsOn: Deploy

condition: failed('Deploy')