

```
def suma_matrices_3x2(matriz1, matriz2):  
    return [[matriz1[i][j] + matriz2[i][j] for j in range(2)] for i in range(3)]  
  
# Ejemplo  
A = [[5, 2], [4, 1], [-1, 0]]  
B = [[-3, 7], [-4, 8], [6, 0]]  
print(suma_matrices_3x2(A, B))
```

```
[[2, 9], [0, 9], [5, 0]]
```

```
A = [3, 4, 5, 1, 6, 7, 2]  
  
print (A)
```

```
[3, 4, 5, 1, 6, 7, 2]
```

```
for i in A:  
    print (i)
```

```
3  
4  
5  
1  
6  
7  
2
```

```
for i in range(len(A)+1):  
    print (i)
```

```
0  
1  
2  
3  
4  
5  
6  
7
```

```
for i in range(len(A)):  
    print (A[i])
```

```
3  
4  
5  
1  
6  
7  
2
```

```
print (A[0])
```

```
3
```

```
import numpy as np  
B=np.matrix([[2, 4], [1, 3]])  
print(B)
```

```
[[2, 4], [1, 3]]
```

```
C=np.matrix([[1,3,2,5,-1], [7,0,2,8,3], [4,-2,0,1,3], [3,6,1,8,5]])  
print(C)
```

```
[[1, 3, 2, 5, -1], [7, 0, 2, 8, 3], [4, -2, 0, 1, 3], [3, 6, 1, 8, 5]]
```

```
import random  
random.randint(1, 10)
```

```
7
```

```
S=0  
for i in range (1, 11):  
    S = 1+S
```

```
print(S)
```

```
10
```

```
S = []  
for i in range(1,11):  
    S.append(i)  
print(S)
```

```
[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
```

```
def suma_matrices (A,B,n,m):  
    for i in range(n):  
        print (i)  
    return i  
  
suma_matrices ([1,2],[3,1],1,2)
```

```
0  
0
```

```
#Tarea:función para sumar matrices usando dos ciclos en código python
```

```
def sumar_matrices(A, B):  
    matriz_resultado = []  
    for i in range(len(A)):  
        fila_nueva = []  
        for j in range(len(A[0])):  
            suma = A[i][j] + B[i][j]  
            fila_nueva.append(suma)  
        matriz_resultado.append(fila_nueva)  
    return matriz_resultado  
  
matriz1 = [[7, 4, -5],[3, 1, 0]]  
  
matriz2 = [[2, 1, 9],[-4, 1, 8]]  
  
resultado = sumar_matrices(matriz1, matriz2)  
  
for fila in resultado:  
    print(fila)
```

```
[9, 5, 4]  
[-1, 2, 8]
```