

HW6 Solution

6.5.1

(a)

```
INSERT
INTO    Product VALUES
      (
          'C'      ,
          '1100'   ,
          'pc'
      ) ;

INSERT
INTO    PC VALUES
      (
          '1100'   ,
          3.2      ,
          1024,180,2499
      ) ;
```

(b)

```
INSERT
INTO    Product
SELECT  make      ,
        model+1100,
        'laptop'
FROM    Product
WHERE   type = 'pc' ;

INSERT
INTO    Laptop
SELECT  model+1100,
        speed     ,
        ram       ,
        hd        ,
        17        ,
        price+500
FROM    PC ;
```

Or if model is character data type

```
INSERT
INTO      Product
SELECT    make
          ,
          CHAR(INT(model)+1100) ,
          'laptop'
FROM      Product
WHERE     type = 'pc' ;

INSERT
INTO      Laptop
SELECT    CHAR(INT(model)+1100) ,
          speed
          ,
          ram
          ,
          hd
          ,
          17
          ,
          price+500
FROM      PC ;
```

```
(c)
DELETE
FROM      PC
WHERE     hd < 100 ;
```

(d)

```
DELETE
FROM   Laptop L
WHERE  L.model IN
      (SELECT R2.model
FROM    Product R2
WHERE   R2.maker IN
      (SELECT DISTINCT R.maker
FROM    Product R
WHERE   R.maker NOT IN
      (SELECT R2.maker
FROM    Product R2
WHERE   R2.type = 'printer'
      )
      )
      )
      ) ;

DELETE
FROM   PRODUCT R3
WHERE  R3.model IN
      (SELECT R2.model
FROM    Product R2
WHERE   R2.maker IN
      (SELECT DISTINCT R.maker
FROM    Product R
WHERE   R.maker NOT IN
      (SELECT R2.maker
FROM    Product R2
WHERE   R2.type = 'printer'
      )
      )
      )
      )
      AND R3.type = 'laptop';
```

(e)

```
UPDATE Product
SET      maker = 'A'
WHERE    maker = 'B' ;
```

(f)

```
UPDATE PC
SET      ram = ram*2,
         hd  =hd  +60 ;
```

(g)

```
UPDATE Laptop L
SET      L.screen = L.screen+1,
         L.price  =L.price  -100
WHERE    L.model      IN
         (SELECT R.model
          FROM      Product R
          WHERE     R.maker = 'B'
         ) ;
```