



[HOME \(HTTPS://WWW.ILSCO.COM/ILSCO/CCRZ_HOMEPage?CCLCL=EN_US\)](https://www.ilSCO.com/ILSCO/CCRZ_HOMEPage?CCLCL=EN_US) / [MECHANICAL \(/ILSCO/CCRZ_PRODUCTLIST?CATEG](#)
/ [POWER DISTRIBUTION BLOCKS \(/ILSCO/CCRZ_PRODUCTLIST?CATEGORYID=A0KF400000G17HGEAR&CCLCL=EN_US\)](#) / **PDC-**



PDC-14-2/0-1

Power Distribution Block, Modular Design, Dual Rated, Line C
Load Range 4-14, 1 Port Per Pole Line Side, 4 Ports Per Pole L

Qty

[Specs](#)

[Documents](#)

Dimensions

Drive Size Main	3/16
Drive Size Tap	NA
Drive Type Main	Internal Hex
Drive Type Tap	Slotted
Height (IN)	1.94
Height BX (IN)	2.75
Height (mm)	49.276
Length (IN)	2.875
Mounting Hole Diameter (IN)	0.201
Mounting Hole Diameter (mm)	5.1054
Mounting Hole Spacing (IN)	2.25
Mounting Hole Spacing (mm)	57.15
Weight (LB)	0.161
Weight BX (LB)	2.2074
Width (IN)	1.029
Width BX (IN)	5
Width (mm)	26.1366

Additional Class Attributes

Block Size	NA
Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	5
Number of Poles	1
Number of Ports Per Pole Primary	1
Number of Ports Per Pole Secondary	4

Material and Finish

Conductor Material	Aluminum
Conductor Material	Copper

Connector Finish	Tin
Enclosure Material	Lexan
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel
Bolt and Screw Sizes	
Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16
Wire Binding Screw Size	10
Wire Binding Screw Size	1/4
Color	
Color	Black
Additional Technical Specifications	
Amperage Rating Per Pole	175 Amps
Conductor Type	Solid
Conductor Type	Stranded
Conductor Ranges	
Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	4 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	2/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	4 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

Voltage

Voltage Rating 600 V

Environment and Temperature

Flammability Rating NA

Temperature Rating 90°C

Testing Standards

CSA File Number LR-29601

CSA Standard C22.2 No. 65-03

Prop65 Compliance WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov

RUS Listed No

UL Control Number NA

UL / CULUS Specification UL 1059 Recognized

UL File Number E84782

General

Bag Quantity 1

Carton Quantity Description STD PACK QTY 12

Dual Rated Yes

NEMA Code S-588-4

UPC Code 78366971128

ABOUT

[Our Company](#)

RESOURCES

[Catalog Download](#)

SUPPORT

[Contact Us](#)

https://www.ilsco.com/ilsco/ccrz_CCPage?pageKey=ad&id=ioc	https://www.delzer.com/ecm/ilsco-catalog	https://www.ilsco.com
Careers	Online Education	pageKey=ICU
	https://go.bluevolt.com/ILSCO/s/	Sales Locator
https://workforcenow.adp.com/mascsr/default/mdf/recruitment/recruitment.html?cid=d8ce884c-b5d6-44ff-916f-449ae9b82e3c&cclId=19000101_000001&source=CC2&pageKey=US&portalUser=&store=&cclId=en_US&selectedProductKey=19000101_000001	Cross Reference	https://www.ilsco.com
News https://www.ilsco.com/ilsco/ccrz_CCPage?pageKey=news	Project Submittal	pageKey=SRL
Copyright © ILSCO Corporation 2020 All Rights Reserved	https://www.ilsco.com/ilsco/ccrz_CCPage?pageKey=PS	Manual Registration
	Technical Documents	Emergency Shipments
United Healthcare creates and publishes the Machine-Readable Files on behalf of ECM Industries. To link to the Machine-Readable Files, please click HERE https://www.ilsco.com/ilsco/ccrz_CCPage?pageKey=ad&id=ies		

