

Δ

Table 11

Conditions of use, voltage, and temperature ratings of flexible cords, heater cords, tinsel cords, equipment wires, Christmas-tree cords, portable power cables, elevator cables, stage lighting, electric vehicle supply equipment cables, and festoon cables
(See Rules 12-010, 12-402, 12-406, and 12-122.)

Location	Use	Kind	CSA type designation	Voltage rating, V	Temperature rating, °C	Reference Notes
Dry locations only	Not for hard usage	Heat-resistant equipment wire	GTF	600	125	4
		Equipment wire	TXF, TXF-S	125	60	15
		Indoor Christmas-tree cord	PXT	125	60	—
			DPT	300	105	—
Damp (or dry) locations	Not for hard usage	Flexible cord	SV	300	60, 75, 90	16
			SVO, SVOO	300	60, 75, 90	3
			SVT	300	60, 75, 90, 105	16
			SVTO, SVTOO	300	60, 75, 90, 105	3
			SPT-1, NISPT-1	300	60, 75, 90, 105	7, 16
			SPT-2, NISPT-2	300	60, 75, 90, 105	16
			SPT-3	300	105	16
			SVE, SVEO, SVEOO, SPE-1, SPE-2, SPE-3, NISPE-1, NISPE-2	300	90, 105	3
		Heater cord	HPN	300	90, 105	3
	Not for hard usage	Tinsel cord	TPT	300	60	—
			TST	300	60	—
		Equipment wire	TEW	600	105	1, 3, 4, 11
			SIS	600	90	4, 11
			REW	300	105	1, 3, 6, 11
			REW	600	105	1, 3, 4, 6, 11
			SEWF-1	300	150	1, 5, 11
			SEW-1	300	200	1, 5, 11
			SEWF-2	600	150	4, 5, 11
			SEW-2	600	200	4, 5, 11
			TEWN	600	105	1, 3, 11
	For hard usage	Flexible cord	SJ	300	60, 75, 90, 105	10
			SJO, SJOO	300	60, 75, 90, 105	3, 10
			SJT	300	60, 75, 90, 105	10
			SJTO, SJTOO	300	60, 75, 90, 105	3, 10
			SJE, SJEO, SJEOO	300	90, 105	3, 10

(Continued)

Table 11 (Continued)

Location	Use	Kind	CSA type designation	Voltage rating, V	Temperature rating, °C	Reference Notes
	For hard usage	Heater cord	HSJ, HSJO, HSJOO	300	90, 105	3, 8, 9, 10
	For extra-hard usage	Flexible cord	S	600	60, 75, 90, 105	10
			SO, SOO	600	60, 75, 90, 105	3, 10
			ST	600	60, 75, 90, 105	10
			STO, STOO	600	60, 75, 90, 105	3, 10
			SE, SEO, SEOO	600	90, 105	3, 10
		Dryer and range cable	DRT	300	60	2
	Elevator travelling cable		E	300	60	11
			E	600	60	11
			ETT, ETP	300	60	11
			ETT, ETP	600	60	11
			EO	300	60	3, 11
			EO	600	60	3, 11
Wet (or damp or dry) locations	Not for hard usage	Outdoor Christmas-tree cord	CXWT	300	60	—
			CXWT	600	60	—
			PXWT	300	60	—
			SPT-1W	300	105	7
			SPT-2W	300	105	—
		Outdoor equipment wire	TXFW, TXFW-S	300	60	—
		Heater cord	HPNW, HSJW	300	90, 105	—
	For hard usage	Outdoor flexible cord	SJOW, SJOOW	300	60, 75, 90, 105	3
			SJTW	300	60, 75, 90, 105	—
			SJTOW, SJTOOW	300	60, 75, 90, 105	3
			SJEW, SJEOW, SJEOOW	300	90, 105	3
		Electric vehicle supply equipment cable	EVJ, EVJT	300	60, 75, 90, 105	3, 10
			EVJE	300	90, 105	3, 10
	For extra-hard usage	Outdoor flexible cord	SOOW	600	60, 75, 90, 105	3
			SOW	600	60, 75, 90, 105	3
			STW	600	60, 75, 90, 105	—
			STOW, STOOW	600	60, 75, 90, 105	—
		Electric vehicle supply equipment cable	EV, EVT	600	60, 75, 90, 105	3, 10
			EVE	600	90, 105	3, 10
			EVK, EVKT	1000	60, 75, 90, 105	3, 10
			EVKE	1000	90, 105	3, 10

(Continued)

Table 11 (Continued)

Location	Use	Kind	CSA type designation	Voltage rating, V	Temperature rating, °C	Reference Notes
		Portable power cables	W	2000	90	12, 13
			G	2000	90	12, 13
			G-GC	2000	90	12
			G-BGC	2000	90	12
			SHC-GC	2000	90	12
			SH, SHD, SHD-GC, SHD-BGC	2000, 5000, 8000, 15 000, 25 000, or 35 000	90	12
			DLO	2000	90	—
	For hard usage	Stage lighting	PPC	600	60, 75, 90, 105	13
		Festoon	Festoon	600	60, 105	14
			Festoon-outdoors	600	60, 105	14

Notes:

- 1) Types REW, SEW, SEWF, TEW, and TEWN shall be permitted in raceways for Class 1 circuits in accordance with Rule 16-112 2).
- 2) Dryer and range cables are for use in household dryer and range power supply cords only. These cables are not for sale to the public for general use.
- 3) When exposed to oil, the following are limited to 60 °C, regardless of the temperature rating of the product:
 - a) the temperature rating of the jacket of Types SVO, SVEO, SVTO, HSJO, EO, SJO, SJEO, SJTO, STO, SO, SEO, SEOW, SOW, SJOW, SJTOW, EV, EVE, EVJ, EVJE, EVJT, EVK, EVKT, EVKE and EVT;
 - b) the insulation and jacket of Types SVOO, SVEOO, SVTOO, SJOO, SJEOO, SJTOO, STOO, SOO, SEOO, SOOW, SEOW, SJOOW, SJEOOW, SJEOW, and SJTOOW; and
 - c) the insulation of Type HPN and HPNW heater cord and TEWN, REW, and TEW equipment wire.
- 4) Types GTF, REW, TEW, TBS, SIS, SEWF-2, and SEW-2 may be used in raceways in accordance with Rule 30-310 2) c) ii).
- 5) Types SEWF-1 and SEWF-2 with an insulated nickel or nickel-coated copper conductor have a temperature rating of 200 °C. Types SEW-1, SEWF-1, SEW-2, and SEWF-2 with an insulated nickel or nickel-coated copper conductor may also have a temperature rating of 250 °C.
- 6) Types having cross-linked PVC insulation are surface marked with the type designation followed by (XLPVC) and types having cross-linked chlorinated polyethylene are surface marked with the type designation followed by (XLCPE).
- 7) Type SPT-1 and SPT-1W No. 20 AWG are for electric clock and decorative lighting use.
- 8) When Type HSJO heater cord is provided with 90 °C polychloroprene insulation (no asbestos insulation), the type designation "HSJO" is surface printed on the cord.
- 9) When Type HSJO heater cord is provided with 90 °C ethylene propylene rubber insulation (no asbestos insulation), the type designation "HSJO" is surface printed on the cord.
- 10) Types HSJO, SJ, SJO, SJOO, SJEO, SJEOW, SJEOO, SJT, SJTO, SJTOO, S, SO, SOO, ST, STO, STOO, EV, EVE, EVJ, EVJE, EVJT, EVK, EVKT, EVKE, and EVT flexible cords are now recognized only as components of equipment.
- 11) Suitable for use in accordance with Rule 38-011 2) when flame-retardant and moisture-resistant.
- 12) Natural rubber jackets are not suitable for use in oily environments.

(Continued)

Table 11 (Concluded)

- 13) *Type PPC is single-conductor cable intended for use in temporary installations, such as portable stage lighting and outdoor functions. If multi-conductor cable is needed for the same applications, Type W or G shall be permitted to be used if ampacities are higher than those for flexible cords specified in Section 44.*
- 14) *Festoon cable has a flat configuration incorporating insulated power and/or control conductors and is supported by a messenger. It supplies power and control wiring for cranes and hoists, indoors or outdoors. See Rule 40-004.*
- 15) *Type TXF is also suitable for indoor Christmas-tree cord.*
- 16) *The type designation may be followed by a “-B” suffix when a decorative braid is applied over the cord.*

△

Allowable ampacity																
Flexible cord					Equipment wire											
Tinsel cord	Christmas-tree cord		Elevator cable	Types NISPT-1, NISPT-2, SV\$, SVO\$, SVEO\$, SVOO\$, SVEOO\$, SJ\$, SJE\$, SJEW\$, SJO\$, SJEQ\$, SJOO\$, SJEEO\$, SJOW\$, SJEOW\$, SJOOW\$, SJEOW\$, SE\$, SEW\$, SO\$, SEO\$, SEOW\$, SOO\$, SEOO\$, SEOW\$, SOW, SOOW, SPT-1, SPT-2, SPT-3, SVT\$, SVTO\$, SVTOO\$, SJT\$, SJTO\$, SJTOO\$, ST\$, STO\$, STOO\$, SJTW\$, SJTOW\$, SJTOOW\$, STW, STOW, STOOW		Types HSI\$, HSIW\$, HSIJ\$, HSIJW\$, HSIJO\$, HSIJOO, HPN\$, HPNW**		Electric vehicle supply equipment cable types EV††, EVE††, EVJ††, EVJE††, EVT††, EVJT††, EVK††, EVKT††, EVKE††		2 current-carrying conductors	3 current-carrying conductors	Type TXF, TXF-S	Type DRT	Type TXFW, TXFW-S	Types GTF*, TEW*, SEW*, SEW*, TEWN*, SEWF*, TBS*, SIS*	
	Types TPT, TST	Types S, SPT-1W, SPT-2W, DPTW		Types PXT, TXF, TXF-S, DPT	2 current-carrying conductors	3 current-carrying conductors*	Types E, EO, ETT, ETP									
27	0.5	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
26	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	1
24	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	2
22	1.8†	—	—	—	—	—	—	—	—	—	—	—	—	1.8†	—	3
20	3.6†	—	—	—	—	2‡	—	—	—	—	—	2	—	3.6†	—	4
18	—	7	—	5	10	7	10	10	10	7	—	—	—	5	—	6
17	—	—	—	—	12	9	13	13	12	9	—	—	—	—	—	—
16	—	10	—	7	13	10	15	15	13	10	—	—	—	7	—	8
15	—	—	—	—	16	12	17	17	16	12	—	—	—	—	—	—
14	—	15	—	15	18	15	20	20	18	15	—	—	—	—	—	17
3	—	—	—	—	21	17	—	—	21	17	—	—	—	—	—	—

(Continued)

Table 12 (Continued)

Allowable ampacity													
Flexible cord					Equipment wire								
Types TPT, TST	Tinsel cord	Christmas-tree cord		Elevator cable	Types NISPT-1, NISPT-2, SV\$, SVO\$, SVEO\$, SVOO\$, SVEOO\$, SJ\$, SJE\$, SJEW\$, SJO\$, SJEQ\$, SJOO\$, SJEQO\$, SJOW\$, SJEOW\$, SJOOW\$, SJEOW\$, S\$, SE\$, SEW\$, SO\$, SEO\$, SEOW\$, SOO\$, SEOO\$, SEOW\$, SOW, SOOW, SPT-1, SPT-2, SPT-3, SVT\$, SVTO\$, SVTOO\$, SJT\$, SJTO\$, SJTOO\$, ST\$, STO\$, STOO\$, SJTW\$, SJTOW\$, SJTOOW\$, STW, STOW, STOOW	Types HSJ\$, HSJW\$, HSJO\$, HSJO\$, HPN\$, HPNW\$	Electric vehicle supply equipment cable types EV\$, EVE\$, EV\$, EVJ\$, EVJ\$, EVT\$, EVT\$, EVK\$, EVKT\$, EVKE\$		Type TXF, TXF-S	Type DRT	Type TXFW, TXFW- S	Types GTF*, TEW*, REW*, TEWN*, SEWF*, TBS*, SIS*	
		Types CXWT, PXWT, TXFW, TXFW- S, SPT- 1W, SPT- 2W, DPTW	Types PXT, TXF, TXF-S, DPT				2 current- carrying conductors	3 current- carrying conductors*					2 current- carrying conductors
12	—	20	—	20	25	20	25	20	—	—	—	—	23
11	—	—	—	—	27	23	—	23	—	—	—	—	—
10	—	—	—	25	30	25	—	30	—	30	—	—	28
9	—	—	—	—	34	29	—	34	—	—	—	—	—
8	—	—	—	35	40	35	—	40	—	40	—	—	40
6	—	—	—	45	55	45	—	55	—	50	—	—	55
4	—	—	—	60	70	60	—	70	—	60	—	—	70
3	—	—	—	—	—	—	—	—	—	—	—	—	80
2	—	—	—	80	95	80	—	95	—	—	—	—	95
1	—	—	—	—	—	—	—	150	—	—	—	—	110
1/0	—	—	—	—	—	—	—	173	—	—	—	—	125
2/0	—	—	—	—	—	—	—	199	—	—	—	—	145
3/0	—	—	—	—	—	—	—	230	—	—	—	—	165
4/0	—	—	—	—	—	—	—	265	—	—	—	—	195
250	—	—	—	—	—	—	—	296	—	—	—	—	—

Continued

Table 12 (Concluded)