
R85/D_candidate_subset | TSP | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

LIB: data/TSPLIB | native/FP64 ind



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | CVRP | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

LIB: data/CVRPLIB | native/FP64 ind



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | ATSP | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRP | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | VRPB | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | VRPL | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | VRPTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRPTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRPB | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRPL | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | VRPBL | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | VRPBTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | VRPLTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRPBL | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRPBTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRPLTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | VRPBLTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.

R85/D_candidate_subset | OVRPBLTW | 方法分布

同一锁定模型: epoch 35 / update 50400 / SHA256 1d0e509c8e06b895

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。

R85/D_candidate_subset: stable global solver-ID score ties. Same R85 lock; LIB inference only; no training/reselection/Rxx mixing.