

R107/A_edge_factorized | TSP | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

LIB: data/TSPLIB | native/FP64 ind





标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.


R107/A_edge_factorized | CVRP | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

LIB: data/CVRPLIB | native/FP64 ind





标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | ATSP | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRP | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | VRPB | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | VRPL | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | VRPTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRPTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRPB | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRPL | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | VRPBL | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | VRPBTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | VRPLTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRPBL | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRPBTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRPLTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | VRPBLTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/A_edge_factorized | OVRPBLTW | 方法分布

同一锁定模型: epoch 26 / update 37440 / SHA256 074788d55df5074e

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。

R107/A_edge_factorized: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.