
R107/B_connected_paths | TSP | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

LIB: data/TSPLIB | native/FP64 ind



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | CVRP | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

LIB: data/CVRPLIB | native/FP64 ind



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | ATSP | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRP | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | VRPB | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | VRPL | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | VRPTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRPTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRPB | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRPL | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | VRPBL | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | VRPBTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | VRPLTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRPBL | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRPBTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRPLTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | VRPBLTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。


R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.

R107/B_connected_paths | OVRPBLTW | 方法分布

同一锁定模型: epoch 27 / update 38880 / SHA256 81c17fe9b2d355e9

新 TEST 数据版本: selection_data_new90k_B_filtered_single_reld_mt_seed2_20261018

标签: 原生 native/FP64 ind; 仅读锁定预测



标注: % (次数); 候选按 TEST 名称对齐，包含零次数候选。

模型Top1 = 100 * mean(pred == saved native winner); 不是最大选择频率。

R107/B_connected_paths: stable global solver-ID score ties. Same R107 lock; LIB inference only; no training/reselection/Rxx mixing.