

# Biosensors


## Lecture 24


# Sensor

- A sensor is a device that measures a physical quantity and converts it into a signal which can be read by an observer or by an instrument.

# Biosensor

- A biosensor is an analytical device, used for the detection of an analyte, that combines a biological component with a physicochemical detector.






Structure of a biosensor, illustrating its two main components: a sensor and a transducer.

# History


## FATHER OF BIOSENSORS

Professor Leland C Clark (1918–2005)





The first and the most widely used commercial biosensor: the blood glucose biosensor – developed by *Leland C. Clark* in 1962

# Components of Biosensor



# Common Analytes









# Elements


- **Sample:** The biological component of analyte which is under study
- **Transducer:** a device which converts energy from one form to the other. It is a combination of :
  - **Bioreceptor:** the sensitive biological element
  - **Electrical interface:** The detector which works in a physicochemical way: optical, piezoelectric, electrochemical etc.) that transforms the signal to electric form
- **Electronic system:** Combination of electronic devices ie., amplifier, signal processor and display




# Elements of biosensor




# Elements of biosensor



# How biosensors work




# Blood glucose testing



# Basic characteristics of a biosensor

- **Linearity:** Linearity of the sensor should be high for the detection of high substrate concentration.
- **Sensitivity:** Value of the electrode response per substrate concentration
- **Selectivity:** Chemical interference must be minimized for obtaining correct result
- **Response time:** Time necessary for having 95% of the response







# Electrochemical transducers

- **Principle:** Many chemical reactions produce or consume ions or electrons which in turn cause some change in the electrical properties of the solution which can be measured out and used as measuring parameter.

# Electrochemical transducers

- In this case, an electrical signal is measured, which shows significant differences in magnitude if antigen-antibody complex are formed.
- The main electrochemical transducers are:
  - **amperometric** (measuring of current),
  - **potentiometric** (measuring of electrode potential or voltage differences)
  - **conductimetric** (measuring of conductivity or resistance).

# Principle of Electrochemical Biosensors




# Blood Glucose Biosensor


- Amperometric Biosensor
- Enzyme **Glucose oxidase** (GOx) catalyzes the oxidation of **glucose** by molecular oxygen producing **glucolactone** and **hydrogen peroxide**.
- In order to work as a catalyst, GOx requires a redox cofactor –flavin adenine dinucleotide (FAD), works as an initial electron acceptor and is reduced to FADH<sub>2</sub>.
- Glucose + GOx –FAD<sup>+</sup> Glucolactone + GOx – FADH<sub>2</sub>


→

# Piezo-electric – measures quartz vibrations under the influence of an electric field




## *piezoelectric immunosensor*






Microcantilever working in static mode. The formation of the antigen-antibody complexes provokes a surface stress and, consequently, a deflection of microcantilever, which is detected optically.

**Optical - involve determining changes in light absorption between the reactants and products of a reaction, or measuring the light output by a luminescent process**




**Surface plasmon resonance-based optical biosensor.**



**Fibre optic**



Immunosensors - to detect and amplify an antigen-antibody reaction





Type	Principle	Advantage	Disadvantages
1. Optical			
a. Fiber optics	Evanescent wave based, allows measurement of binding at the fiber surface	Remote in-situ measurement, inherent sensitivity of optical approaches	Costly equipment and not portable,
b. Laser interferometry	Planar waveguides have evanescent field responsible to change in index of refraction	Highly sensitive, detect up to 1 cell	Susceptibility to turbidity interference
2. Electrochemical			
a. Conductometric	Change in conductance	Fast, low cost	Highly buffered solution may interfere
b. Potentiometric	Electric potential		
c. Amperometric	Oxidation/reduction		
3. Piezoelectric	Quartz crystals oscillation at defined frequency, binding of an analyte to it changes the mass of crystal hence oscillation frequency	High sensitive, fast	Sensitivity level up to 1 cell have not demonstrated
4. Colorimetric/Strip	Color development	Not required any instruments	Not quantitative
5. DNA biochip	Array based	Instrument required	Quantitative


# Advantages

- Highly specific
- Independent of factors like stirring, pH, etc.
- Linear response, Tiny and Biocompatible
- Easy to use, Durable
- Require only Small Sample Volume
- Rapid, Accurate, Stable and Sterilizable


# Applications

- In food industry: to monitor freshness
- Drug discovery: Evaluation of biological activity of new compounds.
- Potentiometric biosensor for monitoring the levels of carbon dioxide, ammonia and other gases in blood
- Environmental: Detection of pesticides, heavy metals etc.
- Analytical measurement of folic acid, biotin, vitamin B12 etc

# Evolution of Blood Glucose Monitor



rechargeable pump



insulin patch (200 u)  
suitable for 3 days



## Googles Smart Lens



A smart contact lens measuring the glucose amount in tears was recently brought out by Google as wearable biosensors

## Healthpatch Biosensor



Gather biometric data like Pulmonary, Neurologic, Cardiovascular (heart rate variability, heart rate, Single-lead ECG, contextual heart rate), and step count, posture, Temperature ,summarized activity, energy expenditure, stress).

## Q™ Sensor



MIT – media labs Launches a Wearable Biosensor to Measure Human Emotions known as Affectiva Q™ Sensor.

## Simband Wearable Biosensors (Samsung)



The sensors in the band project beams of light into the skin at varying strengths in order to reach tissue near the surface or deeper in. The screen then displays metrics like heart rate and blood pressure in real time




## Biosensor tattoos




Wearable Biosensors tattoos monitor sweat to track weight by monitoring the amount of electrolytes, ammonia and sodium in sweat

## Ring Sensor



Ring Sensor is a pulse oximetry sensor which allows monitoring heart rate and oxygen saturation.

## Smart Shirt



Smart shirt developed at Georgia tech uses optical fibers to detect wounds and special sensors and interconnects to monitor the body vital signs.