

**Graph Traversal Methods** 

Sandesh B. J

Department of Computer Science & Engineering



# **Graph Traversals Methods**

Sandesh B. J

Department of Computer Science & Engineering

## **Graph Traversal Methods - Topics**



- Why we need to traverse the graph?
- Traversing the graph using different techniques
  - ✓ Depth First Search and Breadth First Search Traversal
- Algorithms for Depth First and Breadth First Search Traversal

## **Graph Traversals**

- Graph traversal(also known as graph search) refers to the process of visiting/investigating (checking or updating) each vertex of the graph in some systematic order -Wiki
- Traversal can start in any arbitrary vertex
- Traversals are classified by the order in which the vertices are visited

## **Methods to Traverse the Graph**

- Depth First Search
- Breadth First Search




## **Depth first search (DFS)**

- Visits all the nodes related to one neighbour before visiting the other neighbours and its related nodes. Once it reaches dead end, it backtracks along previously visited node and continue traversing from there.
- Analogues to pre-order traversal of an ordered tree
- Uses stack behaviour, hence implemented using recursive algorithm



## **Depth First Search Traversal**


□ DFS traverse the depth of the graph, until it cannot go any further at which point it backtracks and continues



Traversal order: 1, 2, 4, 7, 3, 5, 6



# **Depth First Search Traversal**







## Difficulties in the graph traversals




## Graph may contain cycles

- Traversal algorithm may reach the same vertex second time.
- To prevent the infinite recursion, we introduce Boolean valued array visited
- Set the visited[v] to true once node v is visited
- Check the visited[w] before processing any node w


## Graph may not be connected:

 Traversal algorithm may fail to reach all the nodes from a single starting point



# **DFS Traversal – Using Stack**





## **Breadth first search (BFS)**


PES UNIVERSITY ONLINE

- Explores all the neighbour nodes in first level from an arbitrary node, before moving to next level of neighbouring nodes.
- Uses Queue behaviour

#### **Breadth First Search Traversal**




□ Analogous to level-by-level traversal of ordered tree



Traversal order: 1, 2, 3, 4, 5, 6, 7


## **Breadth first search Traversal**






1 2 4 5 3 7 6 8 9

## **BFS Traversal – Using Queue**





## **BFS – Traversal – Using Queue**





## **DFS - Algorithm**

```
Algorithm DFS (Graph G )

//Implements DFS traversal for given graph

// Input Graph G = (V, E)

//Output Graph G with vertices marked as visited

mark each vertex in V with 0 as a mark of being "unvisited"

for each vertex v in V do

if v is marked with o

dfs(v)
```

```
dfs(v)
// visits recursively all the unvisited vertices connected to
  vertex v by a path
For each vertex w in V adjacent to v do
  if w is marked with o
    mark w as visited
  dfs(w) Courtesy: "Introduction to Design and Analysis of Algorithms" By Anany Levitin
```



## **BFS - Algorithm**

```
Algorithm BFS (Graph G )

//Implements BFS traversal for given graph

// Input Graph G = (V, E)

//Output Graph G with vertices marked as visited

mark each vertex in V with 0 as a mark of being "unvisited"

for each vertex v in V do

if v is marked with 0

bfs(v)
```



## **BFS - Algorithm**

```
PES
UNIVERSITY
ONLINE
```

```
bfs(v)
// visits recursively all the unvisited vertices connected to
  vertex v by a path
While the queue is not empty
  for each vertex w in V adjacent to front vertex do
    if w is marked with 0
      mark w as visited
      add w to queue
      remove the front vertex from the queue
```



# **THANK YOU**

Sandesh B. J

Department of Computer Science & Engineering

sandesh\_bj@pes.edu

+91 80 6618 6623