



OPERATING SYSTEMS

Kernel Data Structures and Computing Environments

Venkatesh Prasad

Department of Computer Science

- The slides/diagrams in this course are an **adaptation**, **combination**, and **enhancement** of material from the following resources and persons:
 1. Slides of Operating System Concepts, Abraham Silberschatz, Peter Baer Galvin, Greg Gagne - 9th edition 2013 and some slides from 10th edition 2018
 2. Some conceptual text and diagram from Operating Systems - Internals and Design Principles, William Stallings, 9th edition 2018
 3. Some presentation transcripts from A. Frank – P. Weisberg
 4. Some conceptual text from Operating Systems: Three Easy Pieces, Remzi Arpaci-Dusseau, Andrea Arpaci Dusseau

OPERATING SYSTEMS


Kernel Data Structures

Venkatesh Prasad


Department of Computer Science

- Standard programming data structures are used extensively in OS


Singly linked list



Doubly linked list



Circular linked list




- Stack uses **LIFO** principle
 - OS often uses a stack when involving function calls.
 - Parameters, local variables and the return address are pushed onto the stack when a function is called
 - Return from the function call pops those items off the stack
- Queue uses **FIFO** principle
 - Tasks waiting to be run on an available CPU are organized in queues
 - Print jobs sent to a printer are printed in the order of submission

- Data structure used to represent data hierarchically



- Binary search tree

ordering between 2 children: left \leq right

- Search performance is $O(n)$
- **Balanced binary search tree** is $O(\lg n)$
 - *Used by Linux as part its CPU-Scheduling algorithm for selecting which task to run next*



- Hash functions can result in the same output value for 2 inputs
- **Hash function** can be used to implement a **hash map**
 - Maps or associates key:value pairs using a hash function




- **Bitmap** - string of n binary digits representing the status of n items
- Availability of each resource is indicated by the value of a binary digit
 - 0 – resource is available
 - 1 – resource is unavailable
- Value of the i^{th} position in the bitmap is associated with the i^{th} resource
 - Ex: bitmap 001011101 shows resources 2, 4, 5, 6, and 8 are unavailable; resources 0, 1, 3, and 7 are available

OPERATING SYSTEMS

Computing Environments – Traditional


- Stand-alone general purpose machines
- But blurred as most systems interconnect with others (i.e., the Internet)
- **Portals** provide web access to internal systems
- **Network computers** (**thin clients**) are like Web terminals
- Mobile computers interconnect via **wireless networks**
- Networking becoming ubiquitous – even home systems use **firewalls** to protect home computers from Internet attacks



OPERATING SYSTEMS

Computing Environments – Mobile


- Handheld smartphones, tablets, etc
- What is the functional difference between them and a “traditional” laptop?
- Extra feature – more OS features (GPS, gyroscope)
- Allows new types of apps like ***augmented reality***
- Use IEEE 802.11 wireless, or cellular data networks for connectivity
- Leaders are **Apple iOS** and **Google Android**



OPERATING SYSTEMS


Computing Environments – Distributed

- Distributed computing
 - Collection of separate, possibly heterogeneous, systems networked together
 - ▶ **Network** is a communications path, **TCP/IP** most common
 - **Local Area Network (LAN)**
 - **Wide Area Network (WAN)**
 - **Metropolitan Area Network (MAN)**
 - **Personal Area Network (PAN)**
 - **Network Operating System** provides features between systems across network
 - ▶ Communication scheme allows systems to exchange messages
 - ▶ Illusion of a single system




■ Client-Server Computing

- Dumb terminals replaced by smart PCs
- Many systems now **servers**, responding to requests generated by **clients**
 - ▶ **Compute-server system** provides an interface to client to request services (i.e., database)
 - ▶ **File-server system** provides interface for clients to store and retrieve files





- Another model of distributed system
- P2P does not distinguish clients and servers
 - Instead all nodes are considered peers
 - May each act as client, server or both
 - Node must join P2P network
 - ▶ Registers its service with central lookup service on network, or
 - ▶ Broadcast request for service and respond to requests for service via ***discovery protocol***
 - Examples include Napster and Gnutella, **Voice over IP (VoIP)** such as Skype



- Allows operating systems to run applications within other OSes
 - Vast and growing industry
- **Emulation** used when source CPU type different from target type (i.e. PowerPC to Intel x86)
 - Generally slowest method
 - When computer language not compiled to native code –
Interpretation
- **Virtualization** – OS natively compiled for CPU, running **guest** OSes also natively compiled
 - Consider VMware running WinXP guests, each running applications, all on native WinXP **host** OS
 - **VMM** (virtual machine Manager) provides virtualization services

- Use cases involve laptops and desktops running multiple OSES for exploration or compatibility
 - Apple laptop running Mac OS X host, Windows as a guest
 - Developing apps for multiple OSES without having multiple systems
 - QA testing applications without having multiple systems
 - Executing and managing compute environments within data centers
- VMM can run natively, in which case they are also the host
 - There is no general purpose host then (VMware ESX and Citrix XenServer)



- Delivers computing, storage, even apps as a service across a network
- Logical extension of virtualization because it uses virtualization as the base for its functionality.
 - Amazon **EC2** has thousands of servers, millions of virtual machines, petabytes of storage available across the Internet, pay based on usage
- Many types
 - **Public cloud** – available via Internet to anyone willing to pay
 - **Private cloud** – run by a company for the company's own use
 - **Hybrid cloud** – includes both public and private cloud components


OPERATING SYSTEMS

Computing Environments – Cloud Computing

- Software as a Service (**SaaS**) – one or more applications available via the Internet (i.e., word processor)
- Platform as a Service (**PaaS**) – software stack ready for application use via the Internet (i.e., a database server)
- Infrastructure as a Service (**IaaS**) – servers or storage available over Internet (i.e., storage available for backup use)



- Cloud computing environments composed of traditional OSe, plus VMMs, plus cloud management tools
 - Internet connectivity requires security like firewalls
 - Load balancers spread traffic across multiple applications



- Real-time embedded systems most prevalent form of computers
 - Vary considerable, special purpose, limited purpose OS, **real-time OS**
 - Use expanding
- Many other special computing environments as well
 - Some have OSes, some perform tasks without an OS
- Real-time OS has well-defined fixed time constraints
 - Processing ***must*** be done within constraint
 - Correct operation only if constraints met



THANK YOU

Venkatesh Prasad

Department of Computer Science Engineering

venkateshprasad@pes.edu