

AUTOMATA, FORMAL LANGUAGES AND LOGIC

MODULE 5

Propositional Logic

Dr Pooja Agarwal

Department of Computer Science & Engineering

Outline

- Proof by resolution
 - Unit resolution
 - Conjunctive normal form
 - Resolution algorithm

AUTOMATA FORMAL LANGUAGES AND LOGIC

Proof by Resolution - Conjunctive Normal Form (CNF)

- Conjunctive Normal Form (CNF)

every sentence of propositional logic is logically equivalent to a conjunction of clauses.

A sentence expressed as a **conjunction** of clauses (**disjunction of literals**) is said to be in **conjunctive normal form or CNF**.

AUTOMATA FORMAL LANGUAGES AND LOGIC

Existing Knowledge Base



$$R_1: \neg P_{1,1}$$

$$R_2: B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

$$R_3: B_{2,1} \Leftrightarrow (P_{1,1} \vee P_{2,2} \vee P_{3,1})$$

$$R_4: \neg B_{1,1}$$

$$R_5: B_{2,1}$$

$$R_6: (B_{1,1} \Rightarrow (P_{1,2} \vee P_{2,1})) \wedge ((P_{1,2} \vee P_{2,1}) \Rightarrow B_{1,1})$$

$$R_7: ((P_{1,2} \vee P_{2,1}) \Rightarrow B_{1,1})$$

$$R_8: (\neg B_{1,1} \Rightarrow \neg(P_{1,2} \vee P_{2,1}))$$

$$R_9: \neg(P_{1,2} \vee P_{2,1})$$

$$R_{10}: \neg P_{1,2} \wedge \neg P_{2,1}$$

$$R_{11}: \neg B_{1,2}$$

$$R_{12}: B_{1,2} \Leftrightarrow (P_{1,1} \vee P_{2,2} \vee P_{1,3})$$

$$R_{13}: \neg P_{2,2}$$

$$R_{14}: \neg P_{1,3}$$

$$R_{15}: P_{1,1} \vee P_{2,2} \vee P_{3,1}$$

$$R_{16}: P_{1,1} \vee P_{3,1}$$

$$R_{17}: P_{3,1}$$

AUTOMATA FORMAL LANGUAGES AND LOGIC

Proof by Resolution - Conjunctive Normal Form (CNF)



$$R_2: B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$$

converting the sentence $B_{1,1} \Leftrightarrow (P_{1,2} \vee P_{2,1})$ into CNF. The steps are as follows:

1. Eliminate \Leftrightarrow , replacing $\alpha \Leftrightarrow \beta$ with $(\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)$. Biconditional Elimination

$$(B_{1,1} \Rightarrow (P_{1,2} \vee P_{2,1})) \wedge ((P_{1,2} \vee P_{2,1}) \Rightarrow B_{1,1}) .$$

2. Eliminate \Rightarrow , replacing $\alpha \Rightarrow \beta$ with $\neg \alpha \vee \beta$:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg (P_{1,2} \vee P_{2,1}) \vee B_{1,1}) .$$

3. CNF requires \neg to appear only in literals

$$\neg(\neg \alpha) \equiv \alpha \text{ (double-negation elimination)}$$

$$\neg(\alpha \wedge \beta) \equiv (\neg \alpha \vee \neg \beta) \text{ (De Morgan)}$$

$$\neg(\alpha \vee \beta) \equiv (\neg \alpha \wedge \neg \beta) \text{ (De Morgan)}$$

In the example, we require just one application of the last rule:

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge ((\neg P_{1,2} \wedge \neg P_{2,1}) \vee B_{1,1}) .$$

4. Now we have a sentence containing nested \wedge and \vee operators applied to literals. We apply the distributivity law

$$(\neg B_{1,1} \vee P_{1,2} \vee P_{2,1}) \wedge (\neg P_{1,2} \vee B_{1,1}) \wedge (\neg P_{2,1} \vee B_{1,1}) .$$

Empty Clause

A disjunction of no disjuncts – is equivalent to False because a disjunction is true only if at least one of its disjuncts is true.

Another way to see empty clause represents a contradiction is to observe that **it arises** only from **resolving two complementary unit clauses** such as P and $\neg P$.

Resolving two singleton clauses leads to the **empty clause**; i.e. the clause **consisting of no literals at all**, as shown below. The derivation of the empty clause means that the database contains a contradiction.

$$\begin{array}{c} \{p\} \\ \{\neg p\} \\ \hline \{\} \end{array}$$

AUTOMATA FORMAL LANGUAGES AND LOGIC

Proof by Resolution



A Resolution Algorithm

```
function PL-RESOLUTION( $KB, \alpha$ ) returns true or false
  inputs:  $KB$ , the knowledge base, a sentence in propositional logic
          $\alpha$ , the query, a sentence in propositional logic

   $clauses \leftarrow$  the set of clauses in the CNF representation of  $KB \wedge \neg \alpha$ 
   $new \leftarrow \{ \}$ 
  loop do
    for each  $C_i, C_j$  in  $clauses$  do
       $resolvents \leftarrow$  PL-RESOLVE( $C_i, C_j$ )
      if  $resolvents$  contains the empty clause then return true
       $new \leftarrow new \cup resolvents$ 
  if  $new \subseteq clauses$  then return false
   $clauses \leftarrow clauses \cup new$ 
```

AUTOMATA FORMAL LANGUAGES AND LOGIC

Proof by Resolution

Example :-

□ Given

$KB = (B_{11} \Leftrightarrow (P_{12} \vee P_{21})) \wedge \neg B_{11}$, prove $\neg P_{12}$

Resolution:

Convert to CNF and $\alpha = \neg P_{12}$

show $KB \wedge \neg \alpha$ is unsatisfiable

$\neg P_{21} \vee B_{11}$

$\neg B_{11} \vee P_{12} \vee P_{21}$

$\neg P_{12} \vee B_{11}$

$\neg B_{11}$

P_{12}


AUTOMATA FORMAL LANGUAGES AND LOGIC

Proof by Resolution

Example :- \square Given

$KB = (B_{11} \Leftrightarrow (P_{12} \vee P_{21})) \wedge \neg B_{11}$, prove $\neg P_{12}$

Resolution: Convert to CNF and $\alpha = \neg P_{12}$
show $KB \wedge \neg\alpha$ is unsatisfiable



AUTOMATA, FORMAL LANGUAGES AND LOGIC

Exercise



- Given the premises $(p \Rightarrow q)$ and $(r \Rightarrow s)$, use Propositional Resolution to prove the conclusion $(p \vee r \Rightarrow q \vee s)$.
- Ans:
 1. $\{\sim p, q\}$ Premise
 2. $\{\sim r, s\}$ Premise
 3. $\{p, r\}$ Goal
 4. $\{\sim q\}$ Goal
 5. $\{\sim s\}$ Goal
 6. $\{\sim p\}$ Resolution: 1, 4
 7. $\{\sim r\}$ Resolution: 2, 5
 8. $\{r\}$ Resolution: 3, 6
 9. $\{\}$ Resolution: 8, 7

In each of the following questions, say which of the answers best characterizes the result of applying resolution to the clauses shown.

1. $\{p, q, \neg r\}$ and $\{r, s\}$

- ☒ $\{p, q, s\}$
- ☐ $\{p, q, r, s\}$
- ☐ $\{p, q, \neg r, s\}$
- ☐ There are no resolvents.

2. $\{p, q, r\}$ and $\{r, \neg s, \neg t\}$

- ☐ $\{p, q, r, \neg s, \neg t\}$
- ☐ $\{p, q, \neg s, \neg t\}$
- ☒ There are no resolvents.

AUTOMATA, FORMAL LANGUAGES AND LOGIC

Exercise



In each of the following questions, say which of the answers best characterizes the result of applying resolution to the clauses shown.

3. $\{q, \neg q\}$ and $\{q, \neg q\}$

- ☒ $\{q, \neg q\}$
- ☐ $\{q\}$
- ☐ $\{\neg q\}$
- ☐ $\{\}$
- ☐ There are no resolvents.

AUTOMATA, FORMAL LANGUAGES AND LOGIC

Exercise



A Propositional 2-CNF expression is a conjunction of clauses, where each clause contains exactly 2-literals.

$(A \vee B) \wedge (\sim A \vee C) \wedge (\sim B \vee D) \wedge (\sim C \vee G) \wedge (\sim D \vee G)$

Prove using Resolution that the above sentence entails G.

Ans:

Given “KB $\wedge \sim$ Alpha” is

R1: $(A \vee B)$, R2: $(\sim A \vee C)$, R3: $(\sim B \vee D)$, R4: $(\sim C \vee G)$,
R5: $(\sim D \vee G)$ and R6: $\sim G$

Resolving R1 and R2: R7 = $B \vee C$

Resolving R3 and R7: R8 = $C \vee D$

Resolving R4 and R8: R9 = $D \vee G$

Resolving R5 and R9: R10 = G

Resolving R6 and R10: R11 = $\{\}$

Hence Contradiction, So Alpha is TRUE and the given Statement entails G.



THANK YOU

Dr Pooja Agarwal

Department of Computer Science and
Engineering

poojaagarwal@pes.edu