



# COMPUTER NETWORKS

---

**Sivaraman Eswaran Ph.D.**

Department of Computer Science and Engineering

# COMPUTER NETWORKS

---

## Computer Networks and the Internet

**Sivaraman Eswaran Ph.D.**


Department of Computer Science and Engineering

# COMPUTER NETWORKS

## Hosts: Send packets of data

Host sending function:

- takes application message
- breaks into smaller chunks, known as *packets*, of length  $L$  bits
- transmits packet into access network at *transmission rate  $R$* 
  - link transmission rate, aka link *capacity*, aka link *bandwidth*




$$\begin{array}{l} \text{packet} \\ \text{transmission} \\ \text{delay} \end{array} = \begin{array}{l} \text{time needed to} \\ \text{transmit } L\text{-bit} \\ \text{packet into link} \end{array} = \frac{L \text{ (bits)}}{R \text{ (bits/sec)}}$$

- **bit:** propagates between transmitter/receiver pairs
- **physical link:** what lies between transmitter & receiver
- **guided media:**
  - signals propagate in solid media: copper, fiber, coax
- **unguided media:**
  - signals propagate freely, e.g., radio

### Twisted pair (TP)

- two insulated copper wires
  - Category 5: 100 Mbps, 1 Gbps Ethernet
  - Category 6: 10Gbps Ethernet



# COMPUTER NETWORKS

## Network Edge: Physical media


### Coaxial cable:

- two concentric copper conductors
- bidirectional
- broadband:
  - multiple frequency channels on cable
  - 100's Mbps per channel



### Fiber optic cable:

- glass fiber carrying light pulses, each pulse a bit
- high-speed operation:
  - high-speed point-to-point transmission (10's-100's Gbps)
- low error rate:
  - repeaters spaced far apart
  - immune to electromagnetic noise



### Wireless radio

- signal carried in electromagnetic spectrum
- no physical “wire”
- broadcast and “half-duplex” (sender to receiver)
- propagation environment effects:
  - reflection
  - obstruction by objects
  - interference

### Radio link types:

- terrestrial microwave
  - up to 45 Mbps channels
- Wireless LAN (WiFi)
  - Up to 100’s Mbps
- wide-area (e.g., cellular)
  - 4G cellular: ~ 10’s Mbps
- satellite
  - up to 45 Mbps per channel
  - 270 msec end-end delay
  - geosynchronous versus low-earth-orbit



Thank You  
For Your Attention



**THANK YOU**

---

**Sivaraman Eswaran Ph.D.**

Department of Computer Science and Engineering

**[sivaramane@pes.edu](mailto:sivaramane@pes.edu)**

**+91 80 6666 3333 Extn 834**