Optimus - Test Strategy

Version 1.10 — Cost-savings report, 2026-11-02; local filing — not activated.

Predecessor: Optimus-Cost-Agent-Test-Strategy-v1.9.pdf; SHA-256 21ab8cacd90fd56bdce7841c48efaf2642cc45555dc5fa43f40786e12fbb60fd. Retain the predecessor unchanged in `docs/archive/`.

Native carried page bodies originate from Optimus-Cost-Agent-Test-Strategy-v1.7.pdf (SHA-256 31a60c6a198c60cc1203ff5c4a8e6e0300a820ec18cc702e25f246edc51dc0b0). This complete successor retains v1.9's carried bodies and corrections except for the changes identified below. Page keys remain those of the native baseline.

What this edition changes. It adds the real Postgres capture/report tier, its explicit selection and resource prerequisites (§3, §15.8), and the claim-to-check and reported-evidence distinctions for Plan 12.9 (§15.8, §16.1). The production and test-source inspection pin is main `a88fde86a2ddf382a9bb39a6e2c1a74a1db20498`, PR #462 merged 2026-11-02T14:02:48Z, with parents `99e6ce7fda20e2a468ef4ce3b17b613e6998f2ad` and PR head `f808289b5d0ebf377538e7b72b94e9c3ffca8a29`.

Inspected facts at a88fde8. `requires_plan12_capture_postgres` is deselected by default. Its tests require a released disposable Postgres resource and inspect its container identity before connecting. Credential-boundary cases run separately with the password absent from the pytest environment and resolved by the Gateway child. Unit checks cover arithmetic, coverage qualifications, references, snapshots, command advertisement and delivery-aware continuation. Real Postgres tests cover migration, immutable readback, concurrent ingest, deadlines, outages and the Gateway read boundary. Test presence is distinct from an executed passing result.

Historical provenance and controlling Plan 12.2 amendment. Unchanged v1.9 statements retain their `91fd64ac78025efe1076bddb106ff89e6adb2030` inspection pin and the named `cf9bb9d` or earlier evidence pins. Their production-absence and deferred-status descriptions are historical, not a new current-state assessment. The 2026-10-18 amendment, `docs/sources/plan-12-2-ordinary-shipping/architecture-amendment.md`, remains controlling for unrefreshed Plan 12.2 material and evidence. HLD v2.24 and LLD v2.47 retain their intervening scoped successors. This edition does not refresh Plans 12.5–12.7's memory work or Plan 12.8 beyond the report's durable-accounting prerequisite. Guardrails is unchanged.

Evidence qualification. The one Plan 12.9 Windows full suite at `f1cb559` failed; its coverage numbers are not a validated passing result. The operator accepted no Windows rerun, conditional on Linux PR CI and the formal safety comparison passing. Final PR evidence is reported at `c2ec782`, separately from the earlier `5613c98` receipt retained in `qualification.json`. Main-push guardrails run 41458258151 subsequently completed successfully at actual merge `a88fde8`, with full-run coverage validity established. The final plain-next delivery fix was not rerun in Zed or a Windows full suite. Zed proof costs are synthetic, and the out-of-plan paid-call incident remains disclosed. Its unrepaired Gateway attachment gap is owned by #465. B2/B3 commissioning and the deferred native memory-evaluation campaign belong to #463. ADR-034 remains Proposed; ADR-032 is accepted by ADR-033; frozen ADR-012 is unchanged.

Authority. Codex's testing-strategy wording; local filing by Claude under the operator's 2026-11-02 answer, verbatim, "Go ahead", to "Go ahead with the Plan 12.9 closure steps?", including Codex drafting these successors and Claude checking and building them. That instruction includes the one-off large-file-hook skip for these PDFs. Publication to main requires the operator's separate approval. The filing label describes the document. No product suite, container, editor session or paid call was run to author this text.

1. Test objectives

The strategy proves that a developer can complete full Plan and Agent runs with only `OPTIMUS_GATEWAY_URL` and `OPTIMUS_API_KEY` in the agent process. No upstream credential is resolvable by the agent. Separately, the loopback Gateway receives exactly its approved aggregator credential and never exposes it.

2. Scope and non-scope

In scope:

- strict loopback URL and bind enforcement, including WSL2 same-network-namespace topology;
- OpenRouter default through the OpenAI-compatible transport (the Vercel option is a design option with no implementation at 91fd64a);
- deterministic search live compatibility and plugin deprecation gate (a target path: the implemented provider is Tavily, and the gate has only 2026-07-27 spike evidence, §7A);
- include/exclude domain enforcement and returned-URL revalidation;
- independent package/OSV routes without search configuration (required; not implemented at 91fd64a, LLD §9C.4);
- bounded extract provenance, redirect, SSRF, media, size, and time controls;
- provider-reported usage/cost authority and full request attribution;
- OTel/OTLP export to a real Phoenix tier;
- separate agent and Gateway credential/egress scans.

Out of scope:

- hosted staging Gateway, OAuth/device flow, tenants, org/project wallets, Vault;
- direct provider adapters;
- cross-run spend policy (`P9.85-FU-3`);
- MCP Gateway endpoint or contract;
- engine/model comparison matrices.

3. Test pyramid and evidence tiers

Tier	Dependency	Fakes permitted	Claim supported
Unit	In-process functions	Yes	Local logic and contracts
Contract	Recorded request/response shape	Yes	Parser and schema behavior
`requires_redis`	Real TimeSeries-capable Redis	No	Persistence and retention
`requires_plan12_capture_postgres`	Real released disposable Postgres, with admitted container identity; separate Gateway-keyring setup for credential-boundary cases	No substitute for Postgres	Durable usage capture, report reads, migrations, concurrency and outage behavior (§15.8)
`requires_gateway`	Real loopback Gateway + approved credential	No	Gateway/provider behavior
ACP protocol	Independent `acpx` client	No	Real client compatibility
E2E	Spawned ACP process + named dependencies	No	Golden workflow
Release	Full process/credential/egress evidence	No	Phase 1 sign-off

There is no hosted staging Gateway. Provider fakes remain confined to unit and contract tests and cannot justify a live claim.

Verification ownership

Every design claim is required to map to an executable unit, integration, E2E, eval, or release-gate check; §16 records which material claims have evidence today and of what kind. Coverage enforces the Optimus product group and separate context_engine / optimus_model_policy 80% floors; all-source aggregate is informational under section 8A, and safety-critical modules do not regress.

LLD Section	Design Claim	Test Category (§)	Tier
§4A — State Machine	AwaitingApproval gate cannot be bypassed	§6 — Mode/State	Unit + Integration
§6 — Gateway Layer	POST /v1/responses uses input field, not messages	§8 — Gateway	Unit + Integration
§6 — Gateway Layer	No provider key present in local environment during run	§8 — Gateway	E2E (Release Gate)
§9 — Tool Policy	EvidenceRequest.query sent verbatim (not substituted)	§7 — Tools	Unit
§9 — Tool Policy	EvidenceExtractRequest rejects out-of-set URLs	§7 — Tools	Unit
§9 — Evidence Ledger	total_cost_usd() reconciles against gateway response	§9 — Cost	Unit + Integration
§9D — Gateway Policy	Gateway revalidates domain allowlist independently	§8 — Gateway	Integration
§10 — Telemetry	RedisTimeSeries TS.CREATE idempotent with TS.ALTER fallback	§10 — Telemetry	Integration
§11 — Sprint 1 Gate	One-key setup: full run with only OPTIMUS_* env vars	§12 — Release Gate	E2E

5. Mode and State Transition Tests

LLD reference: §4 Behavioral Governance, §4A Agent State Model. These tests prove the state machine is deterministic and that no path bypasses the mode enforcement primitives.

Unit Tests — assert_mutation_allowed()

- [ ] In Plan/Chat mode: calling assert_mutation_allowed() raises Code -32002 with message "mutation forbidden in Plan/Chat mode".
- [ ] In Agent mode before AwaitingApproval: assert_mutation_allowed() raises Code -32002.
- [ ] In Agent mode after approval granted: assert_mutation_allowed() returns None (no exception).
- [ ] Calling any mutation tool (write_file, shell_exec, shadow_apply) in Plan/Chat mode raises -32002 before any I/O occurs.

Unit Tests — State Transitions

- [ ] Idle -> Planning: valid on any user request.
- [ ] PlanReady -> Executing (direct): rejected with -32002; must pass through AwaitingApproval.
- [ ] AwaitingApproval -> ChatOnly on timeout: confirmed after configurable timeout_ms expires.
- [ ] Failed -> Planning: retry counter increments; failure context injected into next prompt payload.
- [ ] Failed -> Terminated: at the configured finite work boundary, state transitions truthfully and a stop report is emitted. Pin the current three planning rounds, 30 minutes and two repeated failures separately.

Integration Tests — Mode Boundary

- [ ] Full Plan/Chat run: agent completes discussion and returns plan text; no file in working tree is modified; telemetry records 0 mutation calls.

6. Tool Invocation Tests

- Search is authorized only by existing policy signals and the harness gate.
- The Gateway forwards the effective include/exclude policy and rejects off-policy citation URLs.
- At `max_tokens=16`, the live deterministic plugin returns typed URL annotations or fails.
- URL, title, and non-empty content are required; annotation offsets are ignored.
- Extract requires exact prior Gateway-recorded provenance and passes redirect/SSRF/media/size/time bounds.
- Package and OSV routes remain callable without a Tavily/search credential.
- Search, extract, package, and advisory usage envelopes reconcile independently.

7. OptimusGatewaySettings Unit Tests

- Default `http://127.0.0.1:8765` passes.
- `localhost` and canonical IPv6 loopback pass.
- Non-loopback DNS names and IP literals fail closed.
- URI userinfo, ambiguous host parsing, and non-HTTP(S) schemes fail closed.
- No field or environment variable authorizes non-loopback.
- `production_mode`, extra origins, hosted origins, and signed tenant profiles are absent.
- `optimus_api_key` is masked in repr, serialization, logs, telemetry, and state.

7.1 Integration, E2E, and egress gates

- Direct policy-violation tests target the real loopback Gateway.
- Aggregator routing/fallback evidence records the returned provider and model.
- The agent and ACP child may egress only to the loopback Gateway.
- The Gateway may egress only to the configured aggregator, approved package/OSV hosts, approved extract targets, Redis, and configured OTLP endpoint.
- Agent and Gateway environments are scanned separately.
- The agent has no upstream key; the Gateway has the approved aggregator key by design.
- After replacement acceptance, the Gateway has no direct-provider, Tavily, or LangSmith key. (At 91fd64a the Gateway still holds `TAVILY_API_KEY` as its implemented search provider key; replacement acceptance has not occurred.)
- Crafted tool output cannot cause direct agent egress.
- WSL2 evidence proves both processes share one network namespace.

Failure behavior

Malformed or missing successful provider usage/cost remains invalid; the stage records explicit unknown cost and preserves known subtotals without latching the product session closed. Permanent authentication, policy, schema, and validation failures do not retry. Transient faults have a bounded retry budget and record every attempt.

For enforced model requests, the following bounded retry policy supersedes generic transient-retry examples: The legacy host permits an initial attempt plus at most three retries. The inactive-policy Gateway separately permits at most three upstream attempts, including its legacy transient timeout/URL/5xx retries. Once enforcement is active, the Gateway permits one primary attempt and at most one identical-payload resend on the same route, only after a definitely NOT_SENT result (including a proven pre-connection timeout) or rejected HTTP 429. A timeout after connection, uncertain delivery, 5xx or unknown accounting is not resent. The host honors non-retryable classifications so it cannot multiply attempts. No alternative-model recovery is added. Each physical attempt retains its own receipt.

8A. Coverage policy and shared gate interface

coverage.py with pytest-cov is the canonical line/branch engine. Use one identified full-suite dataset, including unloaded tracked production files from every top-level src/ package, regular or namespace. Focused datasets cannot substitute. The all-source aggregate is informational.

Product group	Exactly-once members	Floor / disposition
Optimus	optimus, optimus_gateway, optimus_security, optimus_model_policy	80% enforced group
Context Engine	context_engine	80% enforced package/group
Evidence Handoff	evidence_handoff, evidence_handoff_runtime	80% informational; enforcement deferred

Independently enforce optimus_model_policy at 80% in addition to its Optimus group. This extra report does not create duplicate ownership. Inventory comes from Git's tracked-file index, not a filesystem walk. Reject missing/duplicate/stale/unmapped groups, top-level src modules with no package ownership, inconsistent coverage sources, missing unloaded files and missing/stale datasets. Native package patterns must not match a similarly named neighbor.

The comparison uses coverage.py/pytest-cov should_fail_under at configured precision 0: round(measured_percentage, 0) < 80 fails. 79.5% compares as 80% and passes; 79.0% fails. Print and retain both measured and compared percentages. This preserves the existing comparison, rather than claiming an unrounded 80% boundary.

Implemented interface (cf9bb9d; present unchanged in purpose at 91fd64a):

```
tools/check_product_coverage.py --run-full-suite --groups tools/product-coverage-groups.json --report-
json <report.json>
tools/check_product_coverage.py --data-file <full-run-data> --run-record <report.run.json> --groups
tools/product-coverage-groups.json --report-json <report.json>
```

Exactly one mode is required. Run mode invokes sys.executable -m pytest once with --cov --cov-branch --cov-fail-under=0 --cov-report=term-missing -q, preserving repository addopts/run-context and the true pytest exit. No nested uv or narrowed selection. It writes <report>.run.json with schema, HEAD, dirty flag, fixed command, times, true exit and dataset SHA-256. Report mode never reruns tests and rejects a dataset that does not match its record hash. A nonzero suite exit fails the gate even when floors pass. Required floor failures also fail; informational rows retain BELOW but do not fail the wrapper. The wrapper calls coverage's reporting/comparison API, not additional coverage CLI subprocesses; therefore no per-row process exit is claimed.

The sidecar is provenance for a trusted recorded run, not an authenticated artifact, a dirty-tree digest or a complete configuration snapshot. Reuse only with the corresponding reviewed full-run log/run context and unchanged source/configuration. Verify those externally when accepting a sealed dataset; do not infer full selection or changed-configuration validity from the hash alone. The current final clean-candidate datasets were independently checked in evidence-verification.json.

Status at 91fd64a: the Plan 11.30 profiles lane has landed (PRs #279, #280 and #281 merged, ADR-020). The commit hook keeps its ID `optimus-pytest-coverage` and name `optimus-check: pytest-coverage` but runs `python -m tools.testing.run_profile --profile commit`: the tests this commit's staged changes select, without coverage. Its historical name does not make it a coverage run. CI (`.github/workflows/guardrails.yml`) runs `tools/check_product_coverage.py --run-full-suite` and then `tools.testing.coverage_products validate` against that export. Checkpoints run `run_profile --profile checkpoint --base <recorded SHA>`. `pyproject.toml` keeps `fail_under = 80` under `[tool.coverage.report]` for direct pytest-cov runs. The released final CP4 gate also uses run mode. Existing ADR-016 skip custody is retained; no new ad hoc waiver. Shared source-scope custody remains HARDENING-ITEM-COVERAGE-SOURCE-SCOPE (issue #299).

CI's rows survive in the step log. JSON report upload is not implemented and is not a claimed retained artifact. No new Evidence Handoff tests are required for informational coverage.

8B. Observability test strategy

Tool	Category	Purpose	Counts toward code coverage	Status at 91fd64a
coverage.py / pytest-cov	Code coverage	Production-code execution	Yes	Implemented; CI-enforced (§8A)
DeepEval / Ragas	LLM quality	Correctness and groundedness	No	Intended; no dependency, import or test; UNRUN
PyRIT	Adversarial	Injection and tool-control safety	No	Intended; no dependency, import or test; UNRUN. The guardrail fixtures in `tests/unit/guardrails` are offline positive controls for named guards, not a red-team campaign
OpenTelemetry / OTLP	Trace observability	Vendor-neutral span contract/export	No	Implemented (`optimus_gateway.observability`); the live Phoenix tier (`requires_phoenix`) is UNRUN without a collector

Run the real Phoenix evidence tier and assert required span attributes and request correlation, parent/child relationships, secret redaction, batching/retry outcome, validation/policy disposition and final failure/success disposition. A missing real collector/exporter makes that claim UNRUN.

Phoenix is the documented default, not an API dependency. No LangSmith dependency, endpoint, credential or amortized per-request charge exists. These observability claims are separate from §8A's source coverage gates.

7A. Deterministic Search Compatibility Gate

The deterministic search compatibility gate uses one cheap Flash/Haiku-class model and one default engine request shape. Status at 91fd64a: the Gateway's implemented search provider is Tavily; the aggregator plugin path this gate would exercise is not implemented in the Gateway, so this is a planned product gate whose only evidence is the 2026-07-27 architecture spike (`tools/run_openrouter_web_search_spike.py`, run against OpenRouter directly, not through the Gateway). As a Gateway gate it is UNRUN. The 2026-07-27 spike baseline is:

- max_tokens=16;
- 3 annotations on the minimal-output probe;
- 3/3 include-domain results allowed and 0 violations;
- 0/3 excluded-domain results forbidden and 0 violations;
- 9/9 annotations with HTTPS URL, title, and non-empty content;
- mean latency 7,068.7 ms/search;
- provider-reported mean cost $0.0051584/search;
- direct extract 270,008 bytes -> 60,077 text characters in 589.5 ms.

These are evidence values, not permanent performance thresholds. Each run reports fresh values and fails on missing search execution, annotations, domain enforcement, or provider usage/cost. Engine and model comparison matrices are out of scope. A verified-or-fail server-tool successor requires a separate live test proving max_uses: 1, exactly one search, search-use accounting, valid annotations, domain enforcement, and fail-closed behavior when execution evidence is absent.

9. Error, Retry, and Failure Injection Tests

LLD reference: §6 Resilient Provider Calling Layer, §4A Failure and Retry Lifecycle. These tests prove that transient failures are retried with backoff and permanent failures abort cleanly without side effects.

Unit Tests - RetryPolicy

- Current RetryPolicy: initial call plus up to three retries; pin third-attempt success and escalation after the fourth attempt. Under enabled Gateway policy, pin a maximum of two physical attempts only after not-sent/429 with identical payload/route and host non-retryable propagation.
- HTTP 429 under enforced policy: at most one identical payload resend on the same route; all physical attempts count.
- PermanentGatewayError: ABORT_WITH_REPORT returned immediately; no retry; failure report emitted.
- PolicyViolationError: ABORT_WITH_REPORT; escalation signal emitted.
- Independent evaluation budget exhaustion stops that evaluation and preserves receipts. A successful product response above the former $0.05 is delivered; no product dollar stop remains after migration.
- Finite configured attempts exhausted: report the true failure and all attempt identities; no retry-until-pass.

Integration Tests - Failure Injection

- The legacy host permits an initial attempt plus at most three retries. The inactive-policy Gateway separately permits at most three upstream attempts, including its legacy transient timeout/URL/5xx retries. Once enforcement is active, the Gateway permits one primary attempt and at most one identical-payload resend on the same route, only after a definitely NOT_SENT result (including a proven pre-connection timeout) or rejected HTTP 429. A timeout after connection, uncertain delivery, 5xx or unknown accounting is not resent. The host honors non-retryable classifications so it cannot multiply attempts. No alternative-model recovery is added. Each physical attempt retains its own receipt. Tests cover third-attempt success and escalation after the fourth attempt in the legacy policy, and separately the enabled Gateway maximum of two physical attempts with host non-retryable propagation.
- Fitness failures use configured planning/time/repeated-failure boundaries; targeted replan context is supplied only while those bounds permit continuation. Pin the actual stop and effect evidence.

- Evaluation cap exhaustion stops only its approved evaluation. Product count/time/cancellation/permission failures preserve truthful telemetry and effect state; do not relabel them as dollar exhaustion.

10. Schema Validation Tests

LLD reference: §1 ACP Protocol Framing, §9 Tool Registry. These tests prove malformed inputs are rejected before processing and Pydantic v2 validators enforce invariants at the boundary.

Unit Tests - ACP Framing

- Content-Length: 0 with non-empty body: rejected with -32700 Parse Error.
- Content-Length > MAX_HEADER_SIZE: rejected with -32600 Invalid Request.
- Non-numeric Content-Length: rejected with -32700 Parse Error.
- Body larger than declared Content-Length: truncated; remaining bytes are not leaked into the next message.
- JSON-RPC body missing method: rejected with -32600 Invalid Request.
- JSON-RPC body with unknown method: rejected with -32601 Method Not Found.

Unit Tests - Pydantic Models

- EvidenceRequest with an empty query string: ValidationError before any Gateway call.
- EvidenceExtractRequest with max_chars_per_source=0: ValidationError.
- OptimusGatewaySettings with empty optimus_api_key: ValidationError.
- GatewayUsage with negative billing_units: ValidationError.
- GatewayUsage with negative cost_usd: ValidationError.

11. Security and Trust Boundary Tests

- Secret scans include the aggregator key and every retired direct-provider, Tavily, and LangSmith key name.
- Strict-loopback validation replaces production-mode permutations.
- URL parsing rejects userinfo, non-HTTP(S), non-loopback hosts, ambiguous IP forms, and DNS rebinding seams.
- Extract revalidates every redirect and final address and blocks private/link-local/loopback resolution.
- Tool output is untrusted and cannot become policy or executable content.
- Provider-reported cost must be Decimal-parseable, non-negative, and attributable.
- Logs and traces preserve field names while redacting secrets.

Golden task evidence

Golden tasks run against the real local Gateway. Named live claims use real dependencies. ACP protocol evidence uses `acpx`, not a project-authored client.

12. Golden Task Regression Suite

Every golden task records:

- expected mode and final state;
- expected tool class and authorization outcome;
- cost band and provider-reported usage;
- mutation behavior;
- Gateway and provider request identity;
- trace identity and final disposition.

The suite covers Plan-only refusal, approved Agent mutation, deterministic search, bounded extract, free package/advisory routes, retry exhaustion, malformed usage/cost, and credential leakage attempts.

OTel/OTLP-to-Phoenix evidence replaces LangSmith assertions. A trace failure cannot silently count as success; delivery state and final disposition must be explicit.

Process-scope assertion

The agent has no upstream credential. The Gateway has exactly the approved aggregator credential and never exposes it through logs, telemetry, state, responses, child environments, or error text.

13. Phase 1 Release Gates

Transport and protocol

- Shadow workspace, mutation guard, and independent ACP-client evidence pass.
- Strict-loopback topology and WSL2 namespace evidence pass.
- Both agent-facing completion shapes validate; mixed shapes fail.

Runtime and credentials

- Full Plan and Agent runs use only the two agent-facing variables.
- Agent and child processes have no direct external egress.
- Gateway has one approved aggregator credential and no retired keys after acceptance.

Evidence and cost

- Search plugin compatibility/deprecation gate passes.
- Package and OSV routes work without search configuration.
- Extract provenance and SSRF gates pass.
- Provider-reported usage/cost reconciles across response, ledger, and TimeSeries.

Observability

- Real OTLP spans reach Phoenix with required fields and redaction.
- No LangSmith dependency or amortized charge exists.

Release sign-off remains governed by the authoritative Plan 9.6 live-verification gate.

14. Guardrail & Workflow Test Cases

LLD reference: §12 (Guardrail & Workflow Component Contracts). Companion reference: Agent Execution Guardrails & Workflow Strategy v1.4 §11. Consistent with Objective 1 (§1), each control below traces to at least one executable test category; a control without a category is not considered validated for Phase 1. Implementation status at 91fd64a: each named component exists and has unit tests under `tests/unit/guardrails` (`test_permissions.py`, `test_pre_tool_guard.py`, `test_command_safety.py`, `test_unicode_confusables.py`, `test_prompt_injection.py`, `test_mcp_trust.py`, `test_ci_parity.py`, `test_network_safety.py`, `test_path_safety.py`) and `tests/unit/agent`; these are offline positive controls and attributable denials for the named guards.

14.1 Permission policy tests — deny precedence over allow; mode short-circuit; impact-class HOLD; classifier cannot overturn a deny.

14.2 Shell validator tests — destructive, pipe-to-shell, environment/credential access, ANSI, insecure-transport, and egress patterns all BLOCK before any subprocess is spawned.

14.3 Unicode / homoglyph tests — Cyrillic-vs-Latin confusables in hostnames and paths (e.g. U+0456 vs U+0069) are detected and held/blocked.

14.4 Prompt-injection fixture tests prove poisoned agent config and poisoned MCP tool metadata are caught by ConfigTrustScanner / MCPTrustRegistry on ingest.

14.5 MCP autoload denial tests — a server bundled in a cloned repo does not auto-load; a manifest-hash change forces re-approval; allowed_tools are enforced.

14.6 Pre-commit / CI parity tests — the same rule set (Ruff, Bandit, AST-grep, hygiene hooks) fails identically locally and in a clean CI checkout.

14.7 Bypass tests — --no-verify, force-push to main, unsafe .env reads, and unsafe network commands are all blocked.

14.8 Loop control tests — the loop stops on completion, on max_iterations, on wall-clock exhaustion and repeated-failure detection; it never bypasses §14.1/§14.2 enforcement.

14.9 Skill loading & trust tests — a skill loads only when matched; an untrusted/draft skill is blocked; declared allowed_tools are enforced; a skill cannot override project/user deny rules.

14.10 Additions to the §4 Requirements-to-Test Traceability Matrix

LLD Section	Design Claim	Test Category (§)	Tier
§12A — Permission	Deny precedes allow; classifier cannot overturn deny	§14 — Guardrails	Unit
§12A — Pre-Tool Guard	Bad tool call blocked before execution	§14 — Guardrails	Unit + Integration
§12A — Shell Validator	Homoglyph / pipe-to-shell / egress blocked pre-spawn	§14 — Guardrails	Unit
§12B — MCP Trust	No auto-load from cloned repo; hash change re-approves	§14 — Guardrails	Unit + Integration
§12B — Config Scan	Poisoned config / tool metadata caught on ingest	§14 — Guardrails	Unit
§6 / §12 — CI Parity	Local and clean-CI checks fail identically	§14 — Guardrails	Integration

LLD Section	Design claim	Test category	Tier
§12C — Goal Loop	Stops on completion / max-iteration / wall-clock / repeated failure	§14 — Guardrails	Unit + Integration
§12D — Skills	Match-only load; draft blocked; allowed-tools enforced	§14 — Guardrails	Unit

Release-gate note: §13 (Phase 1 Release Gates) retains the release-blocking no-guardrail-bypass check covering §14.7. These continuation rows belong to §14.10's requirements traceability matrix.

15. Plan 12 claim-to-evidence strategy

Edition scope. The retained Plan 12.2 strategy and evidence below keep their original pins. The 2026-10-18 ordinary shipping amendment (`docs/sources/plan-12-2-ordinary-shipping/architecture-amendment.md`) controls unrefreshed Plan 12.2 production and evidence statements. Section 15.8 adds Plan 12.9 and its necessary Plan 12.8 accounting prerequisite, inspected at main `a88fde86a2ddf382a9bb39a6e2c1a74a1db20498`. Plans 12.5–12.7's memory work and the remainder of Plan 12.8 are not refreshed; no historical result is transferred to that pin.

15.1 Coverage and checkpoint evidence

Section 8A defines one complete coverage dataset, independent product reports and separate 80% floors for `context_engine` and `optimus_model_policy`. The source-group inventory must cover every top-level import package under `src/` exactly once, including informational groups. A new package, duplicate membership or unassigned package fails the guard rather than disappearing from aggregate measurement. The top-level model-policy package floor is an extra report, not a second product ownership.

Historical candidate/test/coverage seals and post-run deltas belong in the closure records. They do not prove changed executable bytes, route quality, persistent enforcement or live editor behavior.

The three historical strict xfails are resolved at cf9bb9d: their assertions now pass and the markers are removed. This does not turn skipped, deselected or UNRUN evidence into passes. Skips, deselections, failed/invalidated attempts and unrun marked tiers remain explicit. Later testing may measure more files and reduce percentages. A `tail`/wrapper exit never substitutes for the underlying coverage/test exit.

Use existing focused checks for accepted-value assertions and documentation-only fixes. Do not repeat the full suite simply for numeric test additions or provenance wording. A newly released substantive product migration requires its applicable checkpoint verification; do not claim the earlier full run tested those new bytes. Keep this within CP4 rather than inventing per-task review gates.

15.2 Offline claims and required cases

Claim	Required cases / source scopes	Tier
Extractability	Forbidden imports; independent noneditable wheel import; packaged YAML; negative tainted extraction probe	Unit + isolated wheel
Exact authority	All-turn outcomes/effects/approvals preserved when ordinary history is omitted; model text cannot manufacture facts	Unit + host integration
Strategies differ	Hybrid anchor/tail discriminator, deduplication, complete newest-turn sliding, zero sliding maintenance	Unit
Packing safety	ASCII/code/CJK/emoji; exact/one-over token and byte input; maximal fresh/reused summary; non-subadditive negative backstop; preflight zero-call rejection	Unit
Checkpoint integrity	Prefix append/change/reorder, stale configuration/revision, cancellation, malformed/oversized/partial output, no publication on rejection	Unit + host integration
Refusal/fallback	Every known and unknown reason, unavailable zero-provider case, failed-summary receipt retained, <=floor full fallback, >floor OPEN refusal and healthy recovery	Unit + host integration

Claim	Required cases / source scopes	Tier
Selection and approval	Exact retained hints use current files; summary never directly selects; stored-view digest and exact artifact approval; changed-target handling	Unit + controlled-tool integration
Picker/config/meter	Attached-only strategy option; full option set; setter interleaving; old flush/new pending; first sliding notice; largest actual dispatched request and no fabricated refused reading	Unit + real client
Final request guard	Equality/one-over at actual attempt boundary; trusted snapshot; all framing/material and one output reserve; incomplete finish blocked before plan approval	Unit + route evidence
Accounting	Exactly-once known/unknown/cancelled/stale attempts; divergent duplicate rejection; known subtotal retained; no re-debit on stored-plan application	Unit + real ledger
Product/evaluation split	Product result above former $0.05 delivered; no dollar predicates/prompts/constructor requirements; finite count/time/failure retained; separate capped evaluation stops	Completed former strict-xfail assertions + integration

Use actual source scopes including tests/unit/context_engine, model_policy, acp, agent, usage, loops, optimus_gateway, tools, telemetry, retry, package-import tests and tests/integration/loops; use actual collection to select relevant names. Do not invent a passing test file or apply blanket xfail removal.

15.3 Per-route eligibility and D7 boundary evidence

Record exact model/provider/endpoint/quantization/reasoning, window >=262144 and output caps >=role reserve, estimator algorithm/assets/version/digest, normalization/pre-tokenization and framing proof, enforced cap parameter and true finish semantics. Verify both actual request paths at exact and one-over complete capacity, with maximum permitted additional material and one output reserve.

The named ADR-014 exception retains 524288-byte source/admission and its warning but permits readable OPEN refusal when full history cannot fit. The operator's acceptance is recorded verbatim in ADR-018 (source S4; decision 2026-10-04, filed 2026-10-07). No source-floor reduction or capacity exemption. Public JSON/config inspection does not count tokens or install libraries; exact route-tokenizer dependencies remain deferred. Samples/family labels cannot establish conservative safety; unknown/expanding normalization remains ineligible. Verified r=1 substantially reduces usable exact tail/history in bytes, disclosed in the closure proposal.

15.4 Summary qualification

Use the existing `tools/evaluate_context_summarizer.py` and `tests/fixtures/context_engine/calculator-constraints-v1.json`. Step 1 summarizes turns 1-5; step 2 merges that actual summary with turns 6-7. Turns 8-9 are exact tail and cannot mask omission of either early constraints or the late correction. Evaluate the summary itself for Decimal, public calculate API, no eval/exec/network, negative inputs, HALF_EVEN as current, HALF_UP as superseded, both rounding examples, no invented approval/deletion and inert injection text. Protected approval projection must separately equal the host source.

The fixture output cap is **1200 tokens**, not the proposed production summary cap of 8192. Record this scope honestly. Require complete stop status and exact prompt/format/validator/fixture/model/endpoint/reasoning identities; a changed qualification key invalidates receipt reuse. Human review complements the deterministic lexical report. Two steps are a limited gate, not a statistical quality guarantee.

The current offline envelope reports two requests, input-token upper bounds 2333/2766 and up to two allowed provider attempts per request. Its old-price estimates and route blockers are not current paid eligibility. Qualification permits two logical

requests, at most four physical attempts: one identical-route/payload resend only after NOT_SENT (including proven pre-connection timeout)/429. Require current complete input/framing/cost bounds and host non-retryable propagation; uncertain timeout/5xx/usage never retries. No alternative model recovery.

15.5 Real dependencies and editor

Status: Task 13 is deferred and UNRUN by the operator's 2026-10-08 disposition (recorded in `docs/superpowers/reviews/2026-10-08-plan-12-2-cp4-offline-delivery-disposition.md`); its absent-engine cases may run before summary qualification once their own route, service and execution prerequisites are met. Task 13 uses independently authored acpx, the real Optimus process, real loopback Gateway, real TimeSeries-capable Redis and actual Zed rendering, under scoped credentials/TTY/service authority. The reviewed named test composition implements real server dependency injection and enabled GatewayModelPolicy, with HMAC launch approval/authenticated child-manifest hash binding. Positive offline proof uses a synthetic eligible profile; the real qualification profile remains ineligible. It cannot replace the client or claim production bootstrap activation. Use separate absent-engine and small Chat/Agent sessions; reuse one seeded attached session for large source, sliding, fault/recovery and cancellation, restoring compaction before maintenance. Maintenance requires real quality receipt/profile B; otherwise it is UNRUN. Vibhanshu supplies the named Zed prompts/approvals at the keyboard. Do not import old placeholder effects as real authority.

Prove mode/model/strategy option preservation, attached-only picker, sliding disclosure, separate storage/fallback/refusal notices, readable OPEN no-call refusal, truthful meter and absent-engine defaults. Exercise >512 KiB attached source, bounded fault/unavailable recovery and cancellation during maintenance. Record whether >floor history was generated through client traffic or explicitly seeded as synthetic canonical records; seeding is test setup, not proof of a natural conversation or durable resume.

Do not silently introduce a missing production seam to obtain evidence. Establish launch/tool/service prerequisites first and produce claim-specific non-passing rows when unavailable. A test seam's simulated unavailable response proves fault handling, not provider outage. Live cancellation can bill a started request; retain it.

15.6 Evidence package and closing verdict

Every claim records exact source/configuration/registry/launch identities, commands, dependency versions, selected test names, genuine individual exits, attempt receipts, sanitized conclusions and hashes. Preserve failures and seals. A unit fake cannot fill an acpx, Zed, Redis, Gateway or Phoenix live claim. Existing search/plugin and Phase 1 working-agent gates remain unchanged outside this Plan 12 package.

The offline implementation and documentation through `2068366` were accepted by the operator on 2026-10-08 and merged to `main` via PR #276 (`c509fc8`); that acceptance is the offline merge gate, not a full CP4 pass. CP4 clears only when all its required measured-value, route, quality, migration and real-client obligations have named passing evidence or a separately recorded operator disposition. Coverage gates use full-suite data. The existing full WSL run before finalization remains unchanged; inventory that environment early and retain exact candidate, selection and exit. The two independent package floors are settled operator requirements. Evidence Handoff's 80% threshold is deferred in enforcement until revisited; interim coverage requires no new tests. Do not declare the broader Auto/reviewer/savings/loop/resume scopes complete. Deferred work retains its existing owners in the authoritative tracking venue, according to the actual Plan 11.29 cutover. Publication, merge and production activation remain separate decisions.

15.7 Completed offline evidence and remaining claims

Observed offline candidate, 2026-10-04: cf9bb9d (clean local CP4 branch). V1 capacity text/meter, V3 remaining-allowance preflight, Task 11 product/evaluation separation, named trusted test composition, tracked-source coverage gate and Task 12 boundaries pass offline verification. Windows (`final-gate-2`): 6830 passed, 0 failed, 39 skipped, 111 deselected, 1 warning, exit 0, 1:10:40; WSL (`wsl-full-1`): 6641 passed, 0 failed, 228 skipped, 111 deselected, 1 warning, exit 0, 40:09. Scope: the repository's full default marker selection at clean cf9bb9d; the 111 deselected tests are those the default marker selection excludes (live-dependency and other marked tiers). The failed `final-gate-1` attempt (3 failed, 6807 passed) preceded them and remains failed in the sealed evidence; its walker violation and two frozen-lane regressions were corrected before `final-gate-2`. Required coverage at cf9bb9d: Optimus group 89.4393% (Windows) / 88.9078% (WSL); context_engine 95.9243%; optimus_model_policy 96.9880%; Evidence Handoff 68.4165% / 65.9629%, BELOW its informational 80% threshold; the aggregate is informational. The limits and wheel proofs (zero proposal violations, max_repacks=1, planning

material 43795 bytes, D7 upper bound 185581 bytes / 35.40%; wheel SHA-256 13b06132...ffd36, shipped effective registry hash unchanged) were produced at cc6959b and carried to cf9bb9d only because `src/`, `pyproject.toml` and the lockfile were unchanged between those commits; they were not rebuilt at cf9bb9d. All of these are historical measurements at their stated pins, not measurements at 91fd64a. At the filing state of this correction the documentation checks passed; the coverage-free commit-profile hook (`run_profile --profile commit`) selected a broad fallback of 6697 tests and failed on this host's unprovisioned ast-grep hook environment (6659 passed, 37 skipped, 1 warning, 1 error, exit 1), and it emitted the platform obligation `wsl-platform: next checkpoint`, which is undischarged (see §16 and the validation record). No new full-suite, coverage, live-qualification or activation result is claimed. Production ENFORCEMENT_ACTIVE=False, trusted_snapshot() returns None, and the shipped claude-haiku-4.5 default are unchanged. Luna remains ineligible, Qwen remains unqualified, and paid qualification/real editor Task 13 remain UNRUN. See review-disposition.md and evidence-verification.json. This source review is not production activation or full CP4 closure.

The actual HostMaintenance callback and GatewaySummarizerCall boundary test includes summary-prompt/wire framing and one output reserve: equality admission, one-over INPUT_EXCEEDS_CAPACITY and zero upstream attempts on rejection. The final numeric proposal includes max_repacks=1. The refused case requires two repacks: one refuses after exactly one, while two fit. Positive profile capacity/finish proofs use synthetic test estimators and do not establish Luna eligibility.

The Windows and WSL run records name the exact clean candidate and full command; the sealed logs retain each environment’s test-run context. WSL’s Redis 6379 guard blocked its positive control and one existing reachability probe, which sent no Redis command. This is not evidence of arbitrary service isolation or Windows job parity.

Plan 9.88 historical claims use the frozen lane prompt version and retain all evidence checks. Its runner refuses new captures when the product prompt differs. Plan 9.87 keeps current-prompt validation. This preserves old evidence, not a new live acceptance.

15.8 Durable usage capture and cost-savings reporting

Claims and executable checks

The production contracts are HLD §14.10 and LLD §13.13–§13.16. ADR-032 is accepted by ADR-033; ADR-034 remains Proposed. Test sources at `a88fde8` provide the following checks; their existence alone is not a passing run.

Claim	Named executable source and discriminating cases	Evidence class
Canonical actual cost and honest coverage	`tests/unit/optimus_gateway/test_usage_report.py`: duplicate-attempt refusal, unknown cost, missing/open/incomplete epochs, late/conflicting receipts, expected-turn and frontier gaps, unattributed Auto turns, unallocated overhead	Unit
Independent B1 arithmetic	Same file: one fully loaded subtraction, signed negative savings, zero baseline without percentage, nested token categories, missing splits/prices, long-context thresholds, independent reference availability and all-stage fixture	Unit
Reference and snapshot integrity	`tests/unit/model_policy/test_savings_references.py`, `tests/unit/optimus_gateway/test_usage_price_snapshots.py`: strict configuration, content identities, approved overrides and durable-before-stamp behavior	Unit

Claim	Named executable source and discriminating cases	Evidence class
Read-route contract and bounds	`tests/unit/usage/test_usage_report_contract.py`, `tests/unit/optimus_gateway/test_usage_report.py`, `tests/unit/optimus_gateway/test_server.py`: strict schema, authentication, bounded pages, stable errors, sealed cursors, changed revisions and worker deadlines/cap	Unit/contract
Host transport and rendering	`tests/unit/usage/test_savings_report.py`: whole-exchange deadline, slow headers/body, byte bounds, malformed replies, escaping, exact labels and unavailable sections	Unit with local socket checks where required
ACP command lifecycle	`tests/unit/acp/test_savings_command.py`: advertisement after `session/new`, local no-turn handling, session/turn continuation, confirmed flush, cancellation, late reads, retirement and teardown	Unit and real-channel composition; not independent-client acceptance
Auto attribution through escalation	`tests/unit/acp/test_savings_escalation_capture.py`: one Auto context and each captured classifier/planning receipt counted once	Offline composition; no real-model or campaign claim
Durable capture substrate	`tests/integration/usage/test_durable_capture_postgres.py`: pinned migrations, atomic commit, replay, aliases/conflicts, database immutability, concurrency, outage/restart, killed writer and real capture HTTP	Real Postgres tier
Consistent report reading	`tests/integration/usage/test_savings_report_postgres.py`: 001-to-002 migration, immutable snapshots, canonical rows, concurrent ingest between/during pages, lock/read deadlines, outage/restart, replaced ledger, capture frontier and production HTTP	Real Postgres tier
Gateway-only database credential	Both Postgres files' subprocess boundary cases: provisioned Gateway resolves its keyring credential while the host/test environment has no ledger password	Real Postgres plus real OS keyring and Gateway process
ACP compatibility and Zed rendering	Independent acpx and actual editor proof, separately attributed in `reports/plan12-cost-savings/zed-ui.json`	Real protocol/UI dependencies; synthetic costs do not establish real-provider savings

The all-stage fixture is a reducer-level unit check. Real Postgres report receipt fixtures use planning; they do not prove every production stage against Postgres. Preserve that distinction.

Selection and prerequisites

`pyproject.toml` excludes `requires_plan12_capture_postgres` from the default marker expression. A green default suite therefore does not exercise it. After the operator releases the disposable resource, an explicit database-tier selection is:

```
uv run pytest -q -m requires_plan12_capture_postgres
tests/integration/usage/test_durable_capture_postgres.py
tests/integration/usage/test_savings_report_postgres.py
```

This supplies a marker selection while retaining the repository configuration and root conftest. Record the emitted run mode/reason and actual selected tests; it is focused dependency evidence, not a full-default-suite result or proof of active default-run protection.

The ordinary database fixtures require `P128_CAPTURE_K3_CONFIG` and `P128_CAPTURE_K3_PASSWORD`. The configuration names the released container, image identity, dedicated volume, loopback endpoint, database and role. The fixture inspects the container before connecting. Missing prerequisites skip as UNRUN; no shared, production or another plan's database is an acceptable substitute. These tests can create/drop scratch databases and stop/restart the released container, so resource release is a real prerequisite, not implicit permission from this command example.

Credential-boundary cases require a separate invocation: omit `P128_CAPTURE_K3_PASSWORD`, provision the credential in the Gateway's real keyring namespace, and provide `P128_CAPTURE_K3_CONFIG`, `P128_CAPTURE_K3_ACCOUNTING_ROOT` and `P128_CAPTURE_K3_RUN_ID`. Those cases also carry `requires_os_keyring`; select the intended boundary cases explicitly and retain any skips. A pytest process that possesses the password cannot establish the password-absent boundary.

Record source/configuration identities, exact commands, resource identity, platform, every selected/skipped test, genuine exits and retained evidence. Separate focused database, credential-boundary, full-suite, independent-client and editor runs. Provisioning or running any of them requires its applicable service, credential and interaction authority; this document performs none.

Acceptance limits

B1 uses the same reported tokens at dated reference prices and is not realized savings or an Auto-off workload. The actual total already includes captured overhead. B2/B3 remain unavailable and require no speculative reader. OC-4 (#463: https://github.com/vibhanshu-agarwal/optimus-cost-agent/issues/463) owns their commissioning, producer contracts and paid authority, plus the deferred native memory-evaluation campaign.

Section 16.1 records the reported Plan 12.9 results, failed Windows gate, operator disposition and final paging-fix limitations. No test tier silently substitutes synthetic provider values for a real-provider claim.

16. What each result demonstrates (correction of 2026-10-15)

This section maps the material capabilities this strategy covers to the checks that exist and the evidence that has actually been produced, with its source pin, platform or configuration, result and limits. It distinguishes offline fixture positives and attributable denials from real-provider, editor, MCP, Phoenix and sandbox qualification. Historical counts carry their exact scope. Nothing here transfers a historical pass to the current source: at `91fd64ac78025efe1076bddb106ff89e6adb2030` (origin/main, 2026-10-15) this correction's documentation checks (`tests/unit/docs`) passed, and the coverage-free commit-profile hook ran a broad fallback that failed on the host's unprovisioned ast-grep environment (row below, retained as failed). The sealed cf9bb9d runs remain historical evidence for that correction. This successor separately records Plan 12.9's later evidence in §16.1; it does not re-pin those old runs, their activation statements or their unresolved obligations. The 2026-10-18 ordinary shipping amendment controls unrefreshed Plan 12.2 material.

Capability or claim	Existing check	Evidence (pin; platform/configuration)	Result	Limits
Full default suite	`pytest` default selection	cf9bb9d; Windows `final-gate-2`	6830 passed, 0 failed, 39 skipped, 111 deselected, 1 warning; exit 0; 1:10:40	The 111 deselected tests are those the default marker selection excludes (live-dependency and other marked tiers); a clean candidate at that pin only
Full default suite	`pytest` default selection	cf9bb9d; WSL `wsl-full-1`	6641 passed, 0 failed, 228 skipped, 111 deselected, 1 warning; exit 0; 40:09	228 skips include Windows-only tiers; WSL's port-6379 positive control was blocked and proves no general isolation
Preceding full-suite attempt	`pytest` default selection	pre-cf9bb9d; Windows `final-gate-1`	3 failed, 6807 passed	Retained as failed; its walker violation and two frozen-lane regressions were corrected before `final-gate-2`
Commit-profile hook at the filing state (§8A commit cadence)	`python -m tools.testing.run_profile --profile commit` (coverage-free)	Product source `91fd64a` with the staged documentation candidate; Windows; 2026-10-15	Selected 6697 (`fallback=broad`: a documentation-only change has no mapped tests), deselected 1125; 6659 passed, 37 skipped, 1 warning, 1 error; exit 1; verdict failed; 9:25	The error is `test_real_sink_module_passes_the_gate`, which by design fails explicitly when the configured ast-grep hook environment is not provisioned on the host; retained as failed, not reclassified; the run emitted the obligation `wsl-platform: next checkpoint`, undischarged; coverage-free, so no coverage value exists for the pin
Product coverage floors (§8A)	`tools/check_product_coverage.py --run-full-suite`	cf9bb9d; Windows / WSL	Optimus 89.4393% / 88.9078%; context_engine 95.9243%; optimus_model_policy 96.9880%; Evidence Handoff 68.4165% / 65.9629% BELOW informational; aggregate informational	Precision-0 comparison (79.5% compares as 80%); informational rows are not gates; measured at cf9bb9d, not at the pin

Capability or claim	Existing check	Evidence (pin; platform/configuration)	Result	Limits
Limits and wheel proofs	`tools/evaluate_context_summarizer.py` limits run; independent wheel build	cc6959b; carried to cf9bb9d over unchanged `src/`, `pyproject.toml` and lockfile	Zero proposal violations; max_repacks=1; planning material 43795 bytes; D7 bound 185581 bytes / 35.40%; wheel SHA-256 13b06132...ffd36	Not rebuilt at cf9bb9d or at the pin
Mutation guard, shadow workspace, fitness runner (§5, §12)	`tests/unit/gates`, `tests/unit/runtime`, integration	Present at the pin; included in the cf9bb9d suites	Offline positive controls and attributable denials	Covers mediated tool paths; not a host-wide guarantee
Guardrail controls 14.1-14.9	`tests/unit/guardrails` (`test_permissions.py`, `test_pre_tool_guard.py`, `test_command_safety.py`, `test_unicode_confusables.py`, `test_prompt_injection.py`, `test_mcp_trust.py`, `test_ci_parity.py`, `test_network_safety.py`, `test_path_safety.py`), `tests/unit/agent`	Present at the pin; included in the cf9bb9d suites	Offline positive controls and attributable denials for the named guards	Not a general security certification; the borderline classifier is not exercised live
Gateway loopback, credential isolation, tool policy, extract bounds (§7, §7.1, §11)	Unit tests; `requires_gateway` live tier	Unit at cf9bb9d; live tier UNRUN in the sealed runs (deselected)	Unit positive controls	Live egress and credential-scope evidence require the marked tier
Deterministic search compatibility gate (§7A)	Planned Gateway gate	2026-07-27 spike (`tools/run_openrouter_web_search_spike.py`, direct to OpenRouter)	Spike values only	The Gateway search provider at the pin is Tavily; as a Gateway gate the check is UNRUN
Package/OSV routes without search configuration (§2)	None exercising the independence	None	Not implemented at the pin (LLD §9C.4)	Requirement retained; finding for an owning issue
Usage accounting and TimeSeries (§8, §10)	Unit tests; `requires_redis` tier	Unit at cf9bb9d; live tier deselected in the sealed runs	Unit positive controls	Real Redis retention evidence requires the marked tier
OTel/OTLP to Phoenix (§8B, §13)	`requires_phoenix` tier	UNRUN	UNRUN	Needs a live collector reachable through the Gateway-only endpoint
ACP protocol with independent client (§3, §13)	`requires_acpx` tier; `tests/e2e/acp`	Spawned-process e2e tests exist; acpx tier UNRUN for Plan 12.2 Task 13	Not a Task 13 result	Project-authored harness evidence cannot substitute for acpx
Real editor (Zed) rendering, Task 13 (§15.5)	`requires_zed` tier	UNRUN; deferred by operator disposition 2026-10-08	UNRUN	Owner Plan 12.2, issue #237
Luna route/estimator qualification (§15.3)	Profile A (`test_profile_qualification.yaml`)	Free inspection 2026-10-04; profile admits no model	Ineligible; UNRUN	Tokenizer, finish and reasoning facts unverified

Capability or claim	Existing check	Evidence (pin; platform/configuration)	Result	Limits
Genuine summary-quality receipt (§15.4)	`tools/evaluate_context_summarizer.py` with the calculator fixture	UNRUN; profile B declared unavailable	UNRUN	Needs an eligible route; the fixture cap is 1200 tokens, not 8192
Context Engine offline claims (§15.2)	`tests/unit/context_engine`, `tests/unit/model_policy`, host integration	cf9bb9d suites; synthetic eligible profile for positive composition	Offline-verified	Synthetic estimators do not establish route eligibility
D6 product/evaluation split (§9, §15.2)	Former strict-xfail assertions, integration	cf9bb9d suites; merged via PR #276	Pass	Offline evidence; no live cost run
DeepEval, Ragas, PyRIT evaluations (§8B)	None	None	UNRUN; planned	No dependency, import or test at the pin
Performance benchmarks (Roadmap v11)	None	None	UNRUN; planned	Dimensions are defined only; no thresholds exist
MCP supply-chain trust live tiers	`requires_mcp_http`, `requires_mcp_stdio`	Deselected in the sealed runs	UNRUN here	Offline fixtures only establish ingest-time detection
OS keyring credential tiers	`requires_os_keyring`, `requires_os_keyring_write`	Deselected in the sealed runs	UNRUN here	Platform-specific; WSL does not establish Windows parity
Plan 12.9 report arithmetic, coverage, references and ACP lifecycle	Named unit/contract sources in §15.8	Source inspection at `a88fde8`; separately pinned execution in qualification records	Reported focused/revert checks and qualified Linux PR evidence (§16.1)	Test presence is not a new execution result; final plain-next fix lacks a Zed/Windows-full rerun
Durable capture and Postgres report read	`requires_plan12_capture_postgres`; two integration files in §15.8	Reported database tier at `7cce51c`	55 passed, 2 skipped; separate boundary checks reported (§16.1)	Default suite deselects the tier; real database fixtures do not cover every production stage
Independent ACP and Zed report surface	`zed-ui.json`	Reported proof with real client/editor and synthetic upstream costs	Command, report/paging and outage observations	No realized-savings or provider-billing claim; later delivery fix not rerun there
B2/B3 and native memory-evaluation campaign	No qualifying campaign result supplied	OC-4, #463	B2/B3 unavailable	Requires separate commissioning, producer contracts and paid authority

Reading the table. A row marked offline positive control or attributable denial supports the specific guarantee its test names and nothing broader. Future framework evaluations and performance benchmarks are planned and UNRUN. The retained deferred route, receipt and editor statements keep their original provenance and are read with the controlling Plan 12.2 amendment; this report successor does not restart those historical checks.

16.1 Plan 12.9 reported evidence and qualification

The implementation inspection pin is main `a88fde86a2ddf382a9bb39a6e2c1a74a1db20498`. The execution records below concern their own named sources. `reports/plan12-cost-savings/qualification.json`, `final-run-evidence.json`, `test-exclusions.json` and `zed-ui.json` retain the detailed attribution and limitations; none is replaced by this summary.

Windows full suite remains failed. At `f1cb559`, `full-suite-final` exited 1 with 14 failed, 11,508 passed, 54 skipped, 165 deselected and 2 warnings. Its active default-selection context reported COMPLETE records and native valid protection,

but the tests failed. The recorded required coverage floors were numerically met; the gate failed and `coverage-validate-final` exited 3. Those measurements are not a validated passing coverage result.

The failures came from a stale configuration double in the Plan 12.5 harness tests. The later double correction was test-only. The subsequent `70c809e` correction was a product change: plain `/savings next` moves only after confirmed report delivery. `6124a90` repaired its logging-surface manifest key. Focused checks and discriminating revert checks cover those changes; the earlier full suite did not execute them. The final product fix was not run in Zed or a Windows full suite.

Operator disposition. The operator selected "Accept, no rerun" on 2026-11-02, expressly preserving those limitations and requiring Linux PR CI's full suite/coverage validation plus the formal comparison against main. The checked-in qualification records their earlier successful `5613c98` evaluation, not the final publication run.

Final Linux PR evidence. #248 comment 6579096728 (https://github.com/vibhanshu-agarwal/optimus-cost-agent/issues/248#issuecomment-6579096728) reports PR head `f808289` tested at merge ref `c2ec782f8f5912486ee889ee22505e084fc4fbfb` against main `99e6ce7`. Run 41452867293 (https://github.com/vibhanshu-agarwal/optimus-cost-agent/actions/runs/41452867293) produced artifact `product-coverage-c2ec782f8f5912486ee889ee22505e084fc4fbfb-1`: 11,272 passed, 318 skipped and 165 deselected. Bound session `20261102T132659-3011-d247f2` established full-run validity. Required floors passed: Optimus 89.80%, Context Engine 95.92% and model policy 95.11%; Evidence Handoff 66.83% and aggregate 86.43% are informational.

The reported formal comparison against main's run 41343980617 exited 0 with "safety rows comparable, no regression"; all seven safety rows equal main's. Compared coverage SHA-256 values are base `d2a4c441eb5e46a276b5ed8e15cf0a0ab40a78a6dd4afdc40b7e563e4466d95d` and final candidate `58e9c2ec2b100d71a0f15043a6588b59a44e180577b5309519aa16114f8e3f88`.

The final report preserves a timing-sensitive non-safety coverage difference at `src/optimus/acp/spec.py:3070` between the two PR runs. Equal skip counts do not identify identical skipped tests; the retained Windows exclusions inventory does not supply Linux skip identities. Linux records retain their unsupported native-guard-platform qualification and do not establish Windows parity.

Actual main-push evidence. Guardrails run 41458258151 (https://github.com/vibhanshu-agarwal/optimus-cost-agent/actions/runs/41458258151), event `push`, completed with conclusion `success` at actual main merge `a88fde86a2ddf382a9bb39a6e2c1a74a1db20498`. Its `clean-environment-recheck` job (125320405517) used Linux and Python 3.14.10. The full default suite reports 11,272 passed, 318 skipped, 165 deselected and 2 warnings, with exit 0.

The job recorded clean source before and after at that exact SHA, active default selection, COMPLETE records and session `20261102T140403-3002-56d82c`. Native, parent and guard capability were unsupported on Linux. Required floors passed: Optimus 89.7957%, Context Engine 95.9243% and model policy 95.1062%; Evidence Handoff 66.8335% remains below its informational threshold, and aggregate 86.4312% is informational. The "Validate the product coverage run" step established full-run validity. Artifact `product-coverage-a88fde86a2ddf382a9bb39a6e2c1a74a1db20498-1` was uploaded.

This main-push result is separately attributable execution evidence. It neither replaces the formal PR-versus-main safety comparison nor changes the failed Windows result, Linux capability qualification or absence of a final Zed rerun.

Database and boundary evidence. The qualification records `db-tier-final` at `7cce51c`: 55 passed, 2 skipped, exit 0. Separate `boundary-report-final` and `boundary-capture-final` each report one pass at that source. These are real dependency checks with their own scope, not part of the default full suite. The all-stage fixture was added at reducer level; real Postgres receipt cases use planning. Later host continuation publication does not become a database-tier or editor rerun.

Protocol/UI proof and incident. `zed-ui.json` reports independent acpx 0.12.0 and real Zed proof, including advertisement after `session/new`, report rendering/paging, `REPORT_CHANGED`, unavailable-ledger behavior, model work during the outage and delayed delivery after restart. The proof uses a synthetic upstream and synthetic costs; it does not establish actual provider prices, provider billing correctness, matched Auto-off behavior or realized savings.

D4 authorized zero paid calls. A separate setup error attached the host to another launch's real Gateway and caused 26 unauthorized requests, known cost USD 0.01436675. The incident is recorded separately and excluded from proof evidence. The launch-attachment gap remains open and unrepaired, now owned by #465

(https://github.com/vibhanshu-agarwal/optimus-cost-agent/issues/465). The pinned reports' temporary #248 custody is historical; the later transfer does not change the pinned code.

Remaining custody and authority. #463 (https://github.com/vibhanshu-agarwal/optimus-cost-agent/issues/463) owns B2/B3 commissioning, producer-owned contracts, paid authority and the deferred native memory-evaluation campaign, including sampled held-out approval. Filing that issue authorizes no campaign. ADR-034 remains Proposed; frozen ADR-012 is unchanged. This successor records qualified evidence and does not close #248 or declare the Phase 1 agent generally working.