

# CS6713: Scalable Algorithms for Data Analysis

Fahad Panolan



Department of Computer Science and Engineering  
Indian Institute of Technology Hyderabad, India

27-Aug-2022

## **Classical Algorithms:** Random Access Model (RAM)

## Classical Algorithms: Random Access Model (RAM)

### Streaming Model

- The input consists of  $m$  objects/items/tokens  $e_1, e_2, \dots, e_m$  that are seen one by one by the algorithm.
- The algorithm has “limited” memory say for  $B$  tokens where  $B < m$  (often  $B \ll m$ ) and hence cannot store all the input
- Want to compute interesting functions over input

# Classical Algorithms: Random Access Model (RAM)


## Streaming Model

- The input consists of  $m$  objects/items/tokens  $e_1, e_2, \dots, e_m$  that are seen one by one by the algorithm.
- The algorithm has “limited” memory say for  $B$  tokens where  $B < m$  (often  $B \ll m$ ) and hence cannot store all the input
- Want to compute interesting functions over input

## Some examples:

- Each token is a number from  $[n]$
- High-speed network switch: tokens are packets with source, destination IP addresses and message contents.
- Each token is an edge in graph (graph streams)
- Each token is a point in some feature space
- Each token is a row/column of a matrix

# A data stream management system



[“Mining of Massive Data Sets” by Leskovec, Rajaraman, Ullman]

## Finding Majority Element

Given an array  $A$  of  $m$  integers, output an element that occurs more than  $m/2$  times in  $A$ ?

# Finding Majority Element

Given an array  $A$  of  $m$  integers, output an element that occurs more than  $m/2$  times in  $A$ ?

## Algorithm:

- Initialize  $c \leftarrow 0$  and  $s = \text{Null}$
- **For**  $i = 1$  to  $m$ 
  - **If**  $A[i] = s$ , **then**  $c \leftarrow c + 1$ .
  - **If**  $A[i] \neq s$  and  $c > 0$ , **then**  $c \leftarrow c - 1$ .
  - **If**  $A[i] \neq s$  and  $c = 0$ , **then**  $c \leftarrow 1$  and  $s \leftarrow A[i]$ .
- Check whether  $s$  is indeed the majority element and output accordingly.

# Heavy Hitters Problem and Misra-Gries Algorithm

**Heavy Hitters Problem:** Find all elements  $i$  such that  $f_i > m/k$ .



# Heavy Hitters Problem and Misra-Gries Algorithm

**Heavy Hitters Problem:** Find all elements  $i$  such that  $f_i > m/k$ .

---

- Initialize  $D[1, \dots, k] \leftarrow 0$  and  $S[1, \dots, k] = \text{Null}$
  - **For**  $j = 1$  to  $m$ 
    - **If**  $A[j] = S[r]$  for some  $r$ , **then**  $D[r] \leftarrow D[r] + 1$ .
    - **Else If**  $S[r] = \text{Null}$  for some  $r$ , **then**  $D[r] \leftarrow 1$  and  $S[r] \leftarrow A[j]$ .
    - **Else:** for all  $\ell \in [k]$ ,  $D[\ell] \leftarrow D[\ell] - 1$ .
  - Remove elements from  $S$  whose counter values are 0
  - Verify whether elements  $S$  have frequency at least  $m/k$ .
-

# Analysis

Space usage  $O(k \log m)$  bits.

# Analysis

Space usage  $O(k \log m)$  bits.

- For each  $r \in [k]$ ,  $\hat{f}_{S[r]} = D[r]$ .
- For all other elements  $i$ , set  $\hat{f}_i = 0$ .

# Analysis

Space usage  $O(k \log m)$  bits.

- For each  $r \in [k]$ ,  $\hat{f}_{S[r]} = D[r]$ .
- For all other elements  $i$ , set  $\hat{f}_i = 0$ .

## Theorem

For each element  $i$  in  $A$ :  $f_i - \frac{m}{k+1} \leq \hat{f}_i \leq f_i$ .

# Analysis

Space usage  $O(k \log m)$  bits.

- For each  $r \in [k]$ ,  $\hat{f}_{S[r]} = D[r]$ .
- For all other elements  $i$ , set  $\hat{f}_i = 0$ .

## Theorem

For each element  $i$  in  $A$ :  $f_i - \frac{m}{k+1} \leq \hat{f}_i \leq f_i$ .

## Corollary

Any item with  $f_i > \frac{m}{k}$  is in  $D$  at the end of the algorithm.

# Proof of Correctness

## Theorem

*For each element  $i$  in  $A$ :  $f_i - \frac{m}{k+1} \leq \hat{f}_i \leq f_i$ .*

# Proof of Correctness

## Theorem

For each element  $i$  in  $A$ :  $f_i - \frac{m}{k+1} \leq \hat{f}_i \leq f_i$ .

Easy to see:  $\hat{f}_i \leq f_i$ . Why?

# Proof of Correctness

## Theorem

For each element  $i$  in  $A$ :  $f_i - \frac{m}{k+1} \leq \hat{f}_i \leq f_i$ .

Easy to see:  $\hat{f}_i \leq f_i$ . Why?

Alternative view of algorithm:

- Assume  $A \subseteq \{1, \dots, n\}$  for some  $n$  and let  $a_j = A[j]$
- Maintain counts  $C[i]$  for each  $i \in \{1, \dots, n\}$  (initialized to 0). Only  $k$  are non-zero at any time.
- During the  $j$ th iteration
  - **If**  $C[a_j] > 0$  then increment  $C[a_j]$  by one.
  - **Elseif**: less than  $k$  positive counters then set  $C[a_j] = 1$
  - **Else**: decrement all positive counters (exactly  $k$  of them)
- Output  $\hat{f}_i = C[i]$  for each  $i$



## Proof of Correctness

**Want to show:**  $f_i - \hat{f}_i \leq \frac{m}{(k+1)}$

# Proof of Correctness

**Want to show:**  $f_i - \hat{f}_i \leq \frac{m}{(k+1)}$

- Suppose we have  $\ell$  occurrences of  $k$  counters being decremented.

# Proof of Correctness

**Want to show:**  $f_i - \hat{f}_i \leq \frac{m}{(k+1)}$

- Suppose we have  $\ell$  occurrences of  $k$  counters being decremented. Then  $\ell k + \ell \leq m$  which implies  $\ell \leq \frac{m}{(k+1)}$ .
- Consider  $\alpha = (f_i - \hat{f}_i)$  during the execution of the algorithms. Initially 0. Initially  $\ell = 0$ . How big  $\alpha$  can be?

# Proof of Correctness

**Want to show:**  $f_i - \hat{f}_i \leq \frac{m}{(k+1)}$

- Suppose we have  $\ell$  occurrences of  $k$  counters being decremented. Then  $\ell k + \ell \leq m$  which implies  $\ell \leq \frac{m}{(k+1)}$ .
- Consider  $\alpha = (f_i - \hat{f}_i)$  during the execution of the algorithms. Initially 0. Initially  $\ell = 0$ . How big  $\alpha$  can be?
  - If  $a_j = i$  and  $C[i]$  is incremented  $\alpha$  stays same

# Proof of Correctness

**Want to show:**  $f_i - \hat{f}_i \leq \frac{m}{(k+1)}$

- Suppose we have  $\ell$  occurrences of  $k$  counters being decremented. Then  $\ell k + \ell \leq m$  which implies  $\ell \leq \frac{m}{(k+1)}$ .
- Consider  $\alpha = (f_i - \hat{f}_i)$  during the execution of the algorithms. Initially 0. Initially  $\ell = 0$ . How big  $\alpha$  can be?
  - If  $a_j = i$  and  $C[i]$  is incremented  $\alpha$  stays same
  - If  $a_j = i$  and  $C[i]$  is not incremented then  $\alpha$  increases by one and  $k$  counters decremented — charge to  $\ell$

# Proof of Correctness

**Want to show:**  $f_i - \hat{f}_i \leq \frac{m}{(k+1)}$

- Suppose we have  $\ell$  occurrences of  $k$  counters being decremented. Then  $\ell k + \ell \leq m$  which implies  $\ell \leq \frac{m}{(k+1)}$ .
- Consider  $\alpha = (f_i - \hat{f}_i)$  during the execution of the algorithms. Initially  $0$ . Initially  $\ell = 0$ . How big  $\alpha$  can be?
  - If  $a_j = i$  and  $C[i]$  is incremented  $\alpha$  stays same
  - If  $a_j = i$  and  $C[i]$  is not incremented then  $\alpha$  increases by one and  $k$  counters decremented — charge to  $\ell$
  - If  $a_j \neq i$  and  $C[i]$  is decremented. Then  $\alpha$  increases by  $1$  it is because  $C[i]$  is decremented — charge to  $\ell$

# Proof of Correctness

**Want to show:**  $f_i - \hat{f}_i \leq \frac{m}{(k+1)}$

- Suppose we have  $\ell$  occurrences of  $k$  counters being decremented. Then  $\ell k + \ell \leq m$  which implies  $\ell \leq \frac{m}{(k+1)}$ .
- Consider  $\alpha = (f_i - \hat{f}_i)$  during the execution of the algorithms. Initially 0. Initially  $\ell = 0$ . How big  $\alpha$  can be?
  - If  $a_j = i$  and  $C[i]$  is incremented  $\alpha$  stays same
  - If  $a_j = i$  and  $C[i]$  is not incremented then  $\alpha$  increases by one and  $k$  counters decremented — charge to  $\ell$
  - If  $a_j \neq i$  and  $C[i]$  is decremented. Then  $\alpha$  increases by 1 it is because  $C[i]$  is decremented — charge to  $\ell$
- Hence total number of times  $\alpha$  increases is at most  $\ell$ .

Thank You.