

# CS 747, Autumn 2020: Week 4, Lecture 1

Shivaram Kalyanakrishnan

Department of Computer Science and Engineering  
Indian Institute of Technology Bombay

Autumn 2020

# Markov Decision Problems

## 1. Definitions

- ▶ Markov Decision Problem
- ▶ Policy
- ▶ Value Function

## 2. MDP planning

## 3. Alternative formulations

## 4. Applications

## 5. Policy Evaluation

# Markov Decision Problems

## 1. Definitions

- ▶ Markov Decision Problem
- ▶ Policy
- ▶ Value Function


## 2. MDP planning

## 3. Alternative formulations


## 4. Applications

## 5. Policy Evaluation

# Markov Decision Problems (MDPs)




# Markov Decision Problems (MDPs)



An MDP  $M = (S, A, T, R, \gamma)$  has these elements.

$S$ : a set of states.

# Markov Decision Problems (MDPs)




An MDP  $M = (S, A, T, R, \gamma)$  has these elements.

$S$ : a set of states.

Let us assume  $S = \{s_1, s_2, \dots, s_n\}$ , and hence  $|S| = n$ .


# Markov Decision Problems (MDPs)



An MDP  $M = (S, A, T, R, \gamma)$  has these elements.

$A$ : a set of actions.

# Markov Decision Problems (MDPs)



An MDP  $M = (S, A, T, R, \gamma)$  has these elements.


**A**: a set of actions.

Let us assume  $A = \{a_1, a_2, \dots, a_k\}$ , and hence  $|A| = k$ .

Here  $A = \{\text{RED}, \text{BLUE}\}$ .




# Markov Decision Problems (MDPs)



An MDP  $M = (S, A, T, R, \gamma)$  has these elements.

$T$ : a transition function.

# Markov Decision Problems (MDPs)




An MDP  $M = (S, A, T, R, \gamma)$  has these elements.

$T$ : a transition function.

- For  $s, s' \in S, a \in A$ :  $T(s, a, s')$  is the probability of reaching  $s'$  by starting at  $s$  and taking action  $a$ .
- Thus,  $T(s, a, \cdot)$  is a probability distribution over  $S$ .


# Markov Decision Problems (MDPs)



An MDP  $M = (S, A, T, R, \gamma)$  has these elements.

$R$ : a reward function.

# Markov Decision Problems (MDPs)




An MDP  $M = (S, A, T, R, \gamma)$  has these elements.

$R$ : a reward function.

- For  $s, s' \in S, a \in A$ :  $R(s, a, s')$  is the (numeric) reward for reaching  $s'$  by starting at  $s$  and taking action  $a$ .
- Assume rewards are from  $[-R_{\max}, R_{\max}]$  for some  $R_{\max} \geq 0$ .

# Markov Decision Problems (MDPs)



An MDP  $M = (S, A, T, R, \gamma)$  has these elements.  
 $\gamma$ , a discount factor—coming up shortly.

# Agent-Environment Interaction

$t = 0$  Agent is born in some state  $s^0$ , takes action  $a^0$ .  
Environment generates and provides the agent  
next state  $s^1 \sim T(s^0, a^0, \cdot)$  and  
reward  $r^0 = R(s^0, a^0, s^1)$ .

# Agent-Environment Interaction

$t = 0$  Agent is born in some state  $s^0$ , takes action  $a^0$ .  
Environment generates and provides the agent  
next state  $s^1 \sim T(s^0, a^0, \cdot)$  and  
reward  $r^0 = R(s^0, a^0, s^1)$ .

$t = 1$  Agent is in state  $s^1$ , takes action  $a^1$ .  
Environment generates and provides the agent  
next state  $s^2 \sim T(s^1, a^1, \cdot)$  and  
reward  $r^1 = R(s^1, a^1, s^2)$ .

# Agent-Environment Interaction

$t = 0$  Agent is born in some state  $s^0$ , takes action  $a^0$ .  
Environment generates and provides the agent  
next state  $s^1 \sim T(s^0, a^0, \cdot)$  and  
reward  $r^0 = R(s^0, a^0, s^1)$ .

$t = 1$  Agent is in state  $s^1$ , takes action  $a^1$ .  
Environment generates and provides the agent  
next state  $s^2 \sim T(s^1, a^1, \cdot)$  and  
reward  $r^1 = R(s^1, a^1, s^2)$ .

$\vdots$



# Agent-Environment Interaction


$t = 0$  Agent is born in some state  $s^0$ , takes action  $a^0$ .  
Environment generates and provides the agent  
next state  $s^1 \sim T(s^0, a^0, \cdot)$  and  
reward  $r^0 = R(s^0, a^0, s^1)$ .

$t = 1$  Agent is in state  $s^1$ , takes action  $a^1$ .  
Environment generates and provides the agent  
next state  $s^2 \sim T(s^1, a^1, \cdot)$  and  
reward  $r^1 = R(s^1, a^1, s^2)$ .


$\vdots$

Resulting trajectory:  $s^0, a^0, r^0, s^1, a^1, r^1, s^2, \dots$

# Describing the Agent's Behaviour




# Describing the Agent's Behaviour



- How does the agent pick  $a^t$ ?

# Describing the Agent's Behaviour




- How does the agent pick  $a^t$ ?

In principle, it can decide by looking at the preceding history

$$s^0, a^0, r^0, s^1, a^1, r^1, s^2, \dots, s^t.$$

# Describing the Agent's Behaviour




- How does the agent pick  $a^t$ ?

In principle, it can decide by looking at the preceding history

$$s^0, a^0, r^0, s^1, a^1, r^1, s^2, \dots, s^t.$$

For now let us assume that  $a^t$  is picked based on  $s^t$  alone.

# Describing the Agent's Behaviour



- How does the agent pick  $a^t$ ?


In principle, it can decide by looking at the preceding history

$$s^0, a^0, r^0, s^1, a^1, r^1, s^2, \dots, s^t.$$

For now let us assume that  $a^t$  is picked based on  $s^t$  alone.

- In other words, the agent follows a **policy**  $\pi : S \rightarrow A$ .

# Describing the Agent's Behaviour



- How does the agent pick  $a^t$ ?

In principle, it can decide by looking at the preceding history


$$s^0, a^0, r^0, s^1, a^1, r^1, s^2, \dots, s^t.$$

For now let us assume that  $a^t$  is picked based on  $s^t$  alone.

- In other words, the agent follows a **policy**  $\pi : S \rightarrow A$ .

Observe that  $\pi$  is Markovian, deterministic, and stationary.

# Describing the Agent's Behaviour



- How does the agent pick  $a^t$ ?

In principle, it can decide by looking at the preceding history

$$s^0, a^0, r^0, s^1, a^1, r^1, s^2, \dots, s^t.$$

For now let us assume that  $a^t$  is picked based on  $s^t$  alone.


- In other words, the agent follows a **policy**  $\pi : S \rightarrow A$ .

Observe that  $\pi$  is Markovian, deterministic, and stationary.


We will justify this choice in due course!




# Illustration: Policy



# Illustration: Policy




# Illustration: Policy



- Illustrated policy  $\pi$  such that

$$\pi(s_1) = \text{RED}; \pi(s_2) = \text{RED}; \pi(s_3) = \text{BLUE}.$$

# Illustration: Policy




- Illustrated policy  $\pi$  such that

$$\pi(s_1) = \text{RED}; \pi(s_2) = \text{RED}; \pi(s_3) = \text{BLUE}.$$

What happens by “following”  $\pi$ , starting at  $s_1$ ?

# Illustration: Policy




- Illustrated policy  $\pi$  such that

$$\pi(s_1) = \text{RED}; \pi(s_2) = \text{RED}; \pi(s_3) = \text{BLUE}.$$

What happens by “following”  $\pi$ , starting at  $s_1$ ?


- $s_1, \text{RED}, s_1, \text{RED}, s_2, \text{RED}, s_3, \text{BLUE}, s_1, \dots$
- $s_1, \text{RED}, s_2, \text{RED}, s_1, \text{RED}, s_1, \text{RED}, s_1, \dots$

# Illustration: Policy




- Let  $\Pi$  denote the set of all policies.

# Illustration: Policy



- Let  $\Pi$  denote the set of all policies.
- What is  $|\Pi|$ ?


# Illustration: Policy



- Let  $\Pi$  denote the set of all policies.
- What is  $|\Pi|$ ?  $k^n$ .



# Illustration: Policy



- Let  $\Pi$  denote the set of all policies.
- What is  $|\Pi|$ ?  $k^n$ .
- Which  $\pi \in \Pi$  is a “good” policy?

# State Values for Policy $\pi$

- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + r^1 + r^2 + r^3 + \dots | s^0 = s]$

# State Values for Policy $\pi$


- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + \gamma r^1 + \gamma^2 r^2 + \gamma^3 r^3 + \dots | s^0 = s]$   
where  $\gamma \in [0, 1)$  is a discount factor.

# State Values for Policy $\pi$

- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + \gamma r^1 + \gamma^2 r^2 + \gamma^3 r^3 + \dots | s^0 = s]$  where  $\gamma \in [0, 1)$  is a discount factor.
- $\gamma$  is an element of the MDP. Larger  $\gamma$ , farther “lookahead”.


# State Values for Policy $\pi$

- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + \gamma r^1 + \gamma^2 r^2 + \gamma^3 r^3 + \dots | s^0 = s]$  where  $\gamma \in [0, 1)$  is a discount factor.
- $\gamma$  is an element of the MDP. Larger  $\gamma$ , farther “lookahead”.




# State Values for Policy $\pi$

- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + \gamma r^1 + \gamma^2 r^2 + \gamma^3 r^3 + \dots | s^0 = s]$  where  $\gamma \in [0, 1)$  is a discount factor.
- $\gamma$  is an element of the MDP. Larger  $\gamma$ , farther “lookahead”.



# State Values for Policy $\pi$


- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + \gamma r^1 + \gamma^2 r^2 + \gamma^3 r^3 + \dots | s^0 = s]$  where  $\gamma \in [0, 1)$  is a discount factor.
- $\gamma$  is an element of the MDP. Larger  $\gamma$ , farther “lookahead”.



- $V^\pi(s)$  is the **value** of state  $s$  under policy  $\pi$ .

# State Values for Policy $\pi$

- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + \gamma r^1 + \gamma^2 r^2 + \gamma^3 r^3 + \dots | s^0 = s]$  where  $\gamma \in [0, 1)$  is a discount factor.
- $\gamma$  is an element of the MDP. Larger  $\gamma$ , farther “lookahead”.




- $V^\pi(s)$  is the **value** of state  $s$  under policy  $\pi$ .  
 $V^\pi : S \rightarrow \mathbb{R}$  is the **Value Function** of  $\pi$ .



# State Values for Policy $\pi$

- For  $s \in S$ ,  $V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi [r^0 + \gamma r^1 + \gamma^2 r^2 + \gamma^3 r^3 + \dots | s^0 = s]$  where  $\gamma \in [0, 1)$  is a discount factor.
- $\gamma$  is an element of the MDP. Larger  $\gamma$ , farther “lookahead”.



- $V^\pi(s)$  is the **value** of state  $s$  under policy  $\pi$ .  
 $V^\pi : S \rightarrow \mathbb{R}$  is the **Value Function** of  $\pi$ . “Larger is better”.

# Markov Decision Problems

## 1. Definitions

- ▶ Markov Decision Problem
- ▶ Policy
- ▶ Value Function

## 2. MDP planning

## 3. Alternative formulations

## 4. Applications

## 5. Policy Evaluation

# Optimal Policies

- Here are value functions from our example MDP.

$\pi$	$V^\pi(s_1)$	$V^\pi(s_2)$	$V^\pi(s_3)$
RRR	4.45	6.55	10.82
RRB	-5.61	-5.75	-4.05
RBR	2.76	4.48	9.12
RBB	2.76	4.48	3.48
BRR	10.0	9.34	13.10
BRB	10.0	7.25	10.0
BBR	10.0	11.0	14.45
BBB	10.0	11.0	10.0

# Optimal Policies

- Here are value functions from our example MDP.

$\pi$	$V^\pi(s_1)$	$V^\pi(s_2)$	$V^\pi(s_3)$
RRR	4.45	6.55	10.82
RRB	-5.61	-5.75	-4.05
RBR	2.76	4.48	9.12
RBB	2.76	4.48	3.48
BRR	10.0	9.34	13.10
BRB	10.0	7.25	10.0
BBR	10.0	11.0	14.45
BBB	10.0	11.0	10.0

Which policy would **you** prefer?

# Optimal Policies

- Here are value functions from our example MDP.

$\pi$	$V^\pi(s_1)$	$V^\pi(s_2)$	$V^\pi(s_3)$	
RRR	4.45	6.55	10.82	
RRB	-5.61	-5.75	-4.05	
RBR	2.76	4.48	9.12	
RBB	2.76	4.48	3.48	
BRR	10.0	9.34	13.10	
BRB	10.0	7.25	10.0	
BBR	<b>10.0</b>	<b>11.0</b>	<b>14.45</b>	← Optimal policy
BBB	10.0	11.0	10.0	

Which policy would **you** prefer?

# Optimal Policies

- Here are value functions from our example MDP.

$\pi$	$V^\pi(s_1)$	$V^\pi(s_2)$	$V^\pi(s_3)$	
RRR	4.45	6.55	10.82	
RRB	-5.61	-5.75	-4.05	
RBR	2.76	4.48	9.12	
RBB	2.76	4.48	3.48	
BRR	10.0	9.34	13.10	
BRB	10.0	7.25	10.0	
BBR	<b>10.0</b>	<b>11.0</b>	<b>14.45</b>	← Optimal policy
BBB	10.0	11.0	10.0	

Which policy would **you** prefer?

Every MDP is guaranteed to have an optimal policy  $\pi^*$  s.t.

$$\forall \pi \in \Pi, \forall s \in S : V^{\pi^*}(s) \geq V^\pi(s).$$

# MDP Planning

**MDP Planning problem:** Given  $M = (S, A, T, R, \gamma)$ , find a policy  $\pi^*$  from the set of all policies  $\Pi$  such that  $\forall s \in S, \forall \pi \in \Pi: V^{\pi^*}(s) \geq V^{\pi}(s)$ .

# MDP Planning

**MDP Planning problem:** Given  $M = (S, A, T, R, \gamma)$ , find a policy  $\pi^*$  from the set of all policies  $\Pi$  such that  $\forall s \in S, \forall \pi \in \Pi: V^{\pi^*}(s) \geq V^{\pi}(s)$ .

- Every MDP is guaranteed to have a deterministic, Markovian, stationary optimal policy.



# MDP Planning

**MDP Planning problem:** Given  $M = (S, A, T, R, \gamma)$ , find a policy  $\pi^*$  from the set of all policies  $\Pi$  such that  $\forall s \in S, \forall \pi \in \Pi: V^{\pi^*}(s) \geq V^{\pi}(s)$ .

- Every MDP is guaranteed to have a deterministic, Markovian, stationary optimal policy.
- An MDP can have more than one optimal policy.

# MDP Planning

**MDP Planning problem:** Given  $M = (S, A, T, R, \gamma)$ , find a policy  $\pi^*$  from the set of all policies  $\Pi$  such that  $\forall s \in S, \forall \pi \in \Pi: V^{\pi^*}(s) \geq V^{\pi}(s)$ .

- Every MDP is guaranteed to have a deterministic, Markovian, stationary optimal policy.
- An MDP can have more than one optimal policy.
- However, the value function of every optimal policy is the same, unique “optimal value function”  $V^*$ .

# Markov Decision Problems

## 1. Definitions

- ▶ Markov Decision Problem
- ▶ Policy
- ▶ Value Function

## 2. MDP planning

## 3. Alternative formulations

## 4. Applications

## 5. Policy Evaluation

# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

- You might encounter alternative definitions of  $R$ ,  $T$ .

# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

- You might encounter alternative definitions of  $R$ ,  $T$ .
- Sometimes  $R(s, a, s')$  is taken as a random variable bounded in  $[-R_{\max}, R_{\max}]$ .

# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

- You might encounter alternative definitions of  $R$ ,  $T$ .
- Sometimes  $R(s, a, s')$  is taken as a random variable bounded in  $[-R_{\max}, R_{\max}]$ .
- Sometimes there is a reward  $R(s, a)$  given on taking action  $a$  from state  $s$ , regardless of next state  $s'$ .

# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

- You might encounter alternative definitions of  $R$ ,  $T$ .
- Sometimes  $R(s, a, s')$  is taken as a random variable bounded in  $[-R_{\max}, R_{\max}]$ .
- Sometimes there is a reward  $R(s, a)$  given on taking action  $a$  from state  $s$ , regardless of next state  $s'$ .
- Sometimes there is a reward  $R(s')$  given on reaching next state  $s'$ , regardless of start state  $s$  and action  $a$ .



# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

- You might encounter alternative definitions of  $R$ ,  $T$ .
- Sometimes  $R(s, a, s')$  is taken as a random variable bounded in  $[-R_{\max}, R_{\max}]$ .
- Sometimes there is a reward  $R(s, a)$  given on taking action  $a$  from state  $s$ , regardless of next state  $s'$ .
- Sometimes there is a reward  $R(s')$  given on reaching next state  $s'$ , regardless of start state  $s$  and action  $a$ .
- Sometimes  $T$  and  $R$  are combined into a single function  $\mathbb{P}\{s', r | s, a\}$  for  $s' \in S, r \in [-R_{\max}, R_{\max}]$ .

# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

- You might encounter alternative definitions of  $R$ ,  $T$ .
- Sometimes  $R(s, a, s')$  is taken as a **random variable** bounded in  $[-R_{\max}, R_{\max}]$ .
- Sometimes there is a reward  $R(s, a)$  given on taking action  $a$  from state  $s$ , regardless of next state  $s'$ .
- Sometimes there is a reward  $R(s')$  given on reaching next state  $s'$ , regardless of start state  $s$  and action  $a$ .
- Sometimes  $T$  and  $R$  are **combined** into a single function  $\mathbb{P}\{s', r | s, a\}$  for  $s' \in S, r \in [-R_{\max}, R_{\max}]$ .
- Some authors **minimise cost** rather than **maximise reward**.

# Reward and Transition Functions

- We had assumed

$$T : S \times A \times S \rightarrow [0, 1], R : S \times A \times S \rightarrow [-R_{\max}, R_{\max}].$$

- You might encounter alternative definitions of  $R$ ,  $T$ .
- Sometimes  $R(s, a, s')$  is taken as a **random variable** bounded in  $[-R_{\max}, R_{\max}]$ .
- Sometimes there is a reward  $R(s, a)$  given on taking action  $a$  from state  $s$ , regardless of next state  $s'$ .
- Sometimes there is a reward  $R(s')$  given on reaching next state  $s'$ , regardless of start state  $s$  and action  $a$ .
- Sometimes  $T$  and  $R$  are **combined** into a single function  $\mathbb{P}\{s', r | s, a\}$  for  $s' \in S, r \in [-R_{\max}, R_{\max}]$ .
- Some authors **minimise cost** rather than **maximise reward**.
- It is relatively straightforward to handle all these variations.

# Episodic Tasks


- We considered **continuing** tasks, in which trajectories are infinitely long.

# Episodic Tasks

- We considered **continuing** tasks, in which trajectories are infinitely long.
- **Episodic tasks** have a special **sink/terminal state**  $s_{\top}$  from which there are no outgoing transitions on rewards.


# Episodic Tasks

- We considered **continuing** tasks, in which trajectories are infinitely long.
- **Episodic tasks** have a special **sink/terminal state**  $s_T$  from which there are no outgoing transitions on rewards.



# Episodic Tasks


- We considered **continuing** tasks, in which trajectories are infinitely long.
- **Episodic tasks** have a special **sink/terminal state**  $s_T$  from which there are no outgoing transitions on rewards.



- Additionally, from every non-terminal state and for every policy, there is a non-zero probability of reaching the terminal state in a finite number of steps.

# Episodic Tasks

- We considered **continuing** tasks, in which trajectories are infinitely long.
- **Episodic tasks** have a special **sink/terminal state**  $s_T$  from which there are no outgoing transitions on rewards.



- Additionally, from every non-terminal state and for every policy, there is a non-zero probability of reaching the terminal state in a finite number of steps.
- Hence, trajectories or **episodes** almost surely terminate after a finite number of steps.



# Definition of Values

- We defined  $V^\pi(s)$  as an **Infinite discounted reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s].$$

# Definition of Values

- We defined  $V^\pi(s)$  as an **Infinite discounted reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s].$$

There are other choices.

- **Total reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + r^1 + r^2 + \dots | s^0 = s].$$

Can only be used on episodic tasks.

# Definition of Values

- We defined  $V^\pi(s)$  as an **Infinite discounted reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s].$$

There are other choices.

- **Total reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + r^1 + r^2 + \dots | s^0 = s].$$

Can only be used on episodic tasks.

- **Finite horizon reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + r^1 + r^2 + \dots + r^{T-1} | s^0 = s].$$

Horizon  $T \geq 1$  specified, rather than  $\gamma$ .

Optimal policies for this setting need not be stationary.

# Definition of Values

- We defined  $V^\pi(s)$  as an **Infinite discounted reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s].$$

There are other choices.

- **Total reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + r^1 + r^2 + \dots | s^0 = s].$$

Can only be used on episodic tasks.

- **Finite horizon reward**:

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + r^1 + r^2 + \dots + r^{T-1} | s^0 = s].$$

Horizon  $T \geq 1$  specified, rather than  $\gamma$ .

Optimal policies for this setting need not be stationary.

- **Average reward** (withholding some technical details):

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi \left[ \lim_{m \rightarrow \infty} \frac{r^0 + r^1 + \dots + r^{m-1}}{m} \mid s^0 = s \right].$$

# Markov Decision Problems

## 1. Definitions

- ▶ Markov Decision Problem
- ▶ Policy
- ▶ Value Function

## 2. MDP planning

## 3. Alternative formulations

## 4. Applications

## 5. Policy Evaluation

# Controlling a Helicopter (Ng *et al.*, 2003)

- Episodic or continuing task? What are  $S$ ,  $A$ ,  $T$ ,  $R$ ,  $\gamma$ ?




[1]

1. <https://www.publicdomainpictures.net/pictures/20000/velka/police-helicopter-8712919948643Mk.jpg>.

17/26

# Succeeding at Chess

- Episodic or continuing task? What are  $S$ ,  $A$ ,  $T$ ,  $R$ ,  $\gamma$ ?



[1]

1. <https://www.publicdomainpictures.net/pictures/80000/velka/chess-board-and-pieces.jpg>. 18/26

# Preventing Forest Fires (Lauer *et al.*, 2017)

- Episodic or continuing task? What are  $S$ ,  $A$ ,  $T$ ,  $R$ ,  $\gamma$ ?




[1]

1. <https://www.publicdomainpictures.net/pictures/270000/velka/firemen-1533752293Zsu.jpg>. 19/26



# A Familiar MDP?


- Single state.  $k$  actions.
- For  $a \in A$ , treat  $R(s, a, s')$  as a **random** variable.



Annotation: "probability, reward distribution".

# A Familiar MDP?

- Single state.  $k$  actions.
- For  $a \in A$ , treat  $R(s, a, s')$  as a **random** variable.




Annotation: "probability, reward distribution".

- Such an MDP is called a

# A Familiar MDP?

- Single state.  $k$  actions.
- For  $a \in A$ , treat  $R(s, a, s')$  as a **random** variable.



Annotation: "probability, reward distribution".

- Such an MDP is called a **multi-armed bandit**!

# Markov Decision Problems

## 1. Definitions

- ▶ Markov Decision Problem
- ▶ Policy
- ▶ Value Function

## 2. MDP planning

## 3. Alternative formulations

## 4. Applications

## 5. Policy Evaluation

# Structure of State Values

Let us investigate state values. For  $\pi \in \Pi$ ,  $s \in S$ :

$$V^\pi(s) \stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s]$$

# Structure of State Values

Let us investigate state values. For  $\pi \in \Pi, s \in S$ :

$$\begin{aligned} V^\pi(s) &\stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s, s^1 = s'] \end{aligned}$$

# Structure of State Values

Let us investigate state values. For  $\pi \in \Pi, s \in S$ :

$$\begin{aligned} V^\pi(s) &\stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s, s^1 = s'] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^0 | s^0 = s, s^1 = s'] \\ &\quad + \gamma \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^1 + \gamma r^2 + \dots | s^0 = s, s^1 = s'] \end{aligned}$$

# Structure of State Values

Let us investigate state values. For  $\pi \in \Pi, s \in S$ :

$$\begin{aligned} V^\pi(s) &\stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s, s^1 = s'] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^0 | s^0 = s, s^1 = s'] \\ &\quad + \gamma \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^1 + \gamma r^2 + \dots | s^0 = s, s^1 = s'] \\ &= \sum_{s' \in S} T(s, \pi(s), s') R(s, \pi(s), s') \\ &\quad + \gamma \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^1 + \gamma r^2 + \dots | s^1 = s'] \end{aligned}$$



# Structure of State Values

Let us investigate state values. For  $\pi \in \Pi, s \in S$ :

$$\begin{aligned} V^\pi(s) &\stackrel{\text{def}}{=} \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s, s^1 = s'] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^0 | s^0 = s, s^1 = s'] \\ &\quad + \gamma \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^1 + \gamma r^2 + \dots | s^0 = s, s^1 = s'] \\ &= \sum_{s' \in S} T(s, \pi(s), s') R(s, \pi(s), s') \\ &\quad + \gamma \sum_{s' \in S} T(s, \pi(s), s') \mathbb{E}_\pi[r^1 + \gamma r^2 + \dots | s^1 = s'] \\ &= \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}. \end{aligned}$$

# Bellman's Equations

For  $\pi \in \Pi, s \in S$ :

$$V^\pi(s) = \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}.$$

# Bellman's Equations

For  $\pi \in \Pi, s \in S$ :

$$V^\pi(s) = \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}.$$

- Recall that  $S = \{s_1, s_2, \dots, s_n\}$ .

# Bellman's Equations

For  $\pi \in \Pi$ ,  $s \in S$ :

$$V^\pi(s) = \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}.$$

- Recall that  $S = \{s_1, s_2, \dots, s_n\}$ .
- $n$  equations,  $n$  unknowns— $V^\pi(s_1), V^\pi(s_2), \dots, V^\pi(s_n)$ .

# Bellman's Equations

For  $\pi \in \Pi$ ,  $s \in S$ :

$$V^\pi(s) = \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}.$$

- Recall that  $S = \{s_1, s_2, \dots, s_n\}$ .
- $n$  equations,  $n$  unknowns— $V^\pi(s_1), V^\pi(s_2), \dots, V^\pi(s_n)$ .
- Linear!

# Bellman's Equations

For  $\pi \in \Pi, s \in S$ :

$$V^\pi(s) = \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}.$$

- Recall that  $S = \{s_1, s_2, \dots, s_n\}$ .
- $n$  equations,  $n$  unknowns— $V^\pi(s_1), V^\pi(s_2), \dots, V^\pi(s_n)$ .
- Linear!
- Guaranteed to have a unique solution if  $\gamma < 1$ .

# Bellman's Equations

For  $\pi \in \Pi, s \in S$ :

$$V^\pi(s) = \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}.$$

- Recall that  $S = \{s_1, s_2, \dots, s_n\}$ .
- $n$  equations,  $n$  unknowns— $V^\pi(s_1), V^\pi(s_2), \dots, V^\pi(s_n)$ .
- Linear!
- Guaranteed to have a unique solution if  $\gamma < 1$ .
- If task is episodic, guaranteed to have a unique solution even if  $\gamma = 1$ , after we fix  $V^\pi(s^\top) = 0$ .

# Bellman's Equations

For  $\pi \in \Pi, s \in S$ :

$$V^\pi(s) = \sum_{s' \in S} T(s, \pi(s), s') \{R(s, \pi(s), s') + \gamma V^\pi(s')\}.$$

- Recall that  $S = \{s_1, s_2, \dots, s_n\}$ .
- $n$  equations,  $n$  unknowns— $V^\pi(s_1), V^\pi(s_2), \dots, V^\pi(s_n)$ .
- Linear!
- Guaranteed to have a unique solution if  $\gamma < 1$ .
- If task is episodic, guaranteed to have a unique solution even if  $\gamma = 1$ , after we fix  $V^\pi(s^\top) = 0$ .
- **Policy evaluation**: computing  $V^\pi$  for a given policy  $\pi$ .



# Are We Done with this Topic?

# Are We Done with this Topic?

- We claimed that among all the policies for a given MDP, there must be an optimal policy  $\pi^*$ .

# Are We Done with this Topic?

- We claimed that among all the policies for a given MDP, there must be an optimal policy  $\pi^*$ .
- Now you know how to compute the value function of any given policy  $\pi$ .

# Are We Done with this Topic?

- We claimed that among all the policies for a given MDP, there must be an optimal policy  $\pi^*$ .
- Now you know how to compute the value function of any given policy  $\pi$ .
- Can you put the two ideas together and construct an algorithm to find  $\pi^*$ ?

# Are We Done with this Topic?

- We claimed that among all the policies for a given MDP, there must be an optimal policy  $\pi^*$ .
- Now you know how to compute the value function of any given policy  $\pi$ .
- Can you put the two ideas together and construct an algorithm to find  $\pi^*$ ?
- **Yes!** Evaluate each policy and identify one that has a value function dominating all the others'.

# Are We Done with this Topic?

- We claimed that among all the policies for a given MDP, there must be an optimal policy  $\pi^*$ .
- Now you know how to compute the value function of any given policy  $\pi$ .
- Can you put the two ideas together and construct an algorithm to find  $\pi^*$ ?
- **Yes!** Evaluate each policy and identify one that has a value function dominating all the others'.
- This approach needs  $\text{poly}(n, k) \cdot k^n$  arithmetic operations. We hope to be more efficient (wait for next week).

# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots \mid s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots \mid s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

$Q^\pi(s, a)$  is the expected long-term reward from starting at  $s$ , taking  $a$  at  $t = 0$ , and following  $\pi$  for  $t \geq 1$ .



# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots \mid s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

$Q^\pi(s, a)$  is the expected long-term reward from starting at  $s$ , taking  $a$  at  $t = 0$ , and following  $\pi$  for  $t \geq 1$ .

$Q^\pi : S \times A \rightarrow \mathbb{R}$  is called the **action value function** of  $\pi$ .

# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots \mid s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

$Q^\pi(s, a)$  is the expected long-term reward from starting at  $s$ , taking  $a$  at  $t = 0$ , and following  $\pi$  for  $t \geq 1$ .

$Q^\pi : S \times A \rightarrow \mathbb{R}$  is called the **action value function** of  $\pi$ .

Observe that  $Q^\pi$  satisfies, for  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) = \sum_{s' \in S} T(s, a, s') \{R(s, a, s') + \gamma V^\pi(s')\}.$$

# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

$Q^\pi(s, a)$  is the expected long-term reward from starting at  $s$ , taking  $a$  at  $t = 0$ , and following  $\pi$  for  $t \geq 1$ .

$Q^\pi : S \times A \rightarrow \mathbb{R}$  is called the **action value function** of  $\pi$ .

Observe that  $Q^\pi$  satisfies, for  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) = \sum_{s' \in S} T(s, a, s') \{R(s, a, s') + \gamma V^\pi(s')\}.$$

For  $\pi \in \Pi$ ,  $s \in S$ :  $Q^\pi(s, \pi(s)) = V^\pi(s)$ .

# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots \mid s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

$Q^\pi(s, a)$  is the expected long-term reward from starting at  $s$ , taking  $a$  at  $t = 0$ , and following  $\pi$  for  $t \geq 1$ .

$Q^\pi : S \times A \rightarrow \mathbb{R}$  is called the **action value function** of  $\pi$ .

Observe that  $Q^\pi$  satisfies, for  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) = \sum_{s' \in S} T(s, a, s') \{R(s, a, s') + \gamma V^\pi(s')\}.$$

For  $\pi \in \Pi$ ,  $s \in S$ :  $Q^\pi(s, \pi(s)) = V^\pi(s)$ .

- $Q^\pi$  needs  $O(n^2k)$  operations to compute if  $V^\pi$  is available.

# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

$Q^\pi(s, a)$  is the expected long-term reward from starting at  $s$ , taking  $a$  at  $t = 0$ , and following  $\pi$  for  $t \geq 1$ .

$Q^\pi : S \times A \rightarrow \mathbb{R}$  is called the **action value function** of  $\pi$ .

Observe that  $Q^\pi$  satisfies, for  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) = \sum_{s' \in S} T(s, a, s') \{R(s, a, s') + \gamma V^\pi(s')\}.$$

For  $\pi \in \Pi$ ,  $s \in S$ :  $Q^\pi(s, \pi(s)) = V^\pi(s)$ .

- $Q^\pi$  needs  $O(n^2k)$  operations to compute if  $V^\pi$  is available.
- All optimal policies have the same action value function  $Q^*$ .

# Action Value Function

- For  $\pi \in \Pi$ ,  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) \stackrel{\text{def}}{=} \mathbb{E}[r^0 + \gamma r^1 + \gamma^2 r^2 + \dots | s^0 = s; a^0 = a; a^t = \pi(s^t) \text{ for } t \geq 1].$$

$Q^\pi(s, a)$  is the expected long-term reward from starting at  $s$ , taking  $a$  at  $t = 0$ , and following  $\pi$  for  $t \geq 1$ .

$Q^\pi : S \times A \rightarrow \mathbb{R}$  is called the **action value function** of  $\pi$ .

Observe that  $Q^\pi$  satisfies, for  $s \in S$ ,  $a \in A$ :

$$Q^\pi(s, a) = \sum_{s' \in S} T(s, a, s') \{R(s, a, s') + \gamma V^\pi(s')\}.$$

For  $\pi \in \Pi$ ,  $s \in S$ :  $Q^\pi(s, \pi(s)) = V^\pi(s)$ .

- $Q^\pi$  needs  $O(n^2k)$  operations to compute if  $V^\pi$  is available.
- All optimal policies have the same action value function  $Q^*$ .
- We will find use for  $Q^\pi$  and  $Q^*$  next week.

# Markov Decision Problems

## 1. Definitions

- ▶ Markov Decision Problem
- ▶ Policy
- ▶ Value Function

## 2. MDP planning

## 3. Alternative formulations

## 4. Applications

## 5. Policy Evaluation