Does the Virtual Tumor Board Need a Board? A Call-Matched Evaluation of Specialist Multi-Agent LLM Deliberation on Oncology Exam Questions

Vibhum Sharma
Department of Information Technology, Indian Institute of Information Technology Allahabad, India

October 24, 2026

Abstract

Multi-agent "virtual tumor board" systems built from large language models (LLMs) are reported to outperform single models, but published comparisons give the multi-agent system more inference calls than its baseline, or a different backbone model. We test whether specialist deliberation adds accuracy once the backbone and the number of model calls are held fixed. With one open model (Qwen2.5-7B-Instruct), we compare a four-specialist board (medical, surgical and radiation oncologist, pathologist; two rounds plus a chair; nine calls) against self-consistency with nine samples, greedy chain-of-thought, and an identical board of generic agents, on oncology items from MedQA-USMLE and MedMCQA. The protocol, decision rules and power limits were fixed before any model output was produced. [PENDING: primary result: accuracy difference, 95% CI, McNemar p, minimum detectable effect] [PENDING: role ablation and discussion results; error-propagation rates; cost per item]. [PENDING: one-sentence conclusion bounded to exam accuracy and this model].

1 Introduction

Multidisciplinary tumor boards bring oncologists, surgeons, radiologists and pathologists together to decide treatment, and virtual tumor boards extend that meeting to settings with few specialists. A growing line of work proposes LLM systems that imitate this structure: several role-specialised agents analyse a case, discuss, and aggregate a recommendation [1, 2, 3]. Reported gains are large. EvoMDT, for example, reaches 0.86 accuracy on MedQA against 0.76 for Llama-3-70B and 0.79 for Claude-3 [1].

These comparisons share a confound. A multi-agent system makes many model calls per question, while its baselines usually make one. In EvoMDT the board also runs on a different backbone (DeepSeek V3/R1) from the single-model baselines it is compared with [1]. Outside oncology, the evidence on whether discussion beats simply sampling one model several times is mixed. A strong single agent can match multi-agent discussion [4]. Debate does not reliably beat self-consistency on medical and general multiple-choice questions [5], yet small gains over self-consistency at equal compute have been reported on general reasoning benchmarks [6]. The closest oncology studies leave the budget question open. One found that specialist roles improve a discussion-based board but not a voting board, using 31 private head-and-neck cases, an LLM judge, and methods with different numbers of calls [3]. Another found that a gynecologic-oncology agent team beat single-prompt and debate baselines, including universal self-consistency, without reporting matched call or token budgets [7].

This paper asks a narrow question. **RQ1:** with the backbone fixed, is a four-specialist board more accurate than self-consistency with the same number of calls on oncology exam questions? **RQ2:** does replacing the specialists with generic agents change board accuracy? **RQ3:** does the discussion round change the board's vote, and how often does it turn a correct member wrong versus a wrong member right?

Our contributions are limited and stated in advance: (i) a call-matched comparison on public benchmarks with an objective metric and a small open model that runs on free GPUs; (ii) a role ablation and a discussion ablation taken from the same runs; (iii) spontaneous error-propagation rates; and (iv) a pre-registered protocol, code and logs. We do not propose a new architecture and make no claim about real tumor-board decisions.

2 Related Work

AI and tumor boards. Early evaluations compared rule-based decision support with tumor-board decisions; for example, Watson for Oncology agreed with a gastric-cancer board in 86.96% of 322 patients [8]. LLM-era work moved to multi-agent systems that assign specialist roles and aggregate their outputs, by consensus protocols [1], consensus matrices with reinforcement learning [2], moderated group chat [3], fixed-size agent teams [7], or contribution-aware aggregation over partitioned patient data [9]. These systems report gains over their baselines,

which in most cases make fewer model calls. MTBBench evaluates agents on multimodal, longitudinal molecular-tumor-board tasks [10]; our text-only exam setting is far simpler.

Medical multi-agent frameworks. MedAgents organises role-playing experts into a five-stage discussion [11]. MDAgents assigns a solo or group structure according to question complexity [12]; its comparison includes a self-consistency baseline [TO VERIFY: read Table 2 of [12]]. A later benchmark reports that agent frameworks do not consistently beat strong reasoning models and add computational overhead [13] [TO VERIFY: confirm in the paper's results table].

Discussion versus sampling. Chain-of-thought prompting [14, 15] and self-consistency, a majority vote over sampled reasoning paths [16], are the natural single-model baselines. Studies that hold prompts or compute comparable report that discussion offers little over a strong single agent [4, 5], with modest gains in some compute-matched settings [6].

Roles. Adding personas to a single model's system prompt does not improve performance on factual questions [17], whereas role specialisation helped a discussion-based oncology board [3]. Our role ablation tests which pattern holds in a call-matched board.

3 Methodology

3.1 Task and data

Items are multiple-choice questions scored by exact match of the chosen letter. The primary set pools the oncology items of the MedQA-USMLE 5-option test split [18] and the MedMCQA development split [19]. A frozen keyword filter selects items whose stem or correct option concerns cancer. It excludes sentences about relatives, negated mentions and three non-oncology phrases. On MedQA it selects 97 of 1,273 items; the source file's SHA-256 is recorded. MedMCQA keeps single-answer items only, deduplicated, with the same filter plus the topic field; its size is [TO VERIFY: n after the Kaggle build]. Because MedQA items have five options and MedMCQA items four, chance levels differ; results are therefore reported per source as well as pooled. The full MedQA test (1,273 items) is a secondary set, and the 4-option MedQA variant serves only to anchor the baseline against published numbers.

3.2 Methods compared

All arms use the same model, answer instruction (reason briefly, then end with "Answer: <letter>"), sampling settings (temperature 0.7, top-p 0.95, at most 512 new tokens) and parser.

- **CoT:** one greedy call [15].
- **Self-consistency (SC@k):** 15 samples in one request, plurality vote over the first $k \in \{1, 3, 5, 9, 15\}$ [16]. SC@9 is the call-matched comparator.
- **Specialist board:** four agents with system roles (medical, surgical and radiation oncologist, pathologist) answer independently (round 1). Each then reads the other three assessments and may revise (round 2). A greedy chair reads the final assessments and decides. That is $4 + 4 + 1 = 9$ calls.
- **Generic board (ablation):** the identical pipeline with four identical "experienced physician" agents.

Fig. 1 shows the pipeline. The stored transcripts also give the round-1 vote and the round-2 vote of each board, so discussion and chair effects are measured without extra runs.

3.3 Statistical analysis

The primary comparison is specialist board versus SC@9 on the primary set (seed 0), with an exact two-sided McNemar test [20] at $\alpha = 0.05$. A difference is called meaningful only if it is significant *and* at least 2 percentage points. Three secondary comparisons are Holm-adjusted as one family [21]: specialist vs generic board, round-2 vote vs round-1 vote, and specialist board vs CoT. Accuracy differences carry 95% paired item-bootstrap intervals (10,000 resamples). For each non-significant comparison we report the smallest difference the test could detect with 80% power, computed exactly from n and the observed share of discordant items. Member answer changes from round 1 to round 2 are summarised as correct→wrong and wrong→correct rates, with intervals from resampling items. Unparseable answers count as wrong, and parse-failure and truncation rates are reported per arm. Matching calls does not match tokens: board members in round 2 and the chair read the other agents' texts. We therefore report API-equivalent tokens per item for every comparison, and add a pre-registered exploratory comparison against SC@15, a higher-budget sampling arm.

4 Experimental Setup

The model is Qwen2.5-7B-Instruct [22] (Apache-2.0) served with vLLM [23] in fp16 on two NVIDIA T4 GPUs (Kaggle) [TO VERIFY: hardware and library versions from the run logs]. Seeds 0, 1 and 2 are run on the primary set and seed 0 on the secondary set; seed 0 was pre-registered as the primary analysis and the other seeds are reported as sensitivity. Every call's seed is derived from the run seed, item and role. The protocol, including datasets, comparisons, thresholds and seed plan, was frozen before any model output (version 1.2; the change




Figure 1: Study pipeline (protocol v1.2). All arms share the model, prompt format, sampling settings and parser. CoT uses 1 call per item; SC@9, the specialist board and the generic board use 9.

Table 1: Main results on the primary oncology set (seed 0). **PENDING: no real model output yet.**

Method	Calls	Acc. (95% CI)	Δ vs SC@9
CoT (greedy)	1	–	–
SC@9	9	–	–
Specialist board	9	–	–
Generic board	9	–	–

from 1.1 added the SC@15 comparison and was made before any run). Runs were gated on four checks: an overlap check between debugging and test items, a smoke test, parse failures of at most 3%, and CoT accuracy above the accuracy of always choosing the most frequent correct letter (27.8% on the MedQA oncology subset; [TO VERIFY: MedMCQA floor]). Prompts were developed only on 20 MedQA training items. Code, configuration and logs are available in the project repository [TO VERIFY: public repository URL].

5 Results

[PENDING: All results. Tables 1 and 2 are generated from `results/` by `scripts/make_paper_tables.py`; nothing is typed by hand.]

5.1 RQ1: specialist board vs self-consistency at equal calls

[PENDING: difference, CI, p, MDE; reading per the pre-registered decision table]

5.2 RQ2 and RQ3: roles and discussion

[PENDING: role ablation; round-2 vs round-1 vote; correct→wrong and wrong→correct rates; chair overrides]

5.3 Cost and robustness

[PENDING: tokens and seconds per item; seeds 1–2; MedQA vs MedMCQA; stem-only and human-audited subsets]

6 Discussion

[PENDING: written only after results, following the interpretation plan fixed on 24 Oct 2026]

7 Limitations

Exam multiple-choice questions are a proxy for, not a sample of, tumor-board decisions: there are no patient records, images, pathology slides or guidelines in context. The oncology scope is defined by a keyword filter, so a human audit and a stem-only sensitivity set are reported alongside it. Only one 7B model is tested, so nothing generalises to other models. The MedQA oncology subset alone can detect only large differences (about 12–15 points with 80% power), which is why sources are pooled and why every null is reported with its detectable effect. Public benchmarks may appear in the model's pretraining data. This affects all arms equally but inflates absolute accuracy. Finally, call matching equalises the number of calls, not tokens; token-matched readings are reported separately.

Table 2: Pre-specified paired comparisons. **PENDING: no real model output yet.**

Role	Comparison	Δ (pp)	95% CI	p_{Holm}	MDE (pp)
Primary	Specialist board vs SC@9	–	–	–	–
Secondary	Specialist vs generic board	–	–	–	–
Secondary	Round-2 vote vs round-1 vote	–	–	–	–
Secondary	Specialist board vs CoT	–	–	–	–

8 Conclusion

[PENDING: one paragraph, bounded to exam accuracy, this model and this budget]

AI assistance statement

Claude (Anthropic) was used as a supervised research assistant: literature search and verification, gap analysis, code generation and debugging, test writing, statistical tooling and drafting. The bibliographic metadata of every reference was checked against its source; two literature statements taken from AI-generated summaries are marked for verification in the text. Every code path was run and tested, and every number in the results tables is generated from logged model outputs. The decisions, verification steps and AI errors that were caught are recorded in the project's decision log and AI-assistance report.

References

[1] Qicai Liu, Zhichao Hu, Tao Huang, Yupeng Niu, Xinche Zhang, Shanwu Ma, Chutong Lin, Goh Kim Huat, Hyeokkoo Eric Kwon, Feng Gao, Xianfu Sun, Zhitao Ying, and Guangliang Qiang. EvoMDT: a self-evolving multi-agent system for structured clinical decision-making in multi-cancer. *npj Digital Medicine*, 2025. Article in press.

[2] Xudong Han, Xianglun Gao, Xiaoyi Qu, and Zhenyu Yu. Multi-agent medical decision consensus matrix system: An intelligent collaborative framework for oncology MDT consultations. arXiv:2512.14321, 2025.

[3] Jaesik Kim, Byounghan Lee, Kyung-Ah Sohn, Dokyoon Kim, and Young Chan Lee. Evaluation of multi-agent LLMs in multidisciplinary team decision-making for challenging cancer cases. In *Proceedings of the 10th Machine Learning for Healthcare Conference*, volume 298 of *Proceedings of Machine Learning Research*, pages 1–31, 2025.

[4] Qineng Wang, Zihao Wang, Ying Su, Hanghang Tong, and Yangqiu Song. Rethinking the bounds of LLM reasoning: Are multi-agent discussions the key? In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6106–6131. Association for Computational Linguistics, 2024.

[5] Andries Smit, Paul Duckworth, Nathan Grinsztajn, Thomas D. Barrett, and Arnu Pretorius. Should we be going MAD? A look at multi-agent debate strategies for LLMs. arXiv:2311.17371 (v3), 2023.

[6] Florian Valentin Wunderlich, Lars Benedikt Kaesberg, Jan Philip Wahle, Terry Ruas, and Bela Gipp. Multi-agent reasoning improves compute efficiency: Pareto-optimal test-time scaling. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (ACL 2026), Student Research Workshop*, pages 1–14, 2026.

[7] Warisijiang Kuerbanjiang, Xinyu Wang, Yiershatijiang Jiamaliding, Musitapa Maimaitiaili, and Yuexiong Yi. Multidisciplinary large language model agent teams for precision oncology enhance complex gynecologic oncology decision support. medRxiv preprint, 2025.

[8] Yong-Eun Park and Hyundong Chae. The fidelity of artificial intelligence to multidisciplinary tumor board recommendations for patients with gastric cancer: A retrospective study. *Journal of Gastrointestinal Cancer*, 55:365–372, 2024.

[9] Yichen Wu, Kailong Fan, Sangjoon Park, Yuhan Liu, Zhiyi Shi, Sekeun Kim, Dania Daye, Hana Farzaneh, Xiang Li, Raul Uppot, Yujin Oh, and Quanzheng Li. CoMMa: Contribution-aware medical multi-agents for decentralized oncology decision support. arXiv:2602.09159, 2026.

[10] Kiril Vasilev, Alexandre Misrahi, Eeshaan Jain, Phil F. Cheng, Petros Liakopoulos, Olivier Michielin, Michael Moor, and Charlotte Bunne. MTBBench: A multimodal sequential clinical decision-making benchmark in oncology. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks)*, 2025.

[11] Xiangru Tang, Anni Zou, Zhuosheng Zhang, Ziming Li, Yilun Zhao, Xingyao Zhang, Arman Cohan, and Mark Gerstein. MedAgents: Large language models as collaborators for zero-shot medical reasoning. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 599–621. Association for Computational Linguistics, 2024.

[12] Yubin Kim, Chanwoo Park, Hyewon Jeong, Yik Siu Chan, Xuhai Xu, Daniel McDuff, Hyeonhoon Lee, Marzyeh Ghassemi, Cynthia Breazeal, and Hae Won Park. MDAgents: An adaptive collaboration of LLMs for medical decision-making. In *Advances in Neural Information Processing Systems*, volume 37, 2024.

[13] Yanjun Shao, Xiangru Tang, Jiwoong Sohn, Jiapeng Chen, Yuxuan Liao, Jiayi Zhang, Jinyu Xiang, Fang Wu, Yilun Zhao, Chenglin Wu, Wenqi Shi, Arman Cohan, and Mark Gerstein. MedicalAgentsBench for complex medical reasoning: Comparing internalized reasoning models versus externalized agent-based frameworks. arXiv:2503.07459, 2025. Earlier versions titled "MedAgentsBench: Benchmarking Thinking Models and Agent Frameworks for Complex Medical Reasoning".

[14] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

[15] Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. In *Advances in Neural Information Processing Systems*, volume 35, 2022.

[16] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *International Conference on Learning Representations (ICLR)*, 2023.

[17] Mingqian Zheng, Jiaxin Pei, Lajanugen Logeswaran, Moontae Lee, and David Jurgens. When "a helpful assistant" is not really helpful: Personas in system prompts do not improve performances of large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15126–15154. Association for Computational Linguistics, 2024.

[18] Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? A large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 11(14):6421, 2021.

[19] Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. MedMCQA: A large-scale multi-subject multi-choice dataset for medical domain question answering. In *Proceedings of the Conference on Health, Inference, and Learning*, volume 174 of *Proceedings of Machine Learning Research*, pages 248–260, 2022.

[20] Quinn McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157, 1947.

[21] Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979.

[22] Qwen Team, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, et al. Qwen2.5 technical report. arXiv:2412.15115, 2024.

[23] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with PagedAttention. In *Symposium on Operating Systems Principles (SOSP 2023)*, 2023.