Motion control using Pulse Width Modulation in Firebird V

e-Yantra Team
Embedded Real-Time Systems Lab
Indian Institute of Technology-Bombay

IIT Bombay
January 16, 2016

Agenda for Discussion

1. Pulse Width Modulation
   - Duty Cycle
   - Motion Control Using Pulse Width Modulation in Firebird V
2. Registers
   - Timer/Counter 5(TCNT5)
   - Output Compare Register 5
   - Timer/Counter Control Register (TCCR5A and TCCR5B)
     - TCCR5A
     - TCCR5B
3. Summary
4. Program

Pulse Width Modulation

Pulse Width Modulation

1. Pulse Width Modulation (PWM), is a method of transmitting information on a series of pulses

Pulse Width Modulation

1. Pulse Width Modulation (PWM), is a method of transmitting information on a series of pulses

2. The data that is being transmitted is encoded on the width of these pulses to control the amount of power being sent to a load

Pulse Width Modulation

1. Pulse Width Modulation (PWM), is a method of transmitting information on a series of pulses
2. The data that is being transmitted is encoded on the width of these pulses to control the amount of power being sent to a load
3. Examples: Electric stoves, Lamp dimmers, and Robotic Servos

Pulse Width Modulation

1. Pulse Width Modulation (PWM), is a method of transmitting information on a series of pulses
2. The data that is being transmitted is encoded on the width of these pulses to control the amount of power being sent to a load
3. Examples: Electric stoves, Lamp dimmers, and Robotic Servos

Pulse Width Modulation

1. Pulse Width Modulation (PWM), is a method of transmitting information on a series of pulses
2. The data that is being transmitted is encoded on the width of these pulses to control the amount of power being sent to a load
3. Examples: Electric stoves, Lamp dimmers, and Robotic Servos

Duty Cycle

Duty Cycle



Duty Cycle



✓ The signal remains "ON" for some time and "OFF" for some time.

Duty Cycle



- ✓ The signal remains "ON" for some time and "OFF" for some time.
- ✓ Ton = Time the output remains high.

Duty Cycle



- ✓ The signal remains "ON" for some time and "OFF" for some time.
- ✓ Ton = Time the output remains high.
- ✓ Toff = Time the output remains Low.

Duty Cycle



- ✓ The signal remains "ON" for some time and "OFF" for some time.
- ✓ Ton = Time the output remains high.
- ✓ Toff = Time the output remains Low.
- ✓ When output is high the voltage is 5v

Duty Cycle



- ✓ The signal remains "ON" for some time and "OFF" for some time.
- ✓ Ton = Time the output remains high.
- ✓ Toff = Time the output remains Low.
- ✓ When output is high the voltage is 5v
- ✓ When output is low the voltage is 0v

Duty Cycle



- ✓ The signal remains "ON" for some time and "OFF" for some time.
- ✓ Ton = Time the output remains high.
- ✓ Toff = Time the output remains Low.
- ✓ When output is high the voltage is 5v
- ✓ When output is low the voltage is 0v
- ✓ Time Period(T) = Ton + Toff

Duty Cycle



- ✓ The signal remains "ON" for some time and "OFF" for some time.
- ✓ Ton = Time the output remains high.
- ✓ Toff = Time the output remains Low.
- ✓ When output is high the voltage is 5v
- ✓ When output is low the voltage is 0v
- ✓ Time Period(T) = Ton + Toff
- ✓ Duty Cycle = Ton/(Ton + Toff)

Duty Cycle



- ✓ The signal remains "ON" for some time and "OFF" for some time.
- ✓ Ton = Time the output remains high.
- ✓ Toff = Time the output remains Low.
- ✓ When output is high the voltage is 5v
- ✓ When output is low the voltage is 0v
- ✓ Time Period(T) = Ton + Toff
- ✓ Duty Cycle = Ton/(Ton + Toff)
- ✓ Duty Cycle = 50%

Duty Cycle (Contd..)

Duty Cycle (Contd..)



Duty Cycle (Contd..)



✓ Ton = Time the output remains high = 1

Duty Cycle (Contd..)



- ✓ Ton = Time the output remains high = 1
- ✓ Toff = Time the output remains Low = 7

Duty Cycle (Contd..)



- ✓ Ton = Time the output remains high = 1
- ✓ Toff = Time the output remains Low = 7
- ✓ Duty Cycle = 12.5%

Duty Cycle (Contd..)

Duty Cycle (Contd..)



Duty Cycle (Contd..)



✓ Ton = Time the output remains high = 6

Duty Cycle (Contd..)



- ✓ Ton = Time the output remains high = 6
- ✓ Toff = Time the output remains Low = 2

Duty Cycle (Contd..)



- ✓ Ton = Time the output remains high = 6
- ✓ Toff = Time the output remains Low = 2
- ✓ Duty Cycle = 75%

Pulse Width Modulation

- Pulse width waveform generated for motion control of Firebird V is:

Pulse Width Modulation

- Pulse width waveform generated for motion control of Firebird V is:



Pulse Width Modulation

- Pulse width waveform generated for motion control of Firebird V is:



- Its generation involves the use of following registers:

Pulse Width Modulation

- Pulse width waveform generated for motion control of Firebird V is:



- Its generation involves the use of following registers:
  - ✓ Timer/Counter register 5(TCNT5)

Pulse Width Modulation

- Pulse width waveform generated for motion control of Firebird V is:



- Its generation involves the use of following registers:
  - ✓ Timer/Counter register 5(TCNT5)
  - ✓ Output Comparator register 5(OCR5A and OCR5B)

Pulse Width Modulation

- Pulse width waveform generated for motion control of Firebird V is:



- Its generation involves the use of following registers:
  - ✓ Timer/Counter register 5(TCNT5)
  - ✓ Output Comparator register 5(OCR5A and OCR5B)
  - ✓ Timer Counter Comparator register(TCCR5A and TCCR5B)

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.
- The value in the Timer/Counter is compared with a reference value to generate PWM.

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.
- The value in the Timer/Counter is compared with a reference value to generate PWM.
- This value depends upon the resolution of Counter.

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.
- The value in the Timer/Counter is compared with a reference value to generate PWM.
- This value depends upon the resolution of Counter.
- For example, a 3 bit counter will have 8 values (i.e. 0-7). Its waveform will be seen as follows:

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.
- The value in the Timer/Counter is compared with a reference value to generate PWM.
- This value depends upon the resolution of Counter.
- For example, a 3 bit counter will have 8 values (i.e. 0-7). Its waveform will be seen as follows:

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.
- The value in the Timer/Counter is compared with a reference value to generate PWM.
- This value depends upon the resolution of Counter.
- For example, a 3 bit counter will have 8 values (i.e. 0-7). Its waveform will be seen as follows:



- For n-bit counter, maximum value $= 2^n - 1$.

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.
- The value in the Timer/Counter is compared with a reference value to generate PWM.
- This value depends upon the resolution of Counter.
- For example, a 3 bit counter will have 8 values (i.e. 0-7). Its waveform will be seen as follows:



- For n-bit counter, maximum value $= 2^n - 1$.
- The Timer/Counter 5 is a 16 bit register.

Timer/Counter 5 (TCNT5)

- The Timer/Counter is a register that increments its value after every clock cycle.
- The value in the Timer/Counter is compared with a reference value to generate PWM.
- This value depends upon the resolution of Counter.
- For example, a 3 bit counter will have 8 values (i.e. 0-7). Its waveform will be seen as follows:



- For n-bit counter, maximum value $= 2^n - 1$.
- The Timer/Counter 5 is a 16 bit register.
- We use it in 8-bit mode, for PWM generation.

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.
- This reference value is given in the Output Compare Register(OCR).

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.
- This reference value is given in the Output Compare Register(OCR).
- Output Compare Registers associated with Timer 5 for PWM generation:

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.
- This reference value is given in the Output Compare Register(OCR).
- Output Compare Registers associated with Timer 5 for PWM generation:

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.
- This reference value is given in the Output Compare Register(OCR).
- Output Compare Registers associated with Timer 5 for PWM generation: OCR5A, OCR5B and OCR5C.

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.
- This reference value is given in the Output Compare Register(OCR).
- Output Compare Registers associated with Timer 5 for PWM generation: OCR5A, OCR5B and OCR5C.
- For motion control of Firebird V, we use OCR5A and OCR5B registers

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.
- This reference value is given in the Output Compare Register(OCR).
- Output Compare Registers associated with Timer 5 for PWM generation: OCR5A, OCR5B and OCR5C.
- For motion control of Firebird V, we use OCR5A and OCR5B registers
- OCR5A is associated with the OC5A pin (PORTL.3). This pin is connected to the enable(EN2) pin of motor driver, which is associated with the left motor.

Output Compare Register (OCR5A, OCR5B and OCR5C)

- The value of the Timer/Counter 5 is constantly compared with a reference value.
- This reference value is given in the Output Compare Register(OCR).
- Output Compare Registers associated with Timer 5 for PWM generation: OCR5A, OCR5B and OCR5C.
- For motion control of Firebird V, we use OCR5A and OCR5B registers
- OCR5A is associated with the OC5A pin (PORTL.3). This pin is connected to the enable(EN2) pin of motor driver, which is associated with the left motor.
- Similarly, OCR5B is associated with the OC5B pin (PORTL.4), This pin is connected to the enable(EN1) pin of motor driver, which is associated with the right motor.

Timer/Counter Control Register 5A(TCCR5A)

Bit	Symbol	Description	Bit Value
7	COM5A1	Compare Output Mode for Channel A bit 1	1
6	COM5A0	Compare Output Mode for Channel A bit 0	0
5	COM5B1	Compare Output Mode for Channel B bit 1	1
4	COM5B0	Compare Output Mode for Channel B bit 0	0
3	COM5C1	Compare Output Mode for Channel C bit 1	1
2	COM5C0	Compare Output Mode for Channel C bit 0	0
1	WGM51	Waveform Generation Mode bit 1	0
0	WGM50	Waveform Generation Mode bit 0	1

- There are 2 types of bits in TCCR5A: Compare output mode bit & waveform generation mode bit.

Timer/Counter Control Register 5A(TCCR5A)

Bit	Symbol	Description	Bit Value
7	COM5A1	Compare Output Mode for Channel A bit 1	1
6	COM5A0	Compare Output Mode for Channel A bit 0	0
5	COM5B1	Compare Output Mode for Channel B bit 1	1
4	COM5B0	Compare Output Mode for Channel B bit 0	0
3	COM5C1	Compare Output Mode for Channel C bit 1	1
2	COM5C0	Compare Output Mode for Channel C bit 0	0
1	WGM51	Waveform Generation Mode bit 1	0
0	WGM50	Waveform Generation Mode bit 0	1

- There are 2 types of bits in TCCR5A: Compare output mode bit & waveform generation mode bit.
- Compare Output Mode bits decide the action to be taken when counter(TCNT5) value matches reference value in Output Compare Register(OCR5).

Timer/Counter Control Register 5A (TCCR5A) (...contd)

- In the given table:

Timer/Counter Control Register 5A (TCCR5A) (...contd)

- In the given table:
  - COM5A1 and COM5A0 bits are used to control the output on left motor.

Timer/Counter Control Register 5A (TCCR5A) (...contd)

- In the given table:
  - COM5A1 and COM5A0 bits are used to control the output on left motor.
  - COM5B1 and COM5B0 bits are used to control the output on right motor.

Timer/Counter Control Register 5A (TCCR5A) (...contd)

- In the given table:
  - COM5A1 and COM5A0 bits are used to control the output on left motor.
  - COM5B1 and COM5B0 bits are used to control the output on right motor.

Timer/Counter Control Register 5A (TCCR5A) (...contd)

- In the given table:
  - COM5A1 and COM5A0 bits are used to control the output on left motor.
  - COM5B1 and COM5B0 bits are used to control the output on right motor.

COMnA1 COMnB1 COMnC1	COMnA0 COMnB0 COMnC0	Description
0	0	Normal port operation, OCnA/OCnB/OCnC disconnected.
0	1	WGM13:0 = 14 or 15: Toggle OC1A on Compare Match, OC1B and OC1C disconnected (normal port operation). For all other WGM1 settings, normal port operation, OC1A/OC1B/OC1C disconnected.
1	0	Clear OCnA/OCnB/OCnC on compare match, set OCnA/OCnB/OCnC at BOTTOM (non-inverting mode).
1	1	Set OCnA/OCnB/OCnC on compare match, clear OCnA/OCnB/OCnC at BOTTOM (inverting mode).

- We are using non-inverting mode for PWM generation.

Inverting and Non-inverting mode



- There are two modes of PWM waveform generation:

Inverting and Non-inverting mode



- There are two modes of PWM waveform generation:
- Non-inverting mode and inverting mode

TCCR5A: Waveform Generation Mode Bits

Mode	WGMn3	WGMn2 (CTCn)	WGMn1 (PWMn1)	WGMn0 (PWMn0)	Timer/Counter Mode of Operation	TOP	Update of OCRnx at	TOVn Flag Set on
0	0	0	0	0	Normal	0xFFFF	Immediate	MAX
1	0	0	0	1	PWM, Phase Correct, 8-bit	0x00FF	TOP	BOTTOM
2	0	0	1	0	PWM, Phase Correct, 9-bit	0x01FF	TOP	BOTTOM
3	0	0	1	1	PWM, Phase Correct, 10-bit	0x03FF	TOP	BOTTOM
4	0	1	0	0	CTC	OCRnA	Immediate	MAX
5	0	1	0	1	Fast PWM, 8-bit	0x00FF	BOTTOM	TOP
6	0	1	1	0	Fast PWM, 9-bit	0x01FF	BOTTOM	TOP
7	0	1	1	1	Fast PWM, 10-bit	0x03FF	BOTTOM	TOP
8	1	0	0	0	PWM, Phase and Frequency Correct	ICRn	BOTTOM	BOTTOM
9	1	0	0	1	PWM,Phase and Frequency Correct	OCRnA	BOTTOM	BOTTOM
10	1	0	1	0	PWM, Phase Correct	ICRn	TOP	BOTTOM
11	1	0	1	1	PWM, Phase Correct	OCRnA	TOP	BOTTOM
12	1	1	0	0	CTC	ICRn	Immediate	MAX
13	1	1	0	1	(Reserved)	–	–	–
14	1	1	1	0	Fast PWM	ICRn	BOTTOM	TOP
15	1	1	1	1	Fast PWM	OCRnA	BOTTOM	TOP

- The Waveform Generation Mode bits are used to generate the type of PWM signal needed.

TCCR5A: Waveform Generation Mode Bits

Mode	WGMn3	WGMn2 (CTCn)	WGMn1 (PWMn1)	WGMn0 (PWMn0)	Timer/Counter Mode of Operation	TOP	Update of OCRnx at	TOVn Flag Set on
0	0	0	0	0	Normal	0xFFFF	Immediate	MAX
1	0	0	0	1	PWM, Phase Correct, 8-bit	0x00FF	TOP	BOTTOM
2	0	0	1	0	PWM, Phase Correct, 9-bit	0x01FF	TOP	BOTTOM
3	0	0	1	1	PWM, Phase Correct, 10-bit	0x03FF	TOP	BOTTOM
4	0	1	0	0	CTC	OCRnA	Immediate	MAX
5	0	1	0	1	Fast PWM, 8-bit	0x00FF	BOTTOM	TOP
6	0	1	1	0	Fast PWM, 9-bit	0x01FF	BOTTOM	TOP
7	0	1	1	1	Fast PWM, 10-bit	0x03FF	BOTTOM	TOP
8	1	0	0	0	PWM, Phase and Frequency Correct	ICRn	BOTTOM	BOTTOM
9	1	0	0	1	PWM,Phase and Frequency Correct	OCRnA	BOTTOM	BOTTOM
10	1	0	1	0	PWM, Phase Correct	ICRn	TOP	BOTTOM
11	1	0	1	1	PWM, Phase Correct	OCRnA	TOP	BOTTOM
12	1	1	0	0	CTC	ICRn	Immediate	MAX
13	1	1	0	1	(Reserved)	–	–	–
14	1	1	1	0	Fast PWM	ICRn	BOTTOM	TOP
15	1	1	1	1	Fast PWM	OCRnA	BOTTOM	TOP

- The Waveform Generation Mode bits are used to generate the type of PWM signal needed.
- We will be using Fast PWM, 8-bit mode.

Timer/Counter Control Register 5B (TCCR5B)

Bit	Symbol	Description	Bit Value
7	ICNC5	Input Capture Noise Canceller	0
6	ICES5	Input Capture Edge Select	0
5	–	Reserved Bit	0
4	WGM53	Waveform Generation Mode bit 3	0
3	WGM52	Waveform Generation Mode bit 2	1
2	CS52	Clock Select	0
1	CS51	Clock Select	1
0	CS50	Clock Select	1

Timer/Counter Control Register 5B (TCCR5B)

Bit	Symbol	Description	Bit Value
7	ICNC5	Input Capture Noise Canceller	0
6	ICES5	Input Capture Edge Select	0
5	–	Reserved Bit	0
4	WGM53	Waveform Generation Mode bit 3	0
3	WGM52	Waveform Generation Mode bit 2	1
2	CS52	Clock Select	0
1	CS51	Clock Select	1
0	CS50	Clock Select	1

- WGM bits (WGM52 and WGM53), are used for selecting mode of PWM generation.
  - Note: WGM50 and WGM51 bits also used along with these bit are in TCCR5A register.

Timer/Counter Control Register 5B (TCCR5B)

Bit	Symbol	Description	Bit Value
7	ICNC5	Input Capture Noise Canceller	0
6	ICES5	Input Capture Edge Select	0
5	–	Reserved Bit	0
4	WGM53	Waveform Generation Mode bit 3	0
3	WGM52	Waveform Generation Mode bit 2	1
2	CS52	Clock Select	0
1	CS51	Clock Select	1
0	CS50	Clock Select	1

- WGM bits (WGM52 and WGM53), are used for selecting mode of PWM generation.
  - Note: WGM50 and WGM51 bits also used along with these bit are in TCCR5A register.
- CS52, CS51, CS50 (Clock select) bits are used to select a frequency at which timer/counter Register will increment its value.

TCCR5B: Clock Select Bits

CS02	CS01	CS00	Description
0	0	0	No clock source (Timer/Counter stopped)
0	0	1	$clk_{I/O}$/(No prescaling)
0	1	0	$clk_{I/O}$/8 (From prescaler)
0	1	1	$clk_{I/O}$/64 (From prescaler)
1	0	0	$clk_{I/O}$/256 (From prescaler)
1	0	1	$clk_{I/O}$/1024 (From prescaler)
1	1	0	External clock source on T0 pin. Clock on falling edge.
1	1	1	External clock source on T0 pin. Clock on rising edge.

- Prescalar is used to reduce the frequency of the clock, suitable for the type of PWM being generated.

TCCR5B: Clock Select Bits

CS02	CS01	CS00	Description
0	0	0	No clock source (Timer/Counter stopped)
0	0	1	$clk_{I/O}$/(No prescaling)
0	1	0	$clk_{I/O}$/8 (From prescaler)
0	1	1	$clk_{I/O}$/64 (From prescaler)
1	0	0	$clk_{I/O}$/256 (From prescaler)
1	0	1	$clk_{I/O}$/1024 (From prescaler)
1	1	0	External clock source on T0 pin. Clock on falling edge.
1	1	1	External clock source on T0 pin. Clock on rising edge.

- Prescalar is used to reduce the frequency of the clock, suitable for the type of PWM being generated.
- Clock select bits decide the factor with which clock frequency will be divided.

TCCR5B: Clock Select Bits

CS02	CS01	CS00	Description
0	0	0	No clock source (Timer/Counter stopped)
0	0	1	$clk_{I/O}$/(No prescaling)
0	1	0	$clk_{I/O}$/8 (From prescaler)
0	1	1	$clk_{I/O}$/64 (From prescaler)
1	0	0	$clk_{I/O}$/256 (From prescaler)
1	0	1	$clk_{I/O}$/1024 (From prescaler)
1	1	0	External clock source on T0 pin. Clock on falling edge.
1	1	1	External clock source on T0 pin. Clock on rising edge.

- Prescalar is used to reduce the frequency of the clock, suitable for the type of PWM being generated.
- Clock select bits decide the factor with which clock frequency will be divided.
- We are using 64 as prescaler so, Clock select bits, we need is 011 .

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF
  - ✓ TCNT5L = 0x00

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF
  - ✓ TCNT5L = 0x00
  - ✓ TCCR5A = 0xA9

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF
  - ✓ TCNT5L = 0x00
  - ✓ TCCR5A = 0xA9
  - ✓ TCCR5B = 0x0B

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF
  - ✓ TCNT5L = 0x00
  - ✓ TCCR5A = 0xA9
  - ✓ TCCR5B = 0x0B
  - ✓ OCR5AH = 0x00

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF
  - ✓ TCNT5L = 0x00
  - ✓ TCCR5A = 0xA9
  - ✓ TCCR5B = 0x0B
  - ✓ OCR5AH = 0x00
  - ✓ OCR5AL = 0xFF

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF
  - ✓ TCNT5L = 0x00
  - ✓ TCCR5A = 0xA9
  - ✓ TCCR5B = 0x0B
  - ✓ OCR5AH = 0x00
  - ✓ OCR5AL = 0xFF
  - ✓ OCR5BH = 0x00

Summary

- In order to use Fast PWM mode to control the speed of dc motors of Firebird V. We have to initialize following registers with the corresponding values:
  - ✓ TCNT5H = 0xFF
  - ✓ TCNT5L = 0x00
  - ✓ TCCR5A = 0xA9
  - ✓ TCCR5B = 0x0B
  - ✓ OCR5AH = 0x00
  - ✓ OCR5AL = 0xFF
  - ✓ OCR5BH = 0x00
  - ✓ OCR5BL = 0xFF

Syntax for C-Program
Program

Syntax for C-Program
Program

#include

Syntax for C-Program
Program

#include

```
#include <avr/io.h>
#include <avr/interrupt.h>
#include <util/delay.h>
```

Syntax for C-Program
Program

#include

```
#include <avr/io.h>
#include <avr/interrupt.h>
#include <util/delay.h>
```

Main Program

Syntax for C-Program
Program

#include

```
#include <avr/io.h>
#include <avr/interrupt.h>
#include <util/delay.h>
```

Main Program

```
int main(void)
{
  motion_pin_config();
  forward();
  while(1)
  {
    velocity(100,100);
    _delay_ms(500);
    velocity(0,255);
    _delay_ms(500);
  }
}
```

Syntax for C-Program
Program

#include

```
#include <avr/io.h>
#include <avr/interrupt.h>
#include <util/delay.h>
```

Main Program

```
int main(void)
{
  motion_pin_config();
  forward();
  while(1)
  {
    velocity(100,100);
    _delay_ms(500);
    velocity(0,255);
    _delay_ms(500);
  }
}
```

Syntax for C-Program
PWM Initialization

Syntax for C-Program
PWM Initialization

Port Pin Config

Syntax for C-Program
PWM Initialization

Port Pin Config

```
void motion_pin_config (void)  //Configure Pins as Output
{
Port A for motion control and Port L for Velocity Control must be defined Output
}
```

Syntax for C-Program
PWM Initialization

Port Pin Config

```
void motion_pin_config (void)  //Configure Pins as Output
{
Port A for motion control and Port L for Velocity Control must be defined Output
}
```

Velocity Function

Syntax for C-Program
PWM Initialization

Port Pin Config

```
void motion_pin_config (void)  //Configure Pins as Output
{
Port A for motion control and Port L for Velocity Control must be defined Output
}
```

Velocity Function

```
void velocity (unsigned char left_motor, unsigned char right_motor)
{
   OCR5AL = (unsigned char)left_motor;
   OCR5BL = (unsigned char)right_motor;
}
```

PWM Initialization

Syntax for C-Program
PWM Initialization

Port Pin Config

```
void motion_pin_config (void)  //Configure Pins as Output
{
Port A for motion control and Port L for Velocity Control must be defined Output
}
```

Velocity Function

```
void velocity (unsigned char left_motor, unsigned char right_motor)
{
    OCR5AL = (unsigned char)left_motor;
    OCR5BL = (unsigned char)right_motor;
}
```

PWM Initialization

```
void timer5_init()  //Set Register Values for starting Fast 8-bit PWM
{
    TCCR5A =
    TCCR5B =
    TCNT5H = 0xFF;
    TCNT5L = 0x00;
    OCR5AH = 0x00;
    OCR5AL = 0xFF;
    OCR5BH = 0x00;
    OCR5BL = 0xFF;
}
```

Thank You!