

gem5 tutorial

References:

- <https://github.com/gem5bootcamp>



Environment

The steps outlined in this tutorial have been tested on the computers located in Delta 219. These computers are equipped with:

- CPU: 13th Gen Intel(R) Core(TM) i5-13500
- RAM: 16 GB
- SSD: 954 GB

Docker Desktop is pre-installed.

Installation on Your Own Computer

You may also install Docker on your own computer. Please ensure you have at least **10 GB** of disk space available.

This instructions for **Windows** is provided.



Install WSL2 on Windows

STEP 1: Enable Windows Features

1. Open **File Explorer** and type Control **Panel**(控制台)\Programs(程式集) into the address bar, then press Enter.
2. Click on **Turn Windows features on or off**(開啟或關閉Windows功能).
3. Check the boxes for **Windows Subsystem for Linux** and **Virtual Machine Platform**.

If these options are missing, you may need to enable **virtualization technology** (Intel VT-x / AMD-V) in your computer's BIOS/UEFI settings.

4. Click OK, then select Restart now to reboot your computer.

STEP 2: Install WSL2 using PowerShell

1. Open **PowerShell** as Administrator.
2. Run the following command to install WSL2 and the default Linux distribution (Ubuntu):

```
ws1 --update --web-download
```

3. Wait for the installation to complete. Once finished, restart your computer if prompted.

Install Docker Desktop on Windows

For Windows users:

1. Download [the installer](#).
2. Double-click `Docker Desktop Installer.exe` to run the installer.
3. Follow the instructions in the installation wizard to authorize the installer and proceed with the installation.
4. Once the installation is complete, select **Close** to finish the process.



Back up files from `$HOME\workspaces\` to a flash drive

Delta 219 computers are configured to automatically revert to a previously saved system state (a restore point) without prior notice.

- Your files may be permanently deleted without warning at any time (unannounced data loss).
- You cannot predict when these reverts will occur, nor can you prevent them from happening (limited user control).

Temporary data storage:

Your files are temporarily stored in the `$HOME\workspaces\` directory. These files are deleted during the automatic system revert process.

Protecting your data:

To avoid data loss, regularly back up your data using external USB drives or cloud storage services.

Reason for automatic system reverts:

This feature is designed to maintain a consistent simulation environment for all users.



Open Docker Desktop on Windows

For Windows users:

1. Left-click on the **Start button** (or press the `Windows key`).
2. Select **Docker Desktop** (or type `Docker Desktop` and press `Enter`).
3. Wait until Docker Desktop has fully started

Expected outcome: Docker Desktop is open and fully initialized, ready to run containers.

Open a terminal emulator on Windows

For Windows users:

1. Right-click on the **Start button** (or press the `Windows key` + `X`).
2. Select **Windows PowerShell** (or press `I`).

Expected outcome: A terminal emulator will open.

```
Windows PowerShell
```

```
Copyright (C) Microsoft Corporation. 著作權所有，並保留一切權利。
```

```
請嘗試新的跨平台 PowerShell https://aka.ms/pscore6
```

```
PS C:\Users\user>
```

Run a container in PowerShell

For PowerShell users, run this command:

```
docker run -it `
--name ee6455-gem5 `
--volume $HOME\workspaces\:/workspaces/ `
--workdir /workspaces/2025/ `
--hostname EE6455-gem5 `
ghcr.io/gem5/devcontainer:bootcamp-2024
```

Expected outcome: An interactive TTY will indicate its readiness to accept commands.

```
root@EE6455-gem5:/workspaces/2025#
```

Alternative outcome: A newer image will be downloaded before the interactive TTY displays the username, hostname, and working directory.

```
PS C:\Users\user> docker container run -it `
>> --name ee6455-gem5 `
>> --volume $HOME\workspaces\:/workspaces/ `
>> --workdir /workspaces/2025/ `
>> --hostname EE6455-gem5 `
>> ghcr.io/gem5/devcontainer:bootcamp-2024
Unable to find image 'ghcr.io/gem5/devcontainer:bootcamp-2024' locally
bootcamp-2024: Pulling from gem5/devcontainer
00d679a470c4: Pull complete
c782a11a41b6: Pull complete
4f6b9996da3d: Pull complete
bb60cbcef558: Pull complete
92c0abbbf0ee: Pull complete
865d1839a002: Pull complete
2ceb23f2c7bb: Pull complete
31825ae2d134: Pull complete
Digest: sha256:dc299b8bf11b324cbd89aab82bdbe31bf9ce71a33386f2a2153a590a803d2c71
Status: Downloaded newer image for ghcr.io/gem5/devcontainer:bootcamp-2024
root@EE6455-gem5:/workspaces/2025#
```

Manage an Existing Docker Container

- Start an existing container:

```
docker start ee6455-gem5
```

- Attach a shell inside a running container:

```
docker exec -it ee6455-gem5 bash
```

- Opens a new Bash shell inside the container.
- You can have multiple terminals connected at the same time.

- Stop a running container:

```
docker stop ee6455-gem5
```



- Remove a container

```
docker rm ee6455-gem5
```

- Works only if the container is stopped.

Get the source code of gem5

Clone the Bootcamp Repository (inside container):

```
time git clone --recurse-submodules \
https://nas.larc-nthu.net:8443/ee6455_2025/public-gem5bootcamp-2025 /workspaces/2025/
```

Expected outcome: A repository will be cloned, including its submodules.

```
root@EE6455-gem5:/workspaces/2025# time git clone --recurse-submodules https://nas.larc-nthu.net:8443/ee6455_2025/public-gem5bootcamp-2025 /workspaces/2025/
Cloning into '/workspaces/2025'...
warning: redirecting to https://nas.larc-nthu.net:8443/ee6455_2025/public-gem5bootcamp-2025.git/
remote: Enumerating objects: 11106, done.
remote: Counting objects: 100% (130/130), done.
remote: Compressing objects: 100% (130/130), done.
remote: Total 11106 (delta 78), reused 0 (delta 0), pack-reused 10976 (from 1)
Receiving objects: 100% (11106/11106), 385.46 MiB | 11.07 MiB/s, done.
Resolving deltas: 100% (7510/7510), done.
Updating files: 100% (966/966), done.
Submodule 'gem5' (https://github.com/gem5/gem5) registered for path 'gem5'
Submodule 'gem5-resources' (https://github.com/gem5/gem5-resources) registered for path 'gem5-resources'
Cloning into '/workspaces/2025/gem5'...
remote: Enumerating objects: 295271, done.
remote: Counting objects: 100% (604/604), done.
remote: Compressing objects: 100% (329/329), done.
remote: Total 295271 (delta 460), reused 275 (delta 275), pack-reused 294667 (from 3)
Receiving objects: 100% (295271/295271), 171.33 MiB | 5.20 MiB/s, done.
Resolving deltas: 100% (225064/225064), done.
Cloning into '/workspaces/2025/gem5-resources'...
```

Run a simulation using gem5

Run this command inside the container:

```
time gem5-mesi --outdir=/workspaces/m5out/ \
/workspaces/2025/materials/01-Introduction/02-getting-started/completed/basic.py
```

Expected outcome:

- The `X86DemoBoard` will be simulated using `x86-ubuntu-24.04-img` as the workload.
- On first run, gem5 will automatically download required resources:
 - `x86-linux-kernel-5.4.0-105-generic`
 - `x86-ubuntu-24.04-img` (~4.9 GB compressed, takes some time to download and decompress)

Note: Depending on your network speed, downloading and unpacking `x86-ubuntu-24.04-img` may take several minutes.



```

root@EE6455-gem5:/workspaces/2025# time gem5-mesi --outdir=/workspaces/m5out/ \
/workspaces/2025/materials/01-Introduction/02-getting-started/completed/basic.py
gem5 Simulator System.  https://www.gem5.org
gem5 is copyrighted software; use the --copyright option for details.

gem5 version 24.0.0.0
gem5 compiled Jul 25 2024 18:47:27
gem5 started Aug 21 2025 09:19:18
gem5 executing on EE6455-gem5, pid 14
command line: gem5-mesi --outdir=/workspaces/m5out/ /workspaces/2025/materials/01-Introduction/02-getting-started/completed/basic.py

warn: The X86DemoBoard is solely for demonstration purposes. This board is not known to be representative of any real-world system. Use with caution.
info: Using default config
Resource 'x86-linux-kernel-5.4.0-105-generic' was not found locally. Downloading to '/root/.cache/gem5/x86-linux-kernel-5.4.0-105-generic'...
Finished downloading resource 'x86-linux-kernel-5.4.0-105-generic'.
Resource 'x86-ubuntu-24.04-img' was not found locally. Downloading to '/root/.cache/gem5/x86-ubuntu-24.04-img.gz'...
Finished downloading resource 'x86-ubuntu-24.04-img'.
Decompressing resource 'x86-ubuntu-24.04-img' ('/root/.cache/gem5/x86-ubuntu-24.04-img.gz')...
Finished decompressing resource 'x86-ubuntu-24.04-img'.
warn: Max ticks has already been set prior to setting it through the run call. In these cases the max ticks set through the `run` function is used
Global frequency set at 100000000000 ticks per second
src/mem/dram_interface.cc:690: warn: DRAM device capacity (8192 Mbytes) does not match the address range assigned (2048 Mbytes)
src/sim/kernel_workload.cc:46: info: kernel located at: /root/.cache/gem5/x86-linux-kernel-5.4.0-105-generic
src/base/statistics.hh:279: warn: One of the stats is a legacy stat. Legacy stat is a stat that does not belong to any statistics::Group. Legacy stat is deprecated.
    0: board.pc.south_bridge.cmos rtc: Real-time clock set to Sun Jan  1 00:00:00 2012
board.pc.com_1.device: Listening for connections on port 3456
src/base/statistics.hh:279: warn: One of the stats is a legacy stat. Legacy stat is a stat that does not belong to any statistics::Group. Legacy stat is deprecated.
src/dev/intel_8254_timer.cc:128: warn: Reading current count from inactive timer.
board.remote_gdb: Listening for connections on port 7000
src/sim/simulate.cc:199: info: Entering event queue @ 0. Starting simulation...
src/mem/ruby/system/Sequencer.cc:680: warn: Replacement policy updates recently became the responsibility of SLICC state machines. Make sure to setMRU() near callbacks in .sm files!
build/ALL/arch/x86/generated/exec-ns.cc.inc:27: warn: instruction 'fninit' unimplemented

real    42m27.091s
user    0m38.201s
sys     0m16.827s
root@EE6455-gem5:/workspaces/2025#

```

Retrieve the simulation statistics

- On Windows

After the simulation finishes, open `$HOME\workspaces\m5out\stats.txt` using a text editor. This file contains the detailed statistics generated by gem5.

- Inside the container

You can also view the file directly inside the running container, for example by scrolling through the whole file:

```
root@EE6455-gem5:/workspaces/2025# less /workspaces/m5out/stats.txt
```


Expected outcome: The first few lines will resemble this:

```
----- Begin Simulation Statistics -----
simSeconds          0.020000          # Number of seconds simulated (Second)
simTicks            20000000000        # Number of ticks simulated (Tick)
finalTick           20000000000        # Number of ticks from beginning of simulation (restored from checkpoints and never reset) (Tick)
simFreq             10000000000000      # The number of ticks per simulated second ((Tick/Second))
hostSeconds         18.88              # Real time elapsed on the host (Second)
hostTickRate        1059100397         # The number of ticks simulated per host second (ticks/s) ((Tick/Second))
hostMemory          2770924            # Number of bytes of host memory used (Byte)
simInsts            7479814            # Number of instructions simulated (Count)
simOps              34912342           # Number of ops (including micro ops) simulated (Count)
hostInstRate        396059             # Simulator instruction rate (inst/s) ((Count/Second))
hostOpRate          1848597            # Simulator op (including micro ops) rate (op/s) ((Count/Second))
board.cache_hierarchy.ruby_system.delayHistogram::bucket_size 2          # delay histogram for all message (Unspecified)
board.cache_hierarchy.ruby_system.delayHistogram::max_bucket 19          # delay histogram for all message (Unspecified)
board.cache_hierarchy.ruby_system.delayHistogram::samples 735551          # delay histogram for all message (Unspecified)
board.cache_hierarchy.ruby_system.delayHistogram::mean 1.036855          # delay histogram for all message (Unspecified)
board.cache_hierarchy.ruby_system.delayHistogram::stdev 2.687016          # delay histogram for all message (Unspecified)
```

Retrieve the simulation configuration on Windows

- On Windows: open `$HOME\workspaces\m5out\config.ini` using a text editor.
- Inside the container:

```
less /workspaces/m5out/config.ini
```

Expected outcome: The first few lines will resemble this:

```
[board]
type=System
children=cache_hierarchy clk_domain dvfs_handler iobus memory pc processor workload
auto_unlink_shared_backstore=false
cache_line_size=64
eventq_index=0
exit_on_work_items=true
init_param=0
m5ops_base=4294901760
```

```
mem_mode=timing
mem_ranges=0:2147483648 3221225472:3222274048
memories=board.memory.mem_ctrl.dram
mmap_using_noreserve=false
multi_thread=false
num_work_ids=16
readfile=
redirect_paths=
shadow_rom_ranges=
shared_backstore=
symbolfile=
thermal_components=
thermal_model=NULL
work_begin_ckpt_count=0
work_begin_cpu_id_exit=-1
work_begin_exit_count=0
work_cpus_ckpt_count=0
work_end_ckpt_count=0
work_end_exit_count=0
```