

# Index

- ABR *see* Available bit rate
- Access:
  - edge Diffserv, 230–3, 248–9
  - passive monitoring, 337, 340
  - quality of service, 183–9
- Active network monitoring:
  - CAC, 328
  - deployment considerations, 364–71
  - duration, 355–7
  - frequency, 349, 351–7
  - jitter, 360–2
  - measurement metrics, 349, 358–64
  - packet size, 350–1
  - sampling frequency, 349, 351–5
  - SLA, 335–6, 348–71
  - testing, 348–50, 354–7
  - topologies, 365–9
  - traffic test streams, 348–50
- Active queue management (AQM), 132–6
- Admission control *see* Capacity admission control
- AF *see* Assured forwarding
- Aggregate Diffserv-based classification, 319
- Aggregate shaping, 139–40, 229–30
- Aggregation RSVP, 320–5
- Allocation models, 404–5
- Any-to-any VPNs, 17–18
- Application end-system losses, 11, 36, 54
- Application engineering, 198–9
- Application isolation, 242
- Application signaling interaction, 314–16
- Application SLA requirements, 24–76
  - data applications, 58–75
  - interactive data applications, 70–4
  - video, 38–58
  - VoIP, 26–37
- AQM *see* Active queue management
- Architectures:
  - IP QOS, 141–83
  - IPv6 QOS, 170–1
  - MPLS QOS, 171–83
  - quality of service, 141–83
  - see also* Diffserv; Intserv
- Assured forwarding (AF), 156–8, 240
- Asymmetry factors, 393
- Asynchronous transfer mode (ATM), 190–4
- Audio streams, 57
- Autonomous systems, 378
- Availability considerations, 20–2, 363–4
- Available bit rate (ABR), 191
- Average delay, 360
- Average queue depths, 345
- Backbone Diffserv deployment, 210, 249–67
  - classes, 253–6, 258–61
  - design, 256–63
  - marking, 263–7
  - meta-language, 257–8
- Backbone propagation delay, 216
- Bandwidth:
  - active monitoring, 363
  - backbone Diffserv, 251–3, 255
  - CAC, 277–82, 292–302
  - deploying Diffserv, 210–11, 251–3, 255

- Bandwidth (*Contd*)
  - managers, 292–302
  - over-provisioning, 376–7, 382–8
  - scheduling, 112–28
  - sizing, 412–13
  - SLA metrics, 12–18
  - traffic engineering, 376–7, 382–8, 393, 412–13
  - video conferencing, 57–8
- Batch sampling, 353
- Bearer classes, 243
- Best-effort service, 89–90, 307
- BGP *see* Border Gateway Protocol
- Bidirectional “B” frames, 39
- Bidirectional reservations, 60, 284, 327
- Bit rates, 191–2
- Border Gateway Protocol (BGP), 379–80
- Broadcast Video Services, 41–3
- BTC *see* Bulk Transport Capacity
- Bucket mechanisms, 101–8, 138
- Buffers, 128–9, 347
- Bulk Transport Capacity (BTC), 13
- Business data throughput-optimized
  - class, 262
- Bytes, 273, 340–5
- CAC *see* Capacity admission control
- Call admission control, 276–7
- Call manager-bandwidth manager
  - interaction, 297–8
- Call-sequence of events, 298–302, 314–16
- Capacity: SLA metrics, 12–18
- Capacity admission control (CAC), 275–334
  - bandwidth managers, 292–302
  - information requirements, 285–6
  - Intserv over Diffserv, 316–20, 323–4
  - Intserv/RSVP, 303–26
  - MBAC, 328–9
  - measurements-based algorithms, 286, 288–9
  - NSIS, 283, 326–8
  - parameterized algorithms, 286–7
  - resource managers, 292–302
  - RSVP, 282–3, 303–26
  - signaling, 326–8
  - taxonomy, 282–5
  - topology-awareness, 283, 290–302
  - usefulness, 277–82
- Capacity planning, 182, 255, 259–60
  - see also* Core capacity planning
- CBR *see* Constant bit rate
- Cell loss ratio (CLR) 2 QOS, 191
- Characteristics of VoIP codecs, 26–9
- Churn, 324–5
- CIF *see* Common interchange format
- Classes:
  - backbone Diffserv, 253–6, 258–61
  - class-capacity, 12
  - class selector PHB, 158–9, 174–5
  - class of service, 88–9
  - edge Diffserv, 213–18, 221–5, 233–9, 241–4
- Classification:
  - active monitoring, 357–8
  - backbone Diffserv, 257–8
  - Diffserv, 147–8, 257–8
  - Intserv, 303
  - passive monitoring, 338–9
  - quality of service toolsets, 93, 94–9
- Client-side processing delays, 71
- Clock synchronization, 370–1
- CLR *see* Cell loss ratio
- Codecs, 26–9, 57
- Codepoint assignment and management, 152–4
- Code of Practice: MPEG, 49–51
- Color-aware policers, 108–11
- Color markers, 102–8, 239, 339–42
- Committed burst, 194
- Committed information rate, 194
- Common interchange format (CIF), 55
- Complementary technologies to QOS, 197–8

- Complex classification, 95–6, 357
- Component availability, 20–1
- Compression, 28
- Conditioning, 78–9, 147–8, 340
- Congestion:
  - backbone Diffserv, 255
  - Diffserv, 160–5, 255
  - packet loss, 9
  - TCP, 61–7
  - video streaming, 48
  - VoIP, 34–5
- Connectivity, 20–1, 363–4
- Constant bit rate (CBR), 25, 191
- Constraint based path computation, 398–9
- Control classes (Ctrl):
  - backbone Diffserv, 254, 256, 260
  - edge Diffserv, 213, 218, 223–4
- Controlled load service, 307
- Controlling tunneling, 403
- Control planes, 93–4, 284–5, 325
- Convergence, 197
- Core capacity planning, 375–89
  - analysis, 388–9
  - bandwidth over-provisioning, 376–7, 382–8
  - methodology, 376–7
  - network topology overlaying, 388–9
  - over-provisioning factors, 376–7, 382–8
  - simulations, 377, 385–6, 388–9
  - traffic demand matrices, 376, 377–82
- Core Diffserv deployment, 210, 249–67
  - see also* Backbone Diffserv deployment
- Core links, 338, 340
- Core meshes, 409–10, 411
- Core traffic matrices, 347–8
- Ctrl *see* Control classes
- Customer-facing classes, 213–18, 221–5
- Data application SLA requirements, 58–75
- Data planes, 92–141, 284–5, 325
- De-aggregation routers, 321–2
- Decoder delay, 43
- Decryption delay, 43
- Deep packet inspection, 96
- Default PHB, 158
- Deficit Round Robin (DRR), 121–3
- De-jitter buffers, 31–3, 42
- Delay:
  - active monitoring, 358–62
  - application SLA requirements, 24–5
  - budget allocation, 215–17
  - core capacity planning, 385–8
  - interactive data applications, 71–2
  - scheduling algorithms, 124
  - SLA metrics, 4–8
  - TCP, 59, 67–9
  - video conferencing, 57–8
  - video streaming, 40–7
  - VoIP, 29–33, 215–17
- Demand:
  - core capacity planning, 376, 377–82
  - traffic engineering, 389–413
  - video-on-demand, 43–6, 47
- Deploying Diffserv, 209–73
  - network backbone, 210, 249–67
  - network core, 210, 249–67
  - network edge, 210, 211–49
  - random early detection, 263, 268–72
  - weighted random early detection, 239, 263, 268–72
- Deployment:
  - active monitoring, 349, 364–71
  - MPLS TE, 408–11
  - traffic engineering, 391–4
- Design: Diffserv, 211, 218–40, 256–63
- Differentiated services architecture *see* Diffserv
- Diffserv Code Point (DSCP) marking, 149, 151–4, 165–70, 244–5
- Diffserv (differentiated services architecture):
  - active monitoring, 357–8
  - ATM layer 2 QOS, 193–4
  - core capacity planning, 387

- Diffserv (*Contd*)
  - data plane QOS mechanisms, 98
  - deployment, 209–73
    - meta-language, 218–21, 229–38, 257–8, 264
    - network backbone, 210, 249–67
    - network core, 210, 249–67
    - network edge, 210, 211–49
    - weighted random early detection, 239, 263, 268–72
  - design, 211, 218–40, 256–63
  - explicit congestion notification, 160–5
  - frame relay layer 2 QOS, 195
  - Intserv, CAC, 316–20, 323–4
  - IP multicast, 182
  - IP QOS architectures, 147–70
  - MPLS QOS architectures, 173–81
  - MPLS TE, 404–8
  - Per-Domain Behaviors, 159–60
  - Per-Hop Behaviors, 149, 154–9
  - random early detection, 239, 263, 268–72
  - service level agreements, 78–9, 211–18, 233–7, 241–2, 253–6
  - traffic classification and conditioning, 147–8
  - tunneling models, 165–70, 175–81
- Diffserv Field Codepoints Registry (DSCR), 153
- Digital Video Broadcasting (DVB), 48
- Discard probability, 268, 271
- Discrete services, 58
- Dropping, 128–37
  - advanced concepts, 136–7
  - edge Diffserv design, 222
  - passive monitoring, 342–6
  - router QOS implementation, 186
- DRR *see* Deficit Round Robin
- DS *see* Differentiated services
- DSCP *see* Diffserv Code Point
- DSCR *see* Diffserv Field Codepoints Registry
- DVB *see* Digital Video Broadcasting
- Ear-to-mouth delay, 29–30, 215–16
- ECMP *see* Equal costs multipath
- ECN *see* Explicit congestion notification
- ECR *see* Egress committed rates
- Edge conditioning classes, 157
- Edge Diffserv deployment, 212–44
  - classes, 213–18, 221–5, 233–9, 241–4
  - design, 218–40
  - high-speed design, 218–25, 234–5
  - low-speed edge design, 225–8
  - meta-language, 218–21, 229–38
  - policies, 210
  - SLA specifications, 212–18
  - video, 239–40
  - VoIP, 213, 214–17, 221–3, 232–3, 240, 245–9
- Edge keys, 211–12
- Edge-to-core mapping, 254, 264–7
- EF *see* Expedited forwarding
- EFCI *see* Explicit Forward Congestion Indication
- Egress committed rates (ECR), 214
- Elastic applications' utility functions, 279–80
- Embedded agents, 364–5
- E model, 23
- End-system losses:
  - packet loss, 11
  - video streaming, 40, 54
  - VoIP, 29–30, 36, 215–16
- End-system MBAC, 282, 328–9
- End-to-end delay, 4, 29–30, 40, 215–16
- End-to-end links, 387
- End-to-end reservations, 306–7, 387
- End-to-end SLAs, 77
- Engineered SLAs, 76–8
- Equal costs multipath (ECMP), 369–70, 395–6
- Ethernet, 196–7
- Excess burst, 194
- Expedited forwarding (EF), 155–6, 221, 226, 228

- EXP inferred PHB selection, 174–5
- Explicit congestion notification (ECN), 160–5
- Explicit Forward Congestion Indication (EFCI), 164–5
- Explicit mapping, 266
- Explicit standard class, 260
- Exponential weighting constant, 269–70
- External agents, 364–5
- External traffic demands, 378–9
  
- Failure case optimization, 391–2
- Fairness, 119–21, 123–4
- Fair queuing, 119–21
- Fast IGP convergence, 197
- Fast recovery congestion control, 66
- Fast reroute technologies, 198
- Fast retransmit congestion control, 66
- FCFS *see* First-come first served
- FEC *see* Forward error correction
- FECN *see* Forward explicit congestion notification
- FIFO *see* First-in first-out
- FILTERSPEC, 311, 312
- Finger-to-eye delay, 40
- Firewall pinhole configurations, 326
- First-come first served (FCFS), 112
- First-in first-out (FIFO), 112–13, 125–6, 225–6
- Flow:
  - bandwidth thresholds, 280
  - data plane QOS mechanisms, 94–5
  - descriptors, 311
  - FLOWSPEC, 311, 312
  - statistics aggregation, 379–80
- Forecast demand simulations, 377
- Forward error correction (FEC), 43, 49–51
- Forward explicit congestion notification (FECN), 164–5
- Frames:
  - delays, 43
  - frame-based codecs, 27
  - relay, 194–5
  - video streaming, 39–40
- Frequency of monitoring, 349, 351–7
- Full mesh topologies, 366–7
  
- Gaming, 24, 74–6
- GCRA (Generic Cell Rate Algorithm), 138
- General Internet Signaling Protocol (GIST), 327
- Generalized Process Sharing (GPS), 119
- Generic Cell Rate Algorithm (GCRA), 138
- GIST (General Internet Signaling Protocol), 327
- GOP *see* Group of Pictures
- GPS (Generalized Process Sharing), 119
- Group of Pictures (GOP), 39–40, 48, 56
- Guaranteed service, 306–7
  
- HD *see* High definition
- Head drop, 131
- Hierarchical mesh topologies, 368–9
- Hierarchical shaping, 228–30
- High definition (HD) format, 55
- High percentile delay, 359–60
- High-speed design, 218–25, 234–5
- History of IP QOS architectures, 141–2
- Hopping, 149, 154–9, 174–5, 216, 318–19, 322
- Hose models, 17–18
- Hub and spoke VPNs, 16–17
  
- ICR (ingress committed rates), 214
- IETF (Internet Engineering Task Force), 3–4
- “I” frames, 39
- IGP *see* Interior gateway routing protocol
- Implicit classification, 95
- Implicit standard class, 260
- In-contract marking, 340–2
- In-contract traffic, 271–2
- Inelastic application’s utility functions, 280–1

- Information requirements, 285–6
- Ingress committed rates (ICR), 214
- Ingress marking, 100
- Inner core meshes, 410, 411
- Input drops, 347
- Integrated services architecture *see* Intserv
- Interactive data applications, 70–6
- Interactivity of video streaming, 40
- Interface FIFO, 125–6
- Interior gateway routing protocol (IGP), 295–6, 305, 390, 394–7
- Interleaving, 140–1, 226–7
- Internal traffic demands, 378–9
- Internet Engineering Task Force (IETF), 3–4
- Inter-provider SLAs, 77–8
- Intra “I” frames, 39
- Intserv (integrated services architecture):
  - CAC, 303–26
  - definitions, 303–4
  - Diffserv, 303–4, 316–20, 323–4
  - IP multicast, 182–3
  - IP QOS architectures, 147
  - MPLS QOS architectures, 172–3
  - quality of service, 79
  - quality of service toolsets, 93
  - RSVP, 172–3, 182–3
  - service level agreements, 78–9
- IP backbone Diffserv, 263
- IP flow statistics aggregation, 379–80
- IP multicast, 181–3
- IP performance metrics (IPPM), 3–4, 349
- IPPM (IP performance metrics), 3–4, 349
- IP precedence, 144–5, 146
- IP quality of service (IP QOS):
  - access routers, 183–9
  - architectures, 141–83
    - Diffserv, 147–70
    - history, 141–2
    - Integrated Services, 147
    - IP precedence, 144–5, 146
    - IPv6 QOS, 147, 170–1
    - MPLS QOS architectures, 171–83
    - multicast, 181–3
    - precedence, 144–5, 146
    - service types, 142–4, 145–6
  - complementary technologies, 197–8
  - definitions, 91
  - history, 141–2
  - IP precedence, 144–5, 146
  - IPv6 QOS, 147, 170–1
  - MPLS QOS architectures, 171–83
  - service types, 142–4, 145–6
- IP RSVP, 304
- IP security protocols, 327–8
- IP traffic engineering, 389–413
- IP tunneling, 165–70
- IPv6 QOS architectures, 147, 170–1
- Jitter:
  - active monitoring, 360–2
  - SLA metrics, 7–8
  - TCP, 69
  - video conferencing, 57
  - video streaming, 46–7
  - VoIP, 31–3
- Label inferred PHB selection, 175
- Label switch paths (LSP), 380
- LAN *see* Local area networks
- Latency, 221–2, 234
- Layer 1 CAC, 306
- Layer 2 CAC, 306
- Layer 2 marking, 98
- Layer 2 overheads, 13–16
- Layer 2 QOS, 98, 189–97
- Layer 3 CAC, 283, 327
- Lead-times, 393
- Leaky buckets, 138
- LFI *see* Link fragmentation and interleaving
- Link bandwidth, 251–3, 255
- Link capacity, 12
- Link fragmentation and interleaving (LFI), 140–1, 226–7
- Link metrics, 394–5

- Link utilization, 385–8
- Local area networks (LAN), 306
- Logical network topology, 388–9
- Losses:
  - loss distances, 9, 362
  - loss periods, 9, 362
  - TCP, 59, 69–70
  - video streaming, 47–54
  - VoIP, 33–6
- Lower effort PDB, 160
- Lower layer errors, 9–10, 35, 48–9
- Low-speed edge Diffserv design, 225–8
- LSP *see* Label switch paths
- Maintenance: MPLS TE, 403
- Mapping Diffserv, 193–4
- Mapping edge-to-core schemes, 264–7
- Marketed SLAs versus engineered SLAs, 76–8
- Marking:
  - backbone Diffserv, 263–7
  - color markers, 102–8, 239, 339–42
  - Diffserv Code Point, 149, 151–4, 165–70, 244–5
  - edge Diffserv, 244–5, 246
  - IP QOS architectures, 149, 151–4
  - passive monitoring, 339–42
  - quality of service toolsets, 93, 99–111
  - router QOS implementation, 186
- Mark probability denominator, 271
- Maximum allocation models, 404–5
- Maximum queue thresholds, 268, 270–1
- Maximum rate enforcement, 93, 339–40
- MBAC *see* Measurement-based admission control
- Mean Opinion Score (MOS), 23
- Measurement-based admission control (MBAC), 286, 288–9, 328–9
- Measurement metrics, 349, 358–64
- Measuring equal cost multiple paths, 369–70
- Mechanics of data plane QOS, 92–141
- Meshes, 16–17, 366–9, 409–11
- Message processing, 308–14
- Meta-language, 218–21, 229–38, 257–8, 264
- Metering, 111
- Metrics:
  - active monitoring, 349, 358–64
  - service level agreements, 3–24
- Middleware processing, 45
- Minimum delay, 359
- Minimum queue thresholds, 268, 270–1
- Minimum rate assurance, 93
- MLPPP (Multilink Point-to-Point Protocol), 141
- Mobility, 327–8
- Monitoring *see* Network monitoring
- MOS (Mean Opinion Score), 23
- Motion Picture Expert Group (MPEG), 38–40, 47, 49–51, 55–6
- Mouth-to-ear delay, 29–30, 215–16
- MPEG *see* Motion Picture Expert Group
- MPLS *see* Multi-protocol label switching
- Multicast reservations, 41–2, 181–3, 284, 304
- Multi-field classification, 95–6, 357
- Multi-level strict priority, 125–6
- Multilink Point-to-Point Protocol (MLPPP), 141
- Multiple path measurements, 369–70
- Multi-protocol label switching (MPLS):
  - backbone Diffserv, 265, 267
  - EXP fields, 98
  - LSP accounting, 380
  - QOS architectures, 171–83
  - RSVP-TE, 325–6
  - traffic engineering, 93–4, 296, 397–413
  - tunneling, 175–81
- Multi-protocol tunnels, 165, 175–81
- Negative acknowledgements, 52
- Network address translation, 326

- Network asymmetry, 393
- Network availability, 20–1, 363–4
- Network backbone, 210, 249–67
- Network core, 210, 249–67
- Network delays, 4–7, 29–30, 41–5, 59, 67–9, 72
- Network edge, 210, 211–49
- Networked Virtual Environments (NVEs), 74
- Network element failures, 10–11, 35–6, 52–3, 278–9
- Network engineering, 198–9, 389–90
- Networking working case conditions, 278
- Network losses, 59, 69–70
- Network monitoring, 335–73
  - active, 335–6, 348–71
  - passive, 335, 336–48
- Network routing model, 388–9
- Network topology overlaying, 388–9
- Network transmission delays, 41, 42, 43, 45
- Next generation networks (NGN), 294–302
- Next Steps in Signaling *see* NSIS
- NGN (Next generation networks), 294–302
- Non real-time VBR, 191
- NSIS (Next Steps in Signaling), 283, 326–8
- NSIS Signaling Layer Protocols (NSLPs), 327
- NSIS Transport layer Protocol (NTLP), 327
- NVEs *see* Networked Virtual Environments
- Objective measures, 23, 24
- Ockham's razor, 273
- Off-path CAC, 283
- One-rate token bucket policers, 101–2
- One-way delay, 4, 29–30, 40, 358
- On-line gaming, 24, 74–6
- Only Path messages, 334
- On-path network signaled CAC, 282
- Outer core mesh, 409–10
- Out-of-contract marking, 340–2
- Out-of-contract traffic, 271–2
- Over-provisioning factors, 376–7, 382–8
- Packet loss, 9–11, 24–5, 33–6, 362
- Packet marking, 93, 99–111
- Packet numbers, 340–5
- Packet re-ordering, 19, 37, 57, 363
- Packet size, 350–1
- Parameterized algorithms, 286–7
- Partial mesh topologies, 367
- Passive network monitoring, 339–42
  - CAC, 328–9
  - classification, 338–9
  - core traffic matrices, 347–8
  - dropping, 342–6
  - per-link statistics, 337–8
  - policing, 339–42
  - polling, 337, 345
  - queuing, 342–6
  - SLA, 335, 336–48
  - traffic matrices, 347–8
- Paths:
  - active monitoring, 349
  - capacity, 12
  - computation, 398–9
  - coupling, 282–3
  - message processing, 308–14
- PathTear messages, 334
- PDB *see* Per-Domain Behaviors
- Percentile delay, 359–60
- Perceptual Evaluation of Speech Quality (PESQ), 23
- Per-class core capacity planning, 387
- Per-classification rules, 338–9
- Per-Domain Behaviors (PDB), 79, 159–60
- Per-flow admission control, 318–19
- Per-flow sequence preservation, 18–19
- Performance metrics, 349
- Per-hop Behaviors (PHB), 149, 154–9, 174–5, 216
- Periodic sampling, 351–2



- Per-link statistics, 337–8
- Personal video recorders (PVR), 43
- Perturbation factors, 226
- Per-VPN edge-marking, 267
- PESQ (Perceptual Evaluation of Speech Quality), 23
- “P” frames, 39
- PHB *see* Per-Hop Behaviors
- Physical redundancy, 53
- Pipesize, 270–1
- Pipe tunneling model, 16–18, 168–70, 178–81
- Play-out delay: VoIP, 31–3
- Point-of-presence (POP), 378
- Poisson sampling, 352, 353, 354
- Poisson traffic, 383–4
- Policing, 100–11, 186, 222, 339–42
- Policy: information distribution, 398
- Polling, 337, 345
- POP (point-of-presence), 378
- Ports, 357–8
- Positive acknowledgement with retransmission, 60–1
- Precedence, 144–5, 146
- Predictive coded “P” frames, 39
- Pre-emption priority levels, 286
- Premium data delay-optimized class (Prm-delay), 233–7, 261–2
- Premium data loss-optimized class (Prm-loss), 236–9, 262
- Premium data (Prm) classes:
  - backbone Diffserv, 254, 256, 259–60, 261–3
  - edge Diffserv, 223, 233–9
- Premium data throughput-optimized class (Prm-th), 213, 217–18, 223, 233–9, 262
- Prioritized Diffserv, 254–6
- Priority scheduling, 93, 114–15, 125–6, 240, 286
- Private networks, 263, 265, 267
- Prm *see* Premium data
- Prm-delay *see* Premium data delay-optimized class
- Prm-loss *see* Premium data loss-optimized class
- Prm-th *see* Premium data throughput-optimized class
- Probability of delay/discard, 268, 271, 385–6
- Probe packets, 348
- Processing delays, 6, 8, 71–2
- Professional-MPEG [PRO-MPEG] forum, 49–51
- Propagation delay, 5–6, 8, 216, 417
- Protocols, 357–8
  - see also individual protocols*
- Public switched telephony networks (PSTN), 294–302
- PVR (personal video recorders), 43
- QCIF *see* Quarter common interchange format
- QoE *see* Quality of experience
- QOS *see* Quality of service
- QOS Signaling: CAC, 327
- Quality of experience (QoE), 22–4, 58, 364
- Quality of service (QoS):
  - best-effort service, 89–90
  - CAC, 327
  - classification, 93, 94–9
  - class of service, 88–9
  - complementary technologies, 197–8
  - data plane mechanisms, 92–141
  - definition, 87–94
  - dropping, 128–37
  - introduction, 2–3
  - Intserv, 79
  - IP multicast, 181–3
  - layer 2 technologies, 98, 189–97
  - limitations, 198–9
  - link fragmentation and interleaving, 140–1
  - marking, 93, 99–111

Quality of service (*Contd*)

- mechanics, 92–141
- metering, 111
- multicast, 181–3
- packet marking, 93, 99–111
- policing, 100–11
- policy, 183–9
- queuing, 112–28
- reasons for, 91
- requirements, 2–3, 12, 16, 19, 30, 34
- routers, 183–9
- scheduling, 112–28
- shaping, 137–40
- signaling, 327
- time frames, 90–1
- toolsets, 91–141
- type of service, 88–9

## Quarter common interchange format (QCIF), 55

## Queues/queuing:

- buffers, 128–9
- data plane QOS mechanisms, 112–28
- edge Diffserv, 246–9
- FIFO, 112–13
- passive monitoring, 342–6
- premium data delay-optimized class, 234–5
- simulations, 385–6
- SLA metrics, 6, 8, 15
- thresholds, 268, 270–1
- see also* Scheduling

Random early detection (RED), 132–7, 186, 239, 263, 268–72, 344–6

Random sampling, 352–3

Rating Factor, 23

Real-time (RT) classes, 242, 253–4, 256, 258–9

Real-time transmission (RTT), 43, 51–2

Real-time VBR, 191

Received stream metric measurements, 349

Receiver-initiated reservations, 304–5, 327

RECEIVER TSPEC, 311

RED *see* Random early detection

Regional boundaries, 318

Regional meshes, 410–11

Remote control video streaming, 41, 44

Re-ordering packets, 19, 37, 57, 363

Reroute technologies, 198

ReSerVation Protocol *see* RSVP

ReSerVation Protocol-traffic engineering  
*see* RSVP-TE

Reservation setup, 307–14

Resizing, 324–5

Resource information distribution, 398

Resource managers, 292–302

Resource requirements, 285

Responsiveness, 281–2

ResvConf messages, 334

Round robin, 116–19, 121–3

Round trip time (RTT) delay, 4–5, 358

Route pinning, 417

## Routers/routing:

- CAC, 305–6
- edge Diffserv, 230–3, 242–3
- protocol classes, 242–3
- quality of service, 183–9

## RSVP (ReSerVation Protocol):

- aggregation, 320–5
- application signaling interaction, 314–16
- CAC, 282–3, 303–26
- definitions, 304–7
- IP multicast, 182–3

MPLS QOS architectures, 172–3

MPLS TE, 399–402

reservation setup, 307–14

signaling interaction, 314–16

RSVP-TE (ReSerVation Protocol-traffic engineering), 325–6

RT *see* Real-time

RTT *see* Real-time transmission; Round trip time

Russian doll models, 405

- Sampling frequency, 349, 351–5
- Scalability, 147
- Scheduling:
  - advanced concepts, 126–8
  - ATM layer 2 QOS, 192
  - data plane QOS mechanisms, 112–28
  - edge Diffserv design, 228–30, 240
  - FIFO, 112–13
  - Intserv, 303
  - premium data delay-optimized class, 235–6
  - SLA metrics, 6, 8, 15
  - which algorithm?, 123–5
  - see also* Queuing
- Secure tunneling, 165
- Security protocols, 327–8
- Segmented SLAs, 77
- Self-induced VoIP queuing delay, 246–9
- Self-similar traffic, 383–4
- Sender-initiated reservations, 327
- Sequence preservation, 18–19
- Serialization delay, 6–7, 8
- Server-side processing delays, 71
- Service availability, 21–2, 364
- Service classes, 213–18, 221–5, 253–6, 258–61
- Service level agreements (SLA), 1–4
  - active monitoring, 335–6, 348–71
  - application requirements, 24–76
    - data applications, 58–75
    - video, 38–58
  - Voice over IP, 26–37
  - availability factors, 20–2
  - backbone Diffserv, 253–6
  - bandwidth, 12–18
  - CAC, 285–6
  - differentiation, 242
  - Diffserv, 78–9, 211–18, 233–7, 241–2, 253–6
  - edge Diffserv, 212–18, 233–4, 236–7, 241
  - edge keys, 211–12
  - engineered versus marketed, 76–8
  - Intserv, 78–9
  - marketed versus engineered, 76–8
  - metrics, 3–24, 349, 358–64
    - availability factors, 20–2
    - bandwidth, 12–18
    - network delay, 4–7
    - packet loss, 9–11
    - per-flow sequence preservation, 18–19
    - quality of experience, 22–4
    - sequence preservation, 18–19
    - throughput, 12–18
  - network delay, 4–7
  - network monitoring, 335–73
  - packet loss, 9–11
  - passive monitoring, 335, 336–48
  - premium data classes, 233–4, 236–7
  - quality of experience, 22–4
  - requirements, 211
  - sequence preservation, 18–19
  - specifications, 78, 212–18, 233–7, 241, 253–6
  - throughput, 12–18
  - video, 38–58
  - Voice over IP, 26–37
- Service octets, 96–8, 142–4, 145–6
- Service types, 142–4, 145–6
- Session establishment, 60
- Setting tunnel bandwidth, 412–13
- Set-top-box (STB) processing, 41, 42, 44–5
- Shaping:
  - ATM layer 2 QOS, 192
  - data plane QOS mechanisms, 102, 137–40
  - edge Diffserv design, 228–30
  - frame relay layer 2 QOS, 195
  - policers, 137–8
  - SLA metrics, 15
- Short pipe tunneling model, 181
- Signaling, 243, 314–16, 326–8
- Silence suppression: VoIP, 36

- Simple classification, 96–9, 357
- Simple IP-in-IP tunnels, 165
- Simple network management protocol (SNMP), 336
- Simplicity in scheduling algorithms, 124–5
- Simulations in capacity planning, 377, 385–6, 388–9
- Single rate three color markers (SR-TCM), 102–6, 339–42
- Size factors, 324–5
- SLA *see* Service level agreements
- Sliding acknowledgement windows, 61
- Slow start congestion control, 61–3
- SNMP (simple network management protocol), 336
- Soft state, 306
- Source marking, 99
- Spatial redundancy, 53
- SR-TCM *see* Single rate three color markers
- Standard classes (Std):
  - backbone Diffserv, 254, 256, 260–1
  - edge Diffserv, 213, 218, 224–5
- Standard definition (SD) format, 54–5
- Stateful inspection, 96
- STB *see* Set-top-box
- Std *see* Standard classes
- Stratified random sampling, 352–3
- Stream/streaming, 47, 57, 95, 348–50
  - see also* Video streaming
- Strict priority, 125–6
- Subjective measures, 23, 24
- Switching delay, 6, 8, 216
- Synchronizing clocks, 370–1
- Synthetic traffic test streams, 348
- Systematic TE deployment, 396, 409–11
- System monitoring, 346–7
- Tactical TE deployment: MPLS TE, 408–9
- Tail drop, 129–32, 186, 222, 343–4
- Taxonomy of CAC, 282–5
- TCM *see* Three-color markers
- TCP *see* Transmission Control Protocol
- Telephony networks, 294–302
- Temporal redundancy, 53–4
- Testing:
  - duration, 355–7
  - frequency, 349, 354–7
  - test rates, 354–5
  - test streams, 348–50
- Three-color markers (TCM), 106–8, 239, 340–2
- Threshold exceeded count delay, 360
- Throughput:
  - active network monitoring, 363
  - SLA metrics, 12–18
  - TCP applications, 59–70
  - video streaming, 54–6
  - VoIP, 36–7
- Tight SLA services, 211–12
- Time frames, 90–1
- Token bucket mechanisms, 101–8, 138
- Toolsets for QOS, 91–141
- Topologies: active monitoring, 365–9
- Topology-awareness, 283, 290–302, 319
- TOS *see* Type of service
- Traffic assignment to tunnels, 402–5
- Traffic classes, 95, 97
- Traffic classification, 147–8
- Traffic conditioning, 78–9, 147–8, 340
- Traffic demand matrices, 376, 377–82
- Traffic engineering, 389–413
  - bandwidth, 376–7, 382–8, 393, 412–13
  - CAC, 325–6
  - deployment, 391–4
  - Diffserv-aware MPLS TE, 404–8
  - IGP based, 390, 394–7
  - multi-protocol label switching, 397–413
  - RSVP, 325–6
  - tunnels, 300, 402–5
- Traffic management classes, 242–3
- Traffic matrices, 347–8
- Traffic metering, 111
- Traffic shapers, 15

- Traffic test streams, 348–50
- Transmission Control Protocol (TCP), 59–70, 161–5
- Transmission delays, 41, 42, 43, 45
- Transport stream packets, 47
- TR-TCM *see* Two rate three color markers
- Trust boundaries, 110–11
- Tunneling:
  - bandwidth sizing, 412–13
  - CAC, 300, 324
  - Diffserv, 165–70, 175–81
  - MPLS Diffserv, 175–81
  - MPLS TE, 397–404, 412–13
  - next generation networks, 300
  - pipe model, 168–70, 178–81
  - uniform model, 166–8, 176–8
  - voice CAC, 300
- Two rate three color markers (TR-TCM), 106–8, 239, 340–2
- Type of service (TOS), 88–9, 142–4, 145–6
- UBR (unspecified bit rate), 192
- Unicast reservations, 284, 304, 307–14, 327
- Unidirectional reservations, 284, 304
- Uniform tunneling model, 166–8, 176–8
- Universal edge-marking, 267
- Unmanaged access router services, 230–3
- Unspecified bit rate (UBR), 192
- Utility functions, 279–80
- VAD *see* Voice activation detection
- Variable bit rate (VBR), 191
- VC *see* Virtual circuits
- Video:
  - backbone Diffserv, 262
  - conferencing, 57–8
  - edge Diffserv design, 239–40
  - quality of experience, 24
  - SLA requirements, 38–58
  - streaming, 38–57
    - delay, 40–7
    - jitter, 46–7
    - loss impacts, 47–54
    - packet re-ordering, 57
    - throughput, 54–6
- Video-on-demand (VOD), 43–6, 47
- Virtual circuits (VC), 190–4, 320
- Virtual paths (VP), 320
- Virtual private networks (VPN), 16–18, 172, 267
- VOD *see* Video-on-demand
- Voice activation detection (VAD), 36
- Voice class maximum rate enforcement, 339–40
- Voice QoE, 23
- VoIP (Voice over IP):
  - delay, 29–33
  - edge Diffserv, 213, 214–17, 221–3, 232–3, 240, 245–9
  - jitter, 31–3
  - loss impacts, 33–6
  - packet re-ordering, 37
  - SLA requirements, 26–37
  - throughput, 36–7
- VPN *see* Virtual private networks
- VP (Virtual paths), 320
- Weighted bandwidth scheduling, 115–25
- Weighted fair queuing (WFQ), 119–21
- Weighted random early detection (WRED):
  - backbone Diffserv, 263
  - data plane QOS mechanisms, 136, 137
  - Diffserv deployment, 239, 263, 268–72
  - passive monitoring, 346
  - router QOS implementation, 186
- Weighted round robin (WRR), 116–19
- Weighted tail drop, 131–2, 343–4
- WFQ (weighted fair queuing), 119–21
- Worst-case delay bounds, 124
- WRED *see* Weighted random early detection
- WRR (weighted round robin), 116–19