

# Index

- ABR *see* Available bit rate
- Access:
  - edge Diffserv, 230–3, 248–9
  - passive monitoring, 337, 340
  - quality of service, 183–9
- Active network monitoring:
  - CAC, 328
  - deployment considerations, 364–71
  - duration, 355–7
  - frequency, 349, 351–7
  - jitter, 360–2
  - measurement metrics, 349, 358–64
  - packet size, 350–1
  - sampling frequency, 349, 351–5
  - SLA, 335–6, 348–71
  - testing, 348–50, 354–7
  - topologies, 365–9
  - traffic test streams, 348–50
- Active queue management (AQM), 132–6
- Admission control *see* Capacity admission control
- AF *see* Assured forwarding
- Aggregate Diffserv-based classification, 319
- Aggregate shaping, 139–40, 229–30
- Aggregation RSVP, 320–5
- Allocation models, 404–5
- Any-to-any VPNs, 17–18
- Application end-system losses, 11, 36, 54
- Application engineering, 198–9
- Application isolation, 242
- Application signaling interaction, 314–16
- Application SLA requirements, 24–76
  - data applications, 58–75
  - interactive data applications, 70–4
  - video, 38–58
  - VoIP, 26–37
- AQM *see* Active queue management
- Architectures:
  - IP QOS, 141–83
  - IPv6 QOS, 170–1
  - MPLS QOS, 171–83
  - quality of service, 141–83
  - see also* Diffserv; Intserv
- Assured forwarding (AF), 156–8, 240
- Asymmetry factors, 393
- Asynchronous transfer mode (ATM), 190–4
- Audio streams, 57
- Autonomous systems, 378
- Availability considerations, 20–2, 363–4
- Available bit rate (ABR), 191
- Average delay, 360
- Average queue depths, 345
- Backbone Diffserv deployment, 210, 249–67
  - classes, 253–6, 258–61
  - design, 256–63
  - marking, 263–7
  - meta-language, 257–8
- Backbone propagation delay, 216
- Bandwidth:
  - active monitoring, 363
  - backbone Diffserv, 251–3, 255
  - CAC, 277–82, 292–302
  - deploying Diffserv, 210–11, 251–3, 255

- Bandwidth (*Contd*)
  - managers, 292–302
  - over-provisioning, 376–7, 382–8
  - scheduling, 112–28
  - sizing, 412–13
  - SLA metrics, 12–18
  - traffic engineering, 376–7, 382–8, 393, 412–13
  - video conferencing, 57–8
- Batch sampling, 353
- Bearer classes, 243
- Best-effort service, 89–90, 307
- BGP *see* Border Gateway Protocol
- Bidirectional “B” frames, 39
- Bidirectional reservations, 60, 284, 327
- Bit rates, 191–2
- Border Gateway Protocol (BGP), 379–80
- Broadcast Video Services, 41–3
- BTC *see* Bulk Transport Capacity
- Bucket mechanisms, 101–8, 138
- Buffers, 128–9, 347
- Bulk Transport Capacity (BTC), 13
- Business data throughput-optimized
  - class, 262
- Bytes, 273, 340–5
  
- CAC *see* Capacity admission control
- Call admission control, 276–7
- Call manager-bandwidth manager
  - interaction, 297–8
- Call-sequence of events, 298–302, 314–16
- Capacity: SLA metrics, 12–18
- Capacity admission control (CAC), 275–334
  - bandwidth managers, 292–302
  - information requirements, 285–6
  - Intserv over Diffserv, 316–20, 323–4
  - Intserv/RSVP, 303–26
  - MBAC, 328–9
  - measurements-based algorithms, 286, 288–9
  - NSIS, 283, 326–8
  - parameterized algorithms, 286–7
  - resource managers, 292–302
  - RSVP, 282–3, 303–26
  - signaling, 326–8
  - taxonomy, 282–5
  - topology-awareness, 283, 290–302
  - usefulness, 277–82
- Capacity planning, 182, 255, 259–60
  - see also* Core capacity planning
- CBR *see* Constant bit rate
- Cell loss ratio (CLR) 2 QOS, 191
- Characteristics of VoIP codecs, 26–9
- Churn, 324–5
- CIF *see* Common interchange format
- Classes:
  - backbone Diffserv, 253–6, 258–61
  - class-capacity, 12
  - class selector PHB, 158–9, 174–5
  - class of service, 88–9
  - edge Diffserv, 213–18, 221–5, 233–9, 241–4
- Classification:
  - active monitoring, 357–8
  - backbone Diffserv, 257–8
  - Diffserv, 147–8, 257–8
  - Intserv, 303
  - passive monitoring, 338–9
  - quality of service toolsets, 93, 94–9
- Client-side processing delays, 71
- Clock synchronization, 370–1
- CLR *see* Cell loss ratio
- Codecs, 26–9, 57
- Codepoint assignment and management, 152–4
- Code of Practice: MPEG, 49–51
- Color-aware policers, 108–11
- Color markers, 102–8, 239, 339–42
- Committed burst, 194
- Committed information rate, 194
- Common interchange format (CIF), 55
- Complementary technologies to QOS, 197–8

- Complex classification, 95–6, 357
- Component availability, 20–1
- Compression, 28
- Conditioning, 78–9, 147–8, 340
- Congestion:
  - backbone Diffserv, 255
  - Diffserv, 160–5, 255
  - packet loss, 9
  - TCP, 61–7
  - video streaming, 48
  - VoIP, 34–5
- Connectivity, 20–1, 363–4
- Constant bit rate (CBR), 25, 191
- Constraint based path computation, 398–9
- Control classes (Ctrl):
  - backbone Diffserv, 254, 256, 260
  - edge Diffserv, 213, 218, 223–4
- Controlled load service, 307
- Controlling tunneling, 403
- Control planes, 93–4, 284–5, 325
- Convergence, 197
- Core capacity planning, 375–89
  - analysis, 388–9
  - bandwidth over-provisioning, 376–7, 382–8
  - methodology, 376–7
  - network topology overlaying, 388–9
  - over-provisioning factors, 376–7, 382–8
  - simulations, 377, 385–6, 388–9
  - traffic demand matrices, 376, 377–82
- Core Diffserv deployment, 210, 249–67
  - see also* Backbone Diffserv deployment
- Core links, 338, 340
- Core meshes, 409–10, 411
- Core traffic matrices, 347–8
- Ctrl *see* Control classes
- Customer-facing classes, 213–18, 221–5
- Data application SLA requirements, 58–75
- Data planes, 92–141, 284–5, 325
- De-aggregation routers, 321–2
- Decoder delay, 43
- Decryption delay, 43
- Deep packet inspection, 96
- Default PHB, 158
- Deficit Round Robin (DRR), 121–3
- De-jitter buffers, 31–3, 42
- Delay:
  - active monitoring, 358–62
  - application SLA requirements, 24–5
  - budget allocation, 215–17
  - core capacity planning, 385–8
  - interactive data applications, 71–2
  - scheduling algorithms, 124
  - SLA metrics, 4–8
  - TCP, 59, 67–9
  - video conferencing, 57–8
  - video streaming, 40–7
  - VoIP, 29–33, 215–17
- Demand:
  - core capacity planning, 376, 377–82
  - traffic engineering, 389–413
  - video-on-demand, 43–6, 47
- Deploying Diffserv, 209–73
  - network backbone, 210, 249–67
  - network core, 210, 249–67
  - network edge, 210, 211–49
  - random early detection, 263, 268–72
  - weighted random early detection, 239, 263, 268–72
- Deployment:
  - active monitoring, 349, 364–71
  - MPLS TE, 408–11
  - traffic engineering, 391–4
- Design: Diffserv, 211, 218–40, 256–63
- Differentiated services architecture *see* Diffserv
- Diffserv Code Point (DSCP) marking, 149, 151–4, 165–70, 244–5
- Diffserv (differentiated services architecture):
  - active monitoring, 357–8
  - ATM layer 2 QOS, 193–4
  - core capacity planning, 387

- Diffserv (*Contd*)
  - data plane QOS mechanisms, 98
  - deployment, 209–73
    - meta-language, 218–21, 229–38, 257–8, 264
    - network backbone, 210, 249–67
    - network core, 210, 249–67
    - network edge, 210, 211–49
    - weighted random early detection, 239, 263, 268–72
  - design, 211, 218–40, 256–63
  - explicit congestion notification, 160–5
  - frame relay layer 2 QOS, 195
  - Intserv, CAC, 316–20, 323–4
  - IP multicast, 182
  - IP QOS architectures, 147–70
  - MPLS QOS architectures, 173–81
  - MPLS TE, 404–8
  - Per-Domain Behaviors, 159–60
  - Per-Hop Behaviors, 149, 154–9
  - random early detection, 239, 263, 268–72
  - service level agreements, 78–9, 211–18, 233–7, 241–2, 253–6
  - traffic classification and conditioning, 147–8
  - tunneling models, 165–70, 175–81
- Diffserv Field Codepoints Registry (DSCR), 153
- Digital Video Broadcasting (DVB), 48
- Discard probability, 268, 271
- Discrete services, 58
- Dropping, 128–37
  - advanced concepts, 136–7
  - edge Diffserv design, 222
  - passive monitoring, 342–6
  - router QOS implementation, 186
- DRR *see* Deficit Round Robin
- DS *see* Differentiated services
- DSCP *see* Diffserv Code Point
- DSCR *see* Diffserv Field Codepoints Registry
- DVB *see* Digital Video Broadcasting
- Ear-to-mouth delay, 29–30, 215–16
- ECMP *see* Equal costs multipath
- ECN *see* Explicit congestion notification
- ECR *see* Egress committed rates
- Edge conditioning classes, 157
- Edge Diffserv deployment, 212–44
  - classes, 213–18, 221–5, 233–9, 241–4
  - design, 218–40
  - high-speed design, 218–25, 234–5
  - low-speed edge design, 225–8
  - meta-language, 218–21, 229–38
  - policies, 210
  - SLA specifications, 212–18
  - video, 239–40
  - VoIP, 213, 214–17, 221–3, 232–3, 240, 245–9
- Edge keys, 211–12
- Edge-to-core mapping, 254, 264–7
- EF *see* Expedited forwarding
- EFCI *see* Explicit Forward Congestion Indication
- Egress committed rates (ECR), 214
- Elastic applications' utility functions, 279–80
- Embedded agents, 364–5
- E model, 23
- End-system losses:
  - packet loss, 11
  - video streaming, 40, 54
  - VoIP, 29–30, 36, 215–16
- End-system MBAC, 282, 328–9
- End-to-end delay, 4, 29–30, 40, 215–16
- End-to-end links, 387
- End-to-end reservations, 306–7, 387
- End-to-end SLAs, 77
- Engineered SLAs, 76–8
- Equal costs multipath (ECMP), 369–70, 395–6
- Ethernet, 196–7
- Excess burst, 194
- Expedited forwarding (EF), 155–6, 221, 226, 228

- EXP inferred PHB selection, 174–5
- Explicit congestion notification (ECN), 160–5
- Explicit Forward Congestion Indication (EFCI), 164–5
- Explicit mapping, 266
- Explicit standard class, 260
- Exponential weighting constant, 269–70
- External agents, 364–5
- External traffic demands, 378–9
- Failure case optimization, 391–2
- Fairness, 119–21, 123–4
- Fair queuing, 119–21
- Fast IGP convergence, 197
- Fast recovery congestion control, 66
- Fast reroute technologies, 198
- Fast retransmit congestion control, 66
- FCFS *see* First-come first served
- FEC *see* Forward error correction
- FECN *see* Forward explicit congestion notification
- FIFO *see* First-in first-out
- FILTERSPEC, 311, 312
- Finger-to-eye delay, 40
- Firewall pinhole configurations, 326
- First-come first served (FCFS), 112
- First-in first-out (FIFO), 112–13, 125–6, 225–6
- Flow:
  - bandwidth thresholds, 280
  - data plane QOS mechanisms, 94–5
  - descriptors, 311
  - FLOWSPEC, 311, 312
  - statistics aggregation, 379–80
- Forecast demand simulations, 377
- Forward error correction (FEC), 43, 49–51
- Forward explicit congestion notification (FECN), 164–5
- Frames:
  - delays, 43
  - frame-based codecs, 27
  - relay, 194–5
  - video streaming, 39–40
- Frequency of monitoring, 349, 351–7
- Full mesh topologies, 366–7
- Gaming, 24, 74–6
- GCRA (Generic Cell Rate Algorithm), 138
- General Internet Signaling Protocol (GIST), 327
- Generalized Process Sharing (GPS), 119
- Generic Cell Rate Algorithm (GCRA), 138
- GIST (General Internet Signaling Protocol), 327
- GOP *see* Group of Pictures
- GPS (Generalized Process Sharing), 119
- Group of Pictures (GOP), 39–40, 48, 56
- Guaranteed service, 306–7
- HD *see* High definition
- Head drop, 131
- Hierarchical mesh topologies, 368–9
- Hierarchical shaping, 228–30
- High definition (HD) format, 55
- High percentile delay, 359–60
- High-speed design, 218–25, 234–5
- History of IP QOS architectures, 141–2
- Hopping, 149, 154–9, 174–5, 216, 318–19, 322
- Hose models, 17–18
- Hub and spoke VPNs, 16–17
- ICR (ingress committed rates), 214
- IETF (Internet Engineering Task Force), 3–4
- “I” frames, 39
- IGP *see* Interior gateway routing protocol
- Implicit classification, 95
- Implicit standard class, 260
- In-contract marking, 340–2
- In-contract traffic, 271–2
- Inelastic application’s utility functions, 280–1

- Information requirements, 285–6
- Ingress committed rates (ICR), 214
- Ingress marking, 100
- Inner core meshes, 410, 411
- Input drops, 347
- Integrated services architecture *see* Intserv
- Interactive data applications, 70–6
- Interactivity of video streaming, 40
- Interface FIFO, 125–6
- Interior gateway routing protocol (IGP), 295–6, 305, 390, 394–7
- Interleaving, 140–1, 226–7
- Internal traffic demands, 378–9
- Internet Engineering Task Force (IETF), 3–4
- Inter-provider SLAs, 77–8
- Intra “I” frames, 39
- Intserv (integrated services architecture):
  - CAC, 303–26
  - definitions, 303–4
  - Diffserv, 303–4, 316–20, 323–4
  - IP multicast, 182–3
  - IP QOS architectures, 147
  - MPLS QOS architectures, 172–3
  - quality of service, 79
  - quality of service toolsets, 93
  - RSVP, 172–3, 182–3
  - service level agreements, 78–9
- IP backbone Diffserv, 263
- IP flow statistics aggregation, 379–80
- IP multicast, 181–3
- IP performance metrics (IPPM), 3–4, 349
- IPPM (IP performance metrics), 3–4, 349
- IP precedence, 144–5, 146
- IP quality of service (IP QOS):
  - access routers, 183–9
  - architectures, 141–83
    - Diffserv, 147–70
    - history, 141–2
    - Integrated Services, 147
    - IP precedence, 144–5, 146
    - IPv6 QOS, 147, 170–1
    - MPLS QOS architectures, 171–83
    - multicast, 181–3
    - precedence, 144–5, 146
    - service types, 142–4, 145–6
  - complementary technologies, 197–8
  - definitions, 91
  - history, 141–2
  - IP precedence, 144–5, 146
  - IPv6 QOS, 147, 170–1
  - MPLS QOS architectures, 171–83
  - service types, 142–4, 145–6
- IP RSVP, 304
- IP security protocols, 327–8
- IP traffic engineering, 389–413
- IP tunneling, 165–70
- IPv6 QOS architectures, 147, 170–1
- Jitter:
  - active monitoring, 360–2
  - SLA metrics, 7–8
  - TCP, 69
  - video conferencing, 57
  - video streaming, 46–7
  - VoIP, 31–3
- Label inferred PHB selection, 175
- Label switch paths (LSP), 380
- LAN *see* Local area networks
- Latency, 221–2, 234
- Layer 1 CAC, 306
- Layer 2 CAC, 306
- Layer 2 marking, 98
- Layer 2 overheads, 13–16
- Layer 2 QOS, 98, 189–97
- Layer 3 CAC, 283, 327
- Lead-times, 393
- Leaky buckets, 138
- LFI *see* Link fragmentation and interleaving
- Link bandwidth, 251–3, 255
- Link capacity, 12
- Link fragmentation and interleaving (LFI), 140–1, 226–7
- Link metrics, 394–5

- Link utilization, 385–8
- Local area networks (LAN), 306
- Logical network topology, 388–9
- Losses:
  - loss distances, 9, 362
  - loss periods, 9, 362
  - TCP, 59, 69–70
  - video streaming, 47–54
  - VoIP, 33–6
- Lower effort PDB, 160
- Lower layer errors, 9–10, 35, 48–9
- Low-speed edge Diffserv design, 225–8
- LSP *see* Label switch paths
- Maintenance: MPLS TE, 403
- Mapping Diffserv, 193–4
- Mapping edge-to-core schemes, 264–7
- Marketed SLAs versus engineered SLAs, 76–8
- Marking:
  - backbone Diffserv, 263–7
  - color markers, 102–8, 239, 339–42
  - Diffserv Code Point, 149, 151–4, 165–70, 244–5
  - edge Diffserv, 244–5, 246
  - IP QOS architectures, 149, 151–4
  - passive monitoring, 339–42
  - quality of service toolsets, 93, 99–111
  - router QOS implementation, 186
- Mark probability denominator, 271
- Maximum allocation models, 404–5
- Maximum queue thresholds, 268, 270–1
- Maximum rate enforcement, 93, 339–40
- MBAC *see* Measurement-based admission control
- Mean Opinion Score (MOS), 23
- Measurement-based admission control (MBAC), 286, 288–9, 328–9
- Measurement metrics, 349, 358–64
- Measuring equal cost multiple paths, 369–70
- Mechanics of data plane QOS, 92–141
- Meshes, 16–17, 366–9, 409–11
- Message processing, 308–14
- Meta-language, 218–21, 229–38, 257–8, 264
- Metering, 111
- Metrics:
  - active monitoring, 349, 358–64
  - service level agreements, 3–24
- Middleware processing, 45
- Minimum delay, 359
- Minimum queue thresholds, 268, 270–1
- Minimum rate assurance, 93
- MLPPP (Multilink Point-to-Point Protocol), 141
- Mobility, 327–8
- Monitoring *see* Network monitoring
- MOS (Mean Opinion Score), 23
- Motion Picture Expert Group (MPEG), 38–40, 47, 49–51, 55–6
- Mouth-to-ear delay, 29–30, 215–16
- MPEG *see* Motion Picture Expert Group
- MPLS *see* Multi-protocol label switching
- Multicast reservations, 41–2, 181–3, 284, 304
- Multi-field classification, 95–6, 357
- Multi-level strict priority, 125–6
- Multilink Point-to-Point Protocol (MLPPP), 141
- Multiple path measurements, 369–70
- Multi-protocol label switching (MPLS):
  - backbone Diffserv, 265, 267
  - EXP fields, 98
  - LSP accounting, 380
  - QOS architectures, 171–83
  - RSVP-TE, 325–6
  - traffic engineering, 93–4, 296, 397–413
  - tunneling, 175–81
- Multi-protocol tunnels, 165, 175–81
- Negative acknowledgements, 52
- Network address translation, 326

- Network asymmetry, 393
- Network availability, 20–1, 363–4
- Network backbone, 210, 249–67
- Network core, 210, 249–67
- Network delays, 4–7, 29–30, 41–5, 59, 67–9, 72
- Network edge, 210, 211–49
- Networked Virtual Environments (NVEs), 74
- Network element failures, 10–11, 35–6, 52–3, 278–9
- Network engineering, 198–9, 389–90
- Networking working case conditions, 278
- Network losses, 59, 69–70
- Network monitoring, 335–73
  - active, 335–6, 348–71
  - passive, 335, 336–48
- Network routing model, 388–9
- Network topology overlaying, 388–9
- Network transmission delays, 41, 42, 43, 45
- Next generation networks (NGN), 294–302
- Next Steps in Signaling *see* NSIS
- NGN (Next generation networks), 294–302
- Non real-time VBR, 191
- NSIS (Next Steps in Signaling), 283, 326–8
- NSIS Signaling Layer Protocols (NSLPs), 327
- NSIS Transport layer Protocol (NTLP), 327
- NVEs *see* Networked Virtual Environments
- Objective measures, 23, 24
- Ockham's razor, 273
- Off-path CAC, 283
- One-rate token bucket policers, 101–2
- One-way delay, 4, 29–30, 40, 358
- On-line gaming, 24, 74–6
- Only Path messages, 334
- On-path network signaled CAC, 282
- Outer core mesh, 409–10
- Out-of-contract marking, 340–2
- Out-of-contract traffic, 271–2
- Over-provisioning factors, 376–7, 382–8
- Packet loss, 9–11, 24–5, 33–6, 362
- Packet marking, 93, 99–111
- Packet numbers, 340–5
- Packet re-ordering, 19, 37, 57, 363
- Packet size, 350–1
- Parameterized algorithms, 286–7
- Partial mesh topologies, 367
- Passive network monitoring, 339–42
  - CAC, 328–9
  - classification, 338–9
  - core traffic matrices, 347–8
  - dropping, 342–6
  - per-link statistics, 337–8
  - policing, 339–42
  - polling, 337, 345
  - queuing, 342–6
  - SLA, 335, 336–48
  - traffic matrices, 347–8
- Paths:
  - active monitoring, 349
  - capacity, 12
  - computation, 398–9
  - coupling, 282–3
  - message processing, 308–14
- PathTear messages, 334
- PDB *see* Per-Domain Behaviors
- Percentile delay, 359–60
- Perceptual Evaluation of Speech Quality (PESQ), 23
- Per-class core capacity planning, 387
- Per-classification rules, 338–9
- Per-Domain Behaviors (PDB), 79, 159–60
- Per-flow admission control, 318–19
- Per-flow sequence preservation, 18–19
- Performance metrics, 349
- Per-hop Behaviors (PHB), 149, 154–9, 174–5, 216
- Periodic sampling, 351–2



- Per-link statistics, 337–8
- Personal video recorders (PVR), 43
- Perturbation factors, 226
- Per-VPN edge-marking, 267
- PESQ (Perceptual Evaluation of Speech Quality), 23
- “P” frames, 39
- PHB *see* Per-Hop Behaviors
- Physical redundancy, 53
- Pipesize, 270–1
- Pipe tunneling model, 16–18, 168–70, 178–81
- Play-out delay: VoIP, 31–3
- Point-of-presence (POP), 378
- Poisson sampling, 352, 353, 354
- Poisson traffic, 383–4
- Policing, 100–11, 186, 222, 339–42
- Policy: information distribution, 398
- Polling, 337, 345
- POP (point-of-presence), 378
- Ports, 357–8
- Positive acknowledgement with retransmission, 60–1
- Precedence, 144–5, 146
- Predictive coded “P” frames, 39
- Pre-emption priority levels, 286
- Premium data delay-optimized class (Prm-delay), 233–7, 261–2
- Premium data loss-optimized class (Prm-loss), 236–9, 262
- Premium data (Prm) classes:
  - backbone Diffserv, 254, 256, 259–60, 261–3
  - edge Diffserv, 223, 233–9
- Premium data throughput-optimized class (Prm-th), 213, 217–18, 223, 233–9, 262
- Prioritized Diffserv, 254–6
- Priority scheduling, 93, 114–15, 125–6, 240, 286
- Private networks, 263, 265, 267
- Prm *see* Premium data
- Prm-delay *see* Premium data delay-optimized class
- Prm-loss *see* Premium data loss-optimized class
- Prm-th *see* Premium data throughput-optimized class
- Probability of delay/discard, 268, 271, 385–6
- Probe packets, 348
- Processing delays, 6, 8, 71–2
- Professional-MPEG [PRO-MPEG] forum, 49–51
- Propagation delay, 5–6, 8, 216, 417
- Protocols, 357–8
  - see also individual protocols*
- Public switched telephony networks (PSTN), 294–302
- PVR (personal video recorders), 43
- QCIF *see* Quarter common interchange format
- QoE *see* Quality of experience
- QOS *see* Quality of service
- QOS Signaling: CAC, 327
- Quality of experience (QoE), 22–4, 58, 364
- Quality of service (QoS):
  - best-effort service, 89–90
  - CAC, 327
  - classification, 93, 94–9
  - class of service, 88–9
  - complementary technologies, 197–8
  - data plane mechanisms, 92–141
  - definition, 87–94
  - dropping, 128–37
  - introduction, 2–3
  - Intserv, 79
  - IP multicast, 181–3
  - layer 2 technologies, 98, 189–97
  - limitations, 198–9
  - link fragmentation and interleaving, 140–1
  - marking, 93, 99–111

Quality of service (*Contd*)

- mechanics, 92–141
- metering, 111
- multicast, 181–3
- packet marking, 93, 99–111
- policing, 100–11
- policy, 183–9
- queuing, 112–28
- reasons for, 91
- requirements, 2–3, 12, 16, 19, 30, 34
- routers, 183–9
- scheduling, 112–28
- shaping, 137–40
- signaling, 327
- time frames, 90–1
- toolsets, 91–141
- type of service, 88–9

## Quarter common interchange format (QCIF), 55

## Queues/queuing:

- buffers, 128–9
- data plane QOS mechanisms, 112–28
- edge Diffserv, 246–9
- FIFO, 112–13
- passive monitoring, 342–6
- premium data delay-optimized class, 234–5
- simulations, 385–6
- SLA metrics, 6, 8, 15
- thresholds, 268, 270–1
- see also* Scheduling

## Random early detection (RED), 132–7, 186, 239, 263, 268–72, 344–6

## Random sampling, 352–3

## Rating Factor, 23

## Real-time (RT) classes, 242, 253–4, 256, 258–9

## Real-time transmission (RTT), 43, 51–2

## Real-time VBR, 191

## Received stream metric measurements, 349

## Receiver-initiated reservations, 304–5, 327

## RECEIVER TSPEC, 311

RED *see* Random early detection

## Regional boundaries, 318

## Regional meshes, 410–11

## Remote control video streaming, 41, 44

## Re-ordering packets, 19, 37, 57, 363

## Reroute technologies, 198

ReSerVation Protocol *see* RSVPReSerVation Protocol-traffic engineering *see* RSVP-TE

## Reservation setup, 307–14

## Resizing, 324–5

## Resource information distribution, 398

## Resource managers, 292–302

## Resource requirements, 285

## Responsiveness, 281–2

## ResvConf messages, 334

## Round robin, 116–19, 121–3

## Round trip time (RTT) delay, 4–5, 358

## Route pinning, 417

## Routers/routing:

- CAC, 305–6
- edge Diffserv, 230–3, 242–3
- protocol classes, 242–3
- quality of service, 183–9

## RSVP (ReSerVation Protocol):

- aggregation, 320–5
- application signaling interaction, 314–16

- CAC, 282–3, 303–26

- definitions, 304–7

- IP multicast, 182–3

- MPLS QOS architectures, 172–3

- MPLS TE, 399–402

- reservation setup, 307–14

- signaling interaction, 314–16

## RSVP-TE (ReSerVation Protocol-traffic engineering), 325–6

RT *see* Real-timeRTT *see* Real-time transmission; Round trip time

## Russian doll models, 405

- Sampling frequency, 349, 351–5
- Scalability, 147
- Scheduling:
  - advanced concepts, 126–8
  - ATM layer 2 QOS, 192
  - data plane QOS mechanisms, 112–28
  - edge Diffserv design, 228–30, 240
  - FIFO, 112–13
  - Intserv, 303
  - premium data delay-optimized class, 235–6
  - SLA metrics, 6, 8, 15
  - which algorithm?, 123–5
  - see also* Queuing
- Secure tunneling, 165
- Security protocols, 327–8
- Segmented SLAs, 77
- Self-induced VoIP queuing delay, 246–9
- Self-similar traffic, 383–4
- Sender-initiated reservations, 327
- Sequence preservation, 18–19
- Serialization delay, 6–7, 8
- Server-side processing delays, 71
- Service availability, 21–2, 364
- Service classes, 213–18, 221–5, 253–6, 258–61
- Service level agreements (SLA), 1–4
  - active monitoring, 335–6, 348–71
  - application requirements, 24–76
    - data applications, 58–75
    - video, 38–58
  - Voice over IP, 26–37
  - availability factors, 20–2
  - backbone Diffserv, 253–6
  - bandwidth, 12–18
  - CAC, 285–6
  - differentiation, 242
  - Diffserv, 78–9, 211–18, 233–7, 241–2, 253–6
  - edge Diffserv, 212–18, 233–4, 236–7, 241
  - edge keys, 211–12
  - engineered versus marketed, 76–8
  - Intserv, 78–9
  - marketed versus engineered, 76–8
  - metrics, 3–24, 349, 358–64
    - availability factors, 20–2
    - bandwidth, 12–18
    - network delay, 4–7
    - packet loss, 9–11
    - per-flow sequence preservation, 18–19
    - quality of experience, 22–4
    - sequence preservation, 18–19
    - throughput, 12–18
  - network delay, 4–7
  - network monitoring, 335–73
  - packet loss, 9–11
  - passive monitoring, 335, 336–48
  - premium data classes, 233–4, 236–7
  - quality of experience, 22–4
  - requirements, 211
  - sequence preservation, 18–19
  - specifications, 78, 212–18, 233–7, 241, 253–6
  - throughput, 12–18
  - video, 38–58
  - Voice over IP, 26–37
- Service octets, 96–8, 142–4, 145–6
- Service types, 142–4, 145–6
- Session establishment, 60
- Setting tunnel bandwidth, 412–13
- Set-top-box (STB) processing, 41, 42, 44–5
- Shaping:
  - ATM layer 2 QOS, 192
  - data plane QOS mechanisms, 102, 137–40
  - edge Diffserv design, 228–30
  - frame relay layer 2 QOS, 195
  - policers, 137–8
  - SLA metrics, 15
- Short pipe tunneling model, 181
- Signaling, 243, 314–16, 326–8
- Silence suppression: VoIP, 36

- Simple classification, 96–9, 357
- Simple IP-in-IP tunnels, 165
- Simple network management protocol (SNMP), 336
- Simplicity in scheduling algorithms, 124–5
- Simulations in capacity planning, 377, 385–6, 388–9
- Single rate three color markers (SR-TCM), 102–6, 339–42
- Size factors, 324–5
- SLA *see* Service level agreements
- Sliding acknowledgement windows, 61
- Slow start congestion control, 61–3
- SNMP (simple network management protocol), 336
- Soft state, 306
- Source marking, 99
- Spatial redundancy, 53
- SR-TCM *see* Single rate three color markers
- Standard classes (Std):
  - backbone Diffserv, 254, 256, 260–1
  - edge Diffserv, 213, 218, 224–5
- Standard definition (SD) format, 54–5
- Stateful inspection, 96
- STB *see* Set-top-box
- Std *see* Standard classes
- Stratified random sampling, 352–3
- Stream/streaming, 47, 57, 95, 348–50
  - see also* Video streaming
- Strict priority, 125–6
- Subjective measures, 23, 24
- Switching delay, 6, 8, 216
- Synchronizing clocks, 370–1
- Synthetic traffic test streams, 348
- Systematic TE deployment, 396, 409–11
- System monitoring, 346–7
- Tactical TE deployment: MPLS TE, 408–9
- Tail drop, 129–32, 186, 222, 343–4
- Taxonomy of CAC, 282–5
- TCM *see* Three-color markers
- TCP *see* Transmission Control Protocol
- Telephony networks, 294–302
- Temporal redundancy, 53–4
- Testing:
  - duration, 355–7
  - frequency, 349, 354–7
  - test rates, 354–5
  - test streams, 348–50
- Three-color markers (TCM), 106–8, 239, 340–2
- Threshold exceeded count delay, 360
- Throughput:
  - active network monitoring, 363
  - SLA metrics, 12–18
  - TCP applications, 59–70
  - video streaming, 54–6
  - VoIP, 36–7
- Tight SLA services, 211–12
- Time frames, 90–1
- Token bucket mechanisms, 101–8, 138
- Toolsets for QOS, 91–141
- Topologies: active monitoring, 365–9
- Topology-awareness, 283, 290–302, 319
- TOS *see* Type of service
- Traffic assignment to tunnels, 402–5
- Traffic classes, 95, 97
- Traffic classification, 147–8
- Traffic conditioning, 78–9, 147–8, 340
- Traffic demand matrices, 376, 377–82
- Traffic engineering, 389–413
  - bandwidth, 376–7, 382–8, 393, 412–13
  - CAC, 325–6
  - deployment, 391–4
  - Diffserv-aware MPLS TE, 404–8
  - IGP based, 390, 394–7
  - multi-protocol label switching, 397–413
  - RSVP, 325–6
  - tunnels, 300, 402–5
- Traffic management classes, 242–3
- Traffic matrices, 347–8
- Traffic metering, 111
- Traffic shapers, 15

- Traffic test streams, 348–50
- Transmission Control Protocol (TCP), 59–70, 161–5
- Transmission delays, 41, 42, 43, 45
- Transport stream packets, 47
- TR-TCM *see* Two rate three color markers
- Trust boundaries, 110–11
- Tunneling:
  - bandwidth sizing, 412–13
  - CAC, 300, 324
  - Diffserv, 165–70, 175–81
  - MPLS Diffserv, 175–81
  - MPLS TE, 397–404, 412–13
  - next generation networks, 300
  - pipe model, 168–70, 178–81
  - uniform model, 166–8, 176–8
  - voice CAC, 300
- Two rate three color markers (TR-TCM), 106–8, 239, 340–2
- Type of service (TOS), 88–9, 142–4, 145–6
- UBR (unspecified bit rate), 192
- Unicast reservations, 284, 304, 307–14, 327
- Unidirectional reservations, 284, 304
- Uniform tunneling model, 166–8, 176–8
- Universal edge-marking, 267
- Unmanaged access router services, 230–3
- Unspecified bit rate (UBR), 192
- Utility functions, 279–80
- VAD *see* Voice activation detection
- Variable bit rate (VBR), 191
- VC *see* Virtual circuits
- Video:
  - backbone Diffserv, 262
  - conferencing, 57–8
  - edge Diffserv design, 239–40
  - quality of experience, 24
  - SLA requirements, 38–58
  - streaming, 38–57
    - delay, 40–7
    - jitter, 46–7
    - loss impacts, 47–54
    - packet re-ordering, 57
    - throughput, 54–6
- Video-on-demand (VOD), 43–6, 47
- Virtual circuits (VC), 190–4, 320
- Virtual paths (VP), 320
- Virtual private networks (VPN), 16–18, 172, 267
- VOD *see* Video-on-demand
- Voice activation detection (VAD), 36
- Voice class maximum rate enforcement, 339–40
- Voice QoE, 23
- VoIP (Voice over IP):
  - delay, 29–33
  - edge Diffserv, 213, 214–17, 221–3, 232–3, 240, 245–9
  - jitter, 31–3
  - loss impacts, 33–6
  - packet re-ordering, 37
  - SLA requirements, 26–37
  - throughput, 36–7
- VPN *see* Virtual private networks
- VP (Virtual paths), 320
- Weighted bandwidth scheduling, 115–25
- Weighted fair queuing (WFQ), 119–21
- Weighted random early detection (WRED):
  - backbone Diffserv, 263
  - data plane QOS mechanisms, 136, 137
  - Diffserv deployment, 239, 263, 268–72
  - passive monitoring, 346
  - router QOS implementation, 186
- Weighted round robin (WRR), 116–19
- Weighted tail drop, 131–2, 343–4
- WFQ (weighted fair queuing), 119–21
- Worst-case delay bounds, 124
- WRED *see* Weighted random early detection
- WRR (weighted round robin), 116–19