

# Index

6 to 4 tunnels, 255  
10Base2, 87  
10G-base-er (extended range), 88  
100BaseT, 87  
    Ethernet LANs, 62

## A

Abrupt close, 292  
Access charges, 338  
Access control, 33  
Access points (APs), 99–100  
Active open, 56  
Active Service Pages (ASP), 562, 570  
    installation, 562  
    pages, 563  
Adaptive Service Physical Interface Card  
    (AS PIC), 692  
    interface, 692  
    internal interface supported by, 716  
    traffic match-up, 692  
Address resolution, 36  
    ICMPv6, 152, 153  
    IPv6, 152–59  
    Neighbor Discovery, 161–62  
Address Resolution Protocol (ARP), 51, 58,  
    143–62, 165  
    arriving request, 150  
    ATM (ATMARP), 146  
    example operation, 155–57  
    exchange example, 157  
    host to host, 146  
    host to router, 146  
    Illustrated Network, 144–45  
    InARP, 146, 159  
    IPv6 and, 159–62  
    LANs and, 146–53  
    layers and, 146  
    Proxy, 157–58  
    request and reply process, 156  
    results, 143  
    RARP, 146, 158  
    router to host, 147  
    router to router, 147  
    scenarios illustration, 147  
    tables, 146  
    variations, 157–59  
    WANs and, 158–59  
    Windows XP reply capture, 150  
    *See also* ARP cache; ARP messages

Administratively scoped addresses, 407  
AfriNIC (African Network Information  
    Center), 138  
Agent/manager model, 616  
Agents  
    object values, 618  
    proxy, 617  
    SNMP message/command acceptance, 627  
    software, 616, 617, 621  
    SSH, 640  
AH. *See* Authentication header  
Alternate host address message, 203  
American National Standards Institute  
    (ANSI), 17  
American Standard Code for Information  
    Interchange (ASCII), 17  
Anonymous FTP, 619  
Anycast  
    addresses, 116–17  
    one-to-many relationship, 488  
Any-Source Multicast (ASM), 418  
Apache Web server software, 562  
    capture, 564, 583  
    OpenSSL, 588  
    SSL test certificate, 589  
    “success” page, 564  
APNIC (Asian Pacific Network Informa-  
    tion Center), 138  
Application layer, 30, 41, 59–60  
    interface, 52  
    tasks, 41  
    *See also* TCP/IP layers  
Application programming interfaces  
    (APIs), 52  
Applications  
    layers and, 301–4  
    multicast, 406, 407  
    TCP/IP, 11, 41, 42–43  
    UDP, 59  
ARIN (American Registry for Internet  
    Numbers), 138  
ARP cache, 143, 156  
    entry deletion, 151  
    Linux display of, 151  
    Windows XP display of, 152  
    *See also* Address Resolution Protocol  
ARP messages, 153–55  
    fields illustration, 154  
    Hardware Size field, 155

ARP messages (*cont'd*)

- Operation field, 155
- Protocol Size field, 155
- Sender's Ethernet Address field, 155
- Sender's IP Address field, 155
- Target Ethernet Address field, 155
- Target IP Address field, 155
- Type of Hardware field, 154
- Type of Protocol field, 154
- uses, 163

*See also* Address Resolution Protocol (ARP)

ASN.1 (Abstract Syntax Notation version 1), 618

Asymmetric DSL (ADSL), 95

Asynchronous transfer mode (ATM), 18, 71, 85, 434, 438–41

- ATMARP, 146
- cell header, 439
- cell relay, 439
- connection identifier, 440
- as international standard, 439
- logical links, 90
- switches, 442
- VCI, 159
- VPI, 159

Attributes, BGP, 393

- AGGREGATOR, 394
  - AS\_PATH, 394
  - ATOMIC\_AGGREGATE, 394
  - CLUSTER\_LIST, 395
  - COMMUNITY, 394–95
  - discretionary, 393
  - list of, 393
  - LOCAL\_PREF, 394
  - mandatory, 393
  - MULTI\_EXIT\_DISC, 394
  - NEXT\_HOP, 394
  - nontransitive, 393
  - ORIGIN, 394
  - ORIGINATOR\_ID, 395
  - transitive, 393
  - type format, 399
- See also* Border Gateway Protocol (BGP)

Authentication, 594–95

- RIPv2, 361
- servers, 100, 585
- SMTP, 544–45
- SSH, 637–38
- SSH-AUTH, 644–45
- user, 585

Authentication header (AH), 713, 723–25

- Authentication Data field, 725
- fields, 724–25
- ICV, 723
- Next Header field, 724
- packet formats, 723
- Payload Length field, 724
- Reserved field, 724
- Sequence Number field, 724
- SPI field, 724

Authoritative servers, 487

Automatic IP addressing, 112

Automatic tunneling, 253

Autonomous system numbers (ASNs), 348–49

Autonomous systems (ASs), 332–34

- border routers (ASBRs), 332, 368, 369, 370
- multihomed, 389
- RIPng and, 345
- router connectivity, 333

Auxiliary port, 248

Avaya VoIP software, 738

## B

Backbone routers, 246, 334

- architecture, 246
- running RIPng, 351

Backdoor links, 368

Backup Designated Router (BDR), 370–71

Bandwidth

- in protocol evolution, 3–6
- QOS, 327

Base64 encoding, 545

Beacon frames, 99

Berkeley Internet Name Domain (BIND), 497

Best match, 251

Bidirectional NAT, 687–89

- DNS procedure, 688–89
- illustrated, 688
- static mapping, 688

*See also* Network address translation

Binary packet protocol, 643

Bindings, 143

Bit synchronization, 31

Blades, 244

BOOTP, 459, 468–72

- client broadcast, 468
- DHCP message comparison, 481
- flexibility, 469
- implementation, 469
- messages, 469–71
- relay agents, 464, 471, 472

- requests, 468
  - servers, 459, 469
  - vendor-specific area options, 471–72
  - See also* Dynamic Host Configuration Protocol (DHCP)
  - Bootstrap programs, 245
  - Border Gateway Protocol (BGP), 337, 379–401
    - attributes, 393–95
    - birth of, 387–88
    - configuration groups, 383
    - configuring, 382–84
    - default behavior, 383
    - EBGP, 382, 389–90
    - extended communities, 388
    - IBGP, 382, 389–90
    - Identifier, 390
    - Illustrated Network, 380–81
    - import policy, 385
    - Internet and, 386–88
    - Keepalive messages, 396
    - MBGP, 392, 413, 447–48
    - message header, 397
    - message types, 396
    - Multihop, 392
    - next hops, 390
    - NLRI, 382
    - Notification messages, 396, 399–400
    - Open messages, 396, 397, 398
      - as path vector protocol, 388–89
      - route advertisement, 389
      - routing policies, 384–86, 395–96
      - as routing protocol, 379–86
      - scaling, 395–96
      - session growth, 395
      - speakers, 389
      - synchronizing, 391
      - types of, 392–93
      - universally reachable address level, 389
    - Update messages, 396, 397–98
  - Border routers, 334
    - AS, 368
    - EGP, 387
  - Branches, 410
  - Bridges, 63
    - connecting TCP/IP hosts, 64
    - illustrated use, 69
    - operation, 60
      - as protocol independent devices, 64
      - spanning tree, 63
  - Broadband ISDN (B-ISDN), 439
  - Broadband power line (BPL), 86
  - Broadcast domains, 58, 61, 116
    - collision and, 62
  - Broadcast/multicast addresses, 116
  - Broadcasts, VLANs for cutting down, 67
  - Bus/broadcast topology, 31
- ## C
- Cable modems (CMODEMs), 85
  - Call agents, 753
  - Captive portal, 100
  - Carrier-sense multiple access with collision avoidance (CSMA/CA), 100
  - Carrier-sense multiple access with collision detection (CSMA/CD), 87, 101
  - Cascading style sheets (CSSs), 570
  - Cell relay, 439
  - Certificate authorities (CAs), 595
  - Certificate revocation lists (CRLs), 595, 603
  - Certificates
    - Apache SSL test, 589
    - Details tab, 590–91
    - fields, 590
    - private key, 591
    - public key, 591
    - security warning, 588
    - self-signed, 595
    - site, 589
    - SSL and, 604
    - tests, 589
    - viewing, 589, 590
  - Certificate signing request (CSR), 604
  - Chained headers, 124
  - Challenge Handshake Authentication Protocol (CHAP), 666
  - Checksum, 264, 266
  - Chunked encoding, 573
  - Cipher Block Chaining (CBC), 601
  - Cipher Suites, 599, 600
  - Classful IPv4 addresses, 114, 118
    - concepts, 120
    - default masks and, 128
    - illustrated, 118
    - See also* IPv4 addresses
  - Classless interdomain routing (CIDR), 117, 131–35
    - address grouping under, 132
    - aggregation, 135
    - contiguous IP addresses, 132
    - in operation, 135
    - prefixes and addressing, 133–34, 135
    - RFC, 132
  - Classless IP addresses, 119, 120

- Class of service (CoS), 327, 328
  - Clear text encryption, 638
  - Clients, 7, 8
    - BOOTP broadcast, 468
    - DNS, 463
    - email, 538
    - FTP, 304, 513, 519, 529
    - SSH, 639
    - VoIP, 738
  - Client-server model, 54, 55
    - application implementation, 56
    - peer-to-peer model versus, 55
    - TCP/IP layers and, 55–57
  - Collocation facilities, 334
  - Command-line interface (CLI), 8, 11–12
  - Common Management Information Services/
    - Common Management Information Protocol (CMIS/CMIP), 612
  - Communications
    - layers, 22
    - layers summary, 45
    - termination of, 15
  - Community strings, 627
  - Compressed SLIP (CSLIP), 85
  - Confederations, 337
  - Configuration
    - BGP groups, 383
    - for DHCP use, 464
    - multipoint, 31
    - physical layer, 31
    - point-to-point, 31
    - router-by-router, 672–74
    - SSH files, 640
    - VPLS, 672–74, 679
  - Configured tunneling, 253
  - Congestion control, 275
    - TCP, 294
    - UDP, 275
  - Connection control, 40
  - ConnectionLess Network Protocol (CLNP)
    - packets, 372
  - Connectionless networks, 325–28
    - comparison, 325
    - QOS, 326–28
  - Connection-oriented networks, 325–28
    - comparison, 325
    - QOS, 326–28
  - Connections, 279, 324
    - closing, 291–92
    - control, 518, 522–23
    - data, 521–24
    - data transfer, 289–91
    - establishment, 288–89
    - FTP, 518, 521–24
    - maximum segment size (MSS), 286
    - on-demand, 279
    - permanent, 279
    - procedures, 287
    - three-way handshake, 286
  - Console port, 248
  - Constrained path LSPs, 447
  - Contributing source identifiers (CSRC), 746
  - Control connection, FTP
    - in directory listing, 523
    - FTP model, 522
    - setup, 518
  - Convergence, 435–42
    - desire for, 431
    - on Metro Ethernet links, 435
    - on TCP/IP, 441–42
  - Cookies, 570, 580–81
    - issues, 581
    - screening/rejecting, 581
    - third-party, 581
    - as Web state management, 580
    - in Windows XP, 580
  - Core-based trees (CBT), 418
  - CS packets, 740
  - Customer-edge (CE) routers, 9, 47, 670
    - CE0, 672, 716–18
    - CE6, 676, 718–19
  - Cyclic redundancy check (CRC), 33, 103
- ## D
- Data connection, FTP, 521
    - active mode, 524
    - activity on, 524
    - FTP model, 522
    - illustrated, 523
    - passive mode, 524
    - See also* File transfer protocol (FTP)
  - Data Encryption Standard (DES), 601
  - Datagrams, 55, 165, 259
    - conversion errors, 203
    - See also* User Datagram Protocol (UDP)
  - Datagram sockets, 306
  - Data Link Connection Identifier (DLCI), 159, 437, 438
  - Data link layer, 30, 32–35, 84–86
    - forwarding, 34–35
    - frames and, 83–84
    - functions, 32–33
    - illustrated, 32
    - See also* TCP/IP layers
  - Data rate, 31

- Data transfer
  - connections, 289–91
  - FTP, 521–24
  - SSL, 601
  - TCP, 289–91
- Dead routers, 213
- Decryption, 597–98
- Deep inspection, 707
- De facto standards, 16–17
- Default gateways, 233
- De jure standards, 16
- Delayed duplicate, 291
- Demultiplexing, 301–16
- Dense-mode multicast, 410
- Designated intermediate system (DIS), 375
- Designated Router (DR), 370–71
- Destination hosts, 229, 231
- DHCPv6, 479–80
  - operation, 480
  - reasons for use, 479
  - router advertisements and, 479–80
  - servers, 480
  - See also* Dynamic Host Configuration Protocol (DHCP)
- Dialog controllers, 41
- Differentiate Services Code Point (DSCP), 169, 170
- Diffie-Hellman, 643
  - pocket calculator, 643–44
  - SSL use, 599
- Digital signatures, 594, 598
- Digital signature standard (DSS), 642
- Digital subscriber line (DSL), 7–8, 85
  - access multiplexer DSLAM, 79, 93–94, 95
  - ADSL, 95
  - encapsulation, 93–94
  - evolution of, 90–96
  - forms of, 94–96
  - HDSL, 95
  - as ISDN extension, 94
  - ISDN (IDSL), 95
  - links, 7, 78–81
  - link setup screen, 80
  - Lite (G.Lite), 95
  - modulation techniques, 94
  - PPP and, 86, 91–92
  - protocol stacks, 94
  - router log table, 81
  - routers, 78, 79, 329
  - symmetric (SDSL), 95
  - types of, 95
  - VDSL, 85, 95
  - xDSL, 94
- Dijkstra algorithm, 365
- Direct delivery, 226
  - MAC addresses and, 227
  - packets on LANs, 230
  - without routing, 230–31
  - Windows and, 226
- Distance Vector Multicast Routing Protocol (DVMRP), 417
- Distance-vector protocol, 354
- Distance-vector routing, 355–56
  - consequences, 357–58
  - split horizon, 357
  - triggered updates, 357–58
- Distributed coordination function (DCF), 100
- Distribution trees, 409
  - branches, 410
  - leaves, 409
  - See also* Multicast
- DIX Ethernet, 87
- DMZ, 708–10
  - dual firewalls with, 709, 710
  - multiple protection types, 709
  - servers, 709
  - uses, 708
  - See also* Firewalls
- DNS and BIND* (Liu), 506
- DNSSec, 489, 496–97
  - design, 497
  - encryption and, 497
  - specifications, 497
  - See also* Domain Name System (DNS)
- Domain Internet Groper (dig), 497–98, 504
  - feature bloat, 505
- Domain Name Space
  - resource records, 489
  - root, 502
- Domain Name System (DNS), 60, 483–507
  - in action, 498–506
  - authoritative servers, 487
  - basics, 486–89
  - BIND, 497
  - cache poisoning, 497
  - clients, 463
  - concepts, 489–90
  - correct functioning, 483
  - delegation, 491–93
  - dig, 497–98, 504
  - entry update, 463
  - glue records, 493
  - hierarchy, 486–87
  - hosts, adding, 490

Domain Name System (DNS) (*cont'd*)

- host utility, 498
- Illustrated Network, 484–85
- iterative queries, 491
- local, 491, 492
- message format, 495
- message header, 496
- name servers, 489, 491
- nonauthoritative servers, 487
- nslookup utility, 497, 501
- in practice, 493–98
- public, 527
- query message, 495
- records, 499
- recursive queries, 490–91
- referral, 491–93
- resolver, 491
- resource records (RRs), 493–95
- response message, 495
- Security (DNSSec), 489, 496–97
- server log and reply, 500
- servers, 463, 486–87
- service providers, 493
- spoofing, 638
- theory, 489–93
- tools, 497–98

Dotted decimal notation, 119

Double Encryption, 666

Downstream interface, 409

DRAM, as working storage, 245

DSL. *See* Digital subscriber line

Dual protocol stacks, 252

Duplex mode, 32

Dynamic Delegation Discovery System (DDDS), 569

Dynamic Host Configuration Protocol (DHCP), 79, 121, 207, 233, 459–81

- addresses on LAN2, 465–66
- addressing and, 462–68
- BOOTP message comparison, 481
- BOOTP relay agent use, 475
- design functions, 475
- DHCPACK messages, 478
- DHCPDECLINE messages, 477
- DHCPDISCOVER messages, 477
- DHCPINFORM messages, 478
- DHCPNAK messages, 478
- DHCPOFFER messages, 477
- DHCPRELEASE messages, 478
- DHCPREQUEST messages, 477
- discover message details, 467
- with dynamic IP addresses, 493
- flags field, 476

- host direction to, 213
- Illustrated Network, 460–61
- message flow, 477
- message format, 476
- messages, 465, 466
- message types, 477–78
- multicast, 266
- network use, 466–68
- offer message details, 467
- operation, 475–78
- options field, 476
- relay agent, 464–65
- routers and, 479–80
- sequence of messages, 477
- server configuration, 462–64
- servers, 480
- Windows configuration for, 464
- See also* DHCPv6

Dynamic IP address assignment, 121

Dynamic link libraries (DLLs), 309, 310

Dynamic ports, 264, 271, 272

Dynamic Web pages, 573

**E**

ECN Congestion Explicit (ECT-CE), 169

Edge routers, 329, 334

Egress routers, 446, 451–52

Electronic Industries Association (EIA), 17

Email, 535–57

- access and reading, 541–42
- architectures, 538–47
- clients, 538
- delivery of, 541
- evolution, 544
- headers and, 552–55
- home office, 555
- Illustrated Network, 536–37
- Internet illustration, 539
- MAA, 538
- mailboxes, 538
- message composition, 541
- MTA, 538, 543
- POP3 access, 550–52
- processing, 541
- protocols, 542–44
- sending, 540–42
- submission of, 541

Embedded RP, 415

Encapsulating security payload (ESP), 713, 725–28

- ESP Authentication Data field, 728
- fields, 726–28

- header, 725
- IPv4 packet formats, 727
- IPv6 packet formats, 726
- Next Header field, 728
- Padding field, 728
- Pad Length field, 728
- Payload Data field, 726
- Sequence Number field, 726
- SPI field, 726
- Encapsulation, 24, 28–29
  - DSL, 93–94
  - flow, 29
  - sequence, 253
  - wireless LANs, 82
- Encoding
  - base64, 545
  - chunked, 573
  - MIME, 548–49
- Encryption, 598
  - double, 666
  - P2TP, 667
  - public key, 595–98
- End systems, 6, 26
- End-to-end headers, 576
- End-to-end protocols, 570
- Enhanced IGRP (EIGRP), 355, 364–65
  - as hybrid routing protocol, 365
  - as IGRP redesign, 364
- Enterprise-specific trap type, 626
- Entities, 14
- Error control, 40
- Error correction, 15
- Error detection, 15
- Error messages, 177, 199
  - all-0 unused byte, 198
  - ICMP destination unreachable codes, 200
  - ICMPv6, 209
  - list of, 200
  - See also* ICMP messages
- Ethereal, 13, 74
  - capture summary, 50
  - graphical interface, 75
  - IPv6 traffic display, 152
  - protocol hierarchy statistics, 51
- Ethernet, 71, 87
  - DIX, 87
  - evolution, 86–90
  - frames, 74, 76, 79
  - frame structure, 88
  - interface, manual configuration, 330
  - LAN switches, 9, 33
  - links, 72–73

- MIB, 621, 622
  - traffic display, 74–76
  - transparent bridging, 63
- Ethernet II, 88
- Experimental RFCs, 20
- Explicit-Congestion-Notification Capable Transport (ECT), 169
- Extensible MIB, 622
- Extension Headers, 184
- Exterior BGP (EBGP), 382, 389–90
  - NLRI, 391
  - sessions, 389
  - See also* Border Gateway Protocol (BGP)
- Exterior Gateway Protocol (EGP), 386
  - border routers, 387
  - Internet and, 386–87
- External Data Representation (XDR)
  - standard, 531

**F**

- Fast packet switching, 435
- Fastream NETfile FTP server, 516
- Federal Communications Commission (FCC), 18
- Fiber Distributed Data Interface (FDDI), 85
- File transfer
  - Ethereal capture, 13
  - FTP commands for, 529
  - FTP for, 512, 526
  - with GUI, 11
  - to routers, 10–11
  - types, 526
  - for user information, 530
- File Transfer Protocol (FTP), 10, 43, 59, 509–31
  - active mode, 509, 525
  - anonymous, 519
  - application-level operation, 513
  - basics, 518–19
  - block mode, 527
  - CLI, 529
  - client implementations, 513
  - client process, 304
  - client programs, 519
  - client software, 529
  - CLI versions, 512
  - commands, 519–21, 527–31
  - commercial implementations, 530
  - compressed mode, 527
  - control connection, 518, 521, 522, 523
  - conversation, 521
  - data connection, 521, 522, 523

File Transfer Protocol (*cont'd*)

- data transfers, 521–24
- features, 514
- file-structure, 526
- file transfer types, 526
- FreeBSD, 512
- GUI implementations, 529, 530
- GUIs and, 516–27
- Illustrated Network, 510–11
- Linux and, 514
- model, 521
- passive command, 513
- passive mode, 509, 513, 525
- passive with FreeBSD, 515
- passive with Linux, 515
- ports, 518
- record-structure, 527
- remote access for, 10
- reply codes, 520–21
- RFCs, 518
- servers, 304, 519
- sessions, 297, 520
- sockets applied to, 305
- SONET, 32
- SSH and, 647
- stream mode with file-structure, 527
- stream mode with record-structure, 527
- TCP and, 296–98
- TFTP comparison, 472–73
- three-way handshake, 297
- transmission mode, 527
- Web browsers and, 516, 517, 518

FileZilla, 516, 517

Firewalls, 664, 697–711

- appliance general architecture, 707
- appliances, 700, 705
- application proxy, 706
- dedicated, 697
- design advantages/disadvantages, 710
- DMZ, 708–10
- functions, 700–705
- hardware, 700, 705
- ICMP messages and, 195
- Illustrated Network, 698–99
- packet filters, 700–701, 706
- as router packet filter, 700–701
- software, 700, 705
- stateful inspection, 701–5, 706–8
- types of, 705–10

Flow caching, 124

Flow control, 40, 274

- confusion, 275
- implementation, 292

- TCP, 292–94

- UDP, 274–75

Forwarding, 217, 237–57

- hardware-based, 243

- Illustrated Network, 238–39

- Linux, 243

- reverse-path, 411–13

- software-based, 243

Forwarding tables, 217, 220, 246, 330

- location, 247

- longest match, 250

- lookups, 249–51

Fragmentation, 36, 168

- example, 177–82

- fields, 176, 179

- IPv4 and, 172–77

- IPv6 and, 184–86

- path MTU determination and, 176–77

- as processor intensive, 176

- reassembly and, 176

Fragmentation Header fields, 186

Frame addressing, 82

Frame relay, 71, 85, 159, 434, 435–38

- frames, 437

- problems, 438

- today, 438

- as X.25 on steroids, 436

Frames, 74

- beacon, 99

- Ethernet, 74, 76, 79

- filtering, 63

- flooding, 63

- forwarding, 63

- frame relay, 437

- hop-by-hop forwarding, 34

- IEEE 802.3, 88

- link layer and, 83–84, 204

- multicast and, 420–21

- PPP, 93

- SONET, 32, 97

- T1, 32

- types, 83–84

Frame tagging, 66

- VLAN, 66–68, 671

FreeBSD

- flags, 223

- FTP, 512, 515

- routing tables and, 329–30

- servers, 498

FTP. *See* File Transfer Protocol

FTP commands, 519–21, 527–31

- client implementation, 528

- for file server access, 528



- for file transfer, 529
- for remote server file management, 528
- for transfer parameters, 529
- See also* File transfer protocol (FTP)
- Full-duplex mode, 32
- Fully qualified domain names (FQDNs), 486

## G

- Gateways, 7, 8, 222, 329
  - default, 233
  - residential, 78
  - See also* Routers
- Generic Routing Encapsulation (GRE), 662
  - interfaces, 241
  - tunnels, 255
- Generic top-level domains (GLTD), 502
- Gigabit Ethernet (GE), 61, 87
  - frames, 89
  - links, 7, 67
- Gigabit Ethernet Passive Optical Network (GE-PONS), 85–86
- Glue records, 493
- Graphical user interface (GUI), 11–12
  - example use, 11–12
  - file transfer with, 11
  - FTP and, 516–27
- Groups, multicast, 410

## H

- H.323 standard, 749–50
  - signaling stack, 749
  - support, 750
  - zone components, 750
- Half-duplex mode, 32
- Handshaking, 15
- Hardware addresses, 118
- Hardware-based fabric, 246
- Hardware-based forwarding, 243
  - routers, 247
  - switching fabric, 246, 247
  - See also* Forwarding
- Hardware firewalls, 700, 705
- Headers
  - chained, 124
  - end-to-end, 576
  - hop-by-hop, 576–77
  - pseudo, 266–69, 297
  - UDP, 267–68
  - See also* IPv4 packet headers; IPv6 packet headers; TCP headers
- Headers, email
  - added after email creation, 554
  - characteristics, 552–53

- fields, 552–53
  - message path, 554–55
- Headers, HTTP, 576–77
  - entity headers, 579–80
  - general, 577
  - Last-Modified, 580
  - request, 577–78
  - response headers, 578–79
  - See also* Hypertext Transfer Protocol (HTTP)
- Hidden terminal problem, 100, 101
- High-level Data Link Control (HDLC), 436
- High-speed DSL (HDSL), 95
- Home office email, 555
- Hop-by-hop forwarding, 34
- Hop-by-hop headers, 576–77
- Hosts, 6
  - addresses, 121
  - bridges connecting, 64
  - dead, 213
  - destination, 229, 231
  - Linux, 224
  - multicast, 415
  - NICs, 231
  - routing tables, 222–26, 328–32
  - source, 229
  - in TCP/IP networks, 14
  - Windows, 224
- Host-to-host tunnels, 253, 254
- Host-to-router tunnels, 253, 254
- Host utility, 498
- Hypertext Markup Language (HTML), 559, 570
- Hypertext Transfer Protocol (HTTP), 42, 60, 547, 559–83
  - Apache capture, 564
  - caching/proxying support, 571
  - capture, 563
  - chunked encoding, 573
  - commands, 575
  - content negotiation, 571
  - end-to-end headers, 576
  - entity headers, 579–80
  - evolution of, 570–71
  - exchange, 562
  - general headers, 577
  - generic message format, 572
  - headers, 573, 576–77
  - hop-by-hop headers, 576–77
  - HTTP 0.9, 569, 570
  - HTTP 1.0, 569–70
  - HTTP 1.1, 570, 571
  - Illustrated Network, 560–61

Hypertext Transfer Protocol (*cont'd*)

- methods, 575–76
- model, 571–72
- multiple host name support, 571
- partial resource selection, 571
- persistent connections, 571
- pipelining, 571
- request headers, 577–78
- request message, 574
- requests, 573–75
- response headers, 578–79
- response message, 574
- responses, 573–75
- security, 571
- status codes, 576

## I

## ICMP messages, 57

- alternate host address, 203
- Checksum field, 198
- Code field, 197–98
- codes, 198–203
- Destination Unreachable, 198
- Echo reply, 196
- Echo request, 193
- error, 177, 198, 199–201
- fields, 197–98
- firewalls and, 195
- format, 196–203
- format illustration, 197
- IPv4 packets carrying, 193
- must be sent, 204
- must not be sent, 204
- in path MTU discovery, 206–8
- presence of, 204
- query, 201–2
- router advertisement, 203
- sending, 203–4
- solicitation, 203
- suite, 198
- traceroute, 203
- Type field, 197
- types, 198–203
- See also* Internet Control Message Protocol (ICMP)

## ICMPv4, 208

## ICMPv6, 152, 153, 196, 208–13

- autoconfiguration, 211–12
- changes, 208–9
- Destination Unreachable message, 210
- Echo Request and Reply messages, 211
- error messages, 209

- message formats, 209

- messages, 209–11

- multicast packets, 428

- neighbor discovery, 211–12

- Neighbor Solicitation messages, 213

- Packet Too Big message, 210

- Parameter Problem message, 211

- Time Exceeded message, 210

## IEEE 802.11, 98–104

- CRC frame, 103

- duration byte, 103

- frame, 102–4

- frame control, 102, 103

- frame structure, 102

- IBSS, 98

- MAC addresses, 103–4

- MAC layer protocol, 100–101

- MAU, 87

- payload field, 103

- sequence control field, 103

- SSID, 99

- variations, 87

- Wi-Fi, 98–100

## IEEE 802.3, 84, 87

- compliant-hardware, 90

- CSMA/CD frame, 88

- IEEE 802.3ae, 88

- MAU, 87

## IEEE 1394, 85

IGPs. *See* Interior gateway protocols

## Illustrated Network, 7–14

- ARP, 144–45

- BGP, 380–81

- connections, 72–73, 74–84

- DHCP, 460–61

- DNS, 484–85

- DSL link display, 78–81

- email, 536–37

- firewalls, 698–99

- forwarding, 238–39

- frames and link layer, 83–84

- FTP, 510–11

- ICMP, 190–91

- internetworking, 48–49

- IP addressing, 110–11

- IPSec, 714–15

- IPv4/IPv6 headers, 166–67

- MPLS, 432–33

- multicast, 404–5

- NAT, 682–83

- protocol stacks, 50–51

- routers, 9, 346–47

- routing, 218–19
- routing tables, 322–23
- SNMP, 610–11
- sockets, 302–3
- SONET link display, 76–78
- SSH, 634–35
- SSL, 586–87
- TCP, 280–81
- UDP, 260–61
- VLANs, 660–61
- VoIP, 736–37
- VPLS, 673
- Web servers, 560–61
- Web sites, 586–87
- wireless link display, 81–83
- In-band management, 248
- Independent basic service set (IBSS), 98
- Indirect delivery, 229
  - packet destination address, 232–33
  - router and, 231–34
- Informational RFCs, 20
- Ingress routers, 446, 450
- Institute of Electrical and Electronics Engineers (IEEE). *See* IEEE 802.11; IEEE 802.3
- Integrated Information Services (IIS), 562
- Integrated Services Digital Network (ISDN), 85, 90
  - DSL as extension, 94
- Integrity, 593–94
- Integrity check value (ICV), 723
- Inter-Domain Routing Protocol (IDRP), 379
- Interface addresses, 212–13
- Interfaces, 27–28
  - application layer, 52
  - GRE, 241
  - for packets, 84
  - routers, 233–34
  - TCP/IP application, 11
- Interior BGP (IBGP), 382, 389–90
  - full mesh, 392
  - need for, 390
  - peers, 391
  - sessions, 389
  - uses, 389
  - See also* Border Gateway Protocol (BGP)
- Interior gateway protocols (IGPs), 342, 345
  - bootstrapping themselves, 354
  - next hops, 390
  - shortcuts, 447
  - types of, 354
- Interior Gateway Routing Protocol (IGRP), 355
  - Enhanced (EIGRP), 355, 364–65
  - RIP improvement, 365
- Intermediate device control, 638
- Intermediate System–Intermediate System (IS-IS), 345, 354
  - areas, 374
  - attraction, 373
  - backbone area, 373
  - DIS, 375
  - IPv6, 376
  - as link-state protocol, 354
  - LSP handling, 375
  - metrics, 375
  - M-ISIS, 413
  - network addresses, 375
  - network types, 375
  - OSPF and, 373–74
  - OSPF differences, 374–75
  - OSPF similarities, 374
  - route leaking, 374
  - routers, 373
- Intermediate systems, 6
  - as TCP/IP device category, 26
- Internal representation conversion, 41–42
- International Standards Organization (ISO), 17–18
- International Telecommunications Union - Telecommunications sector (ITU-T), 18
- Internet
  - administration, 21–22
  - autonomous system and, 332–34
  - backbone routers, 246
  - connectivity check, 195
  - drafts, 18, 19, 21
  - standards, 18, 20
  - today, 334–36
  - zones, 489
- Internet Architecture Board (IAB), 22
- Internet Assigned Numbers Authority (IANA), 421
- Internet Control Message Protocol (ICMP), 189–215
  - Destination Unreachable codes, 200
  - Destination Unreachable errors, 199, 201
  - Illustrated Network, 190–91
  - IP packets, 165
  - packets, 193
  - ping and, 192–96
  - round-trip time, 192

- Internet Control Message Protocol
  - (*cont'd*)
  - sequence numbers, 192
  - time-exceeded errors, 199
  - See also* ICMP messages
- Internet Corporation for Assigned Names and Numbers (ICANN), 22, 36
- Internet Engineering Task Force (IETF), 18
  - working groups, 22
- Internet exchange points (IXPs), 334
  - linking, 336
  - running of, 334
- Internet Group Management Protocol (IGMP), 416–17
  - backward compatibility, 416
  - messages, 204
  - multicast group, 408
  - versions, 416–17
- Internet key exchange (IKE), 713, 719, 728–29
  - ISAKMP, 728, 729
  - OAKLEY, 729
  - protocols, 728–29
  - SKEME, 729
- Internet Message Access Protocol (IMAP), 542
- Internet Network Information Center (InterNIC), 22
- Internet Research Task Force (IRTF), 22
- Internet Security Association and Key Management Protocol (ISAKMP), 728, 729
- Internet service providers (ISPs)
  - chained, 334
  - grid-net, 334, 338
  - peering arrangements, 334–35, 339
  - peer selection, 340–42
  - router/routing protocol use, 319
- Internet Society (ISOC), 21
- Internetworking, 47
  - Illustrated Network, 48–49
- Interoperability, 16
- Intra-site Automatic Tunnel Addressing Protocol (ISATAP) tunnels, 255
- Inverse ARP (InARP), 146, 159
- IP addressing, 36, 112–17
  - anycast, 116–17
  - assignment, 138–40
  - automatic, 112
  - broadcast/multicast, 116
  - duplicate, 213
  - dynamic assignment, 121
  - host, 121
  - Illustrated Network, 110–11
  - packet headers and, 168–70
  - private, 121
  - public, 120
  - static assignment, 121
  - unicast, 116
- IP layer, 57–58, 165
- IP mapping, 44
- IPoFW IP over Firewire, 85
- IPSec, 665, 713–31
  - in action, 716–19
  - AH, 713
  - BITS, 720
  - BITW, 720
  - endpoints, 719
  - ESP, 713
  - IKE, 713, 719
  - Illustrated Network, 714–15
  - implementation, 719–21
  - introduction to, 719–21
  - RFCs, 719
  - routers and, 721
  - SPI, 203
  - support components, 719
  - topology, 717
  - transport mode, 721
  - tunnel mode, 721
  - tunnels, 717, 718
- IP source routing, 638
- IP spoofing, 638
- IPv4
  - browsers, 251
  - dual protocol stacks, 252
  - ESP packet formats, 727
  - fragmentation and, 172–77
  - fragmentation example, 177–82
  - limitations, 179
  - multicast, 406–8
  - Options, 179
  - ping and, 193–95
  - routing tables, 221
  - transition to IPv6, 256
  - tunnels, 255
  - UDP pseudo-header, 268
- IPv4 addresses, 50, 118–23
  - ARP, 58
  - classful, 114, 118, 120
  - classless, 119, 120
  - dotted decimal notation, 119
  - formats, 122, 141
  - illustrated, 118

- Linux assignment, 113
- multicast, 420, 421–23
- overview, 109
- private, 121, 122
- protocol field, 51
- public, 120, 121
- special forms, 123
- subnetting and, 127–31
- understanding, 122–23
- IPv4-compatible IPv6 address, 256
- IPv4-mapped IPv6 address, 256
- IPv4 packet headers, 170–79
  - Ethernet interpretation of fields, 169
  - fields, 168, 169
  - Flags field, 171
  - Fragment Offset field, 171
  - Header Checksum field, 172
  - Header Length field, 171
  - Identification field, 171
  - illustrated, 170
  - Illustrated Network, 166–67
  - IPv6 header comparison, 182–84
  - multicast, converting, 421
  - Options field, 172
  - Padding field, 172
  - Protocol field, 172
  - Source and Destination Address field, 172
  - Total Packet Length field, 171
  - ToS field, 171
  - TTL field, 172
  - Version field, 171
- IPv6
  - AH packet formats, 723
  - ARP and, 159–62
  - core routers, 139
  - dual protocol stacks, 252
  - ESP packet formats, 726
  - fragmentation and, 184–86
  - Fragmentation Header fields, 186
  - FTP passive command and, 515
  - IS-IS for, 376
  - multicast, 427–28
  - multicast groups, 160
  - NAT and, 684
  - OSPFv3 for, 372
  - ping and, 195–96
  - router announcements, 406
  - routers, 212
  - routing tables, 221, 332
  - transition to, 251, 256
  - tunnel-addressing format, 254
  - tunnels, 254
  - UDP pseudo-header, 268, 269
- IPv6 addresses, 123
  - address allocation, 139
  - address discovery options, 124
  - address resolution, 152, 162
  - address type, 126
  - address types and notation, 125–26
  - assignment, 138–40
  - chained headers, 124
  - details, 135–40
  - Ethernet capture and display, 152
  - features, 123–25
  - flow caching, 124
  - formats, 136–37, 141
  - future of, 109
  - header compression and extension, 124
  - hexadecimal notation for, 119, 125
  - interface, 212–13
  - LAN interface, 114
  - link-local, 7, 127, 136
  - local use, 136
  - multicast, 213, 423–24
  - multicast, format, 424
  - neighbor discovery and address resolution, 162
  - prefixes, 126–27
  - prefix masks, 137
  - private, 127
  - provider based, 136
  - provider independent, 126, 136
  - routable, 349
  - router-assigned prefixes, 113
  - routing, 135
  - site-local, 126–27
  - size increase, 124
  - support, 114–15
  - transition to, 125
  - ULA-L, 137
  - unique local-unicast, 127
  - use of, 123
- IPv6-only address, 256
- IPv6 packet headers, 179–82
  - 64-bit units, 183
  - changes, 183–84
  - Extension Headers, 184
  - Flow Label field, 181, 183
  - Hop Limit field, 182
  - illustrated, 181
  - Illustrated Network, 166–67
  - IPv4 header comparison, 182–84
  - Next Header field, 182

IPv6 packet headers (*cont'd*)

- Payload Length field, 181, 183
- Traffic Class field, 181
- Version field, 181

ISDN DSL (IDSL), 95

ISPs. *See* Internet service providers**J**

Java Applets, 570

Java sandbox, 706

Jitter, 742, 743

Juniper Network routers, 237, 241, 246

- DHCP relay agent, 464–65
- enabling SNMP on, 612
- stateful inspection, 702

**K**

Keepalive message, BGP, 397

Keepalive packets, 78

Kerberos, 514

Key exchange, 643, 644, 652

**L**

Label Distribution Protocol (LDP), 447

Label stacking, 444, 448–49

Label switched paths (LSPs), 446

- constrained, 447
- nested, 448
- path details, 452
- signaled, 446
- static, 446, 450–53
- traceroute and, 452–53
- traffic engineering, 447
- VPNs and, 449

Label tables, 449

LACNIC (Latin American and Caribbean  
Network Information Center), 138

Latency, 742

Layer 2 forwarding (L2F), 666

Layer 2 tunneling protocol (L2TP), 666, 667

- Access Concentrator (LAC), 662
- encryption, 667
- PPTP comparison, 668

Layer 2 VPNs (L2VPNs), 659, 671–72

- architecture, 671
- creation, 659
- MPLS-based, 672–76
- service delivery, 671
- variations, 671
- See also* Virtual private networks (VPNs)

Layer 3 VPNs (L3VPNs), 442, 668–70

- complexity, 669
- connectivity, 669

customer edge, 669–70

provider edge, 670

*See also* Virtual private networks (VPNs)

Layers, 22–25

- applications and, 301–4
- ARP and, 146
- combining, 24
- encapsulation, 28–29
- IP, 57–58, 165
- protocol, 24–25
- simple networking and, 23–24
- TCP/IP, 14, 25, 26–27, 30–41
- See also specific layers*

Link Control Protocol (LCP), 92, 662

Link-local IPv6 addresses, 7, 113

Links

- backdoor, 368
- broken, 356–57
- DSL, 78–81
- external, 348
- internal, 348
- SONET, 76–78
- wireless, 81–83

Link-state advertisements (LSAs), 366,  
373

Link states, 365–66

Linux

- ARP cache display, 151
- BSD style, 152
- flags, 224
- FTP and, 514
- FTP passive using, 515
- hosts, 224
- IP forwarding, 243
- IPv4 address assignment, 113
- Kerberos, 514
- routing tables and, 330–31
- sockets on, 311–16

Listeners, 409

Load balancing, 352

Local area networks (LANs), 7

- 100BaseT Ethernet, 62
- ARP and, 146–53
- IEEE 802.11 and, 98–104
- individual address, 420
- linking, 47
- multicasting on, 420–21
- segmentation, 47, 61–62, 87
- subnetting, 130
- switches, 64–65
- virtual, 47, 58, 65–68, 671
- wireless, 82

Longest match, 250

**M**

- MAC addresses, 58, 75, 89–90
  - all-zero, 149
  - destination host, 231
  - direct delivery and, 227
  - frame IP and, 229
  - interplay, 104
  - NICs, 231
  - wireless LAN frame, 89, 103–4
- Mailboxes, 538
- Mail user agents (MUAs), 535
- Major components, 7
- Management information bases (MIBs), 609, 620–22
  - access field, 621
  - coding/implementing, 621
  - compiler, 621
  - as database description, 618
  - defval field, 621
  - description field, 621
  - Ethernet, 621, 622
  - extensible, 622
  - fields, 620–21
  - index field, 621
  - information structure, 618
  - MIB-II, 618
  - naming tree, 618
  - object-code module, 621
  - objects, 620
  - private, 622–23
  - reference field, 621
  - sample object definitions, 621
  - SONET/SDH, 622
  - status field, 621
  - syntax field, 620
  - trees, 620
  - variables, 618
- Management tasks, 10
- Managers, 616
  - console database, 617
- “Man-in-the-middle” threat, 595
- Manually configured tunnels, 255
- Maximum segment size (MSS), 286
- Maximum Transmission Units (MTUs), 112
  - default sizes, 172
  - fragmentation and, 175–76
  - frame size, 234
  - minimum size, 176
  - path, 206–8
  - path determination, 176–77
  - small size, 174, 176
  - typical sizes, 175
- Media access control (MAC), 33
  - IEEE 802.11 layer protocol, 100
  - See also* MAC addresses
- Media gateways, 752
- Megaco/H.248, 748, 749, 752–53
- Memory
  - DRAM, 245
  - nonvolatile, 243
  - packet, 245
  - RAM and ROM, 243, 245
  - routers, 243, 244
  - volatile, 243
- Message access agent (MAA), 538
- Message delimiters, 15
- Message digest, 594
- Message formats, 15
- Message transfer agent (MTA), 538, 543
- Methods, HTTP, 575–76
- Metrics
  - IS-IS, 375
  - netstat command and, 223
  - OSPF, 366
  - RIP, 355
  - RIPv1, 359
  - routing tables, 221
  - Windows output, 226
- Mobile IP, 203
- Mobility, in protocol evolution, 3–6
- MPLS. *See* Multiprotocol label switching
- MPLS-Enabled Applications* (Minei and Lucek), 659
- Multicast, 266, 403–29
  - administratively scoped addresses, 407
  - applications, 406, 407
  - concepts, 411–14
  - dense-mode, 410
  - in DHCP, 266
  - downstream interface, 409
  - frames and, 420–21
  - groups, 160, 410
  - hosts, 415
  - IGMP group, 408
  - Illustrated Network, 404–5
  - IPv4, 406–8
  - IPv6, 427–28
  - on LANs, 420–21
  - notation, 411
  - one-to-many operation, 403
  - packet capture, 407
  - PGM, 416

Multicast (*cont'd*)

- rendezvous point (RP) model, 414
- rendezvous-point tree (RPT), 414
- reverse-path forwarding, 411–12
- RIP use, 350
- RIPv2, 362
- routers, 409, 415–16
- routing loops and, 409
- RPF table, 412–13
- shortest-path tree (SPT), 413–14
- sparse-mode, 410–11
- TCP/IP, 408
- terminology, 408–10
- upstream interface, 409
- Multicast addresses, 421–24
  - IPv4, 421–23
  - IPv6, 423–24
  - for protocols, 422
  - ranges, 422, 423
  - source addresses and, 421–22
- Multicast Listener Discovery (MLD), 415, 417
- Multicast Open Shortest Path First (MOSPF), 413, 417
- Multicast protocols, 415–28
  - ASM, 418–19
  - CBT, 418
  - characteristics, 418
  - DVMRP, 417
  - group membership, 416–17
  - IGMP, 416–17
  - MLD, 415, 417
  - MOSPF, 417
  - MSDP, 419–20
  - PGM, 426
  - PIM DM, 417
  - PIM SM, 417–18
  - routing, 409, 417–18, 426–27
  - SSM, 418–19
  - suite, 407
  - support, 403
- Multicast Source Discovery Protocol (MSDP), 406, 419–20
- Multihomed, 389
- Multihop BGP, 392
- Multimedia, in protocol evolution, 3–6
- Multimedia Gateway Control Protocol (MGCP), 748, 749, 752–53
- Multiplexing, 39, 301–16
  - need for, 301
  - ports, 270
  - SSH-CONN, 645
- Multipoint configuration, 31

- Multiprotocol BGP (MBGP), 392, 413, 447–48
  - backward compatibility, 448
  - extensions, 447
- Multiprotocol label switching (MPLS), 388, 442–53
  - 32-bit label fields, 444
  - architecture, 444
  - as BGP shortcut, 443
  - domains, 446, 448
  - egress router, 446, 451–52
  - Illustrated Network, 432–33
  - ingress router, 446, 450
  - label stacking, 444, 448–99
  - label values, 445
  - LSP, 664
  - management, 445
  - rationale, 443
  - reconfiguration, 445
  - signaling and, 447–48
  - static LSPs and, 450–53
  - tables, 449–50
  - terminology, 446–47
  - traffic engineering, 442
  - transit router, 446, 450–51
  - tunnels and, 442
  - VPNs and, 449
- Multipurpose Internet Mail Extensions (MIME), 543, 547–50
  - composite types, 548
  - discrete types, 548
  - encoding, 548–49
  - entity headers and, 579
  - media types, 548
  - message, 548
  - message example, 549–50
  - security (S/MIME), 544
- Multitasking, Windows, 310

**N**

- Name servers, 491
  - application interaction, 489
  - referral queries to, 495
- Negotiation of parameters, 15
- Neighbor discovery
  - ICMPv6 functions, 211–12
  - routers and, 212
- Neighbor Discovery Protocol, 160–61
  - address resolution, 161–62
  - Neighbor Advertisement message, 161, 162
  - Neighbor Solicitation message, 160
  - Router Advertisement message, 161
  - Router Solicitation message, 161
- Neighbor routers, 353



- Nested MPLS domains, 448
  - NetBIOS, 310
  - Netstat command
    - lp option, 264
    - metrics and, 223
    - nr option, 223, 225, 329
    - r option, 222
  - Network address translation (NAT), 525, 681–95
    - in action, 691–94
    - address types, 686
    - advantages, 684–85
    - bidirectional, 687–89
    - device, 115
    - disadvantages, 658
    - FTP passive command and, 515
    - Illustrated Network, 682–83
    - IPv6, 137, 684
    - overlapping, 690–91
    - port-based, 689–90
    - private address translation, 122
    - translation, 693
    - translational mappings, 686
    - types of, 685–86
    - unidirectional, 686–87
    - using, 684–91
  - Network File System (NFS), 60, 530–31
    - XDR standard, 531
  - Networking
    - first explorations in, 14
    - layers and, 23–24
    - visions, 91
  - Network interface cards (NICs), 231
  - Network intrusion detection (NID), 289
  - Network layer, 30, 35–38
    - fragmentation, 36
    - illustrated, 35
    - MTUs and, 175–76
    - routing, 324–25
    - routing tables, 37
    - source-to-destination delivery, 37
    - switching, 324–25
    - See also* TCP/IP layers
  - Network layer reachability information (NLRI), 382
  - Network Management Protocol, 617
  - Network operations centers (NOCs), 341, 609
  - Network processor engines (NPEs), 244
  - Networks
    - addresses, 36
    - connectionless, 325–28
    - connection-oriented, 325–28
    - host boundary, 117
    - illustrated, 4–5
    - link technologies, 71–105
    - private, 71
    - public, 71
    - remote device access, 8–10
    - router access, 248–49
  - Network Service Attachment Point (NSAP)
    - addresses, 126
  - Network Virtual Terminal (NVT), 42
  - Next hop, 233
    - BGP, 390
    - determination, 249
    - identification, RIPv2, 361–62
    - IGP, 390
    - RIPng, 364
    - self, 391
  - Nodal processing delay, 742
  - Nonauthoritative servers, 487
  - Non-broadcast multiaccess (NBMA), 159
  - Nonrepudiation, 594, 603–4
  - Nonvolatile RAM (NVRAM), 243, 245
    - startup-config, 245
  - Notification message, BGP, 396, 399–400
  - Not-so-stubby areas (NSSAs), 374
  - Nslookup utility, 497, 501
  - NULL Cipher Suite, 599
- ## 0
- OAKLEY, 729
  - On-demand connections, 279
  - One-way hash, 594
  - Online Certificate Status Protocol (OCSP), 603
  - Open message, BGP, 396, 397, 398
  - Open Shortest Path First (OSPF), 237, 354, 365–72
    - area types, 369
    - backbone area, 367
    - BDR, 370–71
    - classless addressing, 367
    - DR, 370–71
    - equal-cost multipaths, 366
    - functions, 366–68
    - internal/external routes, 367
    - IS-IS and, 373–74
    - IS-IS differences, 374–75
    - IS-IS similarities, 374
    - as link-state routing protocol, 354, 365
    - metrics, 366
    - MOSPF, 413, 417
    - non-backbone, non-stub area, 369

Open Shortest Path First (*cont'd*)

- not-so-stubby area, 370
- OSPFv1, 365
- OSPFv3, 345, 372
- packets, 371–72
- reliable flooding, 366
- router hierarchies, 367
- router types, 368–70
- security, 367
- stub area, 369–70
- ToS routing, 367–68
- total stub area, 370
- OpenSSH, 637
- OpenSSL, 588, 602
  - testing certificate, 589, 604
  - See also* Secure socket layer (SSL)
- Open Standard Interconnection (OSI)
  - reference model, 25
- Outgoing interface list (OIL), 411
- Overflows, 274–75
- Overlapping NAT, 690–91
  - cases, 690
  - illustrated, 691
  - See also* Network address translation

**P**

- Packet filters, 700–701, 706
  - implementation, 706
  - See also* Firewalls
- Packet headers, 165–87
  - addresses and, 168–70
  - Extension Headers, 184
  - fields, 168, 169
  - IPv4, 170–79
  - IPv6, 179–82
- Packetization delay, 742
- Packetized voice, 744
- Packet memory, 245
- Packet over SONET/SDH (POS), 97–98
- Packets
  - ARP, 153–55
  - arriving, 178
  - CLNP, 372
  - CS, 740
  - forwarding, 237–57
  - fragmentation, 168, 178
  - ICMP, 193
  - interfaces for, 84
  - IS-IS, 372
  - keepalive, 78
  - OSPF, 371–72
  - processing, 242–43
  - on PVCs, 324
  - RAS, 740
  - reassembly, 176, 178
  - RIPv1, 358
  - RIPv2, 359–61
  - RTP, 740
  - signaling, 740, 741
  - on SVCs, 324
  - tunneling, 237
  - X.25, 436
- Passive open, 56
- Path MTU
  - discovery, 206–8
  - plateaus, 208
  - seed or probe size, 208
  - size, tuning, 207
- Path Vector Protocol, 388–89
- Payload, 24
- Peering, 334–35, 339
  - candidates, 341
  - public points, 340
- Peer-to-peer models, 55
- Peer-to-Peer Protocol process, 27
- Penultimate hop popping (PHP), 446–47
- Permanent connections, 279
- Permanent virtual circuits (PVCs), 90, 324, 446
  - packets on, 324
- Physical connections, 15
- Physical layer, 30–32
  - bit synchronization, 31
  - configuration, 31
  - contents, 30
  - data rate, 31
  - illustrated, 31
  - mode, 31–32
  - RFCs and, 84
  - specification, 30
  - topology, 31
  - See also* TCP/IP layers
- Ping, 192, 204–5
  - in checking connectivity, 195
  - ICMP and, 192–96
  - ICMP requests and replies, 194
  - implementations, 194, 205
  - IPv4 and, 193–95
  - IPv6 and, 195–96
  - PID identifier, 205
  - quirks, 205
- Pocket calculator encryption, 595–98
  - at client, 595–96
  - Diffie-Hellman, 643–44
  - at server, 597–98

- Point coordination function (PCF), 100
- Points of presence (POP), 334
- Point-to-point links, 31
- Point-to-Point Protocol (PPP), 78, 84
  - compressed data, 666
  - DSL and, 91–92
  - frames, 93
  - framing for packets, 92–93
  - Link Control Protocol (LCP), 92, 662
  - Network Control Protocol (NCP), 92
- Point-to-Point Tunneling Protocol (PPTP), 659, 666–67
  - access concatenator (PAC), 666
  - architecture, 667
  - compressed data, 666
  - L2TP comparison, 668
  - network server (PNS), 666
  - over DSL session, 663
- Policy routing, 333
- Polling, SNMP, 625, 627
- Pop, 446
- POP3, 550–52
  - capture, 550, 557
  - connection, 551
  - TCP port, 551
  - See also* Email
- Port addresses, 39
- Port address translation (PAT), 689
- Port-based NAT, 689–90
- Port mapper, 531
- Ports
  - auxiliary, 248
  - console, 248
  - dynamic, 264, 271, 272
  - dynamically mapping, 531
  - echo, 265
  - FTP, 518
  - input, 243
  - LAN switch, 64
  - multiplexing and distribution, 270
  - numbers, 52, 269–74
  - output, 243
  - persistent, 270
  - registered, 271
  - UDP, 260–61, 262–66
  - well-known, 269–73
- Pragmatic General Multicast (PGM), 416, 426
  - goals, 426
- Privacy, 593
- Private IP addresses, 121
  - IPv4, 122
  - IPv6, 127
  - translation, 122
  - See also* IP addressing
- Private keys, 591
  - clear, 602–3
  - decryption with, 593
  - primes, 596
- Private MIB, 622–23
- Private networks, 71
- Private ports, 264, 271, 272
- Process addressing, 39
- Process-to-process delivery, 38, 40
- Protocol data units (PDUs), 27, 165
- Protocol Independent Multicast dense mode (PIM DM), 417, 426
- Protocol Independent Multicast sparse mode (PIM SM), 417–18, 425
- Protocols, 14–21, 27
  - bandwidth and mobility, 3–6
  - email, 542–44
  - end-to-end, 570
  - interfaces and, 27–28
  - layers, 24–25
  - multicast, 403, 407, 415–28
  - multimedia use, 3
  - new, 6
  - security, 6
  - specifications, 15
  - standards versus, 15
  - trends, 3–6
  - tunneling, 91
  - for VoIP, 744–53
  - VPNs and, 665–66
  - See also specific protocols*
- Protocol stacks
  - DSL, 94
  - dual, 252
  - Illustrated Network, 50–51
  - RTP, 746
  - SSL, 599–601
  - TCP/IP, 624
- Provider-edge (PE) routers, 9, 670
  - PE1, 675–76
  - PE5, 673–74
- Provider (P) routers, 9, 670, 674–76
- Proxy agents, 617
- Proxy ARP, 157–58
- Proxy servers, 752
- Pseudo-header, 266, 267
  - illustrated, 268, 269
  - IPv4, 268
  - IPv6, 268, 269
  - presence, 268

Pseudo-header (*cont'd*)

TCP, 297

UDP, 268–69

Pseudorandom number generators (PRNGs), 603

Public IP addresses, 120

obtaining, 121

voice traffic types, 741–42

*See also* IP addressing

Public key encryption, 595–98

example, 596

pocket calculator, at client, 595–96

pocket calculator, at server, 597–98

security, 595

SSL use, 598

*See also* Encryption

Public key infrastructure (PKI), 585, 598

Public keys, 591

association, 595

digital signatures, 598

message encryption, 593

primes, 596

with symmetrical encryption, 598

toolkits, 601–22

Public networks, 71

Public switched telephone network (PSTN),

18, 36

traffic percentage, 738

VoIP and, 735

Push, 446

PuTTY, 654

**Q**

Quadruple play, 431

Quality of service (QoS), 170, 321, 327

bandwidth, 327

connectionless networks, 326–28

connection-oriented networks,

326–27

consistency, 328

jitter, 327–28

methodology, 326

parameter list, 327

parameters, 57, 326–28

security, 328

Queries

iterative, 491

recursive, 490–91

Query messages, 201–2

DNS, 495

list of, 201, 202

*See also* Internet Control Message Protocol (ICMP)**R**

RAM

nonvolatile, 243, 245

as working storage, 245

Random seeds, 640

Raw sockets, 306

threat, 308–9

Unix-based access, 309

Windows and, 308

*See also* Sockets

Real-Time Protocol (RTP), 59, 739

application layer framing, 745

architecture, 745

header, 746

header fields, 747

packets, 740

payload formats, 747

protocol stack, 746

reports, 747–48

as transport mechanism, 747

for VoIP transport, 745–78

Reassembly, 176, 178

Recursive queries, 490–91

Regional Internet Registries (RIRs), 138

Registered ports, 271

Relay agents, 464–65

BOOTP, 464, 471, 472

DHCP, 464–65

Reliable flooding, 366

Remote access, 8–10

for FTP, 10

securing, 10

Remote procedure calls (RPCs), 531

Rendezvous point (RP)

embedded, 415

model, 414

Rendezvous-point tree (RPT), 414

Repeater operation, 60

Requests for comments (RFCs), 18–19

CIDR, 132

Elective, 20

experimental, 20

FTP, 518

informational, 20

IPSec, 719

Limited Use, 20

maturity levels, 19

Not Recommended, 21

physical layers and, 84

Recommended, 20

Required, 20

- requirement levels, 20
  - TCP, 285–86
- Resource records (RRs), 493
  - Class field, 494
  - Comments field, 495
  - Name field, 493
  - Record-Data field, 495
  - Record-Type field, 494–95
  - TTL field, 494
  - types, 494
- Resource Reservation Protocol (RSVP), 425–26, 447
- Reverse ARP (RARP), 146, 158, 468
- Reverse-path forwarding (RPF), 411–13
  - check, 412
  - table, 412
  - table, populating, 412–13
- Ring topology, 31
- RIPE NCC (Reseaux IP European Network Coordination Center), 138
- RIPng, 345, 352, 362–64
  - configuring, 348, 350
  - for IPv6 packet fields, 363
  - multicast addresses, 350
  - next hop, 364
  - updates, 364
  - See also* Routing Information Protocol (RIP)
- RIPv1, 355, 358–59
  - limitations, 358–59
  - metrics, 359
  - packets, 358
  - subnet masks, 359
  - update timer, 358
  - wasted space, 358
  - See also* Routing Information Protocol (RIP)
- RIPv2, 355, 359–62
  - authentication, 361
  - improvements, 259
  - limitations, 362
  - multicasting, 362
  - next hop identification, 361–62
  - packet format, 359–61
  - subnet masks, 361
  - See also* Routing Information Protocol (RIP)
- RMON (remote monitor), 609, 622
- ROM, 245
- ROM monitor (ROMMON), 245
- Root level certificate authorities, 595
- Root servers, 487–89
  - details, 489
  - list, 488
  - operation, 487–88
  - operators, 488
  - See also* Domain name system (DNS)
- Round-trip times, 205
- Route distinguishers, 670
- Route leaking, 374
- Router advertisement, 212
  - DHCPv6 and, 479–80
  - in host direction to DHCP server, 213
  - message, 203
- Router architectures, 242–47
  - basic, 243–45
  - hardware-based, 243, 246–48
  - network processor engines (NPEs), 244
  - software-based, 243, 244
- Router-assigned prefixes, 113
- Router-based networks. *See* Connectionless networks
- Router-by-router VPLS configuration, 672–74
  - CEO router, 672
  - PE5 router, 673–74
- Routers, 7, 8, 33, 37, 63–64, 77, 222
  - access, 248–49
  - auxiliary port, 248
  - backbone, 246
  - border, 334, 368, 387
  - CE, 9, 47, 669–70, 672, 676, 716–19
  - console port, 248
  - CPU chips, 244
  - dead, 213
  - delay, 67
  - DHCP and, 479–80
  - DSL, 78, 79, 329
  - edge, 329, 334
  - egress, 446, 451–52
  - file transfer to, 10–11
  - function, 220
  - Illustrated Network, 9, 346–47
  - illustrated use, 69
  - in-band management, 248
  - indirect delivery and, 231–34
  - ingress, 446, 450
  - interfaces, 233–34
  - Internet core, 127
  - IPSec and, 721
  - IPv6, 212
  - IS-IS, 373
  - ISP use, 319
  - Juniper Networks, 237, 241, 246
  - loopback interface, 221
  - memory, 243, 244
  - MSDP, 420

Routers (*cont'd*)

- multicast, 409, 415–16
  - neighbor, 353
  - neighbor discovery and, 212
  - network access, 249–50
  - as network nodes, 324, 333
  - NICs, 231
  - NVRAM, 243
  - operation, 60
  - packet filter, 700–701
  - packet-handling, 240
  - provider, 9, 670, 674–76
  - provider edge, 9, 673–74, 697
  - Proxy ARP and, 158
  - self-booting, 243
  - stateful inspection, 701–5
  - steps, 242
  - in TCP/IP networks, 14
  - transit (intermediate), 446, 450–51
- Router-to-host tunnels, 253, 254
- Router-to-router tunnels, 253, 254
- Routing, 37, 217–34
- direct delivery, 226–29, 230–31
  - distance vector, 355–56
  - domains, 336, 353
  - engines, 247
  - Illustrated Network, 218–19
  - indirect delivery, 229, 231–34
  - information exchange, 337
  - with IP addresses, 229
  - loops, 409
  - network layer, 324–25
  - policy, 333
  - switching comparison, 443
  - ToS, 367–68
  - at wire speeds, 243
- Routing Information Protocol (RIP), 345, 354
- backbone routers running, 351
  - as Bellman-Ford routing protocol, 355
  - broken links, 356–57
  - configuring, 350
  - as distance-vector protocol, 354, 355–56
  - enabling, 349
  - flooding updates, 356
  - information flow, 350
  - links, 348
  - metric, 355
  - multicast addresses, 350
  - RIPng, 362–64
  - RIPv1, 355, 358–59
  - RIPv2, 355, 359–62
  - split horizon, 357
  - triggered updates, 357–58
- Routing policies, 321, 333
- BGP, 384–86, 395–96
  - example illustration, 337
  - framework, 337
  - function of, 333
  - IGPs and, 342
  - roles of, 336–38
- Routing protocols, 321, 333
- ASs and, 333
  - ISP use, 319
  - multicast, 409, 417–18, 426–27
  - See also specific protocols*
- Routing tables, 217
- asterisk (\*), 221, 240
  - on CE routers, 670
  - Cisco-like display, 240
  - default route, 221
  - defined, 37, 220, 330
  - for each IP network, 127
  - entries, 329
  - FreeBSD and, 329–30
  - host, 222–26, 328–32
  - Illustrated Network, 322–23
  - information display, 331
  - IPv4, 221
  - IPv6, 221, 241, 332
  - Linux and, 330–31
  - metric entries, 221
  - route preference, 221
  - Windows XP and, 331–32
- RSA Data Security Code (RC4), 601
- RSAREf, 601
- RTP. *See* Real-Time Protocol
- Running-config, 245

## S

- Safe passage, 585
- Scaling, BGP, 395–96
- Secret keys, 593
- Secure shell (SSH), 249, 633–57

  - in action, 649–55
  - agents, 640
  - architecture, 639–40
  - authentication, 636, 637–38
  - basics, 636–37
  - clients, 636, 639
  - as client-server protocol, 636
  - configuration files, 640
  - Ethereal capture, 655
  - features, 637–38
  - FTP and, 647
  - host key, 640
  - Illustrated Network, 634–35

- key generator, 639
- keys, 640–41
- known hosts, 639
- model illustration, 637
- OpenSSH, 637
- protocol operation, 641–42
- protocol relationships, 641
- proxy gateway, 638
- random seeds, 640
- as remote access application, 633
- secure client–server communication, 637
- security add-on, 638
- servers, 639
- session key, 640–41
- sessions, 639
- signer, 640
- as slogin implementation, 636
- SSH1 and SSH2, 636–37
- SSH-AUTH, 641, 642, 644–45
- SSH-CONN, 641, 642, 645–46
- SSH-SFTP, 641, 642, 647–49
- SSH-TRANS, 641, 642, 642–44
- transparency, 638
- user key, 640
- using, 633–49
- versatility, 638
- Secure socket layer (SSL), 585–605, 665
  - Alert Protocol, 599
  - Change Cipher Spec Protocol, 599
  - clear private keys, 602–3
  - computational complexity, 602
  - data transfer, 601
  - Diffie-Hellman, 599
  - Handshake Protocol, 599
  - Illustrated Network and, 586–87
  - implementations, 592, 601–2
  - issues and problems, 602–4
  - MAC, 601
  - nonrepudiation, 603–4
  - OpenSSL, 588
  - page, loading, 591
  - as protocol, 598–604
  - protocol stack, 599
  - pseudorandom numbers, 603
  - public key encryption, 598
  - Record Protocol, 599, 602
  - session establishment, 599–601
  - stolen credentials, 603
  - TCP limitation, 603
  - TCP port, 600
  - TLS relationship, 592
  - as toolkit library, 601
  - Web sites and, 585–92
- Security
  - areas, 599
  - certificate warning, 588
  - PKI, 598
  - protocol, 6
  - public key encryption, 595
  - remote access, 10
  - VLANs for, 66
  - VPNs and, 664–65
  - Web site, 585
- Security association database (SAD), 722
- Security associations (SAs), 713, 722–29
- Security parameter index (SPI), 713, 722
  - AH, 724
  - security policy, 722
- Security policy database (SPD), 722
- Segmentation, 61–62
- Segments, 55, 286
  - handling, 39
  - lost, 290
  - request–response pair, 288
- Selectors, 722
- Self-signed certificates, 595
- Sender keeps all (SKA), 338, 339
- Sending ICMP messages, 203–4
- Serial delay, 743
- Serial Line Interface Protocol (SLIP), 85
- Servers, 7, 8
  - authentication, 100, 585
  - authoritative, 487
  - BOOTP, 459, 469
  - DHCP, 462–64, 480
  - DHCPv6, 480
  - DMZ, 709
  - DNS, 463, 486–87, 489
  - FreeBSD, 498
  - FTP, 304, 519
  - GLTD, 502
  - identity, 585
  - name, 489, 491
  - nonauthoritative, 487
  - pocket calculator decryption at, 597–98
  - proxy, 752
  - root, 487–89
  - SMTP, 542
  - socket, 315, 316
  - SSH, 639
  - TFTP, 469
  - VoIP, 739
  - Web, 559, 562
  - See also* Clients; Client–server model
- Service data unit (SDU), 27

- Services, 27
- Session Announcement Protocol and Source Description Protocol (SAP/SDP)
  - messages, 407
- Session Initiation Protocol (SIP), 750–52
  - registrar, 751
  - request types, 752
  - responses, 752
  - sequence of requests/responses, 751
  - session initiation steps, 751
  - signaling stack, 749
- Session support, 41
- Settlements, 338
- Shared secret key, 593
- Shortest-path tree (SPT), 413–14
  - building, 413
  - size, 414
- Short-inter-frame spacing (SIFS), 101
- Signaled LSPs, 446
- Signaling, 745, 748–49
  - H.323 stack, 749
  - MGCP stack, 749
  - MPLS and, 447–48
  - packets, 740, 741
  - protocols, 279
  - SIP stack, 749
- Signers, 640
- Simple Key Management for Internet Protocols (SKIP), 203
- Simple Mail Transfer Protocol (SMTP), 59–60, 538, 542, 545–47
  - authentication, 544–45, 546
  - basic mail exchange, 546
  - commands, 547
  - mail servers, 542
  - message delivery with, 540
  - as MTA, 543
  - packet sequence, 540
  - reply codes, 545, 547
  - Service Extensions (ESMTP), 544
- Simple Message Transfer Protocol (SMTP), 42
- Simple Network Management Protocol (SNMP), 60, 249, 609–29
  - agent/manager model, 616
  - agent software, 616, 617
  - capabilities, 612–16
  - community, 615
  - community strings, 627
  - as connectionless, 626
  - enabling, 612
  - Illustrated Network, 610–11
  - manager software, 623
  - messages, 624, 625
  - messages and details, 613
  - MIB, 618–22
  - model, 616–23
  - model illustration, 617
  - as network management tool, 616
  - operation, 623–27
  - PDU structure, 626
  - polling, 625, 627
  - private MIB, 622–23
  - read-only access, 614
  - requests, 625
  - RMON, 622
  - router management, 624
  - in security framework, 628
  - sessions, 613
  - SMI, 618–20
  - SNMPv1, 612, 627, 628
  - SNMPv1 PDU, 626
  - SNMPv1 protocol operation, 625
  - SNMPv2, 612
  - SNMPv2 enhancements, 627–28
  - SNMPv3, 628
  - in TCP/IP protocol stack, 624
  - traps, 626
- Simplex mode, 31
- Site certificates, 589
- SKEME, 729
- Sliding window, TCP, 293–94
- Socket interface, 304–7
  - isolation, 307
  - reasons for, 304
  - simplicity, 307
  - Windows, 309–11
- Sockets, 52, 273, 301–16
  - client–server TCP stream, 316
  - colon (:), 273
  - concept applied to FTP, 305
  - datagram, 306
  - dot (.), 273
  - Illustrated Network, 302–3
  - libraries, 305–6
  - on Linux, 311–16
  - listening, displaying, 264
  - power of, 316
  - as programmer's identifier, 305
  - raw, 306, 308–9
  - server, 315, 316
  - stream, 306
  - types, 306
  - UDP, 260–61, 262–66
  - uses, 305–6
  - for Windows, 310–11
- Software-based forwarding, 243



- Software firewalls, 700, 705
- Solicitation message, 203
- Source Specific Multicast (SSM), 418–19
- Spanning tree bridges, 63
- Sparse-mode multicast, 410–11
- Split horizon, 357
- SSH. *See* Secure shell
- SSH-AUTH, 641, 642, 644–45
  - request, 644–45
  - use of, 653
- SSH-CONN, 641, 642, 645–46
  - channel requests, 646
  - channel types, 645–46
  - multiplexing, 645
  - See also* Secure shell (SSH)
- SSH-SFTP, 641, 642, 647–49
  - file transfer with, 648
  - syntax and options, 647–49
- SSH-TRANS, 641, 642, 642–44
  - binary packet protocol, 643
  - key exchange, 643, 644, 652
  - negotiation, 651
  - See also* Secure shell (SSH)
- SSL. *See* Secure socket layer
- SSLava, 601
- SSLRef, 601
- Standards, 16–18
  - data communication, 16
  - de facto, 16–17
  - de jure, 16
  - draft, 19
  - Internet, 18, 20
  - interoperability and, 16
  - proposed, 19
  - protocols versus, 15
  - TCP/IP protocol suite, 17
  - See also specific standards*
- Star topology, 31
- Stateful inspection, 701–5, 706–8
  - anomaly categories, 702–3
  - deep, 707
  - as dynamic/reflexive firewall, 706
  - flows, 702
  - from and then structure, 703
  - interface application, 703
  - Juniper Networks router, 702
  - See also* Firewalls
- State variables, 41
- Static IP address assignment, 121
- Static LSPs, 446
  - link failure and, 452
  - MPLS configuration with, 450–53
  - See also* Label switched paths (LSPs)
- Stream sockets, 306
- Structure of Management Information (SMI)
  - tree, 618–20
  - illustrated, 619
  - Network Management Protocol use, 619
  - objects, 624
  - root, 618
- Subconfederations, 337
- Subnet masks, 128
  - default, 129
  - forms, 128–29
  - RIPv1, 359
  - RIPv2, 361
  - use of, 129–30
- Subnetting, 117, 127–31
  - address masks, 128
  - basics, 128–31
  - LANs, 130
- Supernetting, 117
- Swap, 446
- Switched Multimegabit Data Services (SMDS), 85
- Switched networks. *See* Connection-oriented networks
- Switched virtual circuits (SVCs), 324, 446
  - packets on, 324
- Switches, 37, 324
  - ATM, 442
  - LAN, 9, 33, 64–65
  - See also* Routers
- Symmetrical encryption, 598
- Symmetric DSL (SDSL), 95
- Synchronization source identifier (SSRC), 746
- Synchronous Digital Hierarchy (SDH)
  - as PPP technology, 86
  - SONET frame structure differences, 77
  - See also* Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH)
- Synchronous optical network (SONET)
  - evolution of, 96–98
  - frames, 32
  - links, displaying, 76–78
  - point-to-point, 7
  - SDH frame structure differences, 77
  - standard, 77
  - transmission-frame payload area, 98
- Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH), 71, 84, 244
  - frames, 97
  - high-speed WAN links, 96

Synchronous Optical Network/Synchronous  
Digital Hierarchy (*cont'd*)

links, 72–73

MIB, 622

Packet over (POS), 97–98

Systems, 6

AS, 332–34

end, 6, 26

intermediate, 6, 26

## T

TCP headers, 282–85, 286, 745

ACK field, 283, 289, 291

Acknowledgment Number field, 282–83

Checksum field, 284

Destination Port field, 282

ECN flags, 283

field illustration, 283

FIN field, 283, 289

Header Length field, 283

Options field, 284

PSH field, 283

Reserved field, 283

RST field, 283

Sequence Number field, 282

Source Port field, 282

SYN field, 283, 287, 288, 289

Urgent Pointer field, 284

URG field, 283

Window Size field, 283

*See also* Transmission Control Protocol

TCP/IP

convergence on, 441–42

encapsulation flow, 29

implementations, 86

model, 25

multicast, 408

networks, 14

number of packets exchanged, 14

protocol stack, 624

voice signaling packets, 745

Windows and, 310

TCP/IP applications, 42–43

in applications layer, 41

illustrated, 43

interfaces, 11

TCP/IP layers, 14, 26–27, 30–41

application, 30, 41

contents, 25

data link, 30, 32–35, 84–86

illustrated, 26, 44

interface, 27

network, 30, 35–38

overview, 30

physical, 30–32

transport, 30, 38–40

TCP/IP protocol suite, 3, 25–29, 43–44

detail, 56

device categories, 26

flexibility, 27

illustrated, 44

open, 25

peer protocol, 54

standards, 17

*TCP/IP Sockets in C*, 311, 406

Telnet, 59

Termination of communications, 15

Tethered MAC addresses, 229

Third-party cookies, 581

Three-way handshake, 286

capture, 296

FTP, 297

functions, 288

*See also* Transmission Control Protocol  
(TCP)

Token ring, 84, 87

Topology

bus/broadcast, 31

IPSec, 717

ring, 31

star, 31

VPLS configuration, 679

Traceroute, 205–6

implementations, 206

LSPs and, 452–53

message, 203

on Unix-based systems, 206

Transit fees, 338

Transit (intermediate) routers, 446

Transmission Control Protocol (TCP), 55,  
259, 279–99

as byte-sequencing protocol, 292

client–server connections, 280–81

client–server interaction, 287

complexity, 294

congestion control, 294

as connection-oriented layer, 56

connections, 279, 282, 286–92

control bits, 284

data transfer, 289–91

data units, 55

echo using, 298

flow control, 292–94

FTP and, 296–98

functions and mechanisms, 59

Illustrated Network, 280–81

- ISN, 288, 289
  - lost segment handling, 290
  - mechanisms, 285–86
  - NID, 289
  - on-demand connections, 279
  - option types, 284–85
  - overhead, 570
  - performance algorithms, 294–96
  - permanent connections, 279
  - pseudo-header, 297
  - registered ports, 272
  - reliability, 55–56, 58
  - RFCs, 285–86
  - RTT, 289
  - segments, 286
  - sessions, 297–98
  - sliding window, 293, 294
  - stream service calls, 306–7
  - three-way handshake, 286, 288
  - transactions and, 286
  - as virtual circuit service, 285
  - well-known ports, 271
  - windows, 293–94
  - See also* TCP header
  - Transmission framing, 30
  - Transparent bridging, 63
  - Transport layer, 30, 38–40, 58–59
    - connectionless, 40
    - connection-oriented, 40
    - error control, 40
    - flow control, 40
    - functions, 39–40
    - illustrated, 39
    - process addressing, 39
    - process-to-process delivery, 38, 40
    - protocol packages, 38
    - segmentation, 38
    - segment handling, 39
    - TCP, 55, 58–59
    - UDP, 55, 59
    - See also* TCP/IP layers
  - Transport Layer Interface (TLI), 309
  - Transport Layer Security (TLS), 592
    - SSL relationship, 592
    - TLS 1.0, 592
    - TLS 1.1, 604
  - Traps, 626
  - Triggered updates, 357–58
  - Triple DES (3DES), 601
  - Triple play, 431
  - Trivial File Transfer Protocol (TFTP), 468, 472–74
    - download, 473
    - file transfer, 474
    - FTP comparison, 472–73
    - header, 473, 474
    - messages, 473, 474
    - operation codes, 473
    - servers, 469
    - transactions, 473
  - Tunneling, 237, 252–54
    - 6to4 tunnels, 255
    - automatic, 253
    - configured, 253
    - GRE tunnels, 255
    - host-to-host, 253, 254
    - host-to-router, 253, 254
    - IPv4-compatible tunnels, 255
    - IPv6 addressing formats, 254
    - ISATAP tunnels, 255
    - manually configured tunnels, 255
    - mechanisms, 255
    - in mixed IPv4/IPv6 network, 253
    - occurrence, 252
    - protocols, 91
    - router-to-host, 253, 254
    - router-to-router, 253, 254
    - types illustration, 254
  - Twice NAT. *See* Overlapping NAT
  - Type of Service (ToS) routing, 367–68
- ## U
- Unicast addresses, 116
  - Unidirectional NAT, 686–87
  - Uniform resource identifiers (URIs), 565
  - Uniform resource locators (URLs), 565
    - accesses, 568
    - fields, 566, 567
    - locator part, 566
    - rules, 568
  - Uniform resource names (URNs), 565, 568–69
    - namespace, 569
    - notation, 569
    - resource identification by, 569
  - Unique local-unicast addresses, 127
  - Universally reachable address level, 389
  - Unix
    - raw sockets access, 309
    - TLI, 309
    - traceroute and, 206
  - Update Message, BGP, 396, 397–98
  - Upstream interface, 409
  - User authentication, 585

User Datagram Protocol (UDP), 51, 55, 59, 259–76

- actions, 274
- applications, 59
- checksum, 264, 266
- congestion control, 275
- as connectionless transport layer, 56
- data unit, 55, 259
- flow control, 274–75
- Illustrated Network, 260–61
- operation, 259, 274
- overflows, 274–75
- popularity, 259
- port numbers, 269–74
- ports, 260–61, 262–66
- pseudo-header, 266, 268, 269
- registered ports, 272
- for short transactions, 59
- sockets, 260–61, 262–66, 273
- as stateless, 265, 266
- traffic, 266
- use of, 262
- well-known ports, 271

*See also* Datagrams

User Datagram Protocol header, 267–68

- Checksum field, 267, 268
- Destination Port field, 267
- illustrated, 267
- Length field, 267
- Source Port field, 267

User tracking abuse, 581

## V

Variable bindings, 626

Variable-length subnet masking (VLSM), 117, 131–32

- use of, 135

Very-high-speed DSL (VDSL), 85, 95

Virtual circuits, 158–59, 324

- support over public network, 664

Virtual LANs (VLANs), 47, 58, 65–66, 671

- frame tagging, 66–68
- identifier, 66
- Illustrated Network, 660–61
- in LAN switch, 65, 67
- reasons for, 66–67
- space, increasing, 66
- tagging, 66–68, 671

*See also* Layer 2 VPNs (L2VPNs)

Virtual path identifiers (VPIs), 159

Virtual private LAN service (VPLS), 659, 671, 672–76

- configuration topology, 679
- Illustrated Network, 673
- router-by-router configuration, 672–74
- virtual port, 671, 672

Virtual private networks (VPNs), 442, 659–79

- Layer 2, 659, 671–72
- Layer 3, 442, 449, 668–70
- LSPs and, 449
- MPLS-based, 449, 668–72
- protocols and, 665–66
- security and, 664–65
- types of, 662–64

Virtual routing and forwarding (VRF) tables, 669

Voice over IP (VoIP), 735–55

- in action, 738–44
- address, 739
- attraction of, 741
- Avaya software, 738
- clients, 738
- converged network architecture, 753
- delays, 742–44
- Illustrated Network, 736–37
- jitter, 742, 743
- packetized voice, 744
- protocols for, 744–53
- as PSTN bypass method, 742
- PSTN traffic percentage, 738
- RTP for, 745–48
- servers, 739
- sessions, 739
- signaling architectures, 748–49
- signaling protocols, 740

## W

Web browsers

- built-in security, 591
- FTP and, 516, 517, 518
- screening/rejecting cookies, 581
- secure lock, 585, 590, 591

Web pages

- defined in HTML, 573
- dynamic, 573
- secure, 590

Web servers

- Apache software, 562
- Illustrated Network, 560–61
- stateless, 580

- Web sites
    - Illustrated Network, 586–87
    - security, 585
    - SSL and, 585–92
    - user authentication, 585
  - Well-known ports, 269–73
    - statistically mapping, 304
    - TCP, 271
    - UDP, 271
    - use of, 269
    - See also* Ports
  - Wide area networks (WANs)
    - ARPs and, 158–59
    - links, 7
    - routing and switching comparison, 443
  - Wi-Fi, 98–100
    - captive portal, 100
    - jungle, 99
  - Windowing, 58
  - Windows, Microsoft
    - ARP cache display, 152
    - ARP reply capture, 150
    - configuration for DHCP use, 464
    - cookies in, 580
    - DHCP servers for, 462
    - direct delivery and, 226
    - FTP utility, 296
    - hosts, 224
    - metrics, 226
    - multitasking capabilities, 310
    - raw sockets and, 308
    - routing tables and, 331–32
    - socket interface, 309–11
    - sockets for, 310–11
    - TCP/IP and, 310
  - Windows, TCP, 293–94
  - Windows for Workgroups (WFW), 310
  - WinSock, 309
    - DLL, 310
    - interface, 310
  - Wireless LANs
    - architectures, 99
    - encapsulation, 82
    - frame addressing, 82
    - hidden terminal problem, 100, 101
    - Wi-Fi, 98–100
    - See also* Local area networks (LANs)
  - Wireless links
    - data frames and packets on, 82
    - displaying, 81–83
  - Wire speeds, 243
- X**
- X.25, 84, 435–37
    - network nodes, 437
    - packet routing, 436
    - packets, 436
    - See also* Frame relay
  - X Windows attacks, 638