



Meterpreter

¿Qué veremos?

- Meterpreter:
 - ¿Qué es?
 - Como funciona
 - Comandos principales

<https://medium.com/@msbj/decoding-meterpreter-commands-dca5bd25873f>




Meterpreter

Stage0


Attacking Machine (MSF)



Target Machine (SMB)




Attacking Machine (MSF)




Target Machine (SMB)




Meterpreter




Stage1



Meterpreter




A



B

Stage1



C

Meterpreter

Comandos

Core Commands =====	
Command -----	Description -----
?	Help menu
background	Backgrounds the current session
bg	Alias for background
bgkill	Kills a background meterpreter script
bglist	Lists running background scripts
bgrun	Executes a meterpreter script as a background thread
channel	Displays information or control active channels
close	Closes a channel
disable_unicode_encoding	Disables encoding of unicode strings
enable_unicode_encoding	Enables encoding of unicode strings
exit	Terminate the meterpreter session
get_timeouts	Get the current session timeout values
guid	Get the session GUID
help	Help menu
info	Displays information about a Post module
irb	Open an interactive Ruby shell on the current session
load	Load one or more meterpreter extensions
machine_id	Get the MSF ID of the machine attached to the session
migrate	Migrate the server to another process
pivot	Manage pivot listeners
pry	Open the Pry debugger on the current session
quit	Terminate the meterpreter session
read	Reads data from a channel
resource	Run the commands stored in a file
run	Executes a meterpreter script or Post module
secure	(Re)Negotiate TLV packet encryption on the session
sessions	Quickly switch to another session
set_timeouts	Set the current session timeout values
sleep	Force Meterpreter to go quiet, then re-establish session.
transport	Change the current transport mechanism
use	Deprecated alias for "load"
uuid	Get the UUID for the current session
write	Writes data to a channel

