

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 45463

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

### AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
1	Boiler No. 1	NO <sub>x</sub>	0.41	1.80
		CO	0.35	1.51
		SO <sub>2</sub>	0.01	0.01
		PM	0.03	0.14
		VOC	0.02	0.10
2	Boiler No. 2	NO <sub>x</sub>	0.62	2.71
		CO	0.52	2.27
		SO <sub>2</sub>	0.01	0.02
		PM	0.05	0.21
		VOC	0.03	0.15
3	Hot Oil Heater	NO <sub>x</sub>	1.26	5.53
		CO	1.06	4.65
		SO <sub>2</sub>	0.01	0.03
		PM	0.10	0.42
		VOC	0.07	0.30
5	Burn-Zol Thermal Oxidizer	NO <sub>x</sub>	0.98	4.29
		CO	0.82	3.61
		SO <sub>2</sub>	0.01	0.03
		PM	0.08	0.33
		VOC	0.05	0.24
6	Soap Line Dust Collector	PM	0.06	0.01
7	White Line Dust Collector	PM	0.04	0.01
8	Asphalt Line Dust Collector	PM	1.28	0.01
9	Black Line Dust Collector	PM	0.16	0.02

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	<u>Emission Rates *</u>	
			lb/hr	TPY
10	VG-69 Product Dust Collector	PM	0.13	0.36
11	Hot Oil Fill Tank	VOC	0.10	0.01
12	Diesel Storage Tank	VOC	0.02	0.01
14	Dimer Acid Storage Tank	VOC	0.01	0.01
15	Oleic Acid Storage Tank	VOC	0.01	0.01
18	DETA Storage Tank	VOC	0.01	0.01
19	Alkanolamide Storage Tank	VOC	0.01	0.01
22	Crude Texanol Storage Tank	VOC	0.37	0.01
23	Lube 167 Storage Tank	VOC	7.47	0.12
24	Phenol Storage Tank	VOC	0.12	0.01
26	Dipropylene Glycol Bottoms Storage Tank	VOC	0.05	0.01
27	Imidazoline Storage Tank	VOC (5)	28.47	0.86
28	Imidazoline Storage Tank	VOC (5)	28.47	0.86
30	Diesel Storage Tank	VOC	0.09	0.01
31	Glycol Ether Bottoms Storage Tank	VOC	0.01	0.01
33	Adogen Storage Tank	VOC	11.01	2.49
34	Wet Scrubber	VOC	0.08	0.01

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
35	Wastewater Treatment Plant	VOC	0.37	1.47
36	Process Fugitives (4)	VOC	0.34	1.51
37	Drum Loading Operation	VOC	1.26	0.27
38	Hot House Furnace No. 1	NO <sub>x</sub>	0.02	0.08
		CO	0.01	0.03
		SO <sub>2</sub>	0.01	0.01
		PM	0.01	0.01
		VOC	0.01	0.01
39	Hot House Furnace No. 2	NO <sub>x</sub>	0.02	0.08
		CO	0.01	0.03
		SO <sub>2</sub>	0.01	0.01
		PM	0.01	0.01
		VOC	0.01	0.01

**SOURCES COVERED UNDER PERMITS BY RULE**

The following sources are covered under permits by rule and are not authorized under this permit. They are listed here for reference only.

44	Wet Scrubber	VOC	3.33	5.21
----	--------------	-----	------	------

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NO<sub>x</sub> - total oxides of nitrogen

PM - particulate matter, suspended in the atmosphere, including PM<sub>10</sub>.

PM<sub>10</sub> - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.

SO<sub>2</sub> - sulfur dioxide

CO - carbon monoxide

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

(4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

(5) These tanks shall not be filled simultaneously.

\* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

\_\_\_\_\_Hrs/day \_\_\_\_\_Days/week \_\_\_\_\_Weeks/year or 8,760 Hrs/year

Dated November 10, 2005