## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

## Permit No. 38214

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

## AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emission</u>	Rates
<u>*</u>				
Point No. (1)	Name (2)	Name (3)	<u>lb/hr</u>	<u>TPY</u>
1	Drum/Dryer Baghouse	VOC (a)	16.5	11.36
	Stack	VOC (b)	262.5	17.85
		V0C (c)	67.8	1.13
		$NO_x$	10.8	7.62
		CO	11.4	8.04
		SO <sub>2</sub>	0.59	0.40
		$PM_{10}$	9.59	6.77
2	Material Handling (4	4) PM	3.28	2.35
	, , , , , , , , , , , , , , , , , , ,	PM <sub>10</sub>	0.68	0.50
3	Stockpiles (4)	РМ	*	1.34
-	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	PM <sub>10</sub>	*	0.65
		V0C (c)	2.1	8.93

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) VOC volatile organic compounds as defined in TNRCC General Rule 101.1
  - VOC(a) from standard mix asphalt concrete
  - VOC(b) from cold mix asphalt concrete
- VOC(c) total VOCs from recycled rubber modified asphalt concrete mixes
  - $NO_x$  nitrogen oxide
  - CO carbon monoxide
  - SO<sub>2</sub> sulfur dioxide
  - PM particulate matter, suspended in the atmosphere, including  $PM_{10}$ .
  - $PM_{10}$  particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall

be assumed that no particulate matter greater than 10 microns is emitted.

## EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (4) Fugitive emissions are an estimate only.
- \* Emission rates are based on and the facility is limited to the following asphalt concrete production rates and operating schedule:

	tons/hour	tons/year		
Standard hot mix asphalt conc Cold mix asphalt concrete wit Cold mix asphalt concrete wit Recycled rubber modified mixe	ch emulsion ch medium cure	300 150 75 10,000	400,000 6,000 7,200	
<u> </u>	_days/week	<u>52</u> week	s/year	2,600

Dated\_\_\_\_