Emission Sources - Maximum Allowable Emission Rates

Permit Number 20057

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
APPLICABLE TO BOTH DMTA OPERATION AND HMP OPERATION				
K-1798	Flare Stack	PM	0.01	0.01
		VOC	0.01	0.01
		NO_X	0.02	0.07
		SO_2	0.01	0.01
		CO	0.02	0.07
WB-1769	J-1765 WW Tank Scrubber	VOC	0.10	0.03
		Formaldehyde	0.01	0.01
		MEK	0.01	0.01
		MeOH	0.01	0.01
K-502C	WB-502C Storage Tank	VOC	0.01	0.01
PK-1901	Cooling Tower (5)	VOC	0.40	1.76
K-1970	DMTA Generator	VOC	1.59	0.02
		PM	1.39	0.02
		CO	4.24	0.06
		SO_2	1.30	0.02
		NO_X	19.65	0.26
S582F-1	Tank Farm Fugitives (5)	VOC	0.07	0.29
		Formaldehyde	0.01	0.03
		MeOH	0.01	0.03
		HCl	0.01	0.05
S582F-2	Process Unit Fugitives (5)	VOC	0.91	3.98
		Formaldehyde	0.02	0.07
		MeOH	0.09	0.39

Emission Sources - Maximum Allowable Emission Rates

		HCl	0.09	0.37
		Cl_2	0.06	0.28
		H_2O_2	< 0.01	0.01
		H_2S	0.05	0.22
S582F-3	Wastewater Fugitives (5)	VOC	< 0.01	0.01
		Formaldehyde	< 0.01	< 0.01
		MeOH	< 0.01	0.01
DMTA OPERATION ONLY				
K-1790	Vent Stack	PM	0.01	0.01
		VOC	0.40	1.74
		NO_X	2.06	9.05
		SO_2	0.52	2.29
		CO	0.05	0.23
		Cl_2	0.01	0.09
		HCl	0.10	0.44
		H_2S	0.01	0.02
D-1868	HCl/Cl_2 Scrubber	HCl	0.01	0.01
HMP OPERATION ONLY				
K-1790	Vent Stack	VOC	0.49	0.93
		NO_X	0.72	1.19
		SO_2	0.011	0.013
		CO	3.92	5.26
		PM	0.02	0.017
		Formaldehyde	0.02	0.03
		MEK	0.01	0.01
		MeOH	0.04	0.10
D-1868	HCl/Cl_2 Scrubber	VOC	0.01	0.01
PLANNED MAINTENANCE, STARTUP, AND SHUTDOWN (MSS) EMISSION RATE LIMITS				
MSS-DMTA	Maintenance, Start-Up and Shut-Down	VOC	38.88	2.43

Emission Sources - Maximum Allowable Emission Rates

MSS-DMTA	Small and Large Equipment Purging (DMTA)	Cl_2		
	Filter Clearing (DMTA)	Cl_2		
	Maintenance, Start-Up and Shut-Down	Cl_2	4.50	0.10
MSS-DMTA	Small and Large Equipment Purging (HMP)	HCl		
	Filter Clearing (HMP)	HCl		
	Maintenance, Start-Up and Shut-Down	HCl	1.87	0.04
MSS-DMTA	Small and Large Equipment Purging (DMTA)	H_2S		
	Maintenance, Start-Up and Shut-Down	H_2S	0.01	0.01
MSS-DMTA	Surface Coating (Aerosol)	PM		
	Maintenance, Start-Up and Shut-Down	PM	0.06	0.01

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO_x - total oxides of nitrogen
SO_2 - sulfur dioxide
PM - total particulate matter, suspended in the atmosphere, including PM_{10} and $PM_{2.5}$, as represented
CO - carbon monoxide
Cl_2 - chlorine
HCl - hydrochloric acid mist
H_2S - hydrogen sulfide
MeOH - methyl alcohol
(4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
(5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: March 16, 2018