Permit Number 7286 and PSDTX892M2

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)) Source Name (2)	Air Contaminant Name (3)	Emission Rates (6)	
Limission Form No. (1)		An Contaminant Name (5)	lbs/hour	TPY (4)
Operating Scenario 1				
BOILER-1	Wood-Fired Boiler	VOC#	3.26	14.30
	Venturi Scrubber Stack	NO _x	18.00	78.84
		SO ₂	2.40	10.51
		PM	9.47	41.47
		PM ₁₀	9.47	41.47
		PM _{2.5}	9.35	40.97
		СО	100.78	441.40
		HAP*	0.41	1.80
PLANER-1	Planer Mill Cyclone Filter 1 Stack	PM	9.00	39.42
		PM ₁₀	6.27	27.46
		PM _{2.5}	2.49	10.90
CKILN-1	Continuous Wood	VOC##	57.29	
	Drying Kiln No. 1 Vents (7)	РМ	1.00	
		PM ₁₀	1.00	
		PM _{2.5}	0.99	
		HCHO**	0.17	
		MeOH**	3.93	
		HAP*	4.30	
CKILN-2	Continuous Wood Drying Kiln No. 2	VOC##	57.29	
	Vents (7)	РМ	1.00	
		PM ₁₀	1.00	
		PM _{2.5}	0.99	
		HCHO**	0.17	

		MeOH**	3.93	
		HAP*	4.30	
CKILN-1 and CKILN-2	Total Annual Emissions from both Kilns (7)	VOC##	-	481.25
		PM	-	7.64
		PM ₁₀	-	7.64
		PM _{2.5}	-	7.59
		HCHO**		1.38
		MeOH**	-	33.00
		HAP*	-	36.08
DEBARK-1	Log Debarker No. 1 (8) (5)	PM	0.15	
	(8) (3)	PM ₁₀	0.04	
DEBARK-2	Log Debarker No. 2 (8) (5)	PM	0.73	
		PM ₁₀	0.22	
DEBARK-1 and DEBARK-2	Total Annual Emissions from both Debarkers (8) (5)	PM	-	1.32
DEBARK-2		PM ₁₀	-	0.40
SAW-1	Cutup Saw Line No. 1 (5)	РМ	0.47	0.43
		PM ₁₀	0.17	0.16
CHIPBIN-1	Truck Loadout No. 1 (5)	PM	0.07	0.04
		PM ₁₀	0.03	0.02
		PM _{2.5}	<0.01	<0.01
CHIPBIN-2	Truck Loadout No. 2 (5)	РМ	0.09	0.10
		PM ₁₀	0.04	0.05
		PM _{2.5}	<0.01	<0.01
CHIPBIN-3	Truck Loadout No. 3 (5)	РМ	0.03	0.02
	(5)	PM ₁₀	0.02	0.01
		PM _{2.5}	<0.01	<0.01
TP-FUG	Transfer Point	РМ	2.91	2.15
	Fugitives (5)	PM ₁₀	1.38	1.02
		PM _{2.5}	0.21	0.15

Emission Sources - Maximum Allowable Emission Rates

Operating Scenario	2***			
BOILER-1	Wood-Fired Boiler	VOC#	3.26	14.30
	Venturi Scrubber Stack	NO _x	18.00	78.84
		SO ₂	2.40	10.51
		PM	9.47	41.47
		PM ₁₀	9.47	41.47
		PM _{2.5}	9.35	40.97
		СО	100.78	441.40
		HAP*	0.27	1.20
BOILER-2	BOILER-2 ESP Stack	VOC#	1.93	5.91
		NO _x	12.41	38.02
		SO ₂	1.72	5.28
		PM	2.21	6.76
		PM ₁₀	2.21	6.76
		PM _{2.5}	2.21	6.76
		СО	27.57	84.50
		NH ₃	1.05	3.21
MSS-BOILER	MSS BOILER	VOC#	1.93	<0.01
		NO _x	23.80	0.86
		SO ₂	1.72	0.02
		PM	14.45	0.53
		PM ₁₀	10.69	0.39
		PM _{2.5}	9.39	0.34
		СО	28.90	1.04
PLANER-1	Planer Mill Cyclone Filter 1 Stack	PM	2.14	9.38
		PM ₁₀	2.14	9.38
		PM _{2.5}	1.35	5.91
PLANER-2	Planer Mill Cyclone Filter 2 Stack	РМ	0.61	2.68
		PM ₁₀	0.61	2.68

		PM _{2.5}	0.39	1.69
C-1	Cyclone 1	PM	0.15	0.68
		PM ₁₀	0.05	0.24
		PM _{2.5}	0.02	0.07
C-2	Cyclone 2	PM	0.15	0.68
		PM ₁₀	0.05	0.24
		PM _{2.5}	0.02	0.07
CKILN-1	Continuous Wood Drying Kiln No. 1	VOC##	72.37	
	Vents (7)	PM	1.00	
		PM ₁₀	1,00	
		PM _{2.5}	0.99	
		HCHO**	0.16	
		MeOH**	3.30	
		HAP*	4.47	
CKILN-2	Continuous Wood Drying Kiln No. 2 Vents (7)	VOC##	72.37	
		РМ	1.00	
		PM ₁₀	1.00	
		PM _{2.5}	0.99	
		HCHO**	0.16	
		MeOH**	3.30	
		HAP*	4.47	
CKILN-1 and CKILN-2	Total Annual Emissions from both Kilns (7)	VOC##	-	552.67
		PM	-	7.64
		PM ₁₀	-	7.64
		PM _{2.5}	-	7.59
		HCHO**	-	1.22
		MeOH**	-	25.20
		HAP*	-	34.11
CKILN-3	Continuous Wood Drying Kiln No. 3	VOC##	89.17	267.50

	Vents			
DEBARK-1	Log Debarker No. 1 (8) (5)	РМ	0.16	
		PM ₁₀	0.05	
DEBARK-2	Log Debarker No. 2	РМ	0.79	
	(8) (5)	PM ₁₀	0.24	
DEBARK-1 and DEBARK-2	Total Annual Emissions from both	РМ	-	1.58
DEBARK-2	Debarkers (8) (5)	PM ₁₀		0.47
SAW-1	Cutup Saw Line No. 1 (5)	РМ	0.45	0.89
	(3)	PM ₁₀	0.16	0.32
CHIPBIN-1	Truck Loadout No. 1	РМ	0.06	0.04
	(5)	PM ₁₀	0.03	0.02
		PM _{2.5}	<0.01	<0.01
CHIPBIN-2	Truck Loadout No. 2 (5)	РМ	0.10	0.10
		PM ₁₀	0.05	0.05
		PM _{2.5}	<0.01	<0.01
CHIPBIN-3	Truck Loadout No. 3 (5)	РМ	0.07	0.04
		PM ₁₀	0.03	0.02
		PM _{2.5}	<0.01	<0.01
CHIPBIN-4	Truck Loadout No. 4 (5)	РМ	0.06	0.04
		PM ₁₀	0.03	0.02
		PM _{2.5}	<0.01	<0.01
CHIPBIN-5	Truck Loadout No. 5 (5)	РМ	0.10	0.10
		PM ₁₀	0.05	0.05
		PM _{2.5}	0.01	0.01
TP-FUG	Transfer Point Fugitives (5)	РМ	2.91	2.15
		PM ₁₀	1.38	1.02
		PM _{2.5}	0.21	0.15

⁽¹⁾ Emission point identification - either specific equipment designation or emission point number from plot plan.(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

alteration request authorized on April 5, 2013.

Emission Sources - Maximum Allowable Emission Rates

(3)	VOC		 volatile organic compounds as defined in Title 30 Texas Administrative Code (TAC) Chapter 101.1.
		#	VOC emissions estimates from the boiler are based on VOC measured as carbon.
		##	VOC emissions from the kilns are estimated using Wood Products Protocol 1 (WPP1).
		*	Also included in total VOC or PM, as appropriate
		**	Also included in total HAP
	NO_x		- total oxides of nitrogen
	SO ₂		- sulfur dioxide
	PM		- total particulate matter, suspended in the atmosphere, including PM_{10} and $PM_{2.5}$, as represented
	PM ₁₀		- total particulate matter equal to or less than 10 microns in diameter, including PM _{2.5} , as represented
	$PM_{2.5}$		- particulate matter equal to or less than 2.5 microns in diameter
	CO		- carbon monoxide
	NH₃		- ammonia
	HCHO		- Formaldehyde
	MeOH		- Methanol
	HAP		- hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of
			Federal Regulations Part 63, Subpart C, including methanol and formaldehyde totals. The
			numbers reflected include the emissions of methanol and formaldehyde.
			nnual emission limits (tons per year) is based on a 12-month rolling period.
(5)			n estimate and is enforceable through compliance with the applicable special condition(s) and
			representations.
(6)	Planned sta	artup a	nd shutdown emissions are included as well as maintenance identified as part of the permit

- (7) Annual compliance will be maintained on the sum of the emissions from the two lumber kilns. West Fraser will maintain records of production for each kiln to verify that the annual total limit is not exceeded.

 (8) Annual compliance will be maintained on the sum of the emissions from the two debarkers. West Fraser will maintain the sum of the emissions from the two debarkers.
- (8) Annual compliance will be maintained on the sum of the emissions from the two debarkers. West Fraser will maintain records of total tons of logs processed through both debarkers (aggregate) to verify that the annual total limit is not exceeded.
- *** Operating Scenario 2 will result from the changes authorized by TCEQ Project No. 287216 and Project No. 354336.

	Date:	DRAFT