

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

3800

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source		Air Contaminant		<u>Emission Rates *</u>	
	Name (2)	Name (3)	lb/hr	TPY		
1	Storage Tanks (4)			VOC	0.30	0.30
3	Baghouse			PM10	0.06	0.06

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) PM10 - particulate matter less than 10 microns
VOC - volatile organic compounds as defined in General Rule 101.1
- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

Hrs/day___Days/week___Weeks/year___or Hrs/year 2,000

300 batches per year at 4 hours per batch and the following:

PRODUCT	RAW MATERIAL	RAW MATERIAL USAGE		
			Per Batch	Per Annual
Mightyplate Roof Coating	Asphalt		427 gal	2,371 gal
	Dry Additives		470 lb	11,750 lb
Mightyplate Plastic Cement	Asphalt		605 gal	38,720 gal
	Dry Additives	1,680 lb	107,520 lb	

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Mightyplate II Roof Coating	Asphalt Dry Additives	1,330 lb	876 gal 49,210 lb	32,412 gal
--------------------------------	--------------------------	----------	----------------------	------------

PRODUCT	RAW MATERIAL	RAW MATERIAL USAGE		
			Per Batch	Per Annual

Aluminum Roof Coating	Asphalt Dry Additives	1,800 lb	422 gal 39,600 lb	9,284 gal
--------------------------	--------------------------	----------	----------------------	-----------

Texotropic Fibrated Roof Coating	Asphalt Dry Additives	2,022 lb	443 gal 50,550 lb	11,075 gal
--	--------------------------	----------	----------------------	------------

Revised _____