

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 9578

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
1	Drum/Dryer Baghouse Stack	VOC (a)	8.00	4.80
		VOC (b)	9.44	2.36
		VOC (c)	56.50	3.39
		NO _x	13.75	10.18
		CO	32.50	24.05
		SO ₂	14.50	10.73
		PM ₁₀	8.55	6.33
2	Material Handling (5)	PM	4.28	3.16
		PM ₁₀	0.95	0.70
3	Stockpiles (5)	PM	-.--	0.41
		PM ₁₀	-.--	0.20
4	Lime Silo Baghouse Stack	PM ₁₀	0.03	< 0.01
5	Silo Filling (5)	PM	0.12	0.08
		PM ₁₀	0.12	0.08
		CO	0.18	0.12
		VOC	1.83	1.21
6	Truck Loadout (5)	PM	0.10	0.06
		PM ₁₀	0.10	0.06
		CO	0.20	0.13

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

		VOC	0.59	0.39
7	Hot Oil Heater	SO ₂	0.24	1.06
		NO _x	0.08	0.37
		VOC	< 0.01	< 0.01
		CO	0.01	0.02
		PM	0.02	0.07
		PM ₁₀	0.01	0.06
8-14	Storage Tanks (6)	VOC	0.10	0.44

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - VOC (a) - primarily asphalt vapors
 - VOC (b) - cold-laid asphalt blended with AC 1.5
 - VOC (c) - additional VOC due to the use of recycled rubber
- NO_x - total oxides of nitrogen
- CO - carbon monoxide
- SO₂ - sulfur dioxide
- PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
- PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
- PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
- (6) Includes emissions from the following storage tanks: 8,000 gal [#2 Off Road Diesel]; 20,000 gal [#4 Recycled Fuel Oil]; 35,000 gal [Liquid Asphalt]; 20,000 gal [Liquid Asphalt]; 5,000 gal [ANTI-STRIP]; 8,000 gal [#4 Recycled Fuel Oil]; and 500 gal [#2 Diesel].

Date April 6, 2011
: