Permit No. 19566/PSD-TX-768M1

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Emission	Source	Air Contaminant		Emission Rates *			
Point No. (1)	Name (2)		Name (3)	lb/hr	TPY		
Pretreater No. 3							
27FUG_001	PTR3 Fugitive Emissions (4	·)	VOC	0.20	0.80		
Sulfur Recovery Unit							
32STK_001	SRU2/3 Thermal Oxidizer	H₂S	CO 0.75 NO_x PM_{10} SO_2 VOC	28.90 3.28 13.50 0.60 128.00 0.30	126.60 47.30 2.10 560.60 1.20		
32VNT_002	SRU2/3 No. 2 Vent (5)		CO COS CS_2 H_2S PM_{10} SO_2	36.80 7.70 0.80 1.05 0.10 0.10			
32VNT_003	SRU2/3 No. 3 Vent (5)		CO COS CS_2 H_2S PM_{10} SO_2	36.80 7.70 0.80 1.05 0.10 0.10			
32VNT_002 and 32VNT_003	SRU2/3 No. 2 Vent and SRU2/3 No. 3 Vent (5)		CO COS CS ₂ H ₂ S PM ₁₀ SO ₂		10.68 1.79 0.13 0.38 0.02 0.02		

Emission *	Source Ai	r Contaminant	<u>Emissi</u>	on Rates
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
30VNT_003	SRU1 Sulfur Pit (5)	H ₂ S SO ₂	0.04 1.67	0.01 0.28
32VNT_005	SRU2/3 Sulfur Truck Loading	(5) H ₂ S SO ₂	0.03 1.29	<0.01 0.11
32FUG_001	SRU 2/3 Fugitive Emissions (4	H) H ₂ S NH ₃ SO ₂ VOC	0.31 0.02 0.028 0.927	1.086 0.10 0.106 4.068
30FUG_001	SRU 1 Fugitive Emissions (4)	H ₂ S SO ₂	1.71 1.79	7.51 7.82
Crude Unit B				
05STK_001	Crude B Atm. Heater H-3101 Stack	CO NO_x PM_{10} SO_2 VOC	11.00 94.32 4.72 22.01 1.10	40.16 344.27 17.50 40.16 4.02
05STK_002	Crude B Vacuum Heater H-3102 Stack	CO NO_x PM_{10} SO_2 VOC	2.30 17.90 0.80 4.00 0.40	8.20 62.50 2.70 13.90 1.50
05STK_004	Crude B Heater H-2001 Stack	CO NO_x PM_{10} SO_2 VOC	1.90 14.40 0.60 3.20 0.40	6.60 50.60 2.20 11.20 1.20
05FUG_001	Crude B Fugitive Emissions (4) VOC	2.44	10.57

Emission	Source Ai	ir Contaminant	<u>Emissi</u>	on Rates
<u>*</u> Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
Hydrocracker				
20STK_001	HDC First Stage West Furnac H-3301 Stack	e CO NO _x PM ₁₀ SO ₂ VOC	0.11 1.36 0.18 0.99 0.09	0.36 4.38 0.59 1.53 0.30
20STK_002	HDC First Stage East Furnace H-3302 Stack	PM ₁₀ SO ₂ VOC	0.40 3.00 0.13 0.73 0.08	1.60 12.10 0.50 1.41 0.30
20STK_003	HDC Second Stage Furnace H-3303 Stack	CO NO_{x} PM_{10} SO_{2} VOC	0.40 3.00 0.13 0.73 0.08	1.60 12.10 0.50 1.41 0.30
20STK_004	HDC Stabilizer Reboiler Heate H-3304 Stack	er CO NO _x PM ₁₀ SO ₂ VOC	4.61 11.76 1.18 5.68 0.55	19.56 49.93 4.99 11.65 2.33
20STK_005	HDC Splitter Rblr. H-3305 Stack	CO NO _x PM ₁₀ SO ₂ VOC	0.02 3.75 0.49 2.18 0.20	0.06 14.24 1.85 3.99 0.74
20FUG_001	HDC Fugitive Emissions (4)	VOC	0.84	3.72

Permit No. 19566/PSD-TX-768M1 Page 4

Emission *	Source	Air Contaminant	<u>Emissi</u>	on Rates
Point No. (1)	Name (2)	Name (3)	1b/hr	<u>TPY</u>
Pretreater No. 4				
28STK_001 (6)	PTR4 Rx Charge Heater B-7001 Stack	CO NO_x PM_{10} SO_2 VOC	1.90 14.40 0.60 3.20 0.40	6.60 50.50 2.20 11.20 1.20
28STK_002 (6)	PTR4 Depen. Reboiler Heater B-7002 Stack	CO NO_x PM_{10} SO_2 VOC	2.30 17.40 0.80 3.90 0.40	8.00 61.00 2.70 13.50 1.50
Reformer No. 4				
28STK_003 (7)(8)	PTR4 Reformer Heater B-7101-4 Stack	CO NO_x PM_{10} SO_2 VOC	13.84 105.16 8.76 23.35 1.25	42.91 326.14 27.16 36.12 4.07
28STK_004 (7)	PTR4 Debut Reboiler B-7201 Stack	CO NO_x PM_{10} SO_2 VOC	0.70 4.90 0.20 1.10 0.10	2.30 17.30 0.80 3.80 0.40
28VNT_001	PTR4 Reactor Regen. Ver	of Cl_2 CO HCl PM_{10} SO_2	0.40 0.96 0.03 0.01 0.10	1.90 4.20 0.10 0.04 0.40

Permit No. 19566/PSD-TX-768M1 Page 5

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	Emission Rates		
Point No. (1)	Name (2)	Name (3)	lb/hr	TPY	
28FUG_001	PTR4 Fugitive Emissions (4) Cl ₂ VOC	0.10 1.01	0.44 4.35	
Coker		VOO	1.01	4.00	
04STK_004	Coker Far West Stack	CO NO_x PM_{10} SO_2 VOC	1.80 13.50 0.60 3.00 0.30	6.20 47.30 2.10 10.50 1.20	
04FUG_001	Coker Fugitive Emissions (4) VOC	3.16	13.95	
Amine Regeneration	on Unit				
18FUG_001	DEA3 Fugitive Emissions (4) H₂S VOC	0.20 0.12	0.70 0.71	
Sour Water Strippe	er Unit	VOC	0.12	0.71	
29FUG_001	SWS Fugitive Emissions (4	NH ₃ VOC	0.01 0.01 0.38	0.10 0.10 1.70	
Storage Tanks					
49TFX_0720	OMCC1 Fixed-Roof Tank 720	VOC	7.16	12.03	
49TFX_0721	OMCC1 Fixed-Roof Tank 721	VOC	7.16	12.03	
49TIF_0782	OMCC1 Int. Floating Roof Tank 782	VOC	2.68	10.61	
48TEF_1150	Ethyl Ext. Floating Roof Tank 1150	VOC	4.09	15.14	

Permit No. 19566/PSD-TX-768M1 Page 6

Emission	Source	Air Contaminant	<u>Emissi</u>	on Rates
<u>*</u> Point No. (1)	Name (2)	Name (3)	1b∕hr	TPY
48TEF_1151	Ethyl Ext. Floating Roof Tank 1151	VOC	4.09	15.11
48TEF_1158	Ethyl Ext. Floating Roof Tank 1158	VOC	2.42	7.86
48TEF_1165	Ethyl Ext. Floating Roof Tank 1165	VOC	2.20	9.16
48TEF_1212	Ethyl Ext. Floating Roof Tank 1212	VOC	2.52	8.56
48TEF_1213	Ethyl Ext. Floating Roof Tank 1213	VOC	2.44	8.24
49TEF_1215	OMCC1 Ext. Floating Roof Tank 1215	VOC	3.01	12.94
48TEF_1251	Ethyl Ext. Floating Roof Tank 1251	VOC	2.67	8.30
44TEF_1300	OMCC1 Ext. Floating Roof Tank 1300	VOC	2.67	8.48
49TEF_1314	OMCC1 Ext. Floating Roof Tank 1314	VOC	2.20	9.11
49TEF_1320	OMCC1 Ext. Floating Roof Tank 1320	VOC	2.93	9.38
48TEF_1324	Ethyl Ext. Floating Roof Tank 1324	VOC	2.86	10.78

Permit No. 19566/PSD-TX-768M1 Page 7

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission *	Source	Air Contaminant	<u>Emissio</u>	n Rates
Point No. (1)	Name (2)	Name (3)	lb/hr	<u>TPY</u>
48TEF_1325	Ethyl Ext. Floating Roof Tank 1325	VOC	1.76	7.37
48TEF_1329	Ethyl Ext. Floating Roof Tank 1329	VOC	3.46	9.73
19TEF_1332	Dualayer Ext. Floating Roof Tank 1332	VOC	1.31	7.32
48TEF_1334	Ethyl Ext. Floating Roof Tank 1334	VOC	2.44	7.73
49TEF_1335	OMCC1 Ext. Floating Roof Tank 1335	VOC	2.37	9.07
48TEF_1338	Ethyl Ext. Floating Roof Tank 1338	VOC	2.43	7.73
48TEF_1350	Ethyl Ext. Floating Roof Tank 1350	VOC	2.50	7.65
48TEF_1361	Ethyl Ext. Floating Roof Tank 1361	VOC	1.09	4.78
48TEF_1362	Ethyl Ext. Floating Roof Tank 1362	VOC	3.45	13.93
48TEF_1389	Ethyl Ext. Floating Roof Tank 1389	VOC	3.24	11.72
48TEF_1390	Ethyl Ext. Floating Roof Tank 1390	VOC	3.14	11.28
50TEF_2119	OMCC2 Ext. Floating Roo	f VOC	4.54	6.91

Permit No. 19566/PSD-TX-768M1 Page 8

Fluid Catalytic Cracking Unit

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant	<u>Emission</u>	Rates
<u>*</u> Point No. (1)	Name (2)	Name (3)	lb/hr	TPY
	Tank 2119			
50TEF_2202	OMCC2 Ext. Floating Roof Tank 2202	VOC	1.65	5.03
50TEF_2209	OMCC2 Ext. Floating Roof Tank 2209	VOC	3.60	5.49
50TEF_2210	OMCC2 Ext. Floating Roof Tank 2210	VOC	3.63	6.52
50TEF_2212	OMCC2 Ext. Floating Roof Tank 2212	VOC	3.63	5.61
50TEF_2213	OMCC2 Ext. Floating Roof Tank 2213	VOC	3.60	5.94
50TEF_2221	OMCC2 Ext. Floating Roof Tank 2221	VOC	2.20	8.61
50TEF_2223	OMCC2 Ext. Floating Roof Tank 2223	VOC	1.82	7.97
50TEF_2225	OMCC2 Ext. Floating Roof Tank 2225	VOC	3.17	5.00
49TEF_1377	OMCC1 Ext. Floating Roof Tank 1377	VOC	1.17	3.71
49TEF_1378	OMCC1 Ext. Floating Roof Tank 1378	VOC	1.15	3.63

Permit No. 19566/PSD-TX-768M1 Pagmin No. 19566/PSD-TX-768M1

Page 9

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Emission *	Source	Air	Contaminant	<u>Emiss</u>	sion Rates
Point No. (1)	Name (2)		Name (3)	1b/hr	· TPY
06STK_001	FCC CO Boiler Stack (Until July 31, 2000)		CO NO_x PM_{10} SO_2 VOC	457.00 984.00 155.00 4610.00 1.74	2000.00 2650.00 675.00 12419.94 7.60
06STK_001	FCC CO BOILER (After July 31, 2000)	PM ₁₀ SO ₂ VOC	CO NO _x 155.00 4690.00 1.74	457.00 984.00 675.00 13101.00 7.60	2000.00 2650.00
20CTL_005	Cooling Tower No. 5		VOC	1.51	6.62
Petroleum Coke Handlii	ng Facility				
04FUG002	Coke Pit (9)		PM ₁₀	0.20 0.42	0.11 0.22
04FUG003	Stockpile (9)		PM ₁₀ PM	1.07 2.27	0.26 0.54
04FUG004	Conveyor System 1 (9)		PM ₁₀ PM	0.81 1.71	0.07 0.15
04FUG005	Conveyor System 2 (9)		PM ₁₀	0.94 1.98	0.08 0.17

⁽¹⁾ Emission point identification - either specific equipment designation or emission point number from plot plan.

⁽²⁾ Specific point source name. For fugitive sources use area name or fugitive source name.

⁽³⁾ VOC - volatile organic compounds as defined in 30 Texas Administrative Code Section 101.1

CO - carbon monoxide H₂S - hydrogen sulfide

NO_x - total oxides of nitrogen

PM - particulate matter, suspended in the atmosphere, including PM₁₀

PM₁₀ - particulate matter (PM) equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted

SO₂ - sulfur dioxide COS - carbonyl sulfide CS₂ - carbon disulfide

Cl₂ - chlorine

HCl - hydrogen chloride

NH₃ - ammonia

- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- (5) The TPY rate is based on operating 336 hours/year (rolling annual basis) with the stack burner/thermal oxidizer down.
- (6) Heaters B-7001 and B-7002 share a common stack.
- (7) Heaters B-7101-4 and B-7201 share a common stack.
- (8) Fuel for the Heaters 20STK_001, 20STK_002, 20STK_003, 20STK_004, 20STK_005, and 28STK_003, shall be (1) sweet natural gas or (2) refinery fuel gas which contains not more than 150 ppm(v) of H₂S averaged over any one-hour period and not more than 75 ppm(v) of H₂S averaged over any 12-consecutive month period. Fuel for all other sources shall be (1) sweet natural gas or (2) refinery fuel gas which contains not more than 150 ppm(v) of H₂S averaged over any one-hour period.
- (9) The PM emissions include PM_{10} emissions. PM and TSP are considered interchangeable.

Hrs/day____ Days/week____ Weeks/year___ or Hrs/year_8,760_

*	Emission	rates	are	based	on	and	the	facilities	are	limited	by	the	following	maximum	operating
	schedule:														