

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 25850

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
Sawmill	Sawmill Operations (4)	PM	5.50	10.90
		PM ₁₀	3.09	6.16
Chip Pile	Chip Storage Pile (4)	PM	0.83	1.66
		PM ₁₀	0.28	0.56
Transfer	Sawdust/Small Chip Transfer (4)	PM	2.07	4.13
		PM ₁₀	0.75	1.49
Chip Load	Chip Loading to Trucks (4)	PM	0.83	1.66
		PM ₁₀	0.28	0.56
Bypass	Boiler Bypass Vent 1	PM	11.88	0.31
		PM ₁₀	10.44	0.28
		NO _x	7.92	0.21
		SO ₂	0.90	0.03
		CO	21.60	0.57
		VOC	0.62	0.02
Boiler	Boiler Dust Collector Stack	PM	7.92	17.12
		PM ₁₀	7.20	15.57
		NO _x	7.92	17.12
		SO ₂	0.90	1.95
		CO	21.60	46.69
		VOC	0.62	1.35

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Bypass 2	Boiler Bypass Vent 2	PM	11.88	0.31
		PM ₁₀	10.44	0.28
		NO _x	7.92	0.21
		SO ₂	0.90	0.03
		CO	21.60	0.57
		VOC	0.62	0.02
Boiler 2	Boiler Dust Collector Stack	PM	7.92	17.12
		PM ₁₀	7.20	15.57
		NO _x	7.92	17.12
		SO ₂	0.90	1.95
		CO	21.60	46.69
		VOC	0.62	1.35
Ash	Ash Bin Dumping and Loading (4)	PM	0.02	0.04
		PM ₁₀	0.02	0.02
Old Kiln	Old Steam Dry Kiln (4)	PM ₁₀	0.26	0.78
		VOC	4.36	13.07
Planer	Planer Operations (4)	PM	0.92	1.82
		PM ₁₀	0.36	0.71
New Kiln	New Steam Dry Kiln (4)	PM ₁₀	0.26	0.78
		VOC	4.36	13.07

- (1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
- (2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM₁₀
PM₁₀ - particulate matter equal to or less than 10 microns in diameter
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

NO_x - total oxides of nitrogen

SO₂ - sulfur dioxide

CO - carbon monoxide

(4) Fugitive emissions are an estimate.

- * Emission rates are based on and the facilities are limited by the following maximum operating schedule:

24 Hrs/day 7 Days/week 52 Weeks/year or 8,760 Hrs/year

Maximum Operating Parameters:

Combined wood fuel feed rate through boilers

(EPNs Boiler and Boiler 2):

16,000 lb/hr

35,000 TPY

Kiln throughput (kiln-dried wood)

(EPNs Old Kiln and New Kiln):

220,000 bd ft/dy

55,000,000 bdft/yr

The maximum operating schedule for each Boiler Bypass Vent (EPNs Bypass and Bypass 2) is 52 hours per year in any rolling 12-month period.

- ** Compliance with annual emission limits is based on a rolling 12-month period.

Dated January 17, 2008