

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Number 80483

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY
1	Baghouse Stack	PM ₁₀	8.59	11.50
		VOC(a)	10.40	13.12
		VOC(b)	393.75	8.75
		VOC(c)	73.45	4.52
		NO _x	17.88	23.73
		SO ₂	3.58	4.75
		CO	42.25	56.10
2	Material Handling (4)	PM	0.58	0.78
		PM ₁₀	0.28	0.37
3	Stockpiles (4)	PM	---	1.83
		PM ₁₀	---	0.91
		VOC(b)	2.10	4.38
4	AC Heater	PM ₁₀	0.02	0.08
		VOC	<0.01	0.01
		NO _x	0.11	0.49
		SO ₂	0.33	1.46
		CO	0.03	0.12
5	Plant Loadout (4)	PM ₁₀	0.17	0.22
		VOC	1.27	1.68
		CO	0.44	0.58
6	Silo Filling (4)	PM ₁₀	0.19	0.25
		VOC	3.96	5.24
		CO	0.38	0.51
7	Fuel Tanks	VOC	0.01	0.01
8	AC Tanks	VOC	0.01	0.01

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates **	
			lb/hr	TPY*
REC-1 & 2	Material Receiving	PM	0.03	0.03
		PM ₁₀	0.01	0.02

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) PM - particulate matter, suspended in the atmosphere, including PM₁₀
 PM₁₀ - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no particulate matter greater than 10 microns is emitted.
- VOC - volatile organic compounds (VOC)
 VOC(a) - VOC consisting mainly of asphalt vapor
 VOC(b) - VOC consisting mainly of diesel or kerosene vapor
 VOC(c) - additional VOC resulting from the use of crumb rubber
 NO_x - total oxides of nitrogen
 SO₂ - sulfur dioxide
 CO - carbon monoxide
- (4) Fugitive emissions are an estimate only.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule and production rates:

Hrs/day 12 Days/week 6 up to Hrs/year 4,380

Standard Hot-Mix Asphalt Concrete: Tons/hour 325 Tons/year 820,000

Cold-Mix Asphalt Concrete (produced with emulsions): Tons/hour 225 Tons/week 2,000
 Tons/year 10,000

Standard Hot-Mix with Crumb Rubber: Tons/hour 325 Tons/year 40,000

Dated February 21, 2007