EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit No. 29562A

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission	Source	Air Contaminant		Emission Rates	
<u>*</u>					
Point No. (1)	Name (2)	Name (3)		lb/hr	TPY
1	Drum/Dryer Baghouse 16.65	Stack	VOC	(a)	38.85
		VOC (b)		525.00	87.50
		V0C (c)		56.50	5.65
		NO_x		12.60	5.40
		CO		13.30	5.70
		SO_2		17.85	34.99
		PM_{10}		11.92	5.11
2	Material Handling (4	1) TSP		6.10	2.78
_	That en tall manaring (PM ₁₀		1.50	0.69
3	Stockpiles (4)	TSP		*	1.39
-	2 2 2 C C C C C C C C C C C C C C C C C	PM ₁₀		*	0.68
		VOC (b)		0.32	1.31

- (1) Emission point identification either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) VOC volatile organic compounds as defined in TNRCC General Rule 101.1 VOC(a) from standard mix asphalt concrete
 - VOC(b) from cold mix asphalt concrete
 - VOC(c) -total VOCs from recycled rubber modified asphalt concrete mixes
 - NO_x -nitrogen oxide
 - CO carbon monoxide

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

SO₂ - sulfur dioxide

 PM_{10} -particulate matter less than 10 microns in diameter

TSP - total suspended particulate matter

(4) Fugitive emissions are an estimate only.

* Emission rates are based on and the facility is limited to the following asphalt concrete production rates and operating schedule:

	tons/hour	tons/week	tons/ye	<u>ar</u>
Standard hot mi	X	350		300,000
Recycled rubber	nodified mixes	**250		**50,000
Cold mix asphal	t with emulsion	300	10,000	***
Cold mix asphal	t with slow cure	262	8,750	***
Cold mix asphal	t with rapid cure	210	5,000	***
Cold mix asphal	t with medium cure	150	5,000	***

** Included in the standard hot mix hourly and annual limits *** Total cold mix production as governed by Special Condition No. 19

14 hours/day 7 days/week 52 weeks/year 3,920 hours/year